1 AMQPS binding

AMQP0-9-1 overTLS, interface `generic_amqps`, policy CERT_AUTH. Broker AMQP_HOST/AMQP_PORT defaultamqp-broker:5671; SASL EXTERNAL with LocalCloudManager service certificate. Exchange `arrowhead`, routing `<Cloud>.sysmonitor.LocalCloudManager.LocalCloudManager.<observationType>`. Operations/types `echo`, `power`, `status`; content type application/json, delivery mode persistent, publisher confirm with a10second wait bound. Configure broker SANs, trust, exchange and ACLs independently.

2 Observation schema

Envelope fields: schemaVersion1.0, observationId, providerSystem, serviceInstance, observationType, sourceTime (UTC-Z), sequence, value, quality, metadata. metadata contains publisherMode=native and implementation=go. Non-echo observations include unit1.

Echo value: status=alive, uptimeSeconds, detail. Power: supplyType=line, state=available. Status: state=running, health=healthy, serviceCount. These values do not establish provider readiness or physical supply state.

Registry metadata contract SysMonitor-AMQP-IDD-5.2.2, schemaVersion1.0, publisherMode native, observationTypes array and delivery persistent/publisher-confirmed. baseRoutingKey is `cloud.sysmonitor.LocalCloudManager.LocalCloudManager`. No plaintext AMQP fallback is provided by this publisher.

3 References and verification

Authoritative moved code: LocalCloudManager/internal/cloud and embedded ui sources. Exact original/relocated SHA256 hashes are in docs/source-manifest.json. docs/legacy preserves the earlier local Markdown/SysML, not an endorsement of its parity claims. The revised SysML variability model is descriptive and has not been checked by a SysML parser. Executed checks and qualification limits are recorded in VERIFICATION.md. Source movement does not deploy or alter running clouds.