plantDescriptionManagement HTTP/TLS/JSON

Interface Design Description

Service ID: *"plantDescriptionManagement"*

Abstract
This document describes the HTTP/1.1 protocol with TLS payload security and JSON payload encoding variant of the `plantDescriptionManagement` service of the PlantDescriptionEngine system.

Contents

1 Overview **3**
1.1 Interface registration . . . 3

2 Service Operations **4**
2.1 operation query . . . 4
2.2 operation get . . . 5
2.3 operation create . . . 6
2.4 operation replace . . . 7
2.5 operation update . . . 9
2.6 operation remove . . . 10

3 Data Models **12**
3.1 struct Connection . . . 12
3.2 struct ErrorMessage . . . 12
3.3 struct PdeSystem . . . 12
3.4 struct PlantDescriptionListResponse . . . 12
3.5 struct PlantDescriptionRequest . . . 12
3.6 struct PlantDescriptionResponse . . . 13
3.7 struct PlantDescriptionUpdate . . . 13
3.8 struct Port . . . 13
3.9 struct SystemPort . . . 13
3.10 Primitives . . . 14

4 References **15**

5 Revision History **16**
5.1 Amendments . . . 16
5.2 Quality Assurance . . . 16

1 Overview

This document describes the `plantDescriptionManagement` service interface of the PlantDescriptionEngine system, which provides management of plant descriptions: the engineered systems of the plant, the services they consume and produce (ports), and the connections between ports.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	HTTP	1.1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `plantDescriptionManagement` service interface

This document provides the Interface Design Description IDD to the *plantDescriptionManagement – Service Description* document [5]. For further details about how this service is meant to be used, please consult that document.

The rest of this document describes how to realize the `plantDescriptionManagement` service interface in detail. Both in terms of its operations (Section 2) and its information model (Section 3).

1.1 Interface registration

The service is registered in the ServiceRegistry with the interface template `generic_https`, policy `CERT_AUTH`, access address `plantdescriptionengine`, port 8432 and base path `/plantdescriptionengine/mgmt`. The `operations` property of the interface lists the operations below with their method and path relative to the base path (path parameters are placeholders such as `{id}` that the consumer fills in):

Operation	Method	Path
`query`	GET	`/plant-descriptions`
`get`	GET	`/plant-descriptions/{id}`
`create`	POST	`/plant-descriptions`
`replace`	PUT	`/plant-descriptions/{id}`
`update`	PATCH	`/plant-descriptions/{id}`
`remove`	DELETE	`/plant-descriptions/{id}`

2 Service Operations

The interfaces of the `plantDescriptionManagement` service, its operations, data models and implementation are provided below. In particular, each subsection first names the HTTP method and path used to call the operation, after which it names the abstract operation from the `plantDescriptionManagement` SD document, as well as input and output types.

All operations require the requester's identity, presented according to the provider's authentication policy: the client certificate (mutual TLS) and, with the `outsourced` policy, `Authorization: Bearer IDENTITY-TOKEN//<token>`; systems holding the Authentication secret key send `Bearer AUTHENTICATOR-KEY//<system>//<hash>`, and with the `declared` policy `Bearer SYSTEM//<system>` is sent. Request and response bodies are `application/json` unless stated otherwise. Errors are answered with an ErrorMessage body and the status codes `400 Bad Request` (invalid parameter), `401 Unauthorized` (missing or invalid identity), `403 Forbidden` (not permitted, e.g. by the management, authorization or blacklist filter), `404 Not Found`, `408 Request Timeout`, `423 Locked`, `500 Internal Server Error` and `503 Service Unavailable` (a system it depends on failed).

2.1 GET /plantdescriptionengine/mgmt/plant-descriptions?page={page}&size={size}&direction={direction}&sort_field={sort_field}&active={active}

Operation: query
Output: PlantDescriptionListResponse

Returns a page of plant descriptions, optionally only the active one.

Query parameters: *page* (Integer, optional); *size* (Integer, optional); *direction* (String, optional); *sort_field* (String, optional); *active* (Boolean, optional). List values are repeated or comma-separated.

A successful call returns `200 OK` with the output in the body.

```
GET /plantdescriptionengine/mgmt/plant-descriptions?page=<page>&size=<size>&direction=<direction>&
    sort_field=<sort_field>&active=<active> HTTP/1.1
Host: plantdescriptionengine:8432
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 1: An query invocation.

```
{
  "entries": [
    {
      "id": 42,
      "plantDescription": "Line 1",
      "active": true,
      "include": [
        1
      ],
      "systems": [
        {
          "systemId": "sensor",
          "systemName": "TemperatureSensor",
          "metadata": {
            "unit": "celsius"
          },
          "ports": [
            {}
          ]
        }
      ],
      "connections": [
        {
          "priority": 1
        }
      ],
      "createdAt": "2026-10-22T12:00:00Z",
```

```
      "updatedAt": "2026-10-22T12:00:00Z"
    }
  ],
  "count": 1
}
```

Listing 2: An query response.

2.2 GET /plantdescriptionengine/mgmt/plant-descriptions/*{id}*

Operation: get
Input: String
Output: PlantDescriptionResponse

Returns a plant description.
Path parameter: *id*.
A successful call returns `200 OK` with the output in the body.

```
GET /plantdescriptionengine/mgmt/plant-descriptions/<id> HTTP/1.1
Host: plantdescriptionengine:8432
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 3: An get invocation.

```
{
  "id": 42,
  "plantDescription": "Line 1",
  "active": true,
  "include": [
    1
  ],
  "systems": [
    {
      "systemId": "sensor",
      "systemName": "TemperatureSensor",
      "metadata": {
        "unit": "celsius"
      },
      "ports": [
        {
          "portName": "out",
          "serviceDefinition": "temperatureReading",
          "serviceInterface": "string",
          "metadata": {
            "unit": "celsius"
          },
          "consumer": "TemperatureDisplay"
        }
      ]
    }
  ],
  "connections": [
    {
      "consumer": {
        "systemId": "sensor",
        "portName": "out"
      },
      "producer": {
        "systemId": "sensor",
        "portName": "out"
      },
      "priority": 1
    }
  ],
```

```
  "createdAt": "2026-10-22T12:00:00Z",
  "updatedAt": "2026-10-22T12:00:00Z"
}
```

Listing 4: An get response.

2.3 POST /plantdescriptionengine/mgmt/plant-descriptions

Operation: create
Input: PlantDescriptionRequest
Output: PlantDescriptionResponse

Creates a plant description; if active, it replaces the active one and the rules are synchronized.
A successful call returns `201 Created` with the output in the body.

```
POST /plantdescriptionengine/mgmt/plant-descriptions HTTP/1.1
Host: plantdescriptionengine:8432
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "plantDescription": "Line 1",
  "active": true,
  "include": [
    1
  ],
  "systems": [
    {
      "systemId": "sensor",
      "systemName": "TemperatureSensor",
      "metadata": {
        "unit": "celsius"
      },
      "ports": [
        {
          "portName": "out",
          "serviceDefinition": "temperatureReading",
          "serviceInterface": "string",
          "metadata": {
            "unit": "celsius"
          },
          "consumer": "TemperatureDisplay"
        }
      ]
    }
  ],
  "connections": [
    {
      "consumer": {
        "systemId": "sensor",
        "portName": "out"
      },
      "producer": {
        "systemId": "sensor",
        "portName": "out"
      },
      "priority": 1
    }
  ]
}
```

Listing 5: An create invocation.

```
{
```

```
  "id": 42,
  "plantDescription": "Line 1",
  "active": true,
  "include": [
    1
  ],
  "systems": [
    {
      "systemId": "sensor",
      "systemName": "TemperatureSensor",
      "metadata": {
        "unit": "celsius"
      },
      "ports": [
        {
          "portName": "out",
          "serviceDefinition": "temperatureReading",
          "serviceInterface": "string",
          "metadata": {
            "unit": "celsius"
          },
          "consumer": "TemperatureDisplay"
        }
      ]
    }
  ],
  "connections": [
    {
      "consumer": {
        "systemId": "sensor",
        "portName": "out"
      },
      "producer": {
        "systemId": "sensor",
        "portName": "out"
      },
      "priority": 1
    }
  ],
  "createdAt": "2026-10-22T12:00:00Z",
  "updatedAt": "2026-10-22T12:00:00Z"
}
```

Listing 6: An create response.

2.4 PUT /plantdescriptionengine/mgmt/plant-descriptions/*{id}*

Operation: replace
Input: PlantDescriptionRequest
Output: PlantDescriptionResponse

Replaces a plant description.
Path parameter: *id*.
A successful call returns `200 OK` with the output in the body.

```
PUT /plantdescriptionengine/mgmt/plant-descriptions/<id> HTTP/1.1
Host: plantdescriptionengine:8432
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "plantDescription": "Line 1",
  "active": true,
  "include": [
    1
```

```
  ],
  "systems": [
    {
      "systemId": "sensor",
      "systemName": "TemperatureSensor",
      "metadata": {
        "unit": "celsius"
      },
      "ports": [
        {
          "portName": "out",
          "serviceDefinition": "temperatureReading",
          "serviceInterface": "string",
          "metadata": {
            "unit": "celsius"
          },
          "consumer": "TemperatureDisplay"
        }
      ]
    }
  ],
  "connections": [
    {
      "consumer": {
        "systemId": "sensor",
        "portName": "out"
      },
      "producer": {
        "systemId": "sensor",
        "portName": "out"
      },
      "priority": 1
    }
  ]
}
```

Listing 7: An replace invocation.

```
{
  "id": 42,
  "plantDescription": "Line 1",
  "active": true,
  "include": [
    1
  ],
  "systems": [
    {
      "systemId": "sensor",
      "systemName": "TemperatureSensor",
      "metadata": {
        "unit": "celsius"
      },
      "ports": [
        {
          "portName": "out",
          "serviceDefinition": "temperatureReading",
          "serviceInterface": "string",
          "metadata": {
            "unit": "celsius"
          },
          "consumer": "TemperatureDisplay"
        }
      ]
    }
  ],
  "connections": [
    {
      "consumer": {
```

```
        "systemId": "sensor",
        "portName": "out"
      },
      "producer": {
        "systemId": "sensor",
        "portName": "out"
      },
      "priority": 1
    }
  ],
  "createdAt": "2026-10-22T12:00:00Z",
  "updatedAt": "2026-10-22T12:00:00Z"
}
```

Listing 8: An replace response.

2.5 PATCH /plantdescriptionengine/mgmt/plant-descriptions/*{id}*

Operation: update
Input: PlantDescriptionUpdate
Output: PlantDescriptionResponse

Changes the given fields of a plant description.
Path parameter: *id*.
A successful call returns `200 OK` with the output in the body.

```
PATCH /plantdescriptionengine/mgmt/plant-descriptions/<id> HTTP/1.1
Host: plantdescriptionengine:8432
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "plantDescription": "Line 1",
  "active": true,
  "include": [
    1
  ],
  "systems": [
    {
      "systemId": "sensor",
      "systemName": "TemperatureSensor",
      "metadata": {
        "unit": "celsius"
      },
      "ports": [
        {
          "portName": "out",
          "serviceDefinition": "temperatureReading",
          "serviceInterface": "string",
          "metadata": {
            "unit": "celsius"
          },
          "consumer": "TemperatureDisplay"
        }
      ]
    }
  ],
  "connections": [
    {
      "consumer": {
        "systemId": "sensor",
        "portName": "out"
      },
      "producer": {
        "systemId": "sensor",
```

```
        "portName": "out"
      },
      "priority": 1
    }
  ]
}
```

Listing 9: An update invocation.

```
{
  "id": 42,
  "plantDescription": "Line 1",
  "active": true,
  "include": [
    1
  ],
  "systems": [
    {
      "systemId": "sensor",
      "systemName": "TemperatureSensor",
      "metadata": {
        "unit": "celsius"
      },
      "ports": [
        {
          "portName": "out",
          "serviceDefinition": "temperatureReading",
          "serviceInterface": "string",
          "metadata": {
            "unit": "celsius"
          },
          "consumer": "TemperatureDisplay"
        }
      ]
    }
  ],
  "connections": [
    {
      "consumer": {
        "systemId": "sensor",
        "portName": "out"
      },
      "producer": {
        "systemId": "sensor",
        "portName": "out"
      },
      "priority": 1
    }
  ],
  "createdAt": "2026-10-22T12:00:00Z",
  "updatedAt": "2026-10-22T12:00:00Z"
}
```

Listing 10: An update response.

2.6 DELETE /plantdescriptionengine/mgmt/plant-descriptions/*{id}*

Operation: remove
Input: String

Removes a plant description and its rules.
Path parameter: *id*.
A successful call returns `204 No Content`.

```
DELETE /plantdescriptionengine/mgmt/plant-descriptions/<id> HTTP/1.1
Host: plantdescriptionengine:8432
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 11: An remove invocation.

3 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is meant to denote a JSON Object that must contain certain fields, or names, with values conforming to explicitly named types. Fields that are not needed may be omitted or `null` in requests; empty fields are omitted in responses. As a complement to the primary types defined in this section, there is also a list of secondary types in Section 3.10, which are used to represent things like hashes, identifiers and texts.

3.1 struct Connection

A connection from a consumer port to a producer port.

Object Field	Value Type	Description
"consumer"	SystemPort	The consumer port of the connection.
"producer"	SystemPort	The producer port of the connection.
"priority"	Number	Priority of the resulting orchestration rules (1 highest).

3.2 struct ErrorMessage

Object Field	Value Type	Description
"errorMessage"	String	Error text, if the event is an error.
"errorCode"	Number	
"exceptionType"	ExceptionType	
"origin"	String	

3.3 struct PdeSystem

A system of the plant.

Object Field	Value Type	Description
"systemId"	String	Identifier of the system within the plant description.
"systemName"	String	Name of the registered system (optional; metadata may identify it instead).
"metadata"	Object<String>	Metadata the registered system must have.
"ports"	Array<Port>	Services the system consumes or produces.

3.4 struct PlantDescriptionListResponse

List of plant descriptions.

Object Field	Value Type	Description
"entries"	Array<PlantDescriptionResponse>	Matching records of the current page.
"count"	Number	Total number of matching records (all pages).

3.5 struct PlantDescriptionRequest

A plant description to create or replace.

Object Field	Value Type	Description
"plantDescription"	String	Name of the plant description.
"active"	Boolean	Make this the active plant description.
"include"	Array<Number>	Identifiers of included plant descriptions.
"systems"	Array<PdeSystem>	Systems to create or update.
"connections"	Array<Connection>	Connections between consumer and producer ports.

3.6 struct PlantDescriptionResponse

A stored plant description.

Object Field	Value Type	Description
"id"	Number	Identifier of the plant description.
"plantDescription"	String	Name of the plant description.
"active"	Boolean	Whether this is the active plant description.
"include"	Array<Number>	Identifiers of included plant descriptions.
"systems"	Array<PdeSystem>	Systems to create or update.
"connections"	Array<Connection>	Connections between consumer and producer ports.
"createdAt"	DateTime	UTC time of creation.
"updatedAt"	DateTime	UTC time of the last change.

3.7 struct PlantDescriptionUpdate

Fields of a plant description to change; absent fields are kept.

Object Field	Value Type	Description
"plantDescription"	String	Name of the plant description.
"active"	Boolean	Make this the active plant description.
"include"	Array<Number>	Identifiers of included plant descriptions.
"systems"	Array<PdeSystem>	Systems to create or update.
"connections"	Array<Connection>	Connections between consumer and producer ports.

3.8 struct Port

A service a plant system consumes or produces.

Object Field	Value Type	Description
"portName"	String	Name of the port within its system.
"serviceDefinition"	String	Service definition name.
"serviceInterface"	String	Required interface template of the port, if any.
"metadata"	Object<String>	Metadata the service instance must have.
"consumer"	Boolean	True for a consumed service, false for a produced one.

3.9 struct SystemPort

Reference to a port of a plant system.

Object Field	Value Type	Description
"systemId"	String	Identifier of the system within the plant description.
"portName"	String	Name of the port within its system.

3.10 Primitives

As all messages are encoded using the JSON format [4], the following primitive constructs, part of that standard, become available. Note that the official standard is defined in terms of parsing rules, while this list only concerns syntactic information. Furthermore, the Object and Array types are given optional generic type parameters, which are used in this document to signify when pair values or elements are expected to conform to certain types.

Type	Description
Array	A JSON Array [4]; Array<A> has elements of type A.
Boolean	JSON Boolean, `true` or `false`.
DateTime	JSON String with an ISO 8601 UTC timestamp, e.g. `2026-10-22T12:00:00Z`.
ExceptionType	One of `ARROWHEAD`, `INVALID_PARAMETER`, `AUTH`, `FORBIDDEN`, `DATA_NOT_FOUND`, `TIMEOUT`, `LOCKED`, `INTERNAL_SERVER_ERROR`, `EXTERNAL_SERVER_ERROR` (JSON String).
Number	JSON Number, an integer.
Object	JSON Object; Object<A> has string keys and values of type A.
String	JSON String.

4 References

[1] R. Fielding, M. Nottingham, and J. Reschke, “Http/1.1,” IETF, RFC 9112, 2022.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “plantDescriptionManagement – Service Description (PlantDescriptionEngine),” Eclipse Arrowhead, SD 5.2.2, 2026, plantDescriptionEngine-v5.2.2-plantDescriptionManagement-SD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-23	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing
2	2026-10-30	5.2.2	Checked against the primary Java source tree (Eclipse-Arrowhead-java): services, operations, paths and data models unchanged.	Claude Opus 5.5 (draft)

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	