serviceOrchestrationLockManagement HTTP/TLS/JSON

Interface Design Description

Service ID: *"serviceOrchestrationLockManagement"*

Abstract
This document describes the HTTP/1.1 protocol with TLS payload security and JSON payload encoding variant of the `serviceOrchestrationLockManagement` service of the DynamicServiceOrchestration system.

Contents

1 Overview **3**
1.1 Interface registration . . . 3

2 Service Operations **4**
2.1 operation query . . . 4
2.2 operation remove . . . 5
2.3 operation create . . . 5

3 Data Models **7**
3.1 struct ErrorMessage . . . 7
3.2 struct OrchestrationLockListRequest . . . 7
3.3 struct OrchestrationLockListResponse . . . 7
3.4 struct OrchestrationLockQueryRequest . . . 7
3.5 struct OrchestrationLockRequest . . . 7
3.6 struct OrchestrationLockResponse . . . 8
3.7 struct Page . . . 8
3.8 Primitives . . . 8

4 References **9**

5 Revision History **10**
5.1 Amendments . . . 10
5.2 Quality Assurance . . . 10

1 Overview

This document describes the `serviceOrchestrationLockManagement` service interface of the DynamicServiceOrchestration system, which provides operator management of orchestration locks, the exclusive reservations of service instances.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	HTTP	1.1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `serviceOrchestrationLockManagement` service interface

This document provides the Interface Design Description IDD to the *serviceOrchestrationLockManagement – Service Description* document [5]. For further details about how this service is meant to be used, please consult that document.

The rest of this document describes how to realize the `serviceOrchestrationLockManagement` service interface in detail. Both in terms of its operations (Section 2) and its information model (Section 3).

1.1 Interface registration

The service is registered in the ServiceRegistry with the interface template `generic_https` (`generic_http` when TLS is disabled), access port 8441 and base path `/serviceorchestration/orchestration/mgmt/lock`. The `operations` property of the interface lists the operations below with their method and path relative to the base path (path parameters are placeholders such as `{id}` that the consumer fills in):

Operation	Method	Path
`query`	POST	`/query`
`remove`	DELETE	`/remove/{owner}`
`create`	POST	`/create`

2 Service Operations

The interfaces of the `serviceOrchestrationLockManagement` service, its operations, data models and implementation are provided below. In particular, each subsection first names the HTTP method and path used to call the operation, after which it names the abstract operation from the `serviceOrchestrationLockManagement` SD document, as well as input and output types.

All operations require the requester's identity, presented according to the provider's authentication policy: the client certificate (mutual TLS) and, with the `outsourced` policy, `Authorization: Bearer IDENTITY-TOKEN//<token>`; systems holding the Authentication secret key send `Bearer AUTHENTICATOR-KEY//<system>//<hash>`, and with the `declared` policy `Bearer SYSTEM//<system>` is sent. Request and response bodies are `application/json`. Errors are answered with an ErrorMessage body and the status codes `400 Bad Request` (invalid parameter), `401 Unauthorized` (missing or invalid identity), `403 Forbidden` (not permitted, e.g. by the management or blacklist filter), `404 Not Found`, `408 Request Timeout`, `423 Locked`, `500 Internal Server Error` and `503 Service Unavailable` (a system it depends on failed).

2.1 POST /serviceorchestration/orchestration/mgmt/lock/query

Operation: query
Input: OrchestrationLockQueryRequest
Output: OrchestrationLockListResponse

Returns a page of locks matching the filter.

A successful call returns `200 OK` with the output in the body.

```
POST /serviceorchestration/orchestration/mgmt/lock/query HTTP/1.1
Host: serviceorchestration-dynamic:8441
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "pagination": {
    "page": 0,
    "size": 10,
    "direction": "ASC",
    "sortField": "createdAt"
  },
  "ids": [
    1
  ],
  "orchestrationJobIds": [
    "3fa85f64-5717-4562-b3fc-2c963f66afa6"
  ],
  "serviceInstanceIds": [
    "TemperatureSensor|temperatureReading|1.0.0"
  ],
  "owners": [
    "TemperatureDisplay"
  ],
  "expiresBefore": "2026-10-22T12:00:00Z",
  "expiresAfter": "2026-10-22T12:00:00Z"
}
```

Listing 1: An query invocation.

```
{
  "entries": [
    {
      "id": 1,
      "orchestrationJobId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "serviceInstanceId": "TemperatureSensor|temperatureReading|1.0.0",
```

```
      "owner": "TemperatureDisplay",
      "expiresAt": "2026-10-22T12:00:00Z",
      "temporary": false
    }
  ],
  "count": 1
}
```

Listing 2: An query response.

2.2 DELETE /serviceorchestration/orchestration/mgmt/lock/remove/*{owner}*?instanceIds=*{instanceIds}*

Operation: remove
Input: String

Removes the locks of an owner on the given service instances.
Path parameter: *owner*.
Query parameters: *instanceIds* (List<String>, required). List values are repeated or comma-separated.
A successful call returns `200 OK`.

```
DELETE /serviceorchestration/orchestration/mgmt/lock/remove/<owner>?instanceIds=<instanceIds> HTTP/1.1
Host: serviceorchestration-dynamic:8441
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 3: An remove invocation.

2.3 POST /serviceorchestration/orchestration/mgmt/lock/create

Operation: create
Input: OrchestrationLockListRequest
Output: OrchestrationLockListResponse

Creates locks on service instances for owners.
A successful call returns `200 OK` with the output in the body.

```
POST /serviceorchestration/orchestration/mgmt/lock/create HTTP/1.1
Host: serviceorchestration-dynamic:8441
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "locks": [
    {
      "serviceInstanceId": "TemperatureSensor|temperatureReading|1.0.0",
      "owner": "TemperatureDisplay",
      "expiresAt": "2026-10-22T12:00:00Z"
    }
  ]
}
```

Listing 4: An create invocation.

```
{
  "entries": [
    {
      "id": 1,
      "orchestrationJobId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "serviceInstanceId": "TemperatureSensor|temperatureReading|1.0.0",
```

```
      "owner": "TemperatureDisplay",
      "expiresAt": "2026-10-22T12:00:00Z",
      "temporary": false
    }
  ],
  "count": 1
}
```

Listing 5: An create response.

3 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is meant to denote a JSON Object that must contain certain fields, or names, with values conforming to explicitly named types. Fields that are not needed may be omitted or `null` in requests; empty fields are omitted in responses. As a complement to the primary types defined in this section, there is also a list of secondary types in Section 3.8, which are used to represent things like hashes, identifiers and texts.

3.1 struct ErrorMessage

Object Field	Value Type	Description
"errorMessage"	String	
"errorCode"	Number	
"exceptionType"	ExceptionType	
"origin"	String	

3.2 struct OrchestrationLockListRequest

Locks to create.

Object Field	Value Type	Description
"locks"	Array<OrchestrationLockRequest>	Locks to create.

3.3 struct OrchestrationLockListResponse

List of orchestration locks.

Object Field	Value Type	Description
"entries"	Array<OrchestrationLockResponse>	Matching records of the current page.
"count"	Number	Total number of matching records (all pages).

3.4 struct OrchestrationLockQueryRequest

Paged filter for orchestration locks.

Object Field	Value Type	Description
"pagination"	Page	Paging and sorting of the result.
"ids"	Array<Number>	Lock identifiers to match.
"orchestrationJobIds"	Array<String>	Orchestration job identifiers to match.
"serviceInstanceIds"	Array<String>	Service instance identifiers to match.
"owners"	Array<String>	Lock owner names to match.
"expiresBefore"	DateTime	Upper bound of the expiry time.
"expiresAfter"	DateTime	Lower bound of the expiry time.

3.5 struct OrchestrationLockRequest

Exclusive reservation of a service instance.

Object Field	Value Type	Description
"serviceInstanceId"	String	Service instance identifier `<System>|<serviceDefinition>|<version>`.
"owner"	String	System for which the instance is locked.
"expiresAt"	DateTime	UTC expiry of the lock.

3.6 struct OrchestrationLockResponse

A lock on a service instance.

Object Field	Value Type	Description
"id"	Number	Identifier of the lock.
"orchestrationJobId"	String	Orchestration job that created the lock.
"serviceInstanceId"	String	Service instance identifier `<System>|<serviceDefinition>|<version>`.
"owner"	String	Name of the system owning the lock.
"expiresAt"	DateTime	UTC expiry of the lock.
"temporary"	Boolean	True for a lock held only during an orchestration.

3.7 struct Page

Paging and sorting; all fields optional.

Object Field	Value Type	Description
"page"	Number	Zero-based page number.
"size"	Number	Number of records per page (at most `max.page.size`, default 1000).
"direction"	String	Sort direction, `ASC` or `DESC`.
"sortField"	String	Field to sort by.

3.8 Primitives

As all messages are encoded using the JSON format [4], the following primitive constructs, part of that standard, become available. Note that the official standard is defined in terms of parsing rules, while this list only concerns syntactic information. Furthermore, the Object and Array types are given optional generic type parameters, which are used in this document to signify when pair values or elements are expected to conform to certain types.

Type	Description
Array	A JSON Array [4]; Array<A> has elements of type A.
Boolean	JSON Boolean, `true` or `false`.
DateTime	JSON String with an ISO 8601 UTC timestamp, e.g. `2026-10-22T12:00:00Z`.
ExceptionType	One of `ARROWHEAD`, `INVALID_PARAMETER`, `AUTH`, `FORBIDDEN`, `DATA_NOT_FOUND`, `TIMEOUT`, `LOCKED`, `INTERNAL_SERVER_ERROR`, `EXTERNAL_SERVER_ERROR` (JSON String).
Number	JSON Number, an integer.
Object	JSON Object; Object<A> has string keys and values of type A.
String	JSON String.

4 References

[1] R. Fielding, M. Nottingham, and J. Reschke, “Http/1.1,” IETF, RFC 9112, 2022.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “serviceOrchestrationLockManagement – Service Description (DynamicServiceOrchestration),” Eclipse Arrowhead, SD 5.2.2, 2026, dynamicServiceOrchestration-v5.2.2-serviceOrchestrationLockManagement-SD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	