1 Interface overview

Mandatory mutual TLS, Arrowhead token/certificate binding, JSON request and response documents. Echo responses, orchestration subscription IDs, authorization public keys and encryption IV responses are text. Certificate-only operations and management are distinguished in the table.

1.1 HTTPS interface operations

HTTPS uses JSON unless an operation specifies text. Request bodies are limited to 1 MiB; upstream responses to 8 MiB. Identity-token format: `Bearer IDENTITY-TOKEN//token`. Certificate-only identity operations still require verified mutual TLS and apply credential/certificate binding.

Method	Path	Access
GET	/serviceorchestration/general/mgmt/get-config	management
POST	/serviceorchestration/general/mgmt/logs	management
POST	/serviceorchestration/orchestration/pull	identity
POST	/serviceorchestration/orchestration/subscribe	identity
DELETE	/serviceorchestration/orchestration/unsubscribe/{id}	identity
POST	/serviceorchestration/orchestration/mgmt/push/subscribe	management
POST	/serviceorchestration/orchestration/mgmt/push/trigger	management
DELETE	/serviceorchestration/orchestration/mgmt/push/unsubscribe	management
POST	/serviceorchestration/orchestration/mgmt/push/query	management
POST	/serviceorchestration/orchestration/mgmt/history/query	management
POST	/serviceorchestration/orchestration/mgmt/simple-store/create	management
POST	/serviceorchestration/orchestration/mgmt/simple-store/query	management
PUT	/serviceorchestration/orchestration/mgmt/simple-store/modify-priorities	management
DELETE	/serviceorchestration/orchestration/mgmt/simple-store/remove	management

Errors contain errorMessage, errorCode, exceptionType, origin and timestamp. Exact validation/error parity and all Java security-policy settings remain release gates. Unknown routes return 404; unavailable authorities fail closed.

2 Limitations

Stored candidate priority selection, preferred providers, matchmaking, history, subscriptions and explicit HTTPS push jobs are implemented. Store results intentionally retain Java's sparse result shape. Full Java query/priority-normalization semantics, event-driven reevaluation, MQTT callbacks and Java state import are not ported. Unsupported simple-store criteria are reported as ignored warnings.