1 Interface overview

HTTPS, mandatory mutual TLS, Arrowhead identity-token header and JSON request/response documents. General management is sysop/whitelist protected; enrollment endpoints use approved certificate fingerprints and profile/serial checks instead of ordinary identity tokens. Error responses contain errorMessage, errorCode, origin and timestamp. Exact DTO and status/error parity is not certified.

1.1 HTTPS interface operations

The listener is HTTPS with JSON by default; raw configuration and CRL responses use their declared media types. A request body is capped at 1 MiB. The table records implemented routes, not a claim of complete behavioral conformance.

Method	Path	Access
GET	/choreographer/mgmt/plans	management
GET	/choreographer/mgmt/sessions	management
GET	/choreographer/mgmt/session-steps	management
GET	/choreographer/mgmt/worklog	management
GET	/choreographer/mgmt/executors	management
GET	/choreographer/mgmt/plans/{id}	management
DELETE	/choreographer/mgmt/plans/{id}	management
GET	/choreographer/mgmt/executors/{id}	management
DELETE	/choreographer/mgmt/executors/{id}	management
POST	/choreographer/mgmt/plans	management
GET	/choreographer/mgmt/plans/{id}/check	management
POST	/choreographer/mgmt/executors	management
POST	/choreographer/executor/register	identity
DELETE	/choreographer/executor/unregister	identity
POST	/choreographer/session/start	identity
POST	/choreographer/mgmt/sessions/start	management
DELETE	/choreographer/session/abort/{id}	identity
DELETE	/choreographer/mgmt/sessions/{id}	management
POST	/choreographer/executor/notify-step-done	identity
POST	/choreographer/orchestration-result/{correlationId}	identity
GET	/choreographer/monitor/echo	certificate
GET	/choreographer/general/mgmt/get-config	management
POST	/choreographer/general/mgmt/logs	management

1.2 Important delimitations

This implementation is a development profile, not a certified interchangeable Java replacement. All systems use private JSON snapshots rather than the Java databases. MQTT application APIs, exhaustive DTO normalization and error parity, automatic data migration and production qualification remain outstanding.

- Local synchronous orchestration and executor start/callback flow are implemented. Async orchestration callbacks return 501. Java executor dependency negotiation, optimal selection, session notifications and remote abort propagation are incomplete.