1 Interface overview

HTTPS, mandatory mutual TLS, Arrowhead identity-token header and JSON request/response documents. General management is sysop/whitelist protected; enrollment endpoints use approved certificate fingerprints and profile/serial checks instead of ordinary identity tokens. Error responses contain errorMessage, errorCode, origin and timestamp. Exact DTO and status/error parity is not certified.

1.1 HTTPS interface operations

The listener is HTTPS with JSON by default; raw configuration and CRL responses use their declared media types. A request body is capped at 1 MiB. The table records implemented routes, not a claim of complete behavioral conformance.

Method	Path	Access
GET	/onboarding/echo	certificate
GET	/onboarding/mgmt/enrollments	management
GET	/onboarding/mgmt/enrollments/{deviceName}	management
PUT	/onboarding/mgmt/enrollments/{deviceName}	management
POST	/onboarding/certificate/name	enrollment
POST	/onboarding/certificate/csr	enrollment
POST	/onboarding/device	enrollment
POST	/onboarding/system	enrollment
POST	/onboarding/device/offboard	enrollment
POST	/onboarding/mgmt/enrollments/{deviceName}/offboard	management
DELETE	/onboarding/mgmt/enrollments/{deviceName}	management
GET	/onboarding/monitor/echo	certificate
GET	/onboarding/general/mgmt/get-config	management
POST	/onboarding/general/mgmt/logs	management

1.2 Important delimitations

This implementation is a development profile, not a certified interchangeable Java replacement. All systems use private JSON snapshots rather than the Java databases. MQTT application APIs, exhaustive DTO normalization and error parity, automatic data migration and production qualification remain outstanding.

- Enrollment records use JSON, not the Java database. System/identity/registry operations form a partial compensating saga, not a distributed transaction. Complete renewal, crash recovery, withdrawal of approved systems and prerequisite-service discovery require further work.