1 Interface overview

HTTPS, mandatory mutual TLS, Arrowhead identity-token header and JSON request/response documents. General management is sysop/whitelist protected; enrollment endpoints use approved certificate fingerprints and profile/serial checks instead of ordinary identity tokens. Error responses contain errorMessage, errorCode, origin and timestamp. Exact DTO and status/error parity is not certified.

1.1 HTTPS interface operations

The listener is HTTPS with JSON by default; raw configuration and CRL responses use their declared media types. A request body is capped at 1 MiB. The table records implemented routes, not a claim of complete behavioral conformance.

Method	Path	Access
`POST`	`/translation/bridge/discovery`	identity
`POST`	`/translation/bridge/mgmt/discovery`	management
`POST`	`/translation/bridge/negotiation`	identity
`POST`	`/translation/bridge/mgmt/negotiation`	management
`DELETE`	`/translation/bridge/abort/{bridgeId}`	identity
`DELETE`	`/translation/bridge/mgmt/abort`	management
`POST`	`/translation/bridge/mgmt/query`	management
`POST`	`/translation/event/report`	identity
`GET`	`/translation/monitor/echo`	certificate
`GET`	`/translation/general/mgmt/get-config`	management
`POST`	`/translation/general/mgmt/logs`	management

1.2 Important delimitations

This implementation is a development profile, not a certified interchangeable Java replacement. All systems use private JSON snapshots rather than the Java databases. MQTT application APIs, exhaustive DTO normalization and error parity, automatic data migration and production qualification remain outstanding.

- Port of the Java TranslatorBridgeEngine (2026-10-24): interface translators (interfaceBridgeManagement) and data model translators (dataModelTranslation, or dataModelTranslatorFactoryControl factories) are discovered in the ServiceRegistry by their metadata; check-targets, initialize-bridge and abort-bridge follow the Java driver contracts; bridge statuses, transitions, reports and the 8-hour discovery cleanup are the Java ones.
- Translators are called over mutual TLS with the identity token; translators whose interfaceBridgeManagement interface uses a TOKEN_AUTH policy are not selected, and custom translator configuration (a TODO in the Java reference) is not sent.
- Default matchmaking takes the first acceptable translator; the Java matchmaker beans are not pluggable.