authorizationManagement MQTT/TLS/JSON

Interface Design Description

Service ID: *"authorizationManagement"*

Abstract
This document describes the MQTT protocol with TLS payload security and JSON payload encoding variant of the `authorizationManagement` service of the ConsumerAuthorization system.

Contents

1 Overview **3**

2 Service Operations **4**
2.1 operation grant-policies . . . 4
2.2 operation revoke-policies . . . 5
2.3 operation query-policies . . . 5
2.4 operation check-policies . . . 6

3 Data Models **7**
3.1 struct MqttRequestTemplate . . . 7
3.2 struct MqttResponseTemplate . . . 7
3.3 struct ErrorMessage . . . 7
3.4 struct AuthorizationMgmtGrantListRequest . . . 7
3.5 struct AuthorizationMgmtGrantRequest . . . 7
3.6 struct AuthorizationPolicy . . . 8
3.7 struct AuthorizationPolicyListResponse . . . 8
3.8 struct AuthorizationPolicyRequest . . . 8
3.9 struct AuthorizationPolicyResponse . . . 8
3.10 struct AuthorizationQueryRequest . . . 9
3.11 struct AuthorizationVerifyListRequest . . . 9
3.12 struct AuthorizationVerifyListResponse . . . 9
3.13 struct AuthorizationVerifyRequest . . . 9
3.14 struct AuthorizationVerifyResponse . . . 10
3.15 struct MetadataRequirement . . . 10
3.16 struct Page . . . 10
3.17 Primitives . . . 10

4 References **12**

5 Revision History **13**
5.1 Amendments . . . 13
5.2 Quality Assurance . . . 13

1 Overview

This document describes the `authorizationManagement` service interface of the ConsumerAuthorization system over MQTT, which provides operator management of authorization policies at the management level, and bulk evaluation of authorization questions.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	MQTT	3.1.1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `authorizationManagement` service interface

This document provides the Interface Design Description IDD to the *authorizationManagement – Service Description* document [5]. The operations, their semantics and the data models are the same as in the HTTP/TLS/JSON IDD [6]; this document specifies the MQTT binding.

The MQTT interface is offered only when the system runs with `mqtt.api.enabled=true`; it is then registered with the interface template `generic_mqtts` (`generic_mqtt` without TLS), the broker address and port (`mqtt.broker.address`, `mqtt.broker.port`) and the base topic `arrowhead/consumer-authorization/authorization/management/`. In the Arrowhead-test-cloud-java deployment the MQTT interfaces of the core systems are disabled.

2 Service Operations

The provider subscribes to one topic per operation, the base topic followed by the operation name:

Operation	Request topic
`grant-policies`	`arrowhead/consumer-authorization/authorization/management/grant-policies`
`revoke-policies`	`arrowhead/consumer-authorization/authorization/management/revoke-policies`
`query-policies`	`arrowhead/consumer-authorization/authorization/management/query-policies`
`check-policies`	`arrowhead/consumer-authorization/authorization/management/check-policies`

A consumer publishes a request envelope (MqttRequestTemplate) to the topic and receives the answer (MqttResponseTemplate) on its own `responseTopic`. The `authentication` field carries the requester's identity according to the provider's authentication policy: `IDENTITY-TOKEN//<token>` (outsourced or internal policy), `SYSTEM//<name>` (declared policy) or the requester's X.509 certificate (certificate policy). The `status` of the response uses the HTTP status code numbers (200, 201, 204, 400, 401, 403, 404, 408, 423, 500, 503); on error the payload is an ErrorMessage.

```
{
  "traceId": "a1b2c3",
  "authentication": "IDENTITY-TOKEN//<token>",
  "responseTopic": "arrowhead/response/TemperatureDisplay/a1b2c3",
  "qosRequirement": 1,
  "params": {},
  "payload": {}
}
```

Listing 1: Request envelope.

```
{
  "status": 200,
  "traceId": "a1b2c3",
  "receiver": "TemperatureDisplay",
  "payload": {}
}
```

Listing 2: Response envelope.

2.1 PUBLISH `arrowhead/consumer-authorization/authorization/management/grant-policies`

Operation: grant-policies
Input: AuthorizationMgmtGrantListRequest
Output: AuthorizationPolicyListResponse

Creates management-level policies for the given providers and targets.

```
{
  "list": [
    {
      "cloud": "LOCAL",
      "provider": "TemperatureSensor",
      "targetType": "SERVICE_DEF",
      "target": "temperatureReading",
```

```
      "description": "Display may read",
      "defaultPolicy": {
        "policyType": "WHITELIST",
        "policyList": [
          "TemperatureDisplay"
        ],
        "policyMetadataRequirement": {
          "unit": "celsius"
        }
      },
      "scopedPolicies": {
        "read": {
          "policyType": "ALL"
        }
      }
    }
  ]
}
```

Listing 3: Payload of an grant-policies request.

2.2 PUBLISH arrowhead/consumer-authorization/authorization/management/revoke-policies

Operation: revoke-policies
Input: Array<String>

Removes policies by instance identifier.

```
[
  "TemperatureSensor|temperatureReading|1.0.0"
]
```

Listing 4: Payload of an revoke-policies request.

2.3 PUBLISH arrowhead/consumer-authorization/authorization/management/query-policies

Operation: query-policies
Input: AuthorizationQueryRequest
Output: AuthorizationPolicyListResponse

Returns a page of policies of either level matching the filter.

```
{
  "pagination": {
    "page": 0,
    "size": 10,
    "direction": "ASC",
    "sortField": "createdAt"
  },
  "level": "MGMT",
  "providers": [
    "TemperatureSensor"
  ],
  "instanceIds": [
    "TemperatureSensor|temperatureReading|1.0.0"
  ],
  "cloudIdentifiers": [
    "string"
  ],
  "targetNames": [
    "string"
```

```
  ],
  "targetType": "SERVICE_DEF"
}
```

Listing 5: Payload of an query-policies request.

2.4 PUBLISH arrowhead/consumer-authorization/authorization/management/check-policies

Operation: check-policies
Input: AuthorizationVerifyListRequest
Output: AuthorizationVerifyListResponse

Evaluates a list of authorization questions and returns the answer for each.

```
{
  "list": [
    {
      "provider": "TemperatureSensor",
      "consumer": "TemperatureDisplay",
      "cloud": "LOCAL",
      "targetType": "SERVICE_DEF",
      "target": "temperatureReading",
      "scope": "read"
    }
  ]
}
```

Listing 6: Payload of an check-policies request.

3 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Each *struct* denotes a JSON Object with the named fields; fields that are not needed may be omitted.

3.1 struct MqttRequestTemplate

The request envelope.

Object Field	Value Type	Description
"traceId"	String	Identifier chosen by the requester, returned in the response.
"authentication"	String	Identity of the requester (see Section 2).
"responseTopic"	String	Topic on which the response is published.
"qosRequirement"	Number	MQTT QoS of the response (0, 1 or 2).
"params"	Object<String>	Optional parameters (the query parameters of the HTTP binding).
"payload"	Object	The operation input.

3.2 struct MqttResponseTemplate

The response envelope.

Object Field	Value Type	Description
"status"	Number	Status code.
"traceId"	String	The trace identifier of the request.
"receiver"	String	Name of the requester.
"payload"	Object	The operation output, or an ErrorMessage.

3.3 struct ErrorMessage

Object Field	Value Type	Description
"errorMessage"	String	
"errorCode"	Number	
"exceptionType"	ExceptionType	
"origin"	String	

3.4 struct AuthorizationMgmtGrantListRequest

Management-level policies to create.

Object Field	Value Type	Description
"list"	Array<AuthorizationMgmtGrantRequest>	The list of request items.

3.5 struct AuthorizationMgmtGrantRequest

A management-level authorization policy for one provider and target.

Object Field	Value Type	Description
"cloud"	String	Cloud identifier of the consumer cloud the policy applies to; `LOCAL` for the own cloud.
"provider"	String	Provider system the policy is set for.
"targetType"	String	Target type: `SERVICE_DEF` or `EVENT_TYPE`.
"target"	String	Target of the policy or token: a service definition or event type.
"description"	String	Free-text description.
"defaultPolicy"	AuthorizationPolicyRequest	Policy that applies to all operations without a scoped policy.
"scopedPolicies"	Object<AuthorizationPolicyRequest>	Policies for individual operations, keyed by operation name.

3.6 struct AuthorizationPolicy

One policy rule.

Object Field	Value Type	Description
"policyType"	AuthorizationPolicyType	Policy type: `ALL`, `WHITELIST`, `BLACKLIST` or `SYS_METADATA`.
"policyList"	Array<String>	System names of the white- or blacklist.
"policyMetadata Requirement"	MetadataRequirement	Metadata the consumer system must have (`SYS_METADATA`).

3.7 struct AuthorizationPolicyListResponse

List of authorization policies.

Object Field	Value Type	Description
"entries"	Array<AuthorizationPolicy Response>	Matching records of the current page.
"count"	Number	Total number of matching records (all pages).

3.8 struct AuthorizationPolicyRequest

One policy rule.

Object Field	Value Type	Description
"policyType"	String	Policy type: `ALL`, `WHITELIST`, `BLACKLIST` or `SYS_METADATA`.
"policyList"	Array<String>	System names of the white- or blacklist.
"policyMetadata Requirement"	MetadataRequirement	Metadata the consumer system must have (`SYS_METADATA`).

3.9 struct AuthorizationPolicyResponse

A stored authorization policy.

Object Field	Value Type	Description
"instanceId"	String	Policy instance identifier `<MGMT or PR>|<cloud>|<provider>|<targetType>|<target>`.
"level"	AuthorizationLevel	Policy level: `MGMT` (set by an operator) or `PROVIDER` (set by the provider itself).
"cloud"	String	Cloud identifier of the consumer cloud the policy applies to; `LOCAL` for the own cloud.
"provider"	String	Provider system the policy protects.
"targetType"	AuthorizationTargetType	Target type: `SERVICE_DEF` or `EVENT_TYPE`.
"target"	String	Target of the policy or token: a service definition or event type.
"description"	String	Free-text description.
"defaultPolicy"	AuthorizationPolicy	Policy that applies to all operations without a scoped policy.
"scopedPolicies"	Object<AuthorizationPolicy>	Policies for individual operations, keyed by operation name.
"createdBy"	String	Name of the system that created the record.
"createdAt"	DateTime	UTC time of creation.

3.10 struct AuthorizationQueryRequest

Filter for authorization policies.

Object Field	Value Type	Description
"pagination"	Page	Paging and sorting of the result.
"level"	String	Policy level to match, `MGMT` or `PROVIDER`.
"providers"	Array<String>	Provider system names to match.
"instanceIds"	Array<String>	Policy instance identifiers to match.
"cloudIdentifiers"	Array<String>	Cloud identifiers to match.
"targetNames"	Array<String>	Target names to match.
"targetType"	String	Target type: `SERVICE_DEF` or `EVENT_TYPE`.

3.11 struct AuthorizationVerifyListRequest

Authorization checks to evaluate.

Object Field	Value Type	Description
"list"	Array<AuthorizationVerifyRequest>	The list of request items.

3.12 struct AuthorizationVerifyListResponse

Results of authorization checks.

Object Field	Value Type	Description
"entries"	Array<AuthorizationVerifyResponse>	Matching records of the current page.
"count"	Number	Total number of matching records (all pages).

3.13 struct AuthorizationVerifyRequest

One authorization question: may the consumer use the target (operation) of the provider?

Object Field	Value Type	Description
"provider"	String	Provider system; for `verify` defaults to the requester.
"consumer"	String	Consumer system; for `verify` defaults to the requester.
"cloud"	String	Cloud of the consumer, `LOCAL` by default.
"targetType"	String	Target type: `SERVICE_DEF` or `EVENT_TYPE`.
"target"	String	Target of the policy or token: a service definition or event type.
"scope"	String	Operation to check; empty checks the default policy.

3.14 struct AuthorizationVerifyResponse

The answer to one authorization question.

Object Field	Value Type	Description
"provider"	String	Name of the provider system.
"consumer"	String	Name of the consumer system.
"cloud"	String	Cloud of the consumer.
"targetType"	AuthorizationTargetType	Target type: `SERVICE_DEF` or `EVENT_TYPE`.
"target"	String	Target of the policy or token: a service definition or event type.
"scope"	String	The checked operation.
"granted"	Boolean	Result of the check: true when the consumer is authorized.

3.15 struct MetadataRequirement

A JSON object of metadata requirements: each key is a metadata path (dot notation), each value the required value or an operator object such as `{"op": "LESS_THAN", "value": 10}`.

3.16 struct Page

Paging and sorting; all fields optional.

Object Field	Value Type	Description
"page"	Number	Zero-based page number.
"size"	Number	Number of records per page (at most `max.page.size`, default 1000).
"direction"	String	Sort direction, `ASC` or `DESC`.
"sortField"	String	Field to sort by.

3.17 Primitives

As all messages are encoded using the JSON format [4], the following primitive constructs, part of that standard, become available.

Type	Description
Array	A JSON Array [4]; Array<A> has elements of type A.
AuthorizationLevel	One of `MGMT`, `PROVIDER` (JSON String).
AuthorizationPolicyType	One of `ALL`, `WHITELIST`, `BLACKLIST`, `SYS_METADATA` (JSON String).
AuthorizationTargetType	One of `SERVICE_DEF`, `EVENT_TYPE` (JSON String).
Boolean	JSON Boolean, `true` or `false`.
DateTime	JSON String with an ISO 8601 UTC timestamp, e.g. `2026-10-22T12:00:00Z`.
ExceptionType	One of `ARROWHEAD`, `INVALID_PARAMETER`, `AUTH`, `FORBIDDEN`, `DATA_NOT_FOUND`, `TIMEOUT`, `LOCKED`, `INTERNAL_SERVER_ERROR`, `EXTERNAL_SERVER_ERROR` (JSON String).
Number	JSON Number, an integer.
Object	JSON Object; Object<A> has string keys and values of type A.
String	JSON String.

4 References

[1] A. Banks and R. Gupta, “Mqtt version 3.1.1,” OASIS, Standard, 2014.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “authorizationManagement – Service Description (ConsumerAuthorization),” Eclipse Arrowhead, SD 5.2.2, 2026, consumerAuthorization-v5.2.2-authorizationManagement-SD.pdf.

[6] ——, “authorizationManagement HTTP/TLS/JSON – Interface Design Description (ConsumerAuthorization),” Eclipse Arrowhead, IDD 5.2.2, 2026, consumerAuthorization-v5.2.2-authorizationManagement-HTTP-IDD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	