1 Interface overview

Mandatory mutual TLS, Arrowhead token/certificate binding, JSON request and response documents. Echo responses, orchestration subscription IDs, authorization public keys and encryption IV responses are text. Certificate-only operations and management are distinguished in the table.

1.1 HTTPS interface operations

HTTPS uses JSON unless an operation specifies text. Request bodies are limited to 1 MiB; upstream responses to 8 MiB. Identity-token format: `Bearer IDENTITY-TOKEN//token`. Certificate-only identity operations still require verified mutual TLS and apply credential/certificate binding.

Method	Path	Access
GET	/serviceregistry/general/mgmt/get-config	management
POST	/serviceregistry/general/mgmt/logs	management
GET	/serviceregistry/monitor/echo	certificate
POST	/serviceregistry/device-discovery/register	identity
POST	/serviceregistry/device-discovery/lookup	identity
DELETE	/serviceregistry/device-discovery/revoke/{name}	identity
POST	/serviceregistry/system-discovery/register	identity
POST	/serviceregistry/system-discovery/lookup	identity
DELETE	/serviceregistry/system-discovery/revoke	identity
POST	/serviceregistry/service-discovery/register	identity
POST	/serviceregistry/service-discovery/lookup	identity
DELETE	/serviceregistry/service-discovery/revoke/{instanceId}	identity
POST	/serviceregistry/mgmt/devices/query	management
POST	/serviceregistry/mgmt/devices	management
DELETE	/serviceregistry/mgmt/devices	management
PUT	/serviceregistry/mgmt/devices	management
POST	/serviceregistry/mgmt/systems/query	management
POST	/serviceregistry/mgmt/systems	management
DELETE	/serviceregistry/mgmt/systems	management
PUT	/serviceregistry/mgmt/systems	management
POST	/serviceregistry/mgmt/service-definitions/query	management
POST	/serviceregistry/mgmt/service-definitions	management
DELETE	/serviceregistry/mgmt/service-definitions	management
POST	/serviceregistry/mgmt/service-instances/query	management
POST	/serviceregistry/mgmt/service-instances	management
DELETE	/serviceregistry/mgmt/service-instances	management
PUT	/serviceregistry/mgmt/service-instances	management
POST	/serviceregistry/mgmt/interface-templates/query	management
POST	/serviceregistry/mgmt/interface-templates	management

Method	Path	Access
DELETE	/serviceregistry/mgmt/interface-templates	management

Errors contain errorMessage, errorCode, exceptionType, origin and timestamp. Exact validation/error parity and all Java security-policy settings remain release gates. Unknown routes return 404; unavailable authorities fail closed.

2 Limitations

Registry records, interface templates, expiry, cascades, authorized discovery and management are implemented. Java SQL import, the full property-validator catalogue, normalization, advanced version/time/address matching and all discovery-policy options need additional work. Unsupported custom validators fail explicitly; they are not silently accepted.