GateTunnel

Interface Design Description

Eclipse Arrowhead 5.2.2 | support system | Revision 2026-11-09 | REVIEW DRAFT

Purpose and document structure

This document consolidates the system interface designs. Detailed Java service/transport IDDs are retained as separate appendices, followed by available Go and Rust interface descriptions. The current cross-language sections below precede the detailed implementation appendices. Appendix dates and release labels belong to the retained baseline, not to a newly qualified release. Existing descriptions have been assembled from the primary trees; no live interoperability or semantic-parity claim is made.

Java implementation

Primary folder: Eclipse-Arrowhead-java/ah5-GateTunnel-java-spring. 4 detailed Java IDD source document(s) are included in the appendices. Their architecture, operation parameters, models, transport bindings, access rules and errors remain associated with Java. They must not be read as automatically implemented by the ports.

Go implementation

Primary folder: Eclipse-Arrowhead-go/ah5-GateTunnel-go.

GateTunnel - Go 5.2.2

Standalone support system, reorganized on 2026-10-28 following the Eclipse-Arrowhead-java distribution layout. Build and operate from this folder; no original Arrowhead checkout or sibling source module is required. The executable is bin/GateTunnel. Entry point: ./cmd/gatetunnel. Module: arrowhead/ah5-support-go/gatetunnel. See DEPLOYMENT.md for configuration and standalone container use. Existing compatibility limits remain in the copied upstream documentation and UPSTREAM-README.md. The dedicated launcher selects only this support-system role. The formerly shared internal runtime and regression tests are copied locally, not linked from another tree. Files for common helpers and other route implementations remain in that private runtime; this packaging does not claim new functionality or Java parity. Documentation and license notices are included in this folder. Source provenance and import-only rewrites are listed in the distribution's SOURCE-MANIFEST.json. No running cloud or upstream source was changed.

Listening port

Built-in default 127.0.0.1:8453 (Arrowhead default). The shipped config.json, compose.yaml and Dockerfile use the same port on all interfaces ("listen": "0.0.0.0:8453"; 8540-8555 layout before 2026-11-09). Override with "listen" in the configuration file, SERVER_PORT=N or -server.port N; the port overrides keep the configured host. See [LISTENING-PORTS.md](../LISTENING-PORTS.md) for precedence and all systems.

Documented behavior and remaining work

System	Implemented behavior	Remaining work
GateTunnel	Legacy-mTLS relay forwarding, owner-constrained session control, expired-session rejection	AH-GT-1 data plane; control-session rows are not additional AMQP tunnels; listeners are volatile and renegotiated on restart

Detailed implementation evidence

1 native Go IDD document(s) are included in the appendices. Their protocol and storage descriptions apply to that implementation only. Current primary-folder ownership and current listening-port notes above supersede historical paths or example ports in those retained documents.

Rust implementation

Primary folder: Eclipse-Arrowhead-rust/ah5-GateTunnel-rust.

GateTunnel (Rust)

Arrowhead 5.2.2 GateTunnel support system. Entry point src/main.rs is built as binary gatetunnel by the shared crate in ../ah5-support-runtime-rust (arrowhead-support-rust).

- examples/gatetunnel.json - example configuration (master copy: ../ah5-support-runtime-rust/examples/)

- documentation/ - SysD/SysDD/IDD/SD sources (symlink into ../ah5-support-runtime-rust/documentation/GateTunnel, where the contract generator writes)

Run: cargo run -p arrowhead-support-rust --bin gatetunnel -- <config.json>

Listening port

Default 127.0.0.1:8453 (Arrowhead default, role gatetunnel). Override with "listen": "host:port" in the configuration, SERVER_PORT=N or --server.port N; the port overrides keep the configured host. See [LISTENING-PORTS.md](../LISTENING-PORTS.md) for precedence and all systems.

Documented behavior and remaining work

System	Implemented behavior	Remaining work
GateTunnel	Signed AH-GT-1 exchange, dynamic mTLS listeners, encrypted forwarding, bounded sessions, replay and scoped operation guards	Exhaustive DTO/chaos tests, independent review; segment-exact grants are stricter than reference descendant grants

Detailed implementation evidence

1 native Rust IDD document(s) are included in the appendices. Their protocol and storage descriptions apply to that implementation only. Current primary-folder ownership and current listening-port notes above supersede historical paths or example ports in those retained documents.

Build and state ownership

Core entry points are built by arrowhead-core-rust; the ordinary support entry points are built by arrowhead-support-rust using the shared support runtime. LocalCloudManager has its own crate. Per-system documentation links may point into the shared documentation catalog. Independent identity and state configuration is still required. Read the native appendix for persistence and restart semantics.

Cross-language qualification

Identical system names or HTTP paths do not establish interoperability. For the selected implementation, verify registered service versions and metadata, method/path and payload models, null and optional-field handling, success/error bodies, authentication and per-operation authorization, timeout/retry behavior and persistence across restart. Java MQTT/AMQP descriptions apply to a port only where its own implementation evidence explicitly supports them. Missing transports must not be advertised. State conversion from Java SQL to native snapshots, secret provisioning, backup/restore and rollback require implementation-specific procedures. No data migration, deployment or cloud reconfiguration was performed for this document set.

Detailed appendices and provenance

- Java: Eclipse-Arrowhead-java/ah5-GateTunnel-java-spring/documentation/v5.2.2/GateTunnel-v5.2.2-gateTunnelConnection-HTTP-IDD.tex

- Java: Eclipse-Arrowhead-java/ah5-GateTunnel-java-spring/documentation/v5.2.2/GateTunnel-v5.2.2-gateTunnelKey-HTTP-IDD.tex

- Java: Eclipse-Arrowhead-java/ah5-GateTunnel-java-spring/documentation/v5.2.2/GateTunnel-v5.2.2-gateTunnelManagement-HTTP-IDD.tex

- Java: Eclipse-Arrowhead-java/ah5-GateTunnel-java-spring/documentation/v5.2.2/GateTunnel-v5.2.2-sysMonitor-AMQP-IDD.tex

- Go: Eclipse-Arrowhead-go/ah5-GateTunnel-go/documentation/GateTunnel/GateTunnel-HTTPS-IDD.tex

- Rust: Eclipse-Arrowhead-rust/ah5-support-runtime-rust/documentation/GateTunnel/GateTunnel-HTTPS-IDD.tex

The package sources/ folder retains the selected LaTeX, figures, bibliography, language README/build evidence and source snapshots for newly described contracts. source-manifest.json records SHA-256 hashes of original inputs. build-report.json records whether an appendix used an existing newer PDF or was compiled from source.

gateTunnelConnection HTTP/TLS/JSON

Interface Design Description

Service ID: *"gateTunnelConnection"*

Abstract
This document describes the HTTP/1.1 protocol with TLS payload security and JSON payload encoding variant of the `gateTunnelConnection` service of the GateTunnel system.

Contents

1 Overview **3**
1.1 Interface registration . . . 3

2 Service Operations **4**
2.1 operation connect-provider . . . 4
2.2 operation connect-consumer . . . 4
2.3 operation close-sessions . . . 5
2.4 operation open-provider-session . . . 5
2.5 operation open-consumer-session . . . 6

3 Data Models **7**
3.1 struct ClosePortsRequest . . . 7
3.2 struct ConnectConsumerRequest . . . 7
3.3 struct ConsumerSessionRequest . . . 7
3.4 struct ControlSessionRequest . . . 7
3.5 struct ControlSessionResult . . . 7
3.6 struct ProviderSessionRequest . . . 8
3.7 struct SessionEndpoint . . . 8
3.8 Primitives . . . 8

4 References **9**

5 Revision History **10**
5.1 Amendments . . . 10
5.2 Quality Assurance . . . 10

1 Overview

This document describes the `gateTunnelConnection` service interface of the GateTunnel system, which provides relay sessions between the local cloud and a neighbour cloud: provider and consumer sessions opened by the Gatekeeper, and the legacy control sessions.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	HTTP	1.1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `gateTunnelConnection` service interface

This document provides the Interface Design Description IDD to the *gateTunnelConnection – Service Description* document [5]. For further details about how this service is meant to be used, please consult that document.

The rest of this document describes how to realize the `gateTunnelConnection` service interface in detail. Both in terms of its operations (Section 2) and its information model (Section 3).

1.1 Interface registration

The service is registered in the ServiceRegistry with the interface template `generic_https`, policy `CERT_AUTH`, access address `gatetunnel`, port 8453 and base path `/gatetunnel`. The `operations` property of the interface lists the operations below with their method and path relative to the base path (path parameters are placeholders such as `{id}` that the consumer fills in):

Operation	Method	Path
`connect-provider`	POST	`/connect_provider`
`connect-consumer`	POST	`/connect_consumer`
`close-sessions`	POST	`/close_sessions`
`open-provider-session`	POST	`/intercloud/provider`
`open-consumer-session`	POST	`/intercloud/consumer`

2 Service Operations

The interfaces of the `gateTunnelConnection` service, its operations, data models and implementation are provided below. In particular, each subsection first names the HTTP method and path used to call the operation, after which it names the abstract operation from the `gateTunnelConnection` SD document, as well as input and output types.

Every request needs mutual TLS with a system or operator certificate of the cloud and `Authorization: Bearer IDENTITY-TOKEN//<token>`; the token is verified with Authentication and must belong to the system named by the certificate. Request and response bodies are `application/json` unless stated otherwise. Errors are answered with `{"error": "<text>"}` and the status codes `400 Bad Request` (invalid input), `401 Unauthorized` (no valid identity), `403 Forbidden` (caller not permitted), `404 Not Found`, `500 Internal Server Error`, `502 Bad Gateway` (a system it depends on failed) and `503 Service Unavailable` (overloaded).

2.1 POST /gatetunnel/connect_provider

Operation: connect-provider
Input: ControlSessionRequest
Output: ControlSessionResult

Creates a legacy control session for a provider (v4 API).

A successful call returns `201 Created` with the output in the body.

```
POST /gatetunnel/connect_provider HTTP/1.1
Host: gatetunnel:8453
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "providerCloud": "GoCloud|Company",
  "serviceDefinition": "temperatureReading",
  "queueId": "gatetunnel.7f3c2a10",
  "peerName": "GateTunnel-7f3c2a10"
}
```

Listing 1: An connect-provider invocation.

```
{
  "sessionId": "7f3c2a10",
  "queueId": "gatetunnel.7f3c2a10",
  "peerName": "GateTunnel-7f3c2a10",
  "serverPort": 8000,
  "state": "PROVIDER_READY"
}
```

Listing 2: An connect-provider response.

2.2 POST /gatetunnel/connect_consumer

Operation: connect-consumer
Input: ConnectConsumerRequest
Output: ControlSessionResult

Connects a consumer to a legacy control session.

A successful call returns `201 Created` with the output in the body.

```
POST /gatetunnel/connect_consumer HTTP/1.1
Host: gatetunnel:8453
```

```
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "queueId": "gatetunnel.7f3c2a10"
}
```

Listing 3: An connect-consumer invocation.

```
{
  "sessionId": "7f3c2a10",
  "queueId": "gatetunnel.7f3c2a10",
  "peerName": "GateTunnel-7f3c2a10",
  "serverPort": 8000,
  "state": "PROVIDER_READY"
}
```

Listing 4: An connect-consumer response.

2.3 POST /gatetunnel/close_sessions

Operation: close-sessions
Input: ClosePortsRequest
Output: Array<Object>

Closes legacy control sessions by port; returns the ports that failed.
A successful call returns `200 OK` with the output in the body.

```
POST /gatetunnel/close_sessions HTTP/1.1
Host: gatetunnel:8453
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "ports": [
    8080
  ]
}
```

Listing 5: An close-sessions invocation.

```
[
  {}
]
```

Listing 6: An close-sessions response.

2.4 POST /gatetunnel/intercloud/provider

Operation: open-provider-session
Input: ProviderSessionRequest
Output: SessionEndpoint

Gatekeeper only: opens a relay session towards a local provider for a negotiated foreign consumer.
A successful call returns `201 Created` with the output in the body.

```
POST /gatetunnel/intercloud/provider HTTP/1.1
Host: gatetunnel:8453
Authorization: Bearer IDENTITY-TOKEN//<token>
```

```
Content-Type: application/json

{
  "sessionId": "7f3c2a10",
  "consumer": "TemperatureDisplay",
  "consumerCloud": "LOCAL",
  "provider": "TemperatureSensor",
  "serviceDefinition": "temperatureReading",
  "peer": "GateTunnel.GoCloud.Company.arrowhead.eu",
  "target": 21.5
}
```

Listing 7: An open-provider-session invocation.

```
{
  "address": "gatetunnel",
  "port": 8201,
  "sessionId": "7f3c2a10"
}
```

Listing 8: An open-provider-session response.

2.5 POST /gatetunnel/intercloud/consumer

Operation: open-consumer-session
Input: ConsumerSessionRequest
Output: SessionEndpoint

Gatekeeper only: opens a local listener that forwards a local consumer's requests to the provider cloud. A successful call returns `201 Created` with the output in the body.

```
POST /gatetunnel/intercloud/consumer HTTP/1.1
Host: gatetunnel:8453
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "sessionId": "7f3c2a10",
  "consumer": "TemperatureDisplay",
  "providerCloud": "GoCloud|Company",
  "provider": "TemperatureSensor",
  "serviceDefinition": "temperatureReading",
  "peer": "GateTunnel.GoCloud.Company.arrowhead.eu"
}
```

Listing 9: An open-consumer-session invocation.

```
{
  "address": "gatetunnel",
  "port": 8201,
  "sessionId": "7f3c2a10"
}
```

Listing 10: An open-consumer-session response.

3 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is meant to denote a JSON Object that must contain certain fields, or names, with values conforming to explicitly named types. Fields that are not needed may be omitted or `null` in requests; empty fields are omitted in responses. As a complement to the primary types defined in this section, there is also a list of secondary types in Section 3.8, which are used to represent things like hashes, identifiers and texts.

3.1 struct ClosePortsRequest

Object Field	Value Type	Description
"ports"	Array<Number>	Control ports to close (a bare JSON array is also accepted).

3.2 struct ConnectConsumerRequest

Object Field	Value Type	Description
"queueId"	String	Relay queue of the provider session.

3.3 struct ConsumerSessionRequest

Object Field	Value Type	Description
"sessionId"	String	Session identifier from the provider cloud.
"consumer"	String	Consumer system.
"providerCloud"	String	Provider cloud.
"provider"	String	Provider system.
"serviceDefinition"	String	Service definition.
"peer"	String	Peer GateTunnel common name.

3.4 struct ControlSessionRequest

Object Field	Value Type	Description
"consumer"	Object	Consumer system descriptor.
"provider"	Object	Provider system descriptor.
"consumerCloud"	Object	Consumer cloud.
"providerCloud"	Object	Provider cloud.
"relay"	Object	Relay descriptor.
"serviceDefinition"	String	Service definition.
"queueId"	String	Relay queue; generated if absent.
"peerName"	String	Peer name; generated if absent.

3.5 struct ControlSessionResult

Object Field	Value Type	Description
"sessionId"	String	Session identifier.
"queueId"	String	Relay queue.
"peerName"	String	Peer name.
"serverPort"	Number	Local control port.
"state"	String	Session state.

3.6 struct ProviderSessionRequest

Object Field	Value Type	Description
"sessionId"	String	Session identifier.
"consumer"	String	Consumer system.
"consumerCloud"	String	Consumer cloud, must match the peer certificate.
"provider"	String	Provider system.
"serviceDefinition"	String	Service definition.
"peer"	String	Peer GateTunnel common name.
"target"	Object	Provider endpoint: `address`, `port`, `basePath` and the negotiated `operations`.

3.7 struct SessionEndpoint

Object Field	Value Type	Description
"address"	String	Advertised address of the local session listener.
"port"	Number	Port of the session listener.
"sessionId"	String	Session identifier.

3.8 Primitives

As all messages are encoded using the JSON format [4], the following primitive constructs, part of that standard, become available. Note that the official standard is defined in terms of parsing rules, while this list only concerns syntactic information. Furthermore, the Object and Array types are given optional generic type parameters, which are used in this document to signify when pair values or elements are expected to conform to certain types.

Type	Description
Array	A JSON Array [4]; Array<A> has elements of type A.
Number	JSON Number, an integer.
Object	JSON Object; Object<A> has string keys and values of type A.
String	JSON String.

4 References

[1] R. Fielding, M. Nottingham, and J. Reschke, “Http/1.1,” IETF, RFC 9112, 2022.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “gateTunnelConnection – Service Description (GateTunnel),” Eclipse Arrowhead, SD 5.2.2, 2026, gateTunnel-v5.2.2-gateTunnelConnection-SD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing
2	2026-10-30	5.2.2	Checked against the primary Java source tree (Eclipse-Arrowhead-java): services, operations, paths and data models unchanged.	Claude Opus 5.5 (draft)

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	

gateTunnelKey HTTP/TLS/JSON

Interface Design Description

Service ID: *"gateTunnelKey"*

Abstract
This document describes the HTTP/1.1 protocol with TLS payload security and JSON payload encoding variant of the `gateTunnelKey` service of the GateTunnel system.

Contents

1 Overview **3**
1.1 Interface registration 3

2 Service Operations **4**
2.1 operation public-key 4

3 Data Models **5**
3.1 struct PublicKey 5
3.2 Primitives 5

4 References **6**

5 Revision History **7**
5.1 Amendments 7
5.2 Quality Assurance 7

1 Overview

This document describes the `gateTunnelKey` service interface of the GateTunnel system, which provides publication of the GateTunnel's public key.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	HTTP	1.1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `gateTunnelKey` service interface

This document provides the Interface Design Description IDD to the *gateTunnelKey – Service Description* document [5]. For further details about how this service is meant to be used, please consult that document.

The rest of this document describes how to realize the `gateTunnelKey` service interface in detail. Both in terms of its operations (Section 2) and its information model (Section 3).

1.1 Interface registration

The service is registered in the ServiceRegistry with the interface template `generic_https`, policy `CERT_AUTH`, access address `gatetunnel`, port 8453 and base path `/gatetunnel`. The `operations` property of the interface lists the operations below with their method and path relative to the base path (path parameters are placeholders such as `{id}` that the consumer fills in):

Operation	Method	Path
`public-key`	GET	`/publickey`

2 Service Operations

The interfaces of the `gateTunnelKey` service, its operations, data models and implementation are provided below. In particular, each subsection first names the HTTP method and path used to call the operation, after which it names the abstract operation from the `gateTunnelKey` SD document, as well as input and output types.

Every request needs mutual TLS with a system or operator certificate of the cloud and `Authorization: Bearer IDENTITY-TOKEN//<token>`; the token is verified with Authentication and must belong to the system named by the certificate. Request and response bodies are `application/json` unless stated otherwise. Errors are answered with `{ërror: ẗext>}` and the status codes `400 Bad Request` (invalid input), `401 Unauthorized` (no valid identity), `403 Forbidden` (caller not permitted), `404 Not Found`, `500 Internal Server Error`, `502 Bad Gateway` (a system it depends on failed) and `503 Service Unavailable` (overloaded).

2.1 GET /gatetunnel/publickey

Operation: public-key
Output: PublicKey

Returns the public key of the GateTunnel certificate.

A successful call returns `200 OK` with the output in the body.

```
GET /gatetunnel/publickey HTTP/1.1
Host: gatetunnel:8453
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 1: An public-key invocation.

```
{
  "algorithm": "EC",
  "format": "X.509",
  "publicKey": "-----BEGIN PUBLIC KEY-----\\n..."
}
```

Listing 2: An public-key response.

3 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is meant to denote a JSON Object that must contain certain fields, or names, with values conforming to explicitly named types. Fields that are not needed may be omitted or `null` in requests; empty fields are omitted in responses. As a complement to the primary types defined in this section, there is also a list of secondary types in Section 3.2, which are used to represent things like hashes, identifiers and texts.

3.1 struct PublicKey

Object Field	Value Type	Description
"algorithm"	String	Key algorithm.
"format"	String	`X.509`.
"publicKey"	String	Public key of the GateTunnel certificate, Base64.

3.2 Primitives

As all messages are encoded using the JSON format [4], the following primitive constructs, part of that standard, become available. Note that the official standard is defined in terms of parsing rules, while this list only concerns syntactic information. Furthermore, the Object and Array types are given optional generic type parameters, which are used in this document to signify when pair values or elements are expected to conform to certain types.

Type	Description
Array	A JSON Array [4]; Array<A> has elements of type A.
Object	JSON Object; Object<A> has string keys and values of type A.
String	JSON String.

4 References

[1] R. Fielding, M. Nottingham, and J. Reschke, “Http/1.1,” IETF, RFC 9112, 2022.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “gateTunnelKey – Service Description (GateTunnel),” Eclipse Arrowhead, SD 5.2.2, 2026, gateTunnel-v5.2.2-gateTunnelKey-SD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing
2	2026-10-30	5.2.2	Checked against the primary Java source tree (Eclipse-Arrowhead-java): services, operations, paths and data models unchanged; missing primitive definitions added.	Claude Opus 5.5 (draft)

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	

gateTunnelManagement HTTP/TLS/JSON

Interface Design Description

Service ID: *"gateTunnelManagement"*

Abstract
This document describes the HTTP/1.1 protocol with TLS payload security and JSON payload encoding variant of the `gateTunnelManagement` service of the GateTunnel system.

Contents

1 Overview **3**
1.1 Interface registration . . . 3

2 Service Operations **4**
2.1 operation sessions . . . 4
2.2 operation close . . . 4
2.3 operation status . . . 5

3 Data Models **6**
3.1 struct CloseResult . . . 6
3.2 struct SessionCloseRequest . . . 6
3.3 struct SessionList . . . 6
3.4 struct Status . . . 6
3.5 Primitives . . . 6

4 References **8**

5 Revision History **9**
5.1 Amendments . . . 9
5.2 Quality Assurance . . . 9

1 Overview

This document describes the `gateTunnelManagement` service interface of the GateTunnel system, which provides operator access to GateTunnel sessions and status.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	HTTP	1.1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `gateTunnelManagement` service interface

This document provides the Interface Design Description IDD to the *gateTunnelManagement – Service Description* document [5]. For further details about how this service is meant to be used, please consult that document.

The rest of this document describes how to realize the `gateTunnelManagement` service interface in detail. Both in terms of its operations (Section 2) and its information model (Section 3).

1.1 Interface registration

The service is registered in the ServiceRegistry with the interface template `generic_https`, policy `CERT_AUTH`, access address `gatetunnel`, port 8453 and base path `/gatetunnel`. The `operations` property of the interface lists the operations below with their method and path relative to the base path (path parameters are placeholders such as `{id}` that the consumer fills in):

Operation	Method	Path
`sessions`	GET	`/mgmt/sessions`
`close`	POST	`/mgmt/sessions/close`
`status`	GET	`/mgmt/status`

2 Service Operations

The interfaces of the `gateTunnelManagement` service, its operations, data models and implementation are provided below. In particular, each subsection first names the HTTP method and path used to call the operation, after which it names the abstract operation from the `gateTunnelManagement` SD document, as well as input and output types.

Every request needs mutual TLS with a system or operator certificate of the cloud and `Authorization: Bearer IDENTITY-TOKEN//<token>`; the token is verified with Authentication and must belong to the system named by the certificate. Request and response bodies are `application/json` unless stated otherwise. Errors are answered with `{"error": "<text>"}` and the status codes `400 Bad Request` (invalid input), `401 Unauthorized` (no valid identity), `403 Forbidden` (caller not permitted), `404 Not Found`, `500 Internal Server Error`, `502 Bad Gateway` (a system it depends on failed) and `503 Service Unavailable` (overloaded).

2.1 GET /gatetunnel/mgmt/sessions?limit=*{limit}*

Operation: sessions
Output: SessionList

Returns the control sessions.

Query parameters: *limit* (Integer, optional, default `200`). List values are repeated or comma-separated.

A successful call returns `200 OK` with the output in the body.

```
GET /gatetunnel/mgmt/sessions?limit=<limit> HTTP/1.1
Host: gatetunnel:8453
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 1: An sessions invocation.

```
{
  "entries": [
    {}
  ],
  "count": 1
}
```

Listing 2: An sessions response.

2.2 POST /gatetunnel/mgmt/sessions/close

Operation: close
Input: SessionCloseRequest
Output: CloseResult

Closes a session by identifier or port.

A successful call returns `200 OK` with the output in the body.

```
POST /gatetunnel/mgmt/sessions/close HTTP/1.1
Host: gatetunnel:8453
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "sessionId": "7f3c2a10",
  "tunnelPort": 8000
}
```

Listing 3: An close invocation.

```
{
  "closed": true
}
```

Listing 4: An close response.

2.3 GET /gatetunnel/mgmt/status

Operation: status
Output: Status

Returns the GateTunnel status with relay and session state.
A successful call returns `200 OK` with the output in the body.

```
GET /gatetunnel/mgmt/status HTTP/1.1
Host: gatetunnel:8453
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 5: An status invocation.

```
{
  "status": "ok",
  "system": "Gatekeeper",
  "version": "5.2.2",
  "implementation": "java",
  "activeSessions": 1
}
```

Listing 6: An status response.

3 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is meant to denote a JSON Object that must contain certain fields, or names, with values conforming to explicitly named types. Fields that are not needed may be omitted or `null` in requests; empty fields are omitted in responses. As a complement to the primary types defined in this section, there is also a list of secondary types in Section 3.5, which are used to represent things like hashes, identifiers and texts.

3.1 struct CloseResult

Object Field	Value Type	Description
"closed"	Boolean	Whether a session was closed; 404 when false.

3.2 struct SessionCloseRequest

Object Field	Value Type	Description
"sessionId"	String	Session to close.
"tunnelPort"	Number	Or the control port to close.

3.3 struct SessionList

Object Field	Value Type	Description
"entries"	Array<Object>	Control sessions: `sessionId`, `queueId`, `peerName`, `serviceDefinition`, `tunnelPort`, `state`, `consumer`, `provider`, `consumerCloud`, `providerCloud`, `relay`, `sessionStartedAt`.
"count"	Number	Number of entries.

3.4 struct Status

Object Field	Value Type	Description
"status"	String	`ok`.
"system"	String	`GateTunnel`.
"version"	Version	`5.2.2`.
"implementation"	String	`java`.
"registration"	Object	Registration state.
"relay"	Object	Relay connection state.
"interCloud"	Object	`providerSessions`, `consumerSessions` and session summaries.
"activeSessions"	Number	Control sessions not closed.

3.5 Primitives

As all messages are encoded using the JSON format [4], the following primitive constructs, part of that standard, become available. Note that the official standard is defined in terms of parsing rules, while this list only concerns syntactic information. Furthermore, the Object and Array types are given optional generic type parameters,

which are used in this document to signify when pair values or elements are expected to conform to certain types.

Type	Description
Array	A JSON Array [4]; Array<A> has elements of type A.
Boolean	JSON Boolean, `true` or `false`.
Number	JSON Number, an integer.
Object	JSON Object; Object<A> has string keys and values of type A.
String	JSON String.
Version	JSON String, semantic version `major.minor.patch`.

4 References

[1] R. Fielding, M. Nottingham, and J. Reschke, “Http/1.1,” IETF, RFC 9112, 2022.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “gateTunnelManagement – Service Description (GateTunnel),” Eclipse Arrowhead, SD 5.2.2, 2026, gateTunnel-v5.2.2-gateTunnelManagement-SD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing
2	2026-10-30	5.2.2	Checked against the primary Java source tree (Eclipse-Arrowhead-java): services, operations, paths and data models unchanged.	Claude Opus 5.5 (draft)

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	

sysMonitor AMQP/TLS/JSON

Interface Design Description

Service ID: *"sysMonitor"*

Abstract
This document describes the AMQP 0-9-1 protocol with TLS payload security and JSON payload encoding variant of the `sysMonitor` service of the GateTunnel system (SysMonitor-AMQP-IDD-5.2.2).

Contents

1 Overview **3**
1.1 Interface registration . . . 3

2 Service Operations **4**
2.1 operation echo . . . 4
2.2 operation power . . . 4
2.3 operation status . . . 4

3 Data Models **5**
3.1 struct Observation . . . 5
3.2 Primitives . . . 5

4 References **6**

5 Revision History **7**
5.1 Amendments . . . 7
5.2 Quality Assurance . . . 7

1 Overview

This document describes the AMQP binding of the native `sysMonitor` service of GateTunnel.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	AMQP	0-9-1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `sysMonitor` service interface

This document provides the Interface Design Description IDD to the *sysMonitor – Service Description* document [5].

1.1 Interface registration

With `sysmonitor.enabled=true`, GateTunnel registers the service at start-up with interface template `generic_amqps` (protocol `amqps`, policy `CERT_AUTH`; `generic_amqp` without TLS) and the following properties and metadata:

```
{
  "serviceDefinitionName": "sysMonitor",
  "version": "1.0.0",
  "metadata": {
    "contract": "SysMonitor-AMQP-IDD-5.2.2",
    "schemaVersion": "1.0",
    "publisherMode": "native",
    "observationTypes": [
      "echo",
      "power",
      "status"
    ],
    "delivery": "persistent, publisher-confirmed"
  },
  "interfaces": [
    {
      "templateName": "generic_amqps",
      "protocol": "amqps",
      "policy": "CERT_AUTH",
      "properties": {
        "accessAddresses": [
          "amqp-broker"
        ],
        "accessPort": 5671,
        "exchange": "arrowhead",
        "baseRoutingKey": "TestCloud.sysmonitor.GateTunnel.GateTunnel",
        "operations": [
          "echo",
          "power",
          "status"
        ]
      }
    }
  ]
}
```

Listing 1: Registered service instance (TestCloud).

2 Service Operations

The publisher is the `Messaging.Publisher` of this independently packaged GateTunnel system, configured with `AMQP_HOST`, `AMQP_PORT`, `LOCAL_CLOUD` and `MONITOR_INTERVAL_SECONDS` (30); its `echo` value is `status=alive` and the metadata add `implementation=java`. The publisher connects to the broker (default `amqp-broker`, port 5671) with TLS, verifies the broker host name and authenticates with its X.509 system certificate (SASL `EXTERNAL`; the certificate CN is the broker user name). Every publication interval it publishes each observation to the topic exchange `arrowhead` with the routing key `<baseRoutingKey>.<operation>`, where the base routing key is `<Cloud>.sysmonitor.<System>.<serviceInstance>`. Messages are persistent (delivery mode 2), `application/json`, carry the observation identifier as message id, and are publisher-confirmed (timeout 10 s); a failed cycle is retried with a new connection at the next interval. The broker's topic permissions allow the system to publish only below its own base routing key.

2.1 PUBLISH `<Cloud>.sysmonitor.GateTunnel.GateTunnel.echo`

Operation: echo
Output: Observation

Liveness: `status` (`alive` or `degraded`), `uptimeSeconds` and a `detail` text; quality `good` or `uncertain`.

2.2 PUBLISH `<Cloud>.sysmonitor.GateTunnel.GateTunnel.power`

Operation: power
Output: Observation

Power supply: `supplyType=line`, `state=available`; unit `1`.

2.3 PUBLISH `<Cloud>.sysmonitor.GateTunnel.GateTunnel.status`

Operation: status
Output: Observation

Process state: `state=running`, `health` (`healthy`/`degraded`) and `serviceCount`, the number of registered services.

```
{
  "schemaVersion": "1.0",
  "observationId": "GateTunnel-echo-1792670400000-42",
  "providerSystem": "GateTunnel",
  "serviceInstance": "GateTunnel",
  "observationType": "echo",
  "sourceTime": "2026-10-22T12:00:00.000Z",
  "sequence": 42,
  "value": {
    "status": "alive",
    "uptimeSeconds": 3600,
    "detail": "GateTunnel is running"
  },
  "quality": "good",
  "metadata": {
    "publisherMode": "native"
  }
}
```

Listing 2: An echo observation.

3 Data Models

3.1 struct Observation

Object Field	Value Type	Description
"schemaVersion"	String	`1.0`.
"observationId"	String	`<System>-<type>-<epoch ms>-<sequence>`.
"providerSystem"	String	The publishing system.
"serviceInstance"	String	Service instance, default the system name.
"observationType"	String	`echo`, `power`, `status`.
"sourceTime"	String	ISO 8601 UTC time with milliseconds.
"sequence"	Number	Sequence number per publisher.
"value"	Object	Observed value, see the operations.
"unit"	String	`1` for `power` and `status`; absent for `echo`.
"quality"	String	`good` or `uncertain`.
"metadata"	Object	`{"publisherMode": "native"}`.

3.2 Primitives

Type	Description
Number	JSON Number, an integer.
Object	JSON Object; Object<A> has string keys and values of type A.
String	JSON String.

4 References

[1] AMQP Working Group, “Amqp 0-9-1 specification,” AMQP Working Group, Tech. Rep., 2008.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “sysMonitor – Service Description (GateTunnel),” Eclipse Arrowhead, SD 5.2.2, 2026, gateTunnel-v5.2.2-sysMonitor-SD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing
2	2026-10-25	5.2.2	Independent Java build, private helpers and state, per-system deployment and configuration.	Codex (draft)
3	2026-10-30	5.2.2	Checked against the primary Java source tree (Eclipse-Arrowhead-java): services, operations, paths and data models unchanged.	Claude Opus 5.5 (draft)

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	

1 Interface overview

HTTPS, mandatory mutual TLS, Arrowhead identity-token header and JSON request/response documents. General management is sysop/whitelist protected; enrollment endpoints use approved certificate fingerprints and profile/serial checks instead of ordinary identity tokens. Error responses contain errorMessage, errorCode, origin and timestamp. Exact DTO and status/error parity is not certified.

1.1 HTTPS interface operations

The listener is HTTPS with JSON by default; raw configuration and CRL responses use their declared media types. A request body is capped at 1 MiB. The table records implemented routes, not a claim of complete behavioral conformance.

Method	Path	Access
GET	/gatetunnel/echo	identity
GET	/gatetunnel/publickey	identity
POST	/gatetunnel/connect_provider	identity
POST	/gatetunnel/connect_consumer	identity
POST	/gatetunnel/close_sessions	identity
GET	/gatetunnel/mgmt/sessions	management
POST	/gatetunnel/mgmt/sessions/close	management
POST	/gatetunnel/intercloud/provider	identity
POST	/gatetunnel/intercloud/consumer	identity
GET	/gatetunnel/mgmt/status	management
GET	/gatetunnel/monitor/echo	certificate
GET	/gatetunnel/general/mgmt/get-config	management
POST	/gatetunnel/general/mgmt/logs	management

1.2 Important delimitations

This implementation is a development profile, not a certified interchangeable Java replacement. All systems use private JSON snapshots rather than the Java databases. MQTT application APIs, exhaustive DTO normalization and error parity, automatic data migration and production qualification remain outstanding.

- Legacy-mTLS relay sessions are supported; control-session records are not a second AMQP tunnel data plane. AH-GT-1 encrypted requests are rejected. Consumer listeners are volatile and renegotiated after restart.
- The source reference uses a shared non-Spring HTTP dispatcher. Its route coverage is not inferred from Go route presence; manual JavaSupportRuntime review is required.

1 GateTunnel

1.1 System overview

Native Rust development profile for local Java source `JavaSupportRuntime/`. One independently configured executable, identity, port and state file per role. No Java, Go or Python process implements the service. Some essential operations are explicitly unavailable.

1.2 Design and trust boundaries

Tokio/Hyper/Axum with rustls enforces mutual TLS. Certificate chain, validity, local CN/profile and startup-configured optional CRLs are checked. CRLs need process restart to refresh; without CRLs no revocation enforcement is claimed. Tokens are verified with Authentication and bound to the TLS identity. Business calls require ConsumerAuthorization; management requires a verified sysop or explicit broad whitelist. CA provisioning instead applies Java-style named certificate-principal rights. Outbound authorities are pinned to expected CN/profile before credentials are sent, in addition to chain, SAN and time validation.

1.3 Persistent state

Independent locked atomic JSON replaces SQL. Clone/validate/fsync/rename commits prevent partially published local transactions. Rename is the commit point; directory-sync failure is an uncertain durable commit, not a rollback. Owner-only keys/password files are separate. Network effects are not distributed transactions; interrupted starts and bridge operations require reconciliation. No automatic Java state import, clustering or deployment is delivered.

1.4 Implemented behavior

Public key and empty session catalogue

1.5 Open release gates

Session allocation/listeners/relay data plane absent, returns501. All systems remain development profiles, not certified interchangeable Java replacements. See `COMPATIBILITY.md` for detailed DTO fields and restrictions; the Java sources remain the authoritative contract.

1.6 Produced and consumed services

Advertised implemented HTTPS definitions: `echo`, `gateTunnelKey`, `gateTunnelManagement`, `generalManagement`.

Authorities consumed as applicable: Authentication, ServiceRegistry, ConsumerAuthorization and explicitly configured pinned adapter/provider origins. Only implemented operations are registered. Service versions are 1.0.0 except Gatekeeper/GateTunnel 5.2.2. No AMQP sysMonitor.observe implementation is advertised.

1.7 HTTPS operations

JSON unless raw configuration bytes, PEM CRL or echo text. Bodies: 1 MiB; remote responses: 8 MiB. Header: `Bearer IDENTITY-TOKEN//token`. Unknown routes return 404, absent dependencies 503. Unported

operations return 501 after applicable access checks and are excluded from registration. Route presence is not semantic parity.

Method	Path	Access / status
GET	/gatetunnel/general/mgmt/get-config	management
POST	/gatetunnel/general/mgmt/logs	management
GET	/gatetunnel/monitor/echo	certificate
GET	/gatetunnel/publickey	identity
POST	/gatetunnel/connect_provider	identity / 501
POST	/gatetunnel/connect_consumer	identity / 501
POST	/gatetunnel/close_sessions	identity / 501
GET	/gatetunnel/mgmt/sessions	management
POST	/gatetunnel/mgmt/sessions/close	management / 501

Error envelope: errorMessage, errorCode, exceptionType, origin and timestamp. Full Java status, DTO and validation equivalence requires differential testing.

2 References and qualification

See `contracts.json` for local Java SHA256 hashes/mappings, `COMPATIBILITY.md` for DTO details and gaps, and `VERIFICATION.md` for tests actually run. No upstream release-tag provenance, complete replacement or real-cloud interoperability is asserted.