Gatekeeper

Interface Design Description

Eclipse Arrowhead 5.2.2 | support system | Revision 2026-11-09 | REVIEW DRAFT

Purpose and document structure

This document consolidates the system interface designs. Detailed Java service/transport IDDs are retained as separate appendices, followed by available Go and Rust interface descriptions. The current cross-language sections below precede the detailed implementation appendices. Appendix dates and release labels belong to the retained baseline, not to a newly qualified release. Existing descriptions have been assembled from the primary trees; no live interoperability or semantic-parity claim is made.

Java implementation

Primary folder: Eclipse-Arrowhead-java/ah5-Gatekeeper-java-spring. 4 detailed Java IDD source document(s) are included in the appendices. Their architecture, operation parameters, models, transport bindings, access rules and errors remain associated with Java. They must not be read as automatically implemented by the ports.

Go implementation

Primary folder: Eclipse-Arrowhead-go/ah5-Gatekeeper-go.

Gatekeeper - Go 5.2.2

Standalone support system, reorganized on 2026-10-28 following the Eclipse-Arrowhead-java distribution layout. Build and operate from this folder; no original Arrowhead checkout or sibling source module is required. The executable is bin/Gatekeeper. Entry point: ./cmd/gatekeeper. Module: arrowhead/ah5-support-go/gatekeeper. See DEPLOYMENT.md for configuration and standalone container use. Existing compatibility limits remain in the copied upstream documentation and UPSTREAM-README.md. The dedicated launcher selects only this support-system role. The formerly shared internal runtime and regression tests are copied locally, not linked from another tree. Files for common helpers and other route implementations remain in that private runtime; this packaging does not claim new functionality or Java parity. Documentation and license notices are included in this folder. Source provenance and import-only rewrites are listed in the distribution's SOURCE-MANIFEST.json. No running cloud or upstream source was changed.

Listening port

Built-in default 127.0.0.1:8449 (Arrowhead default). The shipped config.json, compose.yaml and Dockerfile use the same port on all interfaces ("listen": "0.0.0.0:8449"; 8540-8555 layout before 2026-11-09). Override with "listen" in the configuration file, SERVER_PORT=N or -server.port N; the port overrides keep the configured host. See [LISTENING-PORTS.md](../LISTENING-PORTS.md) for precedence and all systems.

Documented behavior and remaining work

System	Implemented behavior	Remaining work
Gatekeeper	Native Go legacy-mTLS cloud discovery/negotiation engine adapted to this runtime	AH-GT-1 encryption, complete current Java edge-case parity, real peer/broker/ACL qualification

Detailed implementation evidence

1 native Go IDD document(s) are included in the appendices. Their protocol and storage descriptions apply to that implementation only. Current primary-folder ownership and current listening-port notes above supersede historical paths or example ports in those retained documents.

Rust implementation

Primary folder: Eclipse-Arrowhead-rust/ah5-Gatekeeper-rust.

Gatekeeper (Rust)

Arrowhead 5.2.2 Gatekeeper support system. Entry point src/main.rs is built as binary gatekeeper by the shared crate in ../ah5-support-runtime-rust (arrowhead-support-rust).

- examples/gatekeeper.json - example configuration (master copy: ../ah5-support-runtime-rust/examples/)

- documentation/ - SysD/SysDD/IDD/SD sources (symlink into ../ah5-support-runtime-rust/documentation/Gatekeeper, where the contract generator writes)

Run: cargo run -p arrowhead-support-rust --bin gatekeeper -- <config.json>

Listening port

Default 127.0.0.1:8449 (Arrowhead default, role gatekeeper). Override with "listen": "host:port" in the configuration, SERVER_PORT=N or --server.port N; the port overrides keep the configured host. See [LISTENING-PORTS.md](../LISTENING-PORTS.md) for precedence and all systems.

Documented behavior and remaining work

System	Implemented behavior	Remaining work
Gatekeeper	Neighbour/relay administration, actual MQTT global discovery and negotiation with explicit cloud/organisation bindings	Exhaustive DTO/filter/failure parity and independent review

Detailed implementation evidence

1 native Rust IDD document(s) are included in the appendices. Their protocol and storage descriptions apply to that implementation only. Current primary-folder ownership and current listening-port notes above supersede historical paths or example ports in those retained documents.

Build and state ownership

Core entry points are built by arrowhead-core-rust; the ordinary support entry points are built by arrowhead-support-rust using the shared support runtime. LocalCloudManager has its own crate. Per-system documentation links may point into the shared documentation catalog. Independent identity and state configuration is still required. Read the native appendix for persistence and restart semantics.

Cross-language qualification

Identical system names or HTTP paths do not establish interoperability. For the selected implementation, verify registered service versions and metadata, method/path and payload models, null and optional-field handling, success/error bodies, authentication and per-operation authorization, timeout/retry behavior and persistence across restart. Java MQTT/AMQP descriptions apply to a port only where its own implementation evidence explicitly supports them. Missing transports must not be advertised. State conversion from Java SQL to native snapshots, secret provisioning, backup/restore and rollback require implementation-specific procedures. No data migration, deployment or cloud reconfiguration was performed for this document set.

Detailed appendices and provenance

- Java: Eclipse-Arrowhead-java/ah5-Gatekeeper-java-spring/documentation/v5.2.2/Gatekeeper-v5.2.2-gatekeeperManagement-HTTP-IDD.tex

- Java: Eclipse-Arrowhead-java/ah5-Gatekeeper-java-spring/documentation/v5.2.2/Gatekeeper-v5.2.2-globalServiceDiscovery-HTTP-IDD.tex

- Java: Eclipse-Arrowhead-java/ah5-Gatekeeper-java-spring/documentation/v5.2.2/Gatekeeper-v5.2.2-interCloudNegotiation-HTTP-IDD.tex

- Java: Eclipse-Arrowhead-java/ah5-Gatekeeper-java-spring/documentation/v5.2.2/Gatekeeper-v5.2.2-sysMonitor-AMQP-IDD.tex

- Go: Eclipse-Arrowhead-go/ah5-Gatekeeper-go/documentation/Gatekeeper/Gatekeeper-HTTPS-IDD.tex

- Rust: Eclipse-Arrowhead-rust/ah5-support-runtime-rust/documentation/Gatekeeper/Gatekeeper-HTTPS-IDD.tex

The package sources/ folder retains the selected LaTeX, figures, bibliography, language README/build evidence and source snapshots for newly described contracts. source-manifest.json records SHA-256 hashes of original inputs. build-report.json records whether an appendix used an existing newer PDF or was compiled from source.

gatekeeperManagement HTTP/TLS/JSON

Interface Design Description

Service ID: *"gatekeeperManagement"*

Abstract
This document describes the HTTP/1.1 protocol with TLS payload security and JSON payload encoding variant of the `gatekeeperManagement` service of the Gatekeeper system.

Contents

1 Overview **3**
1.1 Interface registration . . . 3

2 Service Operations **4**
2.1 operation clouds . . . 4
2.2 operation relays . . . 4
2.3 operation status . . . 5

3 Data Models **6**
3.1 struct CloudList . . . 6
3.2 struct RelayList . . . 6
3.3 struct Status . . . 6
3.4 Primitives . . . 6

4 References **8**

5 Revision History **9**
5.1 Amendments . . . 9
5.2 Quality Assurance . . . 9

1 Overview

This document describes the `gatekeeperManagement` service interface of the Gatekeeper system, which provides read access to the neighbour clouds and relays the Gatekeeper knows and to its status.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	HTTP	1.1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `gatekeeperManagement` service interface

This document provides the Interface Design Description IDD to the *gatekeeperManagement – Service Description* document [5]. For further details about how this service is meant to be used, please consult that document.

The rest of this document describes how to realize the `gatekeeperManagement` service interface in detail. Both in terms of its operations (Section 2) and its information model (Section 3).

1.1 Interface registration

The service is registered in the ServiceRegistry with the interface template `generic_https`, policy `CERT_AUTH`, access address `gatekeeper`, port 8449 and base path `/gatekeeper`. The `operations` property of the interface lists the operations below with their method and path relative to the base path (path parameters are placeholders such as `{id}` that the consumer fills in):

Operation	Method	Path
`clouds`	GET	`/mgmt/clouds`
`relays`	GET	`/mgmt/relays`
`status`	GET	`/mgmt/status`

2 Service Operations

The interfaces of the `gatekeeperManagement` service, its operations, data models and implementation are provided below. In particular, each subsection first names the HTTP method and path used to call the operation, after which it names the abstract operation from the `gatekeeperManagement` SD document, as well as input and output types.

Every request needs mutual TLS with a system or operator certificate of the cloud and `Authorization: Bearer IDENTITY-TOKEN//<token>`; the token is verified with Authentication and must belong to the system named by the certificate. Request and response bodies are `application/json` unless stated otherwise. Errors are answered with `{"error": "<text>"}` and the status codes `400 Bad Request` (invalid input), `401 Unauthorized` (no valid identity), `403 Forbidden` (caller not permitted), `404 Not Found`, `500 Internal Server Error`, `502 Bad Gateway` (a system it depends on failed) and `503 Service Unavailable` (overloaded).

2.1 GET /gatekeeper/mgmt/clouds

Operation: clouds
Output: CloudList

Returns the configured neighbour clouds.

A successful call returns `200 OK` with the output in the body.

```
GET /gatekeeper/mgmt/clouds HTTP/1.1
Host: gatekeeper:8449
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 1: An clouds invocation.

```
{
  "entries": [
    {}
  ],
  "count": 1
}
```

Listing 2: An clouds response.

2.2 GET /gatekeeper/mgmt/relays

Operation: relays
Output: RelayList

Returns the configured relays.

A successful call returns `200 OK` with the output in the body.

```
GET /gatekeeper/mgmt/relays HTTP/1.1
Host: gatekeeper:8449
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 3: An relays invocation.

```
{
  "entries": [
    {}
  ],
  "count": 1
}
```

Listing 4: An relays response.

2.3 GET /gatekeeper/mgmt/status

Operation: status
Output: Status

Returns the Gatekeeper status with the relay connection.
A successful call returns `200 OK` with the output in the body.

```
GET /gatekeeper/mgmt/status HTTP/1.1
Host: gatekeeper:8449
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 5: An status invocation.

```
{
  "status": "ok",
  "system": "Gatekeeper",
  "version": "5.2.2",
  "implementation": "java",
  "x509": true
}
```

Listing 6: An status response.

3 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is meant to denote a JSON Object that must contain certain fields, or names, with values conforming to explicitly named types. Fields that are not needed may be omitted or `null` in requests; empty fields are omitted in responses. As a complement to the primary types defined in this section, there is also a list of secondary types in Section 3.4, which are used to represent things like hashes, identifiers and texts.

3.1 struct CloudList

Object Field	Value Type	Description
"entries"	Array<Object>	Configured neighbour clouds (`name`, `operator`, `gatekeeperAddress`, `gatekeeperPort`, `metadata`).
"count"	Number	Number of entries.

3.2 struct RelayList

Object Field	Value Type	Description
"entries"	Array<Object>	Configured relays (`name`, `address`, `port`, `type`, `secure`, `metadata`).
"count"	Number	Number of entries.

3.3 struct Status

Object Field	Value Type	Description
"status"	String	`ok`.
"system"	String	`Gatekeeper`.
"version"	Version	`5.2.2`.
"implementation"	String	`java`.
"x509"	Boolean	Mutual TLS in use.
"registration"	Object	Registration state in the ServiceRegistry.
"relay"	Object	Connection state of the inter-cloud relay.

3.4 Primitives

As all messages are encoded using the JSON format [4], the following primitive constructs, part of that standard, become available. Note that the official standard is defined in terms of parsing rules, while this list only concerns syntactic information. Furthermore, the Object and Array types are given optional generic type parameters, which are used in this document to signify when pair values or elements are expected to conform to certain types.

Type	Description
Array	A JSON Array [4]; Array<A> has elements of type A.
Boolean	JSON Boolean, `true` or `false`.
Number	JSON Number, an integer.
Object	JSON Object; Object<A> has string keys and values of type A.
String	JSON String.
Version	JSON String, semantic version `major.minor.patch`.

4 References

[1] R. Fielding, M. Nottingham, and J. Reschke, “Http/1.1,” IETF, RFC 9112, 2022.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “gatekeeperManagement – Service Description (Gatekeeper),” Eclipse Arrowhead, SD 5.2.2, 2026, gatekeeper-v5.2.2-gatekeeperManagement-SD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing
2	2026-10-30	5.2.2	Checked against the primary Java source tree (Eclipse-Arrowhead-java): services, operations, paths and data models unchanged.	Claude Opus 5.5 (draft)

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	

globalServiceDiscovery HTTP/TLS/JSON

Interface Design Description

Service ID: *"globalServiceDiscovery"*

Abstract
This document describes the HTTP/1.1 protocol with TLS payload security and JSON payload encoding variant of the `globalServiceDiscovery` service of the Gatekeeper system.

Contents

1 Overview **3**
1.1 Interface registration . . . 3

2 Service Operations **4**
2.1 operation query . . . 4
2.2 operation multi-query . . . 5

3 Data Models **6**
3.1 struct GlobalServiceDiscoveryRequest . . . 6
3.2 struct GlobalServiceDiscoveryResult . . . 6
3.3 struct InterCloudProvider . . . 6
3.4 Primitives . . . 6

4 References **8**

5 Revision History **9**
5.1 Amendments . . . 9
5.2 Quality Assurance . . . 9

1 Overview

This document describes the `globalServiceDiscovery` service interface of the Gatekeeper system, which provides discovery of authorized providers of a service in the neighbour clouds, through the inter-cloud relay.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	HTTP	1.1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `globalServiceDiscovery` service interface

This document provides the Interface Design Description IDD to the *globalServiceDiscovery – Service Description* document [5]. For further details about how this service is meant to be used, please consult that document.

The rest of this document describes how to realize the `globalServiceDiscovery` service interface in detail. Both in terms of its operations (Section 2) and its information model (Section 3).

1.1 Interface registration

The service is registered in the ServiceRegistry with the interface template `generic_https`, policy `CERT_AUTH`, access address `gatekeeper`, port 8449 and base path `/gatekeeper`. The `operations` property of the interface lists the operations below with their method and path relative to the base path (path parameters are placeholders such as `{id}` that the consumer fills in):

Operation	Method	Path
`query`	POST	`/init_gsd`
`multi-query`	POST	`/init_multi_gsd`

2 Service Operations

The interfaces of the `globalServiceDiscovery` service, its operations, data models and implementation are provided below. In particular, each subsection first names the HTTP method and path used to call the operation, after which it names the abstract operation from the `globalServiceDiscovery` SD document, as well as input and output types.

Every request needs mutual TLS with a system or operator certificate of the cloud and `Authorization: Bearer IDENTITY-TOKEN//<token>`; the token is verified with Authentication and must belong to the system named by the certificate. Request and response bodies are `application/json` unless stated otherwise. Errors are answered with `{"error": "<text>"}` and the status codes `400 Bad Request` (invalid input), `401 Unauthorized` (no valid identity), `403 Forbidden` (caller not permitted), `404 Not Found`, `500 Internal Server Error`, `502 Bad Gateway` (a system it depends on failed) and `503 Service Unavailable` (overloaded).

2.1 POST /gatekeeper/init_gsd

Operation: query
Input: GlobalServiceDiscoveryRequest
Output: GlobalServiceDiscoveryResult

Asks the target clouds for authorized providers of the required service.

A successful call returns `200 OK` with the output in the body.

```
POST /gatekeeper/init_gsd HTTP/1.1
Host: gatekeeper:8449
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "serviceRequirement": {
    "serviceDefinition": "temperatureReading",
    "operations": [
      "read"
    ]
  },
  "targetClouds": [
    "GoCloud|Company"
  ],
  "consumerSystem": "TemperatureDisplay"
}
```

Listing 1: An query invocation.

```
{
  "results": [
    {
      "cloud": "GoCloud|Company",
      "providerName": "TemperatureSensor",
      "serviceDefinition": "temperatureReading",
      "version": "5.2.2",
      "metadata": {
        "unit": "celsius"
      },
      "operations": [
        "read"
      ]
    }
  ],
  "unsuccessfulRequests": 0,
  "queriedClouds": 1
}
```

Listing 2: An query response.

2.2 POST /gatekeeper/init_multi_gsd

Operation: multi-query
Input: GlobalServiceDiscoveryRequest
Output: GlobalServiceDiscoveryResult

Same as `query` (v4 multi-GSD path).

A successful call returns `200 OK` with the output in the body.

```
POST /gatekeeper/init_multi_gsd HTTP/1.1
Host: gatekeeper:8449
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "serviceRequirement": {
    "serviceDefinition": "temperatureReading",
    "operations": [
      "read"
    ]
  },
  "targetClouds": [
    "GoCloud|Company"
  ],
  "consumerSystem": "TemperatureDisplay"
}
```

Listing 3: An multi-query invocation.

```
{
  "results": [
    {
      "cloud": "GoCloud|Company",
      "providerName": "TemperatureSensor",
      "serviceDefinition": "temperatureReading",
      "version": "5.2.2",
      "metadata": {
        "unit": "celsius"
      },
      "operations": [
        "read"
      ]
    }
  ],
  "unsuccessfulRequests": 0,
  "queriedClouds": 1
}
```

Listing 4: An multi-query response.

3 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is meant to denote a JSON Object that must contain certain fields, or names, with values conforming to explicitly named types. Fields that are not needed may be omitted or `null` in requests; empty fields are omitted in responses. As a complement to the primary types defined in this section, there is also a list of secondary types in Section 3.4, which are used to represent things like hashes, identifiers and texts.

3.1 struct GlobalServiceDiscoveryRequest

Object Field	Value Type	Description
"serviceRequirement"	Object	Orchestration service requirement; `serviceDefinition` is required, `operations` are checked (alias `requestedService`).
"targetClouds"	Array<String>	Clouds to ask (`<Cloud>` or `<Cloud>|<Organization>`); default all configured peer clouds.
"consumerSystem"	String	Consumer on whose behalf the orchestrator asks; default the requester.

3.2 struct GlobalServiceDiscoveryResult

Object Field	Value Type	Description
"results"	Array<InterCloudProvider>	Authorized providers of all asked clouds.
"unsuccessfulRequests"	Number	Number of clouds that did not answer correctly.
"queriedClouds"	Number	Number of clouds asked.

3.3 struct InterCloudProvider

Object Field	Value Type	Description
"cloud"	String	Provider cloud, `<Cloud>|<Organization>`.
"providerName"	String	Provider system.
"serviceDefinition"	String	Service definition.
"version"	Version	Service version.
"metadata"	Object	Instance metadata.
"operations"	Array<String>	Offered operations.

3.4 Primitives

As all messages are encoded using the JSON format [4], the following primitive constructs, part of that standard, become available. Note that the official standard is defined in terms of parsing rules, while this list only concerns syntactic information. Furthermore, the Object and Array types are given optional generic type parameters, which are used in this document to signify when pair values or elements are expected to conform to certain types.

Type	Description
Array	A JSON Array [4]; Array<A> has elements of type A.
Number	JSON Number, an integer.
Object	JSON Object; Object<A> has string keys and values of type A.
String	JSON String.
Version	JSON String, semantic version `major.minor.patch`.

4 References

[1] R. Fielding, M. Nottingham, and J. Reschke, “Http/1.1,” IETF, RFC 9112, 2022.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “globalServiceDiscovery – Service Description (Gatekeeper),” Eclipse Arrowhead, SD 5.2.2, 2026, gatekeeper-v5.2.2-globalServiceDiscovery-SD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing
2	2026-10-30	5.2.2	Checked against the primary Java source tree (Eclipse-Arrowhead-java): services, operations, paths and data models unchanged.	Claude Opus 5.5 (draft)

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	

interCloudNegotiation HTTP/TLS/JSON

Interface Design Description

Service ID: *"interCloudNegotiation"*

Abstract
This document describes the HTTP/1.1 protocol with TLS payload security and JSON payload encoding variant of the `interCloudNegotiation` service of the Gatekeeper system.

Contents

1 Overview **3**
1.1 Interface registration . . . 3

2 Service Operations **4**
2.1 operation negotiate . . . 4

3 Data Models **6**
3.1 struct InterCloudNegotiationRequest . . . 6
3.2 struct InterCloudNegotiationResult . . . 6
3.3 Primitives . . . 6

4 References **7**

5 Revision History **8**
5.1 Amendments . . . 8
5.2 Quality Assurance . . . 8

1 Overview

This document describes the `interCloudNegotiation` service interface of the Gatekeeper system, which provides negotiation of the use of one provider in a neighbour cloud and opening of the GateTunnel session through which the consumer calls it.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	HTTP	1.1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `interCloudNegotiation` service interface

This document provides the Interface Design Description IDD to the *interCloudNegotiation – Service Description* document [5]. For further details about how this service is meant to be used, please consult that document.

The rest of this document describes how to realize the `interCloudNegotiation` service interface in detail. Both in terms of its operations (Section 2) and its information model (Section 3).

1.1 Interface registration

The service is registered in the ServiceRegistry with the interface template `generic_https`, policy `CERT_AUTH`, access address `gatekeeper`, port 8449 and base path `/gatekeeper`. The `operations` property of the interface lists the operations below with their method and path relative to the base path (path parameters are placeholders such as `{id}` that the consumer fills in):

Operation	Method	Path
`negotiate`	POST	`/init_icn`

2 Service Operations

The interfaces of the `interCloudNegotiation` service, its operations, data models and implementation are provided below. In particular, each subsection first names the HTTP method and path used to call the operation, after which it names the abstract operation from the `interCloudNegotiation` SD document, as well as input and output types.

Every request needs mutual TLS with a system or operator certificate of the cloud and `Authorization: Bearer IDENTITY-TOKEN//<token>`; the token is verified with Authentication and must belong to the system named by the certificate. Request and response bodies are `application/json` unless stated otherwise. Errors are answered with `{ërror: ẗext>}` and the status codes `400 Bad Request` (invalid input), `401 Unauthorized` (no valid identity), `403 Forbidden` (caller not permitted), `404 Not Found`, `500 Internal Server Error`, `502 Bad Gateway` (a system it depends on failed) and `503 Service Unavailable` (overloaded).

2.1 POST /gatekeeper/init_icn

Operation: negotiate
Input: InterCloudNegotiationRequest
Output: InterCloudNegotiationResult

Negotiates one provider in a target cloud and returns the local session interface.

A successful call returns `200 OK` with the output in the body.

```
POST /gatekeeper/init_icn HTTP/1.1
Host: gatekeeper:8449
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "targetCloud": "GoCloud|Company",
  "providerName": "TemperatureSensor",
  "serviceDefinition": "temperatureReading",
  "operations": [
    "read"
  ],
  "consumerSystem": "TemperatureDisplay"
}
```

Listing 1: An negotiate invocation.

```
{
  "negotiated": true,
  "reason": "Compromised certificate",
  "providerCloud": "GoCloud|Company",
  "providerName": "TemperatureSensor",
  "serviceDefinition": "temperatureReading",
  "version": "5.2.2",
  "metadata": {
    "unit": "celsius"
  },
  "sessionId": "7f3c2a10",
  "interface": {
    "templateName": "generic_https",
    "protocol": "https",
    "policy": "CERT_AUTH",
    "properties": {
      "accessAddresses": [
        "gatetunnel"
      ],
      "accessPort": 8201,
      "basePath": "/temperature",
      "operations": {
```

```
        "read": {
          "method": "GET",
          "path": "/read"
        }
      }
    }
  }
}
```

Listing 2: An negotiate response.

3 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is meant to denote a JSON Object that must contain certain fields, or names, with values conforming to explicitly named types. Fields that are not needed may be omitted or `null` in requests; empty fields are omitted in responses. As a complement to the primary types defined in this section, there is also a list of secondary types in Section 3.3, which are used to represent things like hashes, identifiers and texts.

3.1 struct InterCloudNegotiationRequest

Object Field	Value Type	Description
"targetCloud"	String	Provider cloud, `<Cloud>` or `<Cloud>|<Organization>` (alias `providerCloud`).
"providerName"	String	Provider system.
"serviceDefinition"	String	Service definition.
"operations"	Array<String>	Operations to negotiate; default all offered.
"consumerSystem"	String	Consumer; default the requester.

3.2 struct InterCloudNegotiationResult

Object Field	Value Type	Description
"negotiated"	Boolean	Whether a session was opened.
"reason"	String	Refusal reason (when not negotiated).
"providerCloud"	String	Provider cloud, `<Cloud>|<Organization>`.
"providerName"	String	Provider system.
"serviceDefinition"	String	Service definition.
"version"	Version	Service version.
"metadata"	Object	Instance metadata.
"sessionId"	String	GateTunnel session.
"interface"	Object	`generic_https` interface of the local GateTunnel session endpoint (`accessAddresses`, `accessPort`, `basePath`, `operations`).

3.3 Primitives

As all messages are encoded using the JSON format [4], the following primitive constructs, part of that standard, become available. Note that the official standard is defined in terms of parsing rules, while this list only concerns syntactic information. Furthermore, the Object and Array types are given optional generic type parameters, which are used in this document to signify when pair values or elements are expected to conform to certain types.

Type	Description
Array	A JSON Array [4]; Array<A> has elements of type A.
Boolean	JSON Boolean, `true` or `false`.
Object	JSON Object; Object<A> has string keys and values of type A.
String	JSON String.
Version	JSON String, semantic version `major.minor.patch`.

4 References

[1] R. Fielding, M. Nottingham, and J. Reschke, “Http/1.1,” IETF, RFC 9112, 2022.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “interCloudNegotiation – Service Description (Gatekeeper),” Eclipse Arrowhead, SD 5.2.2, 2026, gatekeeper-v5.2.2-interCloudNegotiation-SD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing
2	2026-10-30	5.2.2	Checked against the primary Java source tree (Eclipse-Arrowhead-java): services, operations, paths and data models unchanged.	Claude Opus 5.5 (draft)

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	

sysMonitor AMQP/TLS/JSON

Interface Design Description

Service ID: *"sysMonitor"*

Abstract
This document describes the AMQP 0-9-1 protocol with TLS payload security and JSON payload encoding variant of the `sysMonitor` service of the Gatekeeper system (SysMonitor-AMQP-IDD-5.2.2).

Contents

1 Overview **3**
1.1 Interface registration . . . 3

2 Service Operations **4**
2.1 operation echo . . . 4
2.2 operation power . . . 4
2.3 operation status . . . 4

3 Data Models **5**
3.1 struct Observation . . . 5
3.2 Primitives . . . 5

4 References **6**

5 Revision History **7**
5.1 Amendments . . . 7
5.2 Quality Assurance . . . 7

1 Overview

This document describes the AMQP binding of the native `sysMonitor` service of Gatekeeper.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	AMQP	0-9-1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `sysMonitor` service interface

This document provides the Interface Design Description IDD to the *sysMonitor – Service Description* document [5].

1.1 Interface registration

With `sysmonitor.enabled=true`, Gatekeeper registers the service at start-up with interface template `generic_amqps` (protocol `amqps`, policy `CERT_AUTH`; `generic_amqp` without TLS) and the following properties and metadata:

```
{
  "serviceDefinitionName": "sysMonitor",
  "version": "1.0.0",
  "metadata": {
    "contract": "SysMonitor-AMQP-IDD-5.2.2",
    "schemaVersion": "1.0",
    "publisherMode": "native",
    "observationTypes": [
      "echo",
      "power",
      "status"
    ],
    "delivery": "persistent, publisher-confirmed"
  },
  "interfaces": [
    {
      "templateName": "generic_amqps",
      "protocol": "amqps",
      "policy": "CERT_AUTH",
      "properties": {
        "accessAddresses": [
          "amqp-broker"
        ],
        "accessPort": 5671,
        "exchange": "arrowhead",
        "baseRoutingKey": "TestCloud.sysmonitor.Gatekeeper.Gatekeeper",
        "operations": [
          "echo",
          "power",
          "status"
        ]
      }
    }
  ]
}
```

Listing 1: Registered service instance (TestCloud).

2 Service Operations

The publisher is the `Messaging.Publisher` of this independently packaged Gatekeeper system, configured with `AMQP_HOST`, `AMQP_PORT`, `LOCAL_CLOUD` and `MONITOR_INTERVAL_SECONDS` (30); its `echo` value is `status=alive` and the metadata add `implementation=java`. The publisher connects to the broker (default `amqp-broker`, port 5671) with TLS, verifies the broker host name and authenticates with its X.509 system certificate (SASL `EXTERNAL`; the certificate CN is the broker user name). Every publication interval it publishes each observation to the topic exchange `arrowhead` with the routing key `<baseRoutingKey>.<operation>`, where the base routing key is `<Cloud>.sysmonitor.<System>.<serviceInstance>`. Messages are persistent (delivery mode 2), `application/json`, carry the observation identifier as message id, and are publisher-confirmed (timeout 10 s); a failed cycle is retried with a new connection at the next interval. The broker's topic permissions allow the system to publish only below its own base routing key.

2.1 PUBLISH `<Cloud>.sysmonitor.Gatekeeper.Gatekeeper.echo`

Operation: echo
Output: Observation

Liveness: `status` (`alive` or `degraded`), `uptimeSeconds` and a `detail` text; quality `good` or `uncertain`.

2.2 PUBLISH `<Cloud>.sysmonitor.Gatekeeper.Gatekeeper.power`

Operation: power
Output: Observation

Power supply: `supplyType=line`, `state=available`; unit `1`.

2.3 PUBLISH `<Cloud>.sysmonitor.Gatekeeper.Gatekeeper.status`

Operation: status
Output: Observation

Process state: `state=running`, `health` (`healthy`/`degraded`) and `serviceCount`, the number of registered services.

```
{
  "schemaVersion": "1.0",
  "observationId": "Gatekeeper-echo-1792670400000-42",
  "providerSystem": "Gatekeeper",
  "serviceInstance": "Gatekeeper",
  "observationType": "echo",
  "sourceTime": "2026-10-22T12:00:00.000Z",
  "sequence": 42,
  "value": {
    "status": "alive",
    "uptimeSeconds": 3600,
    "detail": "Gatekeeper is running"
  },
  "quality": "good",
  "metadata": {
    "publisherMode": "native"
  }
}
```

Listing 2: An echo observation.

3 Data Models

3.1 struct Observation

Object Field	Value Type	Description
"schemaVersion"	String	`1.0`.
"observationId"	String	`<System>-<type>-<epoch ms>-<sequence>`.
"providerSystem"	String	The publishing system.
"serviceInstance"	String	Service instance, default the system name.
"observationType"	String	`echo`, `power`, `status`.
"sourceTime"	String	ISO 8601 UTC time with milliseconds.
"sequence"	Number	Sequence number per publisher.
"value"	Object	Observed value, see the operations.
"unit"	String	`1` for `power` and `status`; absent for `echo`.
"quality"	String	`good` or `uncertain`.
"metadata"	Object	`{"publisherMode": "native"}`.

3.2 Primitives

Type	Description
Number	JSON Number, an integer.
Object	JSON Object; Object<A> has string keys and values of type A.
String	JSON String.

4 References

[1] AMQP Working Group, “Amqp 0-9-1 specification,” AMQP Working Group, Tech. Rep., 2008.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “sysMonitor – Service Description (Gatekeeper),” Eclipse Arrowhead, SD 5.2.2, 2026, gatekeeper-v5.2.2-sysMonitor-SD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing
2	2026-10-25	5.2.2	Independent Java build, private helpers and state, per-system deployment and configuration.	Codex (draft)
3	2026-10-30	5.2.2	Checked against the primary Java source tree (Eclipse-Arrowhead-java): services, operations, paths and data models unchanged.	Claude Opus 5.5 (draft)

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	

1 Interface overview

HTTPS, mandatory mutual TLS, Arrowhead identity-token header and JSON request/response documents. General management is sysop/whitelist protected; enrollment endpoints use approved certificate fingerprints and profile/serial checks instead of ordinary identity tokens. Error responses contain errorMessage, errorCode, origin and timestamp. Exact DTO and status/error parity is not certified.

1.1 HTTPS interface operations

The listener is HTTPS with JSON by default; raw configuration and CRL responses use their declared media types. A request body is capped at 1 MiB. The table records implemented routes, not a claim of complete behavioral conformance.

Method	Path	Access
GET	/gatekeeper/echo	identity
POST	/gatekeeper/init_gsd	identity
POST	/gatekeeper/init_multi_gsd	identity
POST	/gatekeeper/init_icn	identity
GET	/gatekeeper/mgmt/clouds	management
POST	/gatekeeper/mgmt/clouds	management
DELETE	/gatekeeper/mgmt/clouds/{operator}/{name}	management
GET	/gatekeeper/mgmt/relays	management
POST	/gatekeeper/mgmt/relays	management
GET	/gatekeeper/mgmt/status	management
GET	/gatekeeper/monitor/echo	certificate
GET	/gatekeeper/general/mgmt/get-config	management
POST	/gatekeeper/general/mgmt/logs	management

1.2 Important delimitations

This implementation is a development profile, not a certified interchangeable Java replacement. All systems use private JSON snapshots rather than the Java databases. MQTT application APIs, exhaustive DTO normalization and error parity, automatic data migration and production qualification remain outstanding.

- Reuses the existing native Go legacy-mTLS relay engine, adapted to pinned clients. AH-GT-1 end-to-end encryption is absent. Broker ACLs and trusted neighbour provisioning remain required; no live federation is exercised by this delivery.
- The source reference uses a shared non-Spring HTTP dispatcher. Its route coverage is not inferred from Go route presence; manual JavaSupportRuntime review is required.

1 Gatekeeper

1.1 System overview

Native Rust development profile for local Java source `JavaSupportRuntime/`. One independently configured executable, identity, port and state file per role. No Java, Go or Python process implements the service. Some essential operations are explicitly unavailable.

1.2 Design and trust boundaries

Tokio/Hyper/Axum with rustls enforces mutual TLS. Certificate chain, validity, local CN/profile and startup-configured optional CRLs are checked. CRLs need process restart to refresh; without CRLs no revocation enforcement is claimed. Tokens are verified with Authentication and bound to the TLS identity. Business calls require ConsumerAuthorization; management requires a verified sysop or explicit broad whitelist. CA provisioning instead applies Java-style named certificate-principal rights. Outbound authorities are pinned to expected CN/profile before credentials are sent, in addition to chain, SAN and time validation.

1.3 Persistent state

Independent locked atomic JSON replaces SQL. Clone/validate/fsync/rename commits prevent partially published local transactions. Rename is the commit point; directory-sync failure is an uncertain durable commit, not a rollback. Owner-only keys/password files are separate. Network effects are not distributed transactions; interrupted starts and bridge operations require reconciliation. No automatic Java state import, clustering or deployment is delivered.

1.4 Implemented behavior

Neighbour and relay administration

1.5 Open release gates

AMQPS federation discovery/negotiation absent, returns501. All systems remain development profiles, not certified interchangeable Java replacements. See `COMPATIBILITY.md` for detailed DTO fields and restrictions; the Java sources remain the authoritative contract.

1.6 Produced and consumed services

Advertised implemented HTTPS definitions: `echo`, `gatekeeperManagement`, `generalManagement`.

Authorities consumed as applicable: Authentication, ServiceRegistry, ConsumerAuthorization and explicitly configured pinned adapter/provider origins. Only implemented operations are registered. Service versions are 1.0.0 except Gatekeeper/GateTunnel 5.2.2. No AMQP sysMonitor.observe implementation is advertised.

1.7 HTTPS operations

JSON unless raw configuration bytes, PEM CRL or echo text. Bodies: 1 MiB; remote responses: 8 MiB. Header: `Bearer IDENTITY-TOKEN//token`. Unknown routes return 404, absent dependencies 503. Unported operations return 501 after applicable access checks and are excluded from registration. Route presence is not semantic parity.

Method	Path	Access / status
GET	/gatekeeper/general/mgmt/get-config	management
POST	/gatekeeper/general/mgmt/logs	management
GET	/gatekeeper/monitor/echo	certificate
POST	/gatekeeper/init_gsd	identity / 501
POST	/gatekeeper/init_multi_gsd	identity / 501
POST	/gatekeeper/init_icn	identity / 501
GET	/gatekeeper/mgmt/clouds	management
POST	/gatekeeper/mgmt/clouds	management
DELETE	/gatekeeper/mgmt/clouds/{operator}/{name}	management
GET	/gatekeeper/mgmt/relays	management
POST	/gatekeeper/mgmt/relays	management

Error envelope: errorMessage, errorCode, exceptionType, origin and timestamp. Full Java status, DTO and validation equivalence requires differential testing.

2 References and qualification

See `contracts.json` for local Java SHA256 hashes/mappings, `COMPATIBILITY.md` for DTO details and gaps, and `VERIFICATION.md` for tests actually run. No upstream release-tag provenance, complete replacement or real-cloud interoperability is asserted.