PlantDescriptionEngine

System Design Description

Eclipse Arrowhead 5.2.2 | support system | Revision 2026-11-09 | REVIEW DRAFT

Purpose and document structure

This document describes implementation ownership, architecture, persistence, security and operational boundaries. The current cross-language sections below precede the detailed implementation appendices. Appendix dates and release labels belong to the retained baseline, not to a newly qualified release. Existing descriptions have been assembled from the primary trees; no live interoperability or semantic-parity claim is made.

Java implementation

Primary folder: Eclipse-Arrowhead-java/ah5-PlantDescriptionEngine-java-spring. 1 detailed Java SysDD source document(s) are included in the appendices. Their architecture, operation parameters, models, transport bindings, access rules and errors remain associated with Java. They must not be read as automatically implemented by the ports.

Go implementation

Primary folder: Eclipse-Arrowhead-go/ah5-PlantDescriptionEngine-go.

PlantDescriptionEngine - Go 5.2.2

Standalone support system, reorganized on 2026-10-28 following the Eclipse-Arrowhead-java distribution layout. Build and operate from this folder; no original Arrowhead checkout or sibling source module is required. The executable is bin/PlantDescriptionEngine. Entry point: ./cmd/plantdescriptionengine. Module: arrowhead/ah5-support-go/plantdescriptionengine. See DEPLOYMENT.md for configuration and standalone container use. Existing compatibility limits remain in the copied upstream documentation and UPSTREAM-README.md. The dedicated launcher selects only this support-system role. The formerly shared internal runtime and regression tests are copied locally, not linked from another tree. Files for common helpers and other route implementations remain in that private runtime; this packaging does not claim new functionality or Java parity. Documentation and license notices are included in this folder. Source provenance and import-only rewrites are listed in the distribution's SOURCE-MANIFEST.json. No running cloud or upstream source was changed.

Listening port

Built-in default 127.0.0.1:8432 (Arrowhead default). The shipped config.json, compose.yaml and Dockerfile use the same port on all interfaces ("listen": "0.0.0.0:8432"; 8540-8555 layout before 2026-11-09). Override with "listen" in the configuration file, SERVER_PORT=N or -server.port N; the port overrides keep the configured host. See [LISTENING-PORTS.md](../LISTENING-PORTS.md) for precedence and all systems.

Documented behavior and remaining work

System	Implemented behavior	Remaining work
PlantDescriptionEngine	Topology/include composition, named/metadata resolution, periodic alarms, DSO snapshot synchronization and monitor enrichment	Java state import, complete normalization/error parity and production qualification

Detailed implementation evidence

1 native Go SysDD document(s) are included in the appendices. Their protocol and storage descriptions apply to that implementation only. Current primary-folder ownership and current listening-port notes above supersede historical paths or example ports in those retained documents.

Rust implementation

Primary folder: Eclipse-Arrowhead-rust/ah5-PlantDescriptionEngine-rust.

PlantDescriptionEngine (Rust)

Arrowhead 5.2.2 PlantDescriptionEngine support system. Entry point src/main.rs is built as binary plantdescriptionengine by the shared crate in ../ah5-support-runtime-rust (arrowhead-support-rust).

- examples/plantdescriptionengine.json - example configuration (master copy: ../ah5-support-runtime-rust/examples/)

- documentation/ - SysD/SysDD/IDD/SD sources (symlink into ../ah5-support-runtime-rust/documentation/PlantDescriptionEngine, where the contract generator writes)

Run: cargo run -p arrowhead-support-rust --bin plantdescriptionengine -- <config.json>

Listening port

Default 127.0.0.1:8432 (Arrowhead default, role plantdescriptionengine). Override with "listen": "host:port" in the configuration, SERVER_PORT=N or --server.port N; the port overrides keep the configured host. See [LISTENING-PORTS.md](../LISTENING-PORTS.md) for precedence and all systems.

Documented behavior and remaining work

System	Implemented behavior	Remaining work
PlantDescriptionEngine	Topology CRUD/include composition, named/metadata matching, periodic registration/mismatch alarms, atomic DSO snapshot synchronization, alarm acknowledgment	Monitoring-staleness alarms, full Java DTO normalization/state import and production qualification

Detailed implementation evidence

1 native Rust SysDD document(s) are included in the appendices. Their protocol and storage descriptions apply to that implementation only. Current primary-folder ownership and current listening-port notes above supersede historical paths or example ports in those retained documents.

Build and state ownership

Core entry points are built by arrowhead-core-rust; the ordinary support entry points are built by arrowhead-support-rust using the shared support runtime. LocalCloudManager has its own crate. Per-system documentation links may point into the shared documentation catalog. Independent identity and state configuration is still required. Read the native appendix for persistence and restart semantics.

Cross-language qualification

Identical system names or HTTP paths do not establish interoperability. For the selected implementation, verify registered service versions and metadata, method/path and payload models, null and optional-field handling, success/error bodies, authentication and per-operation authorization, timeout/retry behavior and persistence across restart. Java MQTT/AMQP descriptions apply to a port only where its own implementation evidence

explicitly supports them. Missing transports must not be advertised. State conversion from Java SQL to native snapshots, secret provisioning, backup/restore and rollback require implementation-specific procedures. No data migration, deployment or cloud reconfiguration was performed for this document set.

Detailed appendices and provenance

- Java: Eclipse-Arrowhead-java/ah5-PlantDescriptionEngine-java-spring/documentation/v5.2.2/PlantDescriptionEngine-v5.2.2-SysDD.tex

- Go: Eclipse-Arrowhead-go/ah5-PlantDescriptionEngine-go/documentation/PlantDescriptionEngine/PlantDescriptionEngine-SysDD.tex

- Rust: Eclipse-Arrowhead-rust/ah5-support-runtime-rust/documentation/PlantDescriptionEngine/PlantDescriptionEngine-SysDD.tex

The package sources/ folder retains the selected LaTeX, figures, bibliography, language README/build evidence and source snapshots for newly described contracts. source-manifest.json records SHA-256 hashes of original inputs. build-report.json records whether an appendix used an existing newer PDF or was compiled from source.

PlantDescriptionEngine

System Design Description

Abstract
This document describes the design and implementation of the PlantDescriptionEngine support system of Arrowhead 5.2.2 (`ah5-PlantDescriptionEngine-java-spring`).

Contents

1 Overview **3**

2 Implementation **4**
2.1 Implementation language and tools 4
2.2 Independent source and build ownership 4
2.3 Functional properties implementation 4
2.4 Non functional properties implementation 5
2.5 Deployment 5
2.6 Local modifications 5
2.7 Verification 6

3 Services **7**

4 References **7**

5 Revision History **9**
5.1 Amendments 9
5.2 Quality Assurance 9

1 Overview

This document describes the PlantDescriptionEngine system implementation, which realizes the PlantDescriptionEngine SysD [1]. The PlantDescriptionEngine keeps the cloud's orchestration consistent with an engineered plant description: it turns the active description's connections into a managed snapshot of DSO provider rules, reconciles them periodically and raises alarms where the running cloud differs. In Section 2, we describe implementation details of the system.

2 Implementation

This implementation is based on the SysD document PlantDescriptionEngine [1] and is located in `ah5-PlantDescriptionEngine-java-spring`.

2.1 Implementation language and tools

- Java 21, Spring Boot 3.4.9, Arrowhead common library 5.2.2 (private source under `vendor/`), Log4j 2; MariaDB Connector/J against MySQL 8.4 with TLS in the standalone deployment.
- Database `ah_plantdescriptionengine` on MySQL 8.4 (MariaDB Connector/J, TLS with server verification in the standalone deployment), schema validated by Hibernate; SQL scripts in `src/main/resources/database`. Stateless request processing; scheduled jobs use Quartz.

2.2 Independent source and build ownership

The project folder owns its application source, Maven build, tests, executable JAR, Dockerfile, configuration and Compose definition. No source or image is taken from a sibling support folder or JavaSupportRuntime. Build with Java 21 and `mvn -B clean verify`; a populated external Maven dependency cache permits offline builds.

Arrowhead common utilities and DTOs are private source copies in `vendor/`, compiled into this system by the local Maven POM. No Arrowhead common/core parent or separately installed Arrowhead library is needed. Upstream POMs, licenses and source hashes are retained for provenance. Security updates must be propagated and tested in every affected copy. Third-party dependencies remain ordinary Maven libraries.

The packaged artifact is `arrowhead-plantdescriptionengine-5.2.2.jar`. The image builds and tests this folder only; the system has a fixed application main class.

2.3 Functional properties implementation

The following components implement the system:

Component	Responsibility
`api.http`	Controllers of the three services.
`service`	Validation, matching, synchronization and alarms.
`jpa`	Description, alarm and log entities.

Every request passes the common filter chain: authentication filter (`authentication.policy`), optional blacklist filter, management filter (management services), the system's authorization filter where present, then the controller, validation and normalization, the service logic and the database service.

2.3.1 Data handled and stored

Storage `ah_plantdescriptionengine`:

Tables	Content
`plant_description`	Plant descriptions (JSON).
`pde_alarm`	Alarms.
`logs`	Log entries.

The data models of the interfaces are Java records (of `eu.arrowhead.dto` in the common library, or of the module); the IDD documents name them without the `DTO` suffix. The records used by this system are: `ConnectionDTO`, `KeyValuesDTO`, `LogEntryDTO`, `LogEntryListResponseDTO`, `LogRequestDTO`, `MonitorPlantDescriptionListResponseDTO`, `Monitor`

`PlantDescriptionResponseDTO`, `MonitorSystemDTO`, `PageDTO`, `PdeAlarmListResponseDTO`, `PdeAlarmResponseDTO`, `PdeAlarmUpdateDTO`, `PdeSystemDTO`, `PlantDescriptionListResponseDTO`, `PlantDescriptionRequestDTO`, `PlantDescriptionResponseDTO`, `PlantDescriptionUpdateDTO`, `PortDTO`, `SystemPortDTO`.

2.4 Non functional properties implementation

2.4.1 Security

TLS and client authentication are configured with the Spring `server.ssl.*` properties (PKCS#12 keystore and truststore, `client-auth=need`). The common library's filters implement the authentication policies; `TokenCertificateBinding` binds identity tokens to the client certificate and `CrlRevocationConfig` enables CRL checking.

2.4.2 Power management

None; the system is a server process without power states. The `sysMonitor power` observation always reports line supply.

2.4.3 Internal monitoring

Log4j 2 logs to stdout and files; log entries are also written to the `logs` table and served by `generalManagement.get-log`. The common library's `SysMonitorPublisher` publishes `echo`, `power` and `status` every 30 s.

2.4.4 Configuration

Configuration is read from `application.properties` and environment variables (Spring relaxed binding); secrets come from files through `SPRING_CONFIG_IMPORT=configtree:/run/secrets/`. The properties are listed in the SysD; `generalManagement.get-config` returns the public ones.

2.5 Deployment

The local `compose.yaml` selects only this support system and its private MySQL database. It joins an operator-selected external cloud network; it does not start core systems or another support system. Copy `.env.example`, provision this system's own identity and credential files, validate the Compose definition, then run `docker compose up -d -build` from this folder. The image uses the secure external `config/application.properties`, mutual TLS, outsourced authentication, certificate/token binding and a mounted CRL. Secrets are read through Spring's file configuration tree. The app runs as UID 10001 with a read-only root filesystem and bounded non-executable temporary/log storage.

The database image initializes this system's own schema on an empty project-owned volume, reads independent random user/root passwords from files and uses a dedicated internal network. It has no host port. The application verifies the database TLS certificate against its public DB CA. The DB key and CA signing key are never mounted into the application. Distinct Compose project names, host ports and private subnets are required for multiple deployments. Existing volumes require explicit migration/backup handling; ordinary shutdown preserves them.

Registry, Authentication, DSO, ConsumerAuthorization and required brokers/providers remain network dependencies. Independent deployment does not remove those service contracts. The listener health check is only a liveness check; inspect successful application startup, registration and authenticated service access before acceptance. The local `DEPLOYMENT.md` supplies the complete procedure. The previously recorded live-cloud deployment is historical baseline evidence; the new packaging does not change a live cloud.

2.6 Local modifications

Notes on this implementation in the workspace:

- Migration of v4.6; liveness from SysMonitor instead of pinging.

- 2026-10-23: replace the SSO dependency with DSO managed scopes and ranked providers. Lower priority wins among surviving eligible candidates; existing client orchestration caches may delay visible changes.

2.7 Verification

Independent folder-only Maven builds run the project's JUnit suite. Artifact inspection checks the system main/source and absence of JavaSupportRuntime or other support-system implementations. Images and project-local Compose definitions are tested with private disposable state and generated test identities. Spring startup and authenticated HTTPS requests use isolated mutual-TLS core-service fixtures; missing-token and missing-certificate requests are refused. The distribution verification report records exact results and limitations. Broker, NTP and inter-cloud acceptance remain separate from deployment/startup validation.

3 Services

The implementation of the services is based on the SD and IDD documents referenced below.

Services produced	**SysD ref**	**SD ref**	**IDD ref**
`plantDescriptionManagement`	[1]	[2]	[3]
`plantDescriptionMonitor`	[1]	[4]	[5]
`generalManagement`	[1]	[6]	[7]
`sysMonitor`	[1]	[8]	[9]
Services consumed	**SysD ref**	**SD ref**	**IDD ref**
systemDiscovery, serviceDiscovery	[10]	[11]	–
serviceRegistryManagement	[10]	[12]	–
identity	[13]	[14]	–
authorization	[15]	[16]	–
serviceOrchestrationPlant Management	[17]	–	–
sysMonitorHistory	[18]	[19]	–
sysMonitor (publisher)	AMQP broker (SysMonitor)	–	–

4 References

[1] J. Delsing, “PlantDescriptionEngine – System Description,” Eclipse Arrowhead, SysD 5.2.2, 2026, ah5-support-java-spring/PlantDescriptionEngine/documentation/v5.2.2/PlantDescriptionEngine-v5.2.2-SysD.pdf.

[2] ——, “plantDescriptionManagement – Service Description (PlantDescriptionEngine),” Eclipse Arrowhead, SD 5.2.2, 2026, plantDescriptionEngine-v5.2.2-plantDescriptionManagement-SD.pdf.

[3] ——, “plantDescriptionManagement HTTP/TLS/JSON – Interface Design Description (PlantDescriptionEngine),” Eclipse Arrowhead, IDD 5.2.2, 2026, plantDescriptionEngine-v5.2.2-plantDescriptionManagement-HTTP-IDD.pdf.

[4] ——, “plantDescriptionMonitor – Service Description (PlantDescriptionEngine),” Eclipse Arrowhead, SD 5.2.2, 2026, plantDescriptionEngine-v5.2.2-plantDescriptionMonitor-SD.pdf.

[5] ——, “plantDescriptionMonitor HTTP/TLS/JSON – Interface Design Description (PlantDescriptionEngine),” Eclipse Arrowhead, IDD 5.2.2, 2026, plantDescriptionEngine-v5.2.2-plantDescriptionMonitor-HTTP-IDD.pdf.

[6] ——, “generalManagement – Service Description (PlantDescriptionEngine),” Eclipse Arrowhead, SD 5.2.2, 2026, plantDescriptionEngine-v5.2.2-generalManagement-SD.pdf.

[7] ——, “generalManagement HTTP/TLS/JSON – Interface Design Description (PlantDescriptionEngine),” Eclipse Arrowhead, IDD 5.2.2, 2026, plantDescriptionEngine-v5.2.2-generalManagement-HTTP-IDD.pdf.

[8] ——, “sysMonitor – Service Description (PlantDescriptionEngine),” Eclipse Arrowhead, SD 5.2.2, 2026, plantDescriptionEngine-v5.2.2-sysMonitor-SD.pdf.

[9] ——, “sysMonitor AMQP/TLS/JSON – Interface Design Description (PlantDescriptionEngine),” Eclipse Arrowhead, IDD 5.2.2, 2026, plantDescriptionEngine-v5.2.2-sysMonitor-AMQP-IDD.pdf.

[10] ——, “ServiceRegistry – System Description,” Eclipse Arrowhead, SysD 5.2.2, 2026, ah5-core-java-spring/serviceregistry/documentation/v5.2.2/ServiceRegistry-v5.2.2-SysD.pdf.

[11] ——, “systemDiscovery – Service Description (ServiceRegistry),” Eclipse Arrowhead, SD 5.2.2, 2026, ah5-core-java-spring/serviceregistry/documentation/v5.2.2/ServiceRegistry-v5.2.2-systemDiscovery-SD.pdf.

[12] ——, “serviceRegistryManagement – Service Description (ServiceRegistry),” Eclipse Arrowhead, SD 5.2.2, 2026, ah5-core-java-spring/serviceregistry/documentation/v5.2.2/ServiceRegistry-v5.2.2-serviceRegistryManagement-SD.pdf.

[13] ——, “Authentication – System Description,” Eclipse Arrowhead, SysD 5.2.2, 2026, ah5-core-java-spring/authentication/documentation/v5.2.2/Authentication-v5.2.2-SysD.pdf.

[14] ——, “identity – Service Description (Authentication),” Eclipse Arrowhead, SD 5.2.2, 2026, ah5-core-java-spring/authentication/documentation/v5.2.2/Authentication-v5.2.2-identity-SD.pdf.

[15] ——, “ConsumerAuthorization – System Description,” Eclipse Arrowhead, SysD 5.2.2, 2026, ah5-core-java-spring/consumer-authorization/documentation/v5.2.2/ConsumerAuthorization-v5.2.2-SysD.pdf.

[16] ——, “authorization – Service Description (ConsumerAuthorization),” Eclipse Arrowhead, SD 5.2.2, 2026, ah5-core-java-spring/consumer-authorization/documentation/v5.2.2/ConsumerAuthorization-v5.2.2-authorization-SD.pdf.

[17] ——, “DynamicServiceOrchestration – System Description,” Eclipse Arrowhead, SysD 5.2.2, 2026, ah5-core-java-spring/serviceorchestration-dynamic/documentation/v5.2.2/DynamicServiceOrchestration-v5.2.2-SysD.pdf.

[18] ——, “SysMonitor – System Description,” Eclipse Arrowhead, SysD 5.2.2, 2026, ah5-support-java-spring/SysMonitor/documentation/v5.2.2/SysMonitor-v5.2.2-SysD.pdf.

[19] ——, “sysMonitorHistory – Service Description (SysMonitor),” Eclipse Arrowhead, SD 5.2.2, 2026, sysMonitor-v5.2.2-sysMonitorHistory-SD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-23	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing
2	2026-10-25	5.2.2	Self-contained build, private library source, configuration, images, database and isolated deployment verification.	Codex (draft)
3	2026-10-30	5.2.2	Checked against the primary Java source tree (Eclipse-Arrowhead-java): standalone deployment, configuration and security statements updated.	Claude Opus 5.5 (draft)

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	

1 PlantDescriptionEngine

1.1 System overview

Plant topology and monitored alarm state. The native Go executable selects this system independently; no Java or Python process implements its operations. Shared source is in `internal/core`; federation code is in `internal/relay`.

1.2 Produced and consumed services

Produced HTTPS services: `echo`, `generalManagement`, `plantDescriptionManagement`, `plantDescriptionMonitor`. HTTPS service version 1.0.0. Optional native AMQPS telemetry produces `sysMonitor`; SysMonitor additionally publishes `sysMonitorData` over MQTT/TLS. Consumed authorities include ServiceRegistry, Authentication and ConsumerAuthorization; optional dependencies are explicit pinned HTTPS origins.

1.3 Important delimitations

This implementation is a development profile, not a certified interchangeable Java replacement. All systems use private JSON snapshots rather than the Java databases. MQTT application APIs, exhaustive DTO normalization and error parity, automatic data migration and production qualification remain outstanding.

- Topology/include composition, named and metadata matching, periodic alarms, and atomic PDE-to-DSO snapshot synchronization are implemented. Missing producers retain managed empty scopes; nonnegative priorities rank eligible providers. Java SQL import, complete DTO normalization and production qualification remain outside this extension.

1.4 Security and persistence

Mutual TLS verifies the configured cloud trust anchors. Application identity tokens must match the client certificate. Authorities are pinned by system CN/profile before credentials are sent. Management requires a verified sysop identity or an explicit broad management whitelist. The default service authorization policy is enforce; identity-only mode must be explicitly selected. No insecure listener or declared-identity mode is implemented. Each executable owns one locked state file, written through fsync and atomic rename. Cross-system operations are not distributed transactions.

2 Implementation

Go 1.26 or newer builds the native binary. State is serialized as private JSON documents; updates clone state, validate, persist and then publish. Server timeouts and bounded message sizes constrain resource use. Persistent outboxes are at-least-once and cannot provide distributed exactly-once delivery. Detailed source, configuration and test instructions are in the repository README and verification report.

2.1 HTTPS interface operations

The listener is HTTPS with JSON by default; raw configuration and CRL responses use their declared media types. A request body is capped at 1 MiB. The table records implemented routes, not a claim of complete behavioral conformance.

Method	Path	Access
GET	/plantdescriptionengine/mgmt/sync-status	management
GET	/plantdescriptionengine/mgmt/plant-descriptions	management
GET	/plantdescriptionengine/mgmt/plant-descriptions/{id}	management
POST	/plantdescriptionengine/mgmt/plant-descriptions	management
PUT	/plantdescriptionengine/mgmt/plant-descriptions/{id}	management
PATCH	/plantdescriptionengine/mgmt/plant-descriptions/{id}	management
DELETE	/plantdescriptionengine/mgmt/plant-descriptions/{id}	management
GET	/plantdescriptionengine/monitor/plant-descriptions	identity
GET	/plantdescriptionengine/monitor/plant-descriptions/{id}	identity
GET	/plantdescriptionengine/monitor/alarms	identity
GET	/plantdescriptionengine/monitor/alarms/{id}	identity
PATCH	/plantdescriptionengine/monitor/alarms/{id}	identity
GET	/plantdescriptionengine/monitor/echo	certificate
GET	/plantdescriptionengine/general/mgmt/get-config	management
POST	/plantdescriptionengine/general/mgmt/logs	management

1 PlantDescriptionEngine

1.1 System overview

Native Rust development profile for local Java source `PlantDescriptionEngine/`. One independently configured executable, identity, port and state file per role. No Java, Go or Python process implements the service. Some essential operations are explicitly unavailable.

1.2 Design and trust boundaries

Tokio/Hyper/Axum with rustls enforces mutual TLS. Certificate chain, validity, local CN/profile and startup-configured optional CRLs are checked. Configured CRLs and TLS material reload without process restart; verification fails closed when required material is unavailable. Tokens are verified with Authentication and bound to the TLS identity. Business calls require ConsumerAuthorization; management requires a verified sysop or explicit broad whitelist. CA provisioning instead applies Java-style named certificate-principal rights. Outbound authorities are pinned to expected CN/profile before credentials are sent, in addition to chain, SAN and time validation.

1.3 Persistent state

Independent locked atomic JSON replaces SQL. Clone/validate/fsync/rename commits prevent partially published local transactions. Rename is the commit point; directory-sync failure is an uncertain durable commit, not a rollback. Owner-only keys/password files are separate. Network effects are not distributed transactions; interrupted starts and bridge operations require reconciliation. No automatic Java state import, clustering or deployment is delivered.

1.4 Implemented behavior

Topology CRUD/include composition, named/metadata matching, periodic registration/mismatch alarms, atomic DSO snapshot synchronization, alarm acknowledgment

1.5 Open release gates

Monitoring-staleness alarms, full Java DTO normalization/state import and production qualification. All systems remain development profiles, not certified interchangeable Java replacements. See `COMPATIBILITY.md` for detailed DTO fields and restrictions; the Java sources remain the authoritative contract.

1.6 Produced and consumed services

Advertised implemented HTTPS definitions: `echo`, `generalManagement`, `plantDescriptionManagement`, `plantDescriptionMonitor`.

Authorities consumed as applicable: Authentication, ServiceRegistry, ConsumerAuthorization and explicitly configured pinned adapter/provider origins. Only implemented operations are registered. Service versions are 1.0.0 except Gatekeeper/GateTunnel 5.2.2. Optional native AMQP monitoring publishes echo, power and status observations.

1.7 HTTPS operations

JSON unless raw configuration bytes, PEM CRL or echo text. Bodies: 1 MiB; remote responses: 8 MiB. Header: `Bearer IDENTITY-TOKEN//token`. Unknown routes return 404, absent dependencies 503. Unported operations return 501 after applicable access checks and are excluded from registration. Route presence is not semantic parity.

Method	Path	Access / status
GET	/plantdescriptionengine/general/mgmt/get-config	management
POST	/plantdescriptionengine/general/mgmt/logs	management
GET	/plantdescriptionengine/monitor/echo	certificate
GET	/plantdescriptionengine/mgmt/sync-status	management
GET	/plantdescriptionengine/mgmt/plant-descriptions	management
POST	/plantdescriptionengine/mgmt/plant-descriptions	management
GET	/plantdescriptionengine/mgmt/plant-descriptions/{id}	management
PUT	/plantdescriptionengine/mgmt/plant-descriptions/{id}	management
PATCH	/plantdescriptionengine/mgmt/plant-descriptions/{id}	management
DELETE	/plantdescriptionengine/mgmt/plant-descriptions/{id}	management
GET	/plantdescriptionengine/monitor/plant-descriptions	identity
GET	/plantdescriptionengine/monitor/plant-descriptions/{id}	identity
GET	/plantdescriptionengine/monitor/alarms	identity
GET	/plantdescriptionengine/monitor/alarms/{id}	identity
PATCH	/plantdescriptionengine/monitor/alarms/{id}	identity

Error envelope: errorMessage, errorCode, exceptionType, origin and timestamp. Full Java status, DTO and validation equivalence requires differential testing.

2 References and qualification

See `contracts.json` for local Java SHA256 hashes/mappings, `COMPATIBILITY.md` for DTO details and gaps, and `VERIFICATION.md` for tests actually run. No upstream release-tag provenance, complete replacement or real-cloud interoperability is asserted.

3 PDE and DSO snapshot extension (23 October 2026)

The local Java, Go and native Rust implementations provide the same HTTPS snapshot contract. The registered service is `serviceOrchestrationPlantManagement`, version 1.0.0. The API is a local extension to the upstream framework.

Method	Resource and operation
POST	`/serviceorchestration/mgmt/plant-rules/query` (query)
PUT	`/serviceorchestration/mgmt/plant-rules/replace` (replace)

Both operations return the complete snapshot. The request for replacement has `rules`, an array of scopes. Each scope contains `consumer`, `serviceDefinition`, and `providers`; each provider contains `serviceInstanceId` and integer `priority`. Priority zero is valid; lower values rank first. Duplicate scopes and provider IDs, null arrays, and invalid priorities are rejected before commit. Empty rules clear management; empty providers retain a managed but unavailable scope.

PDE composes includes and resolves names/metadata against registered systems and instances. Named consumers remain managed when unregistered; missing or ambiguous producers retain empty scopes. Repeated provider IDs use the minimum priority. PDE queries before replacing and requires an equal acknowledgment. Failed reads do not clear rules. Registry query pages are bounded at 1000 entries. An incomplete response fails synchronization and preserves the last DSO snapshot. Changes reconcile normally within two seconds of a plant change and within thirty seconds of registry changes. `/plantdescriptionengine/mgmt/sync-status` exposes the loop state under management access.

DSO restricts candidates to the scope, retains existing authorization, operation/interface and exclusivity checks, then ranks eligible providers. Matchmaking selects the lowest eligible priority. A denied or missing primary can use an engineered fallback. Unrelated providers and both inter-cloud flags cannot escape a managed scope. Unsupported existing translation/QoS features remain unsupported.

Mutual TLS and certificate-bound identity tokens remain mandatory. Only PDE or Sysop can replace; PDE, LocalCloudManager or Sysop can query. PDE gains no general DSO administration right. ServiceRegistry reserves the new service definition for DSO. Native Rust permits PDE only the two required registry query operations. DSO's `plantRules.active` record is persisted by an atomic private JSON commit and survives restart. Existing native state files need no SQL migration. Java uses its separate table migration.

The Go deployment script regenerates pinned runtime origins and installs scoped policies; the Rust script targets the native candidate. Both preserve state. Legacy SimpleStore rows remain independent and are not imported or automatically deleted. Coordinated rollback must restore PDE and its backend together. Current live evidence covers priority zero, fallback, unavailable producers, both inter-cloud guards, restart persistence with PDE stopped, and deactivation. This does not claim complete Java equivalence or production load qualification.