authorizationTokenManagement HTTP/TLS/JSON

Interface Design Description

Service ID: *"authorizationTokenManagement"*

Abstract
This document describes the HTTP/1.1 protocol with TLS payload security and JSON payload encoding variant of the `authorizationTokenManagement` service of the ConsumerAuthorization system.

Contents

1 Overview **3**
1.1 Interface registration . . . 3

2 Service Operations **4**
2.1 operation generate-tokens . . . 4
2.2 operation query-tokens . . . 5
2.3 operation revoke-tokens . . . 6
2.4 operation add-encryption-keys . . . 6
2.5 operation remove-encryption-keys . . . 7

3 Data Models **8**
3.1 struct AuthorizationMgmtEncryptionKeyListResponse . . . 8
3.2 struct AuthorizationMgmtEncryptionKeyRegistrationListRequest . . . 8
3.3 struct AuthorizationMgmtEncryptionKeyRegistrationRequest . . . 8
3.4 struct AuthorizationMgmtEncryptionKeyResponse . . . 8
3.5 struct AuthorizationTokenGenerationMgmtListRequest . . . 8
3.6 struct AuthorizationTokenGenerationMgmtRequest . . . 9
3.7 struct AuthorizationTokenMgmtListResponse . . . 9
3.8 struct AuthorizationTokenQueryRequest . . . 9
3.9 struct AuthorizationTokenResponse . . . 10
3.10 struct ErrorMessage . . . 10
3.11 struct Page . . . 10
3.12 Primitives . . . 11

4 References **12**

5 Revision History **13**
5.1 Amendments . . . 13
5.2 Quality Assurance . . . 13

1 Overview

This document describes the `authorizationTokenManagement` service interface of the ConsumerAuthorization system, which provides operator management of authorization tokens and of provider encryption keys.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	HTTP	1.1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `authorizationTokenManagement` service interface

This document provides the Interface Design Description IDD to the *authorizationTokenManagement – Service Description* document [5]. For further details about how this service is meant to be used, please consult that document.

The rest of this document describes how to realize the `authorizationTokenManagement` service interface in detail. Both in terms of its operations (Section 2) and its information model (Section 3).

1.1 Interface registration

The service is registered in the ServiceRegistry with the interface template `generic_https` (`generic_http` when TLS is disabled), access port 8445 and base path `/consumerauthorization/authorization/mgmt/token`. The `operations` property of the interface lists the operations below with their method and path relative to the base path:

Operation	Method	Path
`generate-tokens`	POST	`/generate`
`query-tokens`	POST	`/query`
`revoke-tokens`	DELETE	`/revoke`
`add-encryption-keys`	POST	`/encryption-key`
`remove-encryption-keys`	DELETE	`/encryption-key`

2 Service Operations

The interfaces of the `authorizationTokenManagement` service, its operations, data models and implementation are provided below. In particular, each subsection first names the HTTP method and path used to call the operation, after which it names the abstract operation from the `authorizationTokenManagement` SD document, as well as input and output types.

All operations require the requester's identity, presented according to the provider's authentication policy: the client certificate (mutual TLS) and, with the `outsourced` policy, `Authorization: Bearer IDENTITY-TOKEN//<token>`; systems holding the Authentication secret key send `Bearer AUTHENTICATOR-KEY//<system>//<hash>`, and with the `declared` policy `Bearer SYSTEM//<system>` is sent. Request and response bodies are `application/json`. Errors are answered with an ErrorMessage body and the status codes `400 Bad Request` (invalid parameter), `401 Unauthorized` (missing or invalid identity), `403 Forbidden` (not permitted, e.g. by the management or blacklist filter), `404 Not Found`, `408 Request Timeout`, `423 Locked`, `500 Internal Server Error` and `503 Service Unavailable` (a system it depends on failed).

2.1 POST /consumerauthorization/authorization/mgmt/token/generate?unbound=*{unbound}*

Operation: generate-tokens
Input: AuthorizationTokenGenerationMgmtListRequest
Output: AuthorizationTokenMgmtListResponse

Generates tokens on behalf of consumers. With `unbound=true` the authorization check is skipped (only for systems in `unbounded.token.generation.whitelist`).

Query parameters: *unbound* (boolean, optional, default `false`). List values are repeated or comma-separated.

A successful call returns `201 Created` with the output in the body.

```
POST /consumerauthorization/authorization/mgmt/token/generate?unbound=<unbound> HTTP/1.1
Host: consumerauthorization:8445
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "list": [
    {
      "tokenVariant": "TIME_LIMITED_TOKEN_AUTH",
      "targetType": "SERVICE_DEF",
      "consumerCloud": "LOCAL",
      "consumer": "TemperatureDisplay",
      "provider": "TemperatureSensor",
      "target": "temperatureReading",
      "scope": "read",
      "expiresAt": "2026-10-22T12:00:00Z",
      "usageLimit": 5
    }
  ]
}
```

Listing 1: An generate-tokens invocation.

```
{
  "entries": [
    {
      "tokenType": "TIME_LIMITED_TOKEN",
      "variant": "TIME_LIMITED_TOKEN_AUTH",
      "token": "<token>",
      "tokenReference": "<token reference>",
      "requester": "DynamicServiceOrchestration",
```

```
      "consumerCloud": "LOCAL",
      "consumer": "TemperatureDisplay",
      "provider": "TemperatureSensor",
      "targetType": "SERVICE_DEF",
      "target": "temperatureReading",
      "scope": "read",
      "createdAt": "2026-10-22T12:00:00Z",
      "usageLimit": 5,
      "usageLeft": 5,
      "expiresAt": "2026-10-22T12:00:00Z"
    }
  ],
  "count": 1
}
```

Listing 2: An generate-tokens response.

2.2 POST /consumerauthorization/authorization/mgmt/token/query

Operation: query-tokens
Input: AuthorizationTokenQueryRequest
Output: AuthorizationTokenMgmtListResponse

Returns a page of tokens matching the filter.

A successful call returns `200 OK` with the output in the body.

```
POST /consumerauthorization/authorization/mgmt/token/query HTTP/1.1
Host: consumerauthorization:8445
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "pagination": {
    "page": 0,
    "size": 10,
    "direction": "ASC",
    "sortField": "createdAt"
  },
  "requester": "DynamicServiceOrchestration",
  "tokenType": "TIME_LIMITED_TOKEN",
  "consumerCloud": "LOCAL",
  "consumer": "TemperatureDisplay",
  "provider": "TemperatureSensor",
  "targetType": "SERVICE_DEF",
  "target": "temperatureReading"
}
```

Listing 3: An query-tokens invocation.

```
{
  "entries": [
    {
      "tokenType": "TIME_LIMITED_TOKEN",
      "variant": "TIME_LIMITED_TOKEN_AUTH",
      "token": "<token>",
      "tokenReference": "<token reference>",
      "requester": "DynamicServiceOrchestration",
      "consumerCloud": "LOCAL",
      "consumer": "TemperatureDisplay",
      "provider": "TemperatureSensor",
      "targetType": "SERVICE_DEF",
      "target": "temperatureReading",
      "scope": "read",
      "createdAt": "2026-10-22T12:00:00Z",
```

```
      "usageLimit": 5,
      "usageLeft": 5,
      "expiresAt": "2026-10-22T12:00:00Z"
    }
  ],
  "count": 1
}
```

Listing 4: An query-tokens response.

2.3 DELETE /consumerauthorization/authorization/mgmt/token/revoke?tokenReferences=*{tokenReferences}*

Operation: revoke-tokens
Input: Array<String>

Revokes tokens by token reference.

Query parameters: *tokenReferences* (List<String>, required). List values are repeated or comma-separated.

A successful call returns `200 OK`.

```
DELETE /consumerauthorization/authorization/mgmt/token/revoke?tokenReferences=<tokenReferences> HTTP/1.1
Host: consumerauthorization:8445
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 5: An revoke-tokens invocation.

2.4 POST /consumerauthorization/authorization/mgmt/token/encryption-key

Operation: add-encryption-keys
Input: AuthorizationMgmtEncryptionKeyRegistrationListRequest
Output: AuthorizationMgmtEncryptionKeyListResponse

Registers encryption keys on behalf of providers.

A successful call returns `201 Created` with the output in the body.

```
POST /consumerauthorization/authorization/mgmt/token/encryption-key HTTP/1.1
Host: consumerauthorization:8445
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "list": [
    {
      "systemName": "TemperatureSensor",
      "key": "0123456789abcdef",
      "algorithm": "AES/ECB/PKCS5Padding"
    }
  ]
}
```

Listing 6: An add-encryption-keys invocation.

```
{
  "entries": [
    {
      "systemName": "TemperatureSensor",
      "rawKey": "0123456789abcdef",
      "algorithm": "AES/ECB/PKCS5Padding",
      "keyAdditive": "",
```

```
      "createdAt": "2026-10-22T12:00:00Z"
    }
  ],
  "count": 1
}
```

Listing 7: An add-encryption-keys response.

2.5 DELETE /consumerauthorization/authorization/mgmt/token/encryption-key?systemNames=*{systemNames}*

Operation: remove-encryption-keys
Input: Array<String>

Removes the encryption keys of the named providers.
Query parameters: *systemNames* (List<String>, required). List values are repeated or comma-separated.
A successful call returns `200 OK`.

```
DELETE /consumerauthorization/authorization/mgmt/token/encryption-key?systemNames=<systemNames> HTTP/1.1
Host: consumerauthorization:8445
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 8: An remove-encryption-keys invocation.

3 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is meant to denote a JSON Object that must contain certain fields, or names, with values conforming to explicitly named types. Fields that are not needed may be omitted or `null` in requests; empty fields are omitted in responses. As a complement to the primary types defined in this section, there is also a list of secondary types in Section 3.12, which are used to represent things like hashes, identifiers and texts.

3.1 struct AuthorizationMgmtEncryptionKeyListResponse

List of registered encryption keys.

Object Field	Value Type	Description
"entries"	Array<AuthorizationMgmtEncryptionKeyResponse>	Matching records of the current page.
"count"	Number	Total number of matching records (all pages).

3.2 struct AuthorizationMgmtEncryptionKeyRegistrationListRequest

Encryption keys to register on behalf of providers.

Object Field	Value Type	Description
"list"	Array<AuthorizationMgmtEncryptionKeyRegistrationRequest>	The list of request items.

3.3 struct AuthorizationMgmtEncryptionKeyRegistrationRequest

Encryption key of one provider.

Object Field	Value Type	Description
"systemName"	String	Provider system the key belongs to.
"key"	String	The encryption key, as a string.
"algorithm"	String	Encryption algorithm of the key, e.g. `AES/ECB/PKCS5Padding` or `AES/CBC/PKCS5Padding`.

3.4 struct AuthorizationMgmtEncryptionKeyResponse

A registered encryption key.

Object Field	Value Type	Description
"systemName"	String	Name of the system, PascalCase (e.g. `TemperatureSensor`).
"rawKey"	String	The registered encryption key.
"algorithm"	String	Encryption algorithm of the key, e.g. `AES/ECB/PKCS5Padding` or `AES/CBC/PKCS5Padding`.
"keyAdditive"	String	Initialization vector (CBC mode), Base64; empty for ECB.
"createdAt"	DateTime	UTC time of creation.

3.5 struct AuthorizationTokenGenerationMgmtListRequest

Tokens to generate on behalf of consumers.

Object Field	Value Type	Description
"list"	Array<AuthorizationTokenGenerationMgmtRequest>	The list of request items.

3.6 struct AuthorizationTokenGenerationMgmtRequest

One token to generate on behalf of a consumer.

Object Field	Value Type	Description
"tokenVariant"	String	Requested token variant, as interface security policy (e.g. `TIME_LIMITED_TOKEN_AUTH`, `RSA_SHA512_JSON_WEB_TOKEN_AUTH`).
"targetType"	String	Target type: `SERVICE_DEF` or `EVENT_TYPE`.
"consumerCloud"	String	Cloud identifier of the consumer system.
"consumer"	String	Name of the consumer system.
"provider"	String	Name of the provider system.
"target"	String	Target of the policy or token: a service definition or event type.
"scope"	String	Operation the token or policy is limited to; empty for all operations.
"expiresAt"	DateTime	Requested expiry; default `token.time.limit` from now.
"usageLimit"	Number	Requested uses; default `simple.token.usage.limit`.

3.7 struct AuthorizationTokenMgmtListResponse

List of generated tokens.

Object Field	Value Type	Description
"entries"	Array<AuthorizationTokenResponse>	Matching records of the current page.
"count"	Number	Total number of matching records (all pages).

3.8 struct AuthorizationTokenQueryRequest

Filter for generated tokens.

Object Field	Value Type	Description
"pagination"	Page	Paging and sorting of the result.
"requester"	String	Name of the system that requested the token.
"tokenType"	String	Token type to match.
"consumerCloud"	String	Cloud identifier of the consumer system.
"consumer"	String	Name of the consumer system.
"provider"	String	Name of the provider system.
"targetType"	String	Target type: `SERVICE_DEF` or `EVENT_TYPE`.
"target"	String	Target of the policy or token: a service definition or event type.

3.9 struct AuthorizationTokenResponse

A generated token with its bookkeeping data.

Object Field	Value Type	Description
"tokenType"	AuthorizationTokenType	Token type: `TIME_LIMITED_TOKEN`, `USAGE_LIMITED_TOKEN`, `SELF_CONTAINED_TOKEN` or `TRANSLATION_BRIDGE_TOKEN`.
"variant"	String	Token variant (interface security policy).
"token"	String	The token, for simple tokens only in hashed form.
"tokenReference"	String	Reference of the token, used to revoke it.
"requester"	String	Name of the system that requested the token.
"consumerCloud"	String	Cloud identifier of the consumer system.
"consumer"	String	Name of the consumer system.
"provider"	String	Name of the provider system.
"targetType"	AuthorizationTargetType	Target type: `SERVICE_DEF` or `EVENT_TYPE`.
"target"	String	Target of the policy or token: a service definition or event type.
"scope"	String	Operation the token or policy is limited to; empty for all operations.
"createdAt"	DateTime	UTC time of creation.
"usageLimit"	Number	Number of allowed uses (usage-limited tokens).
"usageLeft"	Number	Remaining uses of a usage-limited token.
"expiresAt"	DateTime	UTC expiry time; no value means no expiry.

3.10 struct ErrorMessage

Object Field	Value Type	Description
"errorMessage"	String	
"errorCode"	Number	
"exceptionType"	ExceptionType	
"origin"	String	

3.11 struct Page

Paging and sorting; all fields optional.

Object Field	Value Type	Description
"page"	Number	Zero-based page number.
"size"	Number	Number of records per page (at most `max.page.size`, default 1000).
"direction"	String	Sort direction, `ASC` or `DESC`.
"sortField"	String	Field to sort by.

3.12 Primitives

As all messages are encoded using the JSON format [4], the following primitive constructs, part of that standard, become available. Note that the official standard is defined in terms of parsing rules, while this list only concerns syntactic information. Furthermore, the Object and Array types are given optional generic type parameters, which are used in this document to signify when pair values or elements are expected to conform to certain types.

Type	Description
Array	A JSON Array [4]; Array<A> has elements of type A.
AuthorizationTargetType	One of `SERVICE_DEF`, `EVENT_TYPE` (JSON String).
AuthorizationTokenType	One of `TIME_LIMITED_TOKEN`, `USAGE_LIMITED_TOKEN`, `SELF_CONTAINED_TOKEN`, `TRANSLATION_BRIDGE_TOKEN` (JSON String).
DateTime	JSON String with an ISO 8601 UTC timestamp, e.g. `2026-10-22T12:00:00Z`.
ExceptionType	One of `ARROWHEAD`, `INVALID_PARAMETER`, `AUTH`, `FORBIDDEN`, `DATA_NOT_FOUND`, `TIMEOUT`, `LOCKED`, `INTERNAL_SERVER_ERROR`, `EXTERNAL_SERVER_ERROR` (JSON String).
Number	JSON Number, an integer.
String	JSON String.

4 References

[1] R. Fielding, M. Nottingham, and J. Reschke, “Http/1.1,” IETF, RFC 9112, 2022.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “authorizationTokenManagement – Service Description (ConsumerAuthorization),” Eclipse Arrowhead, SD 5.2.2, 2026, consumerAuthorization-v5.2.2-authorizationTokenManagement-SD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	