authorizationTokenManagement MQTT/TLS/JSON

Interface Design Description

Service ID: *"authorizationTokenManagement"*

Abstract
This document describes the MQTT protocol with TLS payload security and JSON payload encoding variant of the `authorizationTokenManagement` service of the ConsumerAuthorization system.

Contents

1 Overview **3**

2 Service Operations **4**
2.1 operation generate-tokens . . . 4
2.2 operation query-tokens . . . 5
2.3 operation revoke-tokens . . . 5
2.4 operation add-encryption-keys . . . 5
2.5 operation remove-encryption-keys . . . 6

3 Data Models **7**
3.1 struct MqttRequestTemplate . . . 7
3.2 struct MqttResponseTemplate . . . 7
3.3 struct ErrorMessage . . . 7
3.4 struct AuthorizationMgmtEncryptionKeyListResponse . . . 7
3.5 struct AuthorizationMgmtEncryptionKeyRegistrationListRequest . . . 7
3.6 struct AuthorizationMgmtEncryptionKeyRegistrationRequest . . . 8
3.7 struct AuthorizationMgmtEncryptionKeyResponse . . . 8
3.8 struct AuthorizationTokenGenerationMgmtListRequest . . . 8
3.9 struct AuthorizationTokenGenerationMgmtRequest . . . 8
3.10 struct AuthorizationTokenMgmtListResponse . . . 9
3.11 struct AuthorizationTokenQueryRequest . . . 9
3.12 struct AuthorizationTokenResponse . . . 9
3.13 struct Page . . . 10
3.14 Primitives . . . 10

4 References **12**

5 Revision History **13**
5.1 Amendments . . . 13
5.2 Quality Assurance . . . 13

1 Overview

This document describes the `authorizationTokenManagement` service interface of the ConsumerAuthorization system over MQTT, which provides operator management of authorization tokens and of provider encryption keys.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	MQTT	3.1.1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `authorizationTokenManagement` service interface

This document provides the Interface Design Description IDD to the *authorizationTokenManagement – Service Description* document [5]. The operations, their semantics and the data models are the same as in the HTTP/TLS/JSON IDD [6]; this document specifies the MQTT binding.

The MQTT interface is offered only when the system runs with `mqtt.api.enabled=true`; it is then registered with the interface template `generic_mqtts` (`generic_mqtt` without TLS), the broker address and port (`mqtt.broker.address`, `mqtt.broker.port`) and the base topic `arrowhead/consumerauthorization/authorization-token/management/`. In the Arrowhead-test-cloud-java deployment the MQTT interfaces of the core systems are disabled.

2 Service Operations

The provider subscribes to one topic per operation, the base topic followed by the operation name:

Operation	Request topic
`generate-tokens`	`arrowhead/consumer-authorization/authorization-token/management/generate-tokens`
`query-tokens`	`arrowhead/consumer-authorization/authorization-token/management/query-tokens`
`revoke-tokens`	`arrowhead/consumer-authorization/authorization-token/management/revoke-tokens`
`add-encryption-keys`	`arrowhead/consumer-authorization/authorization-token/management/add-encryption-keys`
`remove-encryption-keys`	`arrowhead/consumer-authorization/authorization-token/management/remove-encryption-keys`

A consumer publishes a request envelope (MqttRequestTemplate) to the topic and receives the answer (MqttResponseTemplate) on its own `responseTopic`. The `authentication` field carries the requester's identity according to the provider's authentication policy: `IDENTITY-TOKEN//<token>` (outsourced or internal policy), `SYSTEM//<name>` (declared policy) or the requester's X.509 certificate (certificate policy). The `status` of the response uses the HTTP status code numbers (200, 201, 204, 400, 401, 403, 404, 408, 423, 500, 503); on error the payload is an ErrorMessage.

```
{
  "traceId": "a1b2c3",
  "authentication": "IDENTITY-TOKEN//<token>",
  "responseTopic": "arrowhead/response/TemperatureDisplay/a1b2c3",
  "qosRequirement": 1,
  "params": {},
  "payload": {}
}
```

Listing 1: Request envelope.

```
{
  "status": 200,
  "traceId": "a1b2c3",
  "receiver": "TemperatureDisplay",
  "payload": {}
}
```

Listing 2: Response envelope.

2.1 PUBLISH `arrowhead/consumer-authorization/authorization-token/management/generate-tokens`

Operation: generate-tokens
Input: AuthorizationTokenGenerationMgmtListRequest
Output: AuthorizationTokenMgmtListResponse

Generates tokens on behalf of consumers. With `unbound=true` the authorization check is skipped (only for systems in `unbounded.token.generation.whitelist`).

Optional entries of `params`: `unbound`.

```
{
  "list": [
    {
      "tokenVariant": "TIME_LIMITED_TOKEN_AUTH",
      "targetType": "SERVICE_DEF",
      "consumerCloud": "LOCAL",
      "consumer": "TemperatureDisplay",
      "provider": "TemperatureSensor",
      "target": "temperatureReading",
      "scope": "read",
      "expiresAt": "2026-10-22T12:00:00Z",
      "usageLimit": 5
    }
  ]
}
```

Listing 3: Payload of an generate-tokens request.

2.2 PUBLISH arrowhead/consumer-authorization/authorization-token/management/query-tokens

Operation: query-tokens
Input: AuthorizationTokenQueryRequest
Output: AuthorizationTokenMgmtListResponse

Returns a page of tokens matching the filter.

```
{
  "pagination": {
    "page": 0,
    "size": 10,
    "direction": "ASC",
    "sortField": "createdAt"
  },
  "requester": "DynamicServiceOrchestration",
  "tokenType": "TIME_LIMITED_TOKEN",
  "consumerCloud": "LOCAL",
  "consumer": "TemperatureDisplay",
  "provider": "TemperatureSensor",
  "targetType": "SERVICE_DEF",
  "target": "temperatureReading"
}
```

Listing 4: Payload of an query-tokens request.

2.3 PUBLISH arrowhead/consumer-authorization/authorization-token/management/revoke-tokens

Operation: revoke-tokens
Input: Array<String>

Revokes tokens by token reference.

```
[
  "<token reference>"
]
```

Listing 5: Payload of an revoke-tokens request.

2.4 PUBLISH arrowhead/consumer-authorization/authorization-token/management/add-encryption-keys

Operation: add-encryption-keys
Input: AuthorizationMgmtEncryptionKeyRegistrationListRequest
Output: AuthorizationMgmtEncryptionKeyListResponse

Registers encryption keys on behalf of providers.

```
{
  "list": [
    {
      "systemName": "TemperatureSensor",
      "key": "0123456789abcdef",
      "algorithm": "AES/ECB/PKCS5Padding"
    }
  ]
}
```

Listing 6: Payload of an add-encryption-keys request.

2.5 PUBLISH arrowhead/consumer-authorization/authorization-token/management/remove-encryption-keys

Operation: remove-encryption-keys
Input: Array<String>

Removes the encryption keys of the named providers.

```
[
  "TemperatureSensor"
]
```

Listing 7: Payload of an remove-encryption-keys request.

3 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Each *struct* denotes a JSON Object with the named fields; fields that are not needed may be omitted.

3.1 struct MqttRequestTemplate

The request envelope.

Object Field	Value Type	Description
"traceId"	String	Identifier chosen by the requester, returned in the response.
"authentication"	String	Identity of the requester (see Section 2).
"responseTopic"	String	Topic on which the response is published.
"qosRequirement"	Number	MQTT QoS of the response (0, 1 or 2).
"params"	Object<String>	Optional parameters (the query parameters of the HTTP binding).
"payload"	Object	The operation input.

3.2 struct MqttResponseTemplate

The response envelope.

Object Field	Value Type	Description
"status"	Number	Status code.
"traceId"	String	The trace identifier of the request.
"receiver"	String	Name of the requester.
"payload"	Object	The operation output, or an ErrorMessage.

3.3 struct ErrorMessage

Object Field	Value Type	Description
"errorMessage"	String	
"errorCode"	Number	
"exceptionType"	ExceptionType	
"origin"	String	

3.4 struct AuthorizationMgmtEncryptionKeyListResponse

List of registered encryption keys.

Object Field	Value Type	Description
"entries"	Array<AuthorizationMgmtEncryptionKeyResponse>	Matching records of the current page.
"count"	Number	Total number of matching records (all pages).

3.5 struct AuthorizationMgmtEncryptionKeyRegistrationListRequest

Encryption keys to register on behalf of providers.

Object Field	Value Type	Description
"list"	Array<AuthorizationMgmtEncryption KeyRegistrationRequest>	The list of request items.

3.6 struct AuthorizationMgmtEncryptionKeyRegistrationRequest

Encryption key of one provider.

Object Field	Value Type	Description
"systemName"	String	Provider system the key belongs to.
"key"	String	The encryption key, as a string.
"algorithm"	String	Encryption algorithm of the key, e.g. `AES/ECB/PKCS5Padding` or `AES/CBC/PKCS5Padding`.

3.7 struct AuthorizationMgmtEncryptionKeyResponse

A registered encryption key.

Object Field	Value Type	Description
"systemName"	String	Name of the system, PascalCase (e.g. `TemperatureSensor`).
"rawKey"	String	The registered encryption key.
"algorithm"	String	Encryption algorithm of the key, e.g. `AES/ECB/PKCS5Padding` or `AES/CBC/PKCS5Padding`.
"keyAdditive"	String	Initialization vector (CBC mode), Base64; empty for ECB.
"createdAt"	DateTime	UTC time of creation.

3.8 struct AuthorizationTokenGenerationMgmtListRequest

Tokens to generate on behalf of consumers.

Object Field	Value Type	Description
"list"	Array<AuthorizationTokenGeneration MgmtRequest>	The list of request items.

3.9 struct AuthorizationTokenGenerationMgmtRequest

One token to generate on behalf of a consumer.

Object Field	Value Type	Description
"tokenVariant"	String	Requested token variant, as interface security policy (e.g. `TIME_LIMITED_TOKEN_AUTH`, `RSA_SHA512_JSON_WEB_TOKEN_AUTH`).
"targetType"	String	Target type: `SERVICE_DEF` or `EVENT_TYPE`.
"consumerCloud"	String	Cloud identifier of the consumer system.
"consumer"	String	Name of the consumer system.
"provider"	String	Name of the provider system.
"target"	String	Target of the policy or token: a service definition or event type.
"scope"	String	Operation the token or policy is limited to; empty for all operations.
"expiresAt"	DateTime	Requested expiry; default `token.time.limit` from now.
"usageLimit"	Number	Requested uses; default `simple.token.usage.limit`.

3.10 struct AuthorizationTokenMgmtListResponse

List of generated tokens.

Object Field	Value Type	Description
"entries"	Array<AuthorizationTokenResponse>	Matching records of the current page.
"count"	Number	Total number of matching records (all pages).

3.11 struct AuthorizationTokenQueryRequest

Filter for generated tokens.

Object Field	Value Type	Description
"pagination"	Page	Paging and sorting of the result.
"requester"	String	Name of the system that requested the token.
"tokenType"	String	Token type to match.
"consumerCloud"	String	Cloud identifier of the consumer system.
"consumer"	String	Name of the consumer system.
"provider"	String	Name of the provider system.
"targetType"	String	Target type: `SERVICE_DEF` or `EVENT_TYPE`.
"target"	String	Target of the policy or token: a service definition or event type.

3.12 struct AuthorizationTokenResponse

A generated token with its bookkeeping data.

Object Field	Value Type	Description
"tokenType"	AuthorizationTokenType	Token type: `TIME_LIMITED_TOKEN`, `USAGE_LIMITED_TOKEN`, `SELF_CONTAINED_TOKEN` or `TRANSLATION_BRIDGE_TOKEN`.
"variant"	String	Token variant (interface security policy).
"token"	String	The token, for simple tokens only in hashed form.
"tokenReference"	String	Reference of the token, used to revoke it.
"requester"	String	Name of the system that requested the token.
"consumerCloud"	String	Cloud identifier of the consumer system.
"consumer"	String	Name of the consumer system.
"provider"	String	Name of the provider system.
"targetType"	AuthorizationTargetType	Target type: `SERVICE_DEF` or `EVENT_TYPE`.
"target"	String	Target of the policy or token: a service definition or event type.
"scope"	String	Operation the token or policy is limited to; empty for all operations.
"createdAt"	DateTime	UTC time of creation.
"usageLimit"	Number	Number of allowed uses (usage-limited tokens).
"usageLeft"	Number	Remaining uses of a usage-limited token.
"expiresAt"	DateTime	UTC expiry time; no value means no expiry.

3.13 struct Page

Paging and sorting; all fields optional.

Object Field	Value Type	Description
"page"	Number	Zero-based page number.
"size"	Number	Number of records per page (at most `max.page.size`, default 1000).
"direction"	String	Sort direction, `ASC` or `DESC`.
"sortField"	String	Field to sort by.

3.14 Primitives

As all messages are encoded using the JSON format [4], the following primitive constructs, part of that standard, become available.

Type	Description
Array	A JSON Array [4]; Array<A> has elements of type A.
AuthorizationTargetType	One of `SERVICE_DEF`, `EVENT_TYPE` (JSON String).
AuthorizationTokenType	One of `TIME_LIMITED_TOKEN`, `USAGE_LIMITED_TOKEN`, `SELF_CONTAINED_TOKEN`, `TRANSLATION_BRIDGE_TOKEN` (JSON String).
DateTime	JSON String with an ISO 8601 UTC timestamp, e.g. `2026-10-22T12:00:00Z`.
Number	JSON Number, an integer.
Object	JSON Object; Object<A> has string keys and values of type A.
String	JSON String.

4 References

[1] A. Banks and R. Gupta, “Mqtt version 3.1.1,” OASIS, Standard, 2014.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “authorizationTokenManagement – Service Description (ConsumerAuthorization),” Eclipse Arrowhead, SD 5.2.2, 2026, consumerAuthorization-v5.2.2-authorizationTokenManagement-SD.pdf.

[6] ——, “authorizationTokenManagement HTTP/TLS/JSON – Interface Design Description (ConsumerAuthorization),” Eclipse Arrowhead, IDD 5.2.2, 2026, consumerAuthorization-v5.2.2-authorizationTokenManagement-HTTP-IDD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	