serviceOrchestrationSimpleStoreManagement HTTP/TLS/JSON

Interface Design Description

Service ID: *"serviceOrchestrationSimpleStoreManagement"*

Abstract
This document describes the HTTP/1.1 protocol with TLS payload security and JSON payload encoding variant of the `serviceOrchestrationSimpleStoreManagement` service of the SimpleStoreServiceOrchestration system.

Contents

1 Overview **3**
1.1 Interface registration . . . 3

2 Service Operations **4**
2.1 operation query . . . 4
2.2 operation remove . . . 5
2.3 operation create . . . 5
2.4 operation modify-priorities . . . 6

3 Data Models **7**
3.1 struct ErrorMessage . . . 7
3.2 struct OrchestrationSimpleStoreListRequest . . . 7
3.3 struct OrchestrationSimpleStoreListResponse . . . 7
3.4 struct OrchestrationSimpleStoreQueryRequest . . . 7
3.5 struct OrchestrationSimpleStoreRequest . . . 7
3.6 struct OrchestrationSimpleStoreResponse . . . 8
3.7 struct Page . . . 8
3.8 struct PriorityRequest . . . 8
3.9 Primitives . . . 8

4 References **10**

5 Revision History **11**
5.1 Amendments . . . 11
5.2 Quality Assurance . . . 11

1 Overview

This document describes the `serviceOrchestrationSimpleStoreManagement` service interface of the SimpleStoreServiceOrchestration system, which provides operator management of the orchestration store: the static rules telling which service instance a consumer shall use, with priorities.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	HTTP	1.1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `serviceOrchestrationSimpleStoreManagement` service interface

This document provides the Interface Design Description IDD to the *serviceOrchestrationSimpleStoreManagement – Service Description* document [5]. For further details about how this service is meant to be used, please consult that document.

The rest of this document describes how to realize the `serviceOrchestrationSimpleStoreManagement` service interface in detail. Both in terms of its operations (Section 2) and its information model (Section 3).

1.1 Interface registration

The service is registered in the ServiceRegistry with the interface template `generic_https` (`generic_http` when TLS is disabled), access port 8442 and base path `/serviceorchestration/orchestration/mgmt/simple-store`. The `operations` property of the interface lists the operations below with their method and path relative to the base path:

Operation	Method	Path
`query`	POST	`/query`
`remove`	DELETE	`/remove`
`create`	POST	`/create`
`modify-priorities`	PUT	`/modify-priorities`

2 Service Operations

The interfaces of the `serviceOrchestrationSimpleStoreManagement` service, its operations, data models and implementation are provided below. In particular, each subsection first names the HTTP method and path used to call the operation, after which it names the abstract operation from the `serviceOrchestrationSimpleStoreManagement` SD document, as well as input and output types.

All operations require the requester's identity, presented according to the provider's authentication policy: the client certificate (mutual TLS) and, with the `outsourced` policy, `Authorization: Bearer IDENTITY-TOKEN//<token>`; systems holding the Authentication secret key send `Bearer AUTHENTICATOR-KEY//<system>//<hash>`, and with the `declared` policy `Bearer SYSTEM//<system>` is sent. Request and response bodies are `application/json`. Errors are answered with an ErrorMessage body and the status codes `400 Bad Request` (invalid parameter), `401 Unauthorized` (missing or invalid identity), `403 Forbidden` (not permitted, e.g. by the management or blacklist filter), `404 Not Found`, `408 Request Timeout`, `423 Locked`, `500 Internal Server Error` and `503 Service Unavailable` (a system it depends on failed).

2.1 POST /serviceorchestration/orchestration/mgmt/simple-store/query

Operation: query
Input: OrchestrationSimpleStoreQueryRequest
Output: OrchestrationSimpleStoreListResponse

Returns a page of store entries matching the filter.

A successful call returns `200 OK` with the output in the body.

```
POST /serviceorchestration/orchestration/mgmt/simple-store/query HTTP/1.1
Host: serviceorchestration-simple:8442
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "pagination": {
    "page": 0,
    "size": 10,
    "direction": "ASC",
    "sortField": "createdAt"
  },
  "ids": [
    "3fa85f64-5717-4562-b3fc-2c963f66afa6"
  ],
  "consumerNames": [
    "string"
  ],
  "serviceDefinitions": [
    "temperatureReading"
  ],
  "serviceInstanceIds": [
    "TemperatureSensor|temperatureReading|1.0.0"
  ],
  "minPriority": 1,
  "maxPriority": 10,
  "createdBy": "Sysop"
}
```

Listing 1: An query invocation.

```
{
  "entries": [
    {
      "id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "consumer": "TemperatureDisplay",
```

```
      "serviceDefinition": "temperatureReading",
      "serviceInstanceId": "TemperatureSensor|temperatureReading|1.0.0",
      "priority": 1,
      "createdBy": "Sysop",
      "updatedBy": "Sysop",
      "createdAt": "2026-10-22T12:00:00Z",
      "updatedAt": "2026-10-22T12:00:00Z"
    }
  ],
  "count": 1
}
```

Listing 2: An query response.

2.2 DELETE /serviceorchestration/orchestration/mgmt/simple-store/remove?uuids=*{uuids}*

Operation: remove
Input: Array<String>

Removes store entries by identifier.
Query parameters: *uuids* (List<String>, required). List values are repeated or comma-separated.
A successful call returns `200 OK`.

```
DELETE /serviceorchestration/orchestration/mgmt/simple-store/remove?uuids=<uuids> HTTP/1.1
Host: serviceorchestration-simple:8442
Authorization: Bearer IDENTITY-TOKEN//<token>
```

Listing 3: An remove invocation.

2.3 POST /serviceorchestration/orchestration/mgmt/simple-store/create

Operation: create
Input: OrchestrationSimpleStoreListRequest
Output: OrchestrationSimpleStoreListResponse

Creates store entries; the service definition is taken from the instance identifier.
A successful call returns `200 OK` with the output in the body.

```
POST /serviceorchestration/orchestration/mgmt/simple-store/create HTTP/1.1
Host: serviceorchestration-simple:8442
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "candidates": [
    {
      "consumer": "TemperatureDisplay",
      "serviceInstanceId": "TemperatureSensor|temperatureReading|1.0.0",
      "priority": 1
    }
  ]
}
```

Listing 4: An create invocation.

```
{
  "entries": [
    {
      "id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
```

```
      "consumer": "TemperatureDisplay",
      "serviceDefinition": "temperatureReading",
      "serviceInstanceId": "TemperatureSensor|temperatureReading|1.0.0",
      "priority": 1,
      "createdBy": "Sysop",
      "updatedBy": "Sysop",
      "createdAt": "2026-10-22T12:00:00Z",
      "updatedAt": "2026-10-22T12:00:00Z"
    }
  ],
  "count": 1
}
```

Listing 5: An create response.

2.4 PUT /serviceorchestration/orchestration/mgmt/simple-store/modify-priorities

Operation: modify-priorities
Input: PriorityRequest
Output: OrchestrationSimpleStoreListResponse

Changes the priorities of store entries.

A successful call returns `200 OK` with the output in the body.

```
PUT /serviceorchestration/orchestration/mgmt/simple-store/modify-priorities HTTP/1.1
Host: serviceorchestration-simple:8442
Authorization: Bearer IDENTITY-TOKEN//<token>
Content-Type: application/json

{
  "3fa85f64-5717-4562-b3fc-2c963f66afa6": 2
}
```

Listing 6: An modify-priorities invocation.

```
{
  "entries": [
    {
      "id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "consumer": "TemperatureDisplay",
      "serviceDefinition": "temperatureReading",
      "serviceInstanceId": "TemperatureSensor|temperatureReading|1.0.0",
      "priority": 1,
      "createdBy": "Sysop",
      "updatedBy": "Sysop",
      "createdAt": "2026-10-22T12:00:00Z",
      "updatedAt": "2026-10-22T12:00:00Z"
    }
  ],
  "count": 1
}
```

Listing 7: An modify-priorities response.

3 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is meant to denote a JSON Object that must contain certain fields, or names, with values conforming to explicitly named types. Fields that are not needed may be omitted or `null` in requests; empty fields are omitted in responses. As a complement to the primary types defined in this section, there is also a list of secondary types in Section 3.9, which are used to represent things like hashes, identifiers and texts.

3.1 struct ErrorMessage

Object Field	Value Type	Description
"errorMessage"	String	
"errorCode"	Number	
"exceptionType"	ExceptionType	
"origin"	String	

3.2 struct OrchestrationSimpleStoreListRequest

Store entries to create.

Object Field	Value Type	Description
"candidates"	Array<OrchestrationSimpleStore Request>	Store entries to create.

3.3 struct OrchestrationSimpleStoreListResponse

List of store entries.

Object Field	Value Type	Description
"entries"	Array<OrchestrationSimpleStore Response>	Matching records of the current page.
"count"	Number	Total number of matching records (all pages).

3.4 struct OrchestrationSimpleStoreQueryRequest

Paged filter for store entries.

Object Field	Value Type	Description
"pagination"	Page	Paging and sorting of the result.
"ids"	Array<String>	Store entry identifiers (UUID) to match.
"consumerNames"	Array<String>	Consumer system names to match.
"serviceDefinitions"	Array<String>	Service definition names to match.
"serviceInstanceIds"	Array<String>	Service instance identifiers to match.
"minPriority"	Number	Lower bound of the priority.
"maxPriority"	Number	Upper bound of the priority.
"createdBy"	String	Creator system to match.

3.5 struct OrchestrationSimpleStoreRequest

One orchestration rule: consumer, service instance and priority.

Object Field	Value Type	Description
"consumer"	String	Consumer system the rule applies to.
"serviceInstanceId"	String	Service instance offered to the consumer.
"priority"	Number	Priority of the rule; 1 is the highest.

3.6 struct OrchestrationSimpleStoreResponse

A stored orchestration rule.

Object Field	Value Type	Description
"id"	String	Identifier (UUID) of the store entry.
"consumer"	String	Name of the consumer system.
"serviceDefinition"	String	Service definition name.
"serviceInstanceId"	String	Service instance identifier `<System>|<serviceDefinition>|<version>`.
"priority"	Number	Priority of the entry; 1 is the highest.
"createdBy"	String	Name of the system that created the record.
"updatedBy"	String	Name of the system that changed the record last.
"createdAt"	DateTime	UTC time of creation.
"updatedAt"	DateTime	UTC time of the last change.

3.7 struct Page

Paging and sorting; all fields optional.

Object Field	Value Type	Description
"page"	Number	Zero-based page number.
"size"	Number	Number of records per page (at most `max.page.size`, default 1000).
"direction"	String	Sort direction, `ASC` or `DESC`.
"sortField"	String	Field to sort by.

3.8 struct PriorityRequest

A JSON object mapping store entry identifiers (UUID) to new priorities, e.g. `{"123e4567-e89b-12d3-a456-426614174000": 5}`.

3.9 Primitives

As all messages are encoded using the JSON format [4], the following primitive constructs, part of that standard, become available. Note that the official standard is defined in terms of parsing rules, while this list only concerns syntactic information. Furthermore, the Object and Array types are given optional generic type parameters, which are used in this document to signify when pair values or elements are expected to conform to certain types.

Type	Description
Array	A JSON Array [4]; Array<A> has elements of type A.
DateTime	JSON String with an ISO 8601 UTC timestamp, e.g. `2026-10-22T12:00:00Z`.
ExceptionType	One of `ARROWHEAD`, `INVALID_PARAMETER`, `AUTH`, `FORBIDDEN`, `DATA_NOT_FOUND`, `TIMEOUT`, `LOCKED`, `INTERNAL_SERVER_ERROR`, `EXTERNAL_SERVER_ERROR` (JSON String).
Number	JSON Number, an integer.
String	JSON String.

4 References

[1] R. Fielding, M. Nottingham, and J. Reschke, “Http/1.1,” IETF, RFC 9112, 2022.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “serviceOrchestrationSimpleStoreManagement – Service Description (SimpleStoreServiceOrchestration),” Eclipse Arrowhead, SD 5.2.2, 2026, simpleStoreServiceOrchestration-v5.2.2-serviceOrchestrationSimpleStoreManagement-SD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	