serviceOrchestrationSimpleStoreManagement MQTT/TLS/JSON

Interface Design Description

Service ID: *"serviceOrchestrationSimpleStoreManagement"*

Abstract
This document describes the MQTT protocol with TLS payload security and JSON payload encoding variant of the `serviceOrchestrationSimpleStoreManagement` service of the SimpleStoreServiceOrchestration system.

Contents

1 Overview **3**

2 Service Operations **4**
2.1 operation create . . . 4
2.2 operation query . . . 5
2.3 operation remove . . . 5
2.4 operation modify-priorities . . . 5

3 Data Models **7**
3.1 struct MqttRequestTemplate . . . 7
3.2 struct MqttResponseTemplate . . . 7
3.3 struct ErrorMessage . . . 7
3.4 struct OrchestrationSimpleStoreListRequest . . . 7
3.5 struct OrchestrationSimpleStoreListResponse . . . 7
3.6 struct OrchestrationSimpleStoreQueryRequest . . . 8
3.7 struct OrchestrationSimpleStoreRequest . . . 8
3.8 struct OrchestrationSimpleStoreResponse . . . 8
3.9 struct Page . . . 8
3.10 struct PriorityRequest . . . 9
3.11 Primitives . . . 9

4 References **10**

5 Revision History **11**
5.1 Amendments . . . 11
5.2 Quality Assurance . . . 11

1 Overview

This document describes the `serviceOrchestrationSimpleStoreManagement` service interface of the SimpleStoreServiceOrchestration system over MQTT, which provides operator management of the orchestration store: the static rules telling which service instance a consumer shall use, with priorities.

It's implemented using protocol, encoding as stated in below table:

Profile type	Type	Version
Transfer protocol	MQTT	3.1.1 [1]
Data encryption	TLS	1.3 [2], 1.2 [3]
Encoding	JSON	RFC 8259 [4]
Compression	N/A	-
Semantics	N/A	-
Ontology	N/A	-

Table 1: Communication and semantics details used for the `serviceOrchestrationSimpleStoreManagement` service interface

This document provides the Interface Design Description IDD to the *serviceOrchestrationSimpleStoreManagement – Service Description* document [5]. The operations, their semantics and the data models are the same as in the HTTP/TLS/JSON IDD [6]; this document specifies the MQTT binding.

The MQTT interface is offered only when the system runs with `mqtt.api.enabled=true`; it is then registered with the interface template `generic_mqtts` (`generic_mqtt` without TLS), the broker address and port (`mqtt.broker.address`, `mqtt.broker.port`) and the base topic `arrowhead/serviceorchestration/orchestration/management/store/`. In the Arrowhead-test-cloud-java deployment the MQTT interfaces of the core systems are disabled.

2 Service Operations

The provider subscribes to one topic per operation, the base topic followed by the operation name:

Operation	Request topic
`create`	`arrowhead/serviceorchestration/orchestration/management/store/create`
`query`	`arrowhead/serviceorchestration/orchestration/management/store/query`
`remove`	`arrowhead/serviceorchestration/orchestration/management/store/remove`
`modify-priorities`	`arrowhead/serviceorchestration/orchestration/management/store/modify-priorities`

A consumer publishes a request envelope (MqttRequestTemplate) to the topic and receives the answer (MqttResponseTemplate) on its own `responseTopic`. The `authentication` field carries the requester's identity according to the provider's authentication policy: `IDENTITY-TOKEN//<token>` (outsourced or internal policy), `SYSTEM//<name>` (declared policy) or the requester's X.509 certificate (certificate policy). The `status` of the response uses the HTTP status code numbers (200, 201, 204, 400, 401, 403, 404, 408, 423, 500, 503); on error the payload is an ErrorMessage.

```
{
  "traceId": "a1b2c3",
  "authentication": "IDENTITY-TOKEN//<token>",
  "responseTopic": "arrowhead/response/TemperatureDisplay/a1b2c3",
  "qosRequirement": 1,
  "params": {},
  "payload": {}
}
```

Listing 1: Request envelope.

```
{
  "status": 200,
  "traceId": "a1b2c3",
  "receiver": "TemperatureDisplay",
  "payload": {}
}
```

Listing 2: Response envelope.

2.1 PUBLISH `arrowhead/serviceorchestration/orchestration/management/store/create`

Operation: create
Input: OrchestrationSimpleStoreListRequest
Output: OrchestrationSimpleStoreListResponse

Creates store entries; the service definition is taken from the instance identifier.

```
{
  "candidates": [
    {
      "consumer": "TemperatureDisplay",
      "serviceInstanceId": "TemperatureSensor|temperatureReading|1.0.0",
      "priority": 1
```

```
    }
  ]
}
```

Listing 3: Payload of an create request.

2.2 PUBLISH arrowhead/serviceorchestration/orchestration/management/store/query

Operation: query
Input: OrchestrationSimpleStoreQueryRequest
Output: OrchestrationSimpleStoreListResponse

Returns a page of store entries matching the filter.

```
{
  "pagination": {
    "page": 0,
    "size": 10,
    "direction": "ASC",
    "sortField": "createdAt"
  },
  "ids": [
    "3fa85f64-5717-4562-b3fc-2c963f66afa6"
  ],
  "consumerNames": [
    "string"
  ],
  "serviceDefinitions": [
    "temperatureReading"
  ],
  "serviceInstanceIds": [
    "TemperatureSensor|temperatureReading|1.0.0"
  ],
  "minPriority": 1,
  "maxPriority": 10,
  "createdBy": "Sysop"
}
```

Listing 4: Payload of an query request.

2.3 PUBLISH arrowhead/serviceorchestration/orchestration/management/store/remove

Operation: remove
Input: Array<String>

Removes store entries by identifier.

```
[
  "string"
]
```

Listing 5: Payload of an remove request.

2.4 PUBLISH `arrowhead/serviceorchestration/orchestration/management/store/modify-priorities`

Operation: modify-priorities
Input: PriorityRequest
Output: OrchestrationSimpleStoreListResponse

Changes the priorities of store entries.

```
{
  "3fa85f64-5717-4562-b3fc-2c963f66afa6": 2
}
```

Listing 6: Payload of an modify-priorities request.

3 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Each *struct* denotes a JSON Object with the named fields; fields that are not needed may be omitted.

3.1 struct MqttRequestTemplate

The request envelope.

Object Field	Value Type	Description
"traceId"	String	Identifier chosen by the requester, returned in the response.
"authentication"	String	Identity of the requester (see Section 2).
"responseTopic"	String	Topic on which the response is published.
"qosRequirement"	Number	MQTT QoS of the response (0, 1 or 2).
"params"	Object<String>	Optional parameters (the query parameters of the HTTP binding).
"payload"	Object	The operation input.

3.2 struct MqttResponseTemplate

The response envelope.

Object Field	Value Type	Description
"status"	Number	Status code.
"traceId"	String	The trace identifier of the request.
"receiver"	String	Name of the requester.
"payload"	Object	The operation output, or an ErrorMessage.

3.3 struct ErrorMessage

Object Field	Value Type	Description
"errorMessage"	String	
"errorCode"	Number	
"exceptionType"	ExceptionType	
"origin"	String	

3.4 struct OrchestrationSimpleStoreListRequest

Store entries to create.

Object Field	Value Type	Description
"candidates"	Array<OrchestrationSimpleStoreRequest>	Store entries to create.

3.5 struct OrchestrationSimpleStoreListResponse

List of store entries.

Object Field	Value Type	Description
"entries"	Array<OrchestrationSimpleStore Response>	Matching records of the current page.
"count"	Number	Total number of matching records (all pages).

3.6 struct OrchestrationSimpleStoreQueryRequest

Paged filter for store entries.

Object Field	Value Type	Description
"pagination"	Page	Paging and sorting of the result.
"ids"	Array<String>	Store entry identifiers (UUID) to match.
"consumerNames"	Array<String>	Consumer system names to match.
"serviceDefinitions"	Array<String>	Service definition names to match.
"serviceInstanceIds"	Array<String>	Service instance identifiers to match.
"minPriority"	Number	Lower bound of the priority.
"maxPriority"	Number	Upper bound of the priority.
"createdBy"	String	Creator system to match.

3.7 struct OrchestrationSimpleStoreRequest

One orchestration rule: consumer, service instance and priority.

Object Field	Value Type	Description
"consumer"	String	Consumer system the rule applies to.
"serviceInstanceId"	String	Service instance offered to the consumer.
"priority"	Number	Priority of the rule; 1 is the highest.

3.8 struct OrchestrationSimpleStoreResponse

A stored orchestration rule.

Object Field	Value Type	Description
"id"	String	Identifier (UUID) of the store entry.
"consumer"	String	Name of the consumer system.
"serviceDefinition"	String	Service definition name.
"serviceInstanceId"	String	Service instance identifier `<System>|<serviceDefinition>|<version>`.
"priority"	Number	Priority of the entry; 1 is the highest.
"createdBy"	String	Name of the system that created the record.
"updatedBy"	String	Name of the system that changed the record last.
"createdAt"	DateTime	UTC time of creation.
"updatedAt"	DateTime	UTC time of the last change.

3.9 struct Page

Paging and sorting; all fields optional.

Object Field	Value Type	Description
"page"	Number	Zero-based page number.
"size"	Number	Number of records per page (at most `max.page.size`, default 1000).
"direction"	String	Sort direction, `ASC` or `DESC`.
"sortField"	String	Field to sort by.

3.10 struct PriorityRequest

A JSON object mapping store entry identifiers (UUID) to new priorities, e.g. `{"123e4567-e89b-12d3-a456-426614174000": 5}`.

3.11 Primitives

As all messages are encoded using the JSON format [4], the following primitive constructs, part of that standard, become available.

Type	Description
Array	A JSON Array [4]; Array<A> has elements of type A.
DateTime	JSON String with an ISO 8601 UTC timestamp, e.g. `2026-10-22T12:00:00Z`.
Number	JSON Number, an integer.
Object	JSON Object; Object<A> has string keys and values of type A.
String	JSON String.

4 References

[1] A. Banks and R. Gupta, “Mqtt version 3.1.1,” OASIS, Standard, 2014.

[2] E. Rescorla, “The transport layer security (tls) protocol version 1.3,” IETF, RFC 8446, 2018.

[3] T. Dierks and E. Rescorla, “The transport layer security (tls) protocol version 1.2,” IETF, RFC 5246, 2008.

[4] T. Bray, “The javascript object notation (json) data interchange format,” IETF, RFC 8259, 2017.

[5] J. Delsing, “serviceOrchestrationSimpleStoreManagement – Service Description (SimpleStoreServiceOrchestration),” Eclipse Arrowhead, SD 5.2.2, 2026, simpleStoreServiceOrchestration-v5.2.2-serviceOrchestrationSimpleStoreManagement-SD.pdf.

[6] ——, “serviceOrchestrationSimpleStoreManagement HTTP/TLS/JSON – Interface Design Description (SimpleStoreServiceOrchestration),” Eclipse Arrowhead, IDD 5.2.2, 2026, simpleStoreServiceOrchestration-v5.2.2-serviceOrchestrationSimpleStoreManagement-HTTP-IDD.pdf.

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2026-10-22	5.2.2	Document created from the Arrowhead LaTeX templates for the 5.2.2 Java Spring implementation, including the local extensions of this workspace.	Jerker Delsing

5.2 Quality Assurance

No.	Date	Version	Approved by
1		5.2.2	