UNIVERSITI TEKNOLOGI MARA
MARKING SCHEME

COURSE	:	PROGRAMMING I
COURSE CODE	:	CSC402
EXAMINATION	:	NOV 2026 (MOCK)
TIME	:	3 HOURS

MARKING SCHEME NOTES

1. This marking scheme accompanies the CSC402 mock paper (November 2026). Generated answers show working; all questions are deterministic and paper-derived; no lecture slides are used.

2. Marking points show the expected answer and the allocation of marks; unresolved slots would remain visible.

3. Part A = 10 x 1 mark; Part B = 5 questions (60 marks); Part C = 2 x 15 marks; total = 100 marks.

4. Questions: 17. Slots: 22. Placeholders: 0. No LLM call. Questions and answers are for local study use only.

5. Structure derived from 21 unique CSC402 past papers; no past-paper text is copied.

FOR MARKERS' USE ONLY

This marking scheme consists of 6 printed pages

© Hak Cipta Universiti Teknologi MARA

PART A — ANSWER KEY

Q	Ans	Question	Solution
A1	D	Which statement immediately exits a loop?	break terminates the nearest loop or switch.
A2	D	What is displayed by the following code?	a[1] is 6 and a[3] is 12, so the sum is 18.
A3	C	How many times does a while loop execute when its condition is false initially?	while is a pretest loop; a false condition skips the body.
A4	A	Which structure chooses between two alternative paths?	if...else performs two-way selection.
A5	D	Which of the following are valid identifiers?	total_score and _count are valid identifiers.
A6	D	Which values can a bool variable hold?	A bool holds true or false.
A7	A	Which term describes a finite sequence of precise steps that solves a problem?	An algorithm is a finite, ordered set of unambiguous steps.
A8	C	Which item is NOT a programming paradigm?	Debugging is an activity, not a programming paradigm.
A9	D	Which identifier is valid in C++?	An identifier may contain letters, digits and underscores, but cannot start with a digit or be a keyword.
A10	B	Which input pattern stops when the user enters -1?	A sentinel value ends the loop.

© Hak Cipta Universiti Teknologi MARA

PART B — WORKED ANSWERS

QUESTION 1

Topic: debugging testing

a) Define compiler and interpreter.

A compiler translates the whole source program before execution; an interpreter translates and executes one statement at a time.

Marking: Award 1 mark for each correct definition.

(3 marks)

b) State THREE differences between a compiler and an interpreter.

Compiler: whole program, produces object code, reports errors after compilation. Interpreter: statement by statement, no object file, stops at the first error; generally slower execution.

Marking: Award 1 mark for each valid difference.

(2 marks)

QUESTION 2

Topic: fundamentals

a) Draw a flowchart for the ticket price selection.

Start -> read age -> if age < 0 display invalid; else if age <= 12 price = 15; else if age <= 17 price = 25; else price = 40 -> display price -> end.

Marking: Award marks for validation, all ranges, output and flow.

(6 marks)

b) Write pseudocode and a complete C++ program for the ticket price selection.

Use if/else if with the three ranges and an invalid-age branch.

Marking: Award marks for validation, range conditions, assignment and output.

(7 marks)

QUESTION 3

Topic: data types

a) Write C++ declarations for: an integer age, a double price, a constant discount rate of 0.10 and a character grade.

int age; double price; const double DISCOUNT = 0.10; char grade;

Marking: Award marks for correct types, names and const initialisation.

(5 marks)

b) Write C++ statements to read age and price, calculate price after discount, and display the result.

cin >> age >> price; price = price - price * DISCOUNT; cout << price;

Marking: Award marks for input, discount expression and output.

(6 marks)

QUESTION 4

Topic: input output

a) Trace the program and state the output.

30

Marking: The sum of 2+4+6+8+10 is 30.

(10 marks)

b) Rewrite the segment using a do...while loop that sums only values greater than 5.

int i=0,s=0; do { if(a[i]>5) s+=a[i]; i++; } while(i<5); cout<<s;

Marking: Award marks for do...while, condition, filter and output.

(5 marks)

© Hak Cipta Universiti Teknologi MARA

QUESTION 5

Topic: arrays

a) Declare two parallel arrays for the five sports in Table 1 and initialise them with those values.

string sports[5] = {"Swimming","Badminton","Athletics","Cycling","Hockey"}; int medals[5] = {8,12,7,5,9};

Marking: Award marks for both declarations, correct sizes and related indices.

(6 marks)

b) Write a program segment to display each sport with its medals, then calculate the total and average medals.

Loop i=0..4 to display sports[i] and medals[i], accumulate total, average = double(total)/5.

Marking: Award marks for paired display, total, average and output.

(10 marks)

© Hak Cipta Universiti Teknologi MARA

PART C — WORKED ANSWERS

QUESTION 1

A cafe sells the items shown in Table 1. A 10% discount is given when the subtotal is at least RM50.

Write a complete C++ program that reads the item code and quantity, calculates the subtotal and discount, and displays a formatted receipt with the item name, quantity, subtotal, discount and amount to pay.

```
#include <iostream>
#include <iomanip>
#include <string>
using namespace std;
int main() {
    int code, quantity;
    double price = 0, subtotal, discount = 0;
    string name;
    cout << "Item code (1 coffee, 2 tea, 3 juice): ";
    cin >> code;
    cout << "Quantity: ";
    cin >> quantity;
    if (code == 1) { name = "Coffee"; price = 8.50; }
    else if (code == 2) { name = "Tea"; price = 6.00; }
    else if (code == 3) { name = "Juice"; price = 9.50; }
    else { cout << "Invalid item code" << endl; return 1; }
    subtotal = price * quantity;
    if (subtotal >= 50) discount = subtotal * 0.10;
    cout << fixed << setprecision(2);
    cout << "Item: " << name << endl;
    cout << "Quantity: " << quantity << endl;
    cout << "Subtotal: RM" << subtotal << endl;
    cout << "Discount: RM" << discount << endl;
    cout << "Amount to pay: RM" << subtotal - discount << endl;
    return 0;
}
```

Marking: Award 3 marks for input, 5 for price/subtotal, 4 for discount, 2 for formatting and 1 for completeness.

(15 marks)

QUESTION 2

A lecturer records the marks of ten students in an array.

Write a complete C++ program that reads ten marks, displays the average, the highest mark and its index, and counts how many marks are above the average.

```
#include <iostream>
using namespace std;
int main() {
    int marks[10], total = 0, highest, highestIndex = 0;
    int aboveAverage = 0;
    for (int i = 0; i < 10; i++) {
        cin >> marks[i];
        total += marks[i];
        if (i == 0 || marks[i] > highest) {
            highest = marks[i];
            highestIndex = i;
        }
    }
    double average = total / 10.0;
    for (int i = 0; i < 10; i++) {
        if (marks[i] > average) aboveAverage++;
    }
    cout << "Average: " << average << endl;
    cout << "Highest: " << highest
         << " at index " << highestIndex << endl;
    cout << "Above average: " << aboveAverage << endl;
    return 0;
}
```

Marking: Award 3 marks for input, 4 for total/average, 3 for highest/index, 3 for above-average count and 2 for

© Hak Cipta Universiti Teknologi MARA

output.

(15 marks)

END OF MARKING SCHEME

© Hak Cipta Universiti Teknologi MARA