UNIVERSITI TEKNOLOGI MARA
MARKING SCHEME

COURSE	:	PROGRAMMING I
COURSE CODE	:	CSC402
EXAMINATION	:	NOV 2026 (MOCK)
TIME	:	3 HOURS

MARKING SCHEME NOTES

1. This marking scheme accompanies the CSC402 mock paper (November 2026). Generated answers show working; all questions are deterministic and paper-derived; no lecture slides are used.

2. Marking points show the expected answer and the allocation of marks; unresolved slots would remain visible.

3. Part A = 10 x 1 mark; Part B = 5 questions (60 marks); Part C = 2 x 15 marks; total = 100 marks.

4. Questions: 17. Slots: 22. Placeholders: 0. No LLM call. Questions and answers are for local study use only.

5. Structure derived from 21 unique CSC402 past papers; no past-paper text is copied.

FOR MARKERS' USE ONLY

This marking scheme consists of 6 printed pages

© Hak Cipta Universiti Teknologi MARA

PART A — ANSWER KEY

Q	Ans	Question	Solution
A1	D	Which data type stores a whole number?	int stores whole numbers; float stores real values.
A2	C	What is displayed by the following code?	The loop displays 2, 4, 6 and 8 without spaces.
A3	C	What is pseudocode?	Pseudocode expresses algorithm logic without strict language syntax.
A4	B	How many times does a while loop execute when its condition is false initially?	while is a pretest loop; a false condition skips the body.
A5	D	Which of the following are selection structures?	if and switch select among alternatives.
A6	C	Which declaration creates an integer array of five elements?	int a[5]; reserves five integer elements.
A7	B	Which input pattern stops when the user enters -1?	A sentinel value ends the loop.
A8	A	What does a compiler do?	A compiler translates the complete source file into object code.
A9	C	Which of the following are valid identifiers?	total_score and _count are valid identifiers.
A10	A	Which keyword prevents a variable's value from being changed after initialisation?	const defines a read-only variable.

© Hak Cipta Universiti Teknologi MARA

PART B — WORKED ANSWERS

QUESTION 1

Topic: fundamentals

a) Define source code and object code.

Source code is the human-readable program text; object code is the machine-oriented output produced by a compiler.

Marking: Award 1 mark for each definition.

(3 marks)

b) Describe THREE stages of the program development life cycle.

Analysis (requirements), design (algorithm/flowchart), coding (implementation), testing (verification), maintenance (updates). Any three stages.

Marking: Award 1 mark for each correctly described stage.

(2 marks)

QUESTION 2

Topic: control structures

a) Draw a flowchart for the ticket price selection.

Start -> read age -> if age < 0 display invalid; else if age <= 12 price = 15; else if age <= 17 price = 25; else price = 40 -> display price -> end.

Marking: Award marks for validation, all ranges, output and flow.

(6 marks)

b) Write pseudocode and a complete C++ program for the ticket price selection.

Use if/else if with the three ranges and an invalid-age branch.

Marking: Award marks for validation, range conditions, assignment and output.

(7 marks)

QUESTION 3

Topic: data types

a) Explain the difference between implicit and explicit type conversion, and give one C++ example of each.

Implicit conversion is automatic (int to double); explicit conversion uses a cast such as double(total) or static_cast<double>(total).

Marking: Award marks for both definitions and valid examples.

(5 marks)

b) Write a C++ program segment that calculates the average of three integer marks as a double and displays it to two decimal places.

double average = (m1 + m2 + m3) / 3.0; cout << fixed << setprecision(2) << average;

Marking: Award marks for floating-point division, fixed/setprecision and output.

(6 marks)

QUESTION 4

Topic: input output

a) Trace the program and state the output.

30

Marking: The sum of 2+4+6+8+10 is 30.

(10 marks)

b) Rewrite the segment using a do...while loop that sums only values greater than 5.

int i=0,s=0; do { if(a[i]>5) s+=a[i]; i++; } while(i<5); cout<<s;

Marking: Award marks for do...while, condition, filter and output.

(5 marks)

© Hak Cipta Universiti Teknologi MARA

QUESTION 5

Topic: arrays

a) Declare two parallel arrays for the five sports in Table 1 and initialise them with those values.

string sports[5] = {"Swimming","Badminton","Athletics","Cycling","Hockey"}; int medals[5] = {8,12,7,5,9};

Marking: Award marks for both declarations, correct sizes and related indices.

(8 marks)

b) Write a program segment to display each sport with its medals, then calculate the total and average medals.

Loop i=0..4 to display sports[i] and medals[i], accumulate total, average = double(total)/5.

Marking: Award marks for paired display, total, average and output.

(8 marks)

© Hak Cipta Universiti Teknologi MARA

PART C — WORKED ANSWERS

QUESTION 1

A bookstore records up to five books. Table 1 shows an example of the fields.

Define a struct Book. Write a complete C++ program that reads the records, calculates the total inventory value, and displays the title of the most expensive book.

```
#include <iostream>
#include <string>
using namespace std;
struct Book {
    string title;
    double price;
    int quantity;
};
int main() {
    Book books[5];
    double totalValue = 0;
    int mostExpensive = 0;
    for (int i = 0; i < 5; i++) {
        cin.ignore();
        cout << "Title: ";
        getline(cin, books[i].title);
        cout << "Price and quantity: ";
        cin >> books[i].price >> books[i].quantity;
        totalValue += books[i].price * books[i].quantity;
        if (books[i].price > books[mostExpensive].price) {
            mostExpensive = i;
        }
    }
    cout << "Total inventory value: RM" << totalValue << endl;
    cout << "Most expensive: " << books[mostExpensive].title
         << " (RM" << books[mostExpensive].price << ")" << endl;
    return 0;
}
```

Marking: Award 3 marks for struct definition, 4 for input, 4 for inventory value, 3 for most expensive and 1 for output.

(15 marks)

QUESTION 2

A lecturer records the marks of ten students in an array.

Write a complete C++ program that reads ten marks, displays the average, the highest mark and its index, and counts how many marks are above the average.

```
#include <iostream>
using namespace std;
int main() {
    int marks[10], total = 0, highest, highestIndex = 0;
    int aboveAverage = 0;
    for (int i = 0; i < 10; i++) {
        cin >> marks[i];
        total += marks[i];
        if (i == 0 || marks[i] > highest) {
            highest = marks[i];
            highestIndex = i;
        }
    }
    double average = total / 10.0;
    for (int i = 0; i < 10; i++) {
        if (marks[i] > average) aboveAverage++;
    }
    cout << "Average: " << average << endl;
    cout << "Highest: " << highest
         << " at index " << highestIndex << endl;
    cout << "Above average: " << aboveAverage << endl;
    return 0;
}
```

© Hak Cipta Universiti Teknologi MARA

Marking: Award 3 marks for input, 4 for total/average, 3 for highest/index, 3 for above-average count and 2 for output.

(15 marks)

END OF MARKING SCHEME

© Hak Cipta Universiti Teknologi MARA