UNIVERSITI TEKNOLOGI MARA
MARKING SCHEME

COURSE	:	PROGRAMMING I
COURSE CODE	:	CSC402
EXAMINATION	:	NOV 2026 (MOCK)
TIME	:	3 HOURS

MARKING SCHEME NOTES

1. This marking scheme accompanies the CSC402 mock paper (November 2026). Generated answers show working; all questions are deterministic and paper-derived; no lecture slides are used.

2. Marking points show the expected answer and the allocation of marks; unresolved slots would remain visible.

3. Part A = 10 x 1 mark; Part B = 5 questions (60 marks); Part C = 2 x 15 marks; total = 100 marks.

4. Questions: 17. Slots: 22. Placeholders: 0. No LLM call. Questions and answers are for local study use only.

5. Structure derived from 21 unique CSC402 past papers; no past-paper text is copied.

FOR MARKERS' USE ONLY

This marking scheme consists of 6 printed pages

© Hak Cipta Universiti Teknologi MARA

PART A — ANSWER KEY

Q	Ans	Question	Solution
A1	B	What does endl do?	endl inserts a newline and flushes the output buffer.
A2	D	What is displayed by the following code?	a[1] is 6 and a[3] is 12, so the sum is 18.
A3	D	Which statement immediately exits a loop?	break terminates the nearest loop or switch.
A4	C	Given the declaration, what is displayed?	word[3] is 't' because array indexing starts at zero.
A5	D	Which of the following are valid identifiers?	total_score and _count are valid identifiers.
A6	D	Which term describes a finite sequence of precise steps that solves a problem?	An algorithm is a finite, ordered set of unambiguous steps.
A7	B	Which values can a bool variable hold?	A bool holds true or false.
A8	B	How many times does a while loop execute when its condition is false initially?	while is a pretest loop; a false condition skips the body.
A9	D	Which of the following are selection structures?	if and switch select among alternatives.
A10	A	Which item is NOT a programming paradigm?	Debugging is an activity, not a programming paradigm.

© Hak Cipta Universiti Teknologi MARA

PART B — WORKED ANSWERS

QUESTION 1

Topic: fundamentals

a) Define algorithm and pseudocode.

An algorithm is a finite sequence of precise steps that solves a problem. Pseudocode is a structured English-like description of an algorithm.

Marking: Award 1 mark for each correct definition.

(3 marks)

b) Explain THREE types of programming errors and give one example of each.

Syntax error: missing semicolon. Runtime error: division by zero. Logic error: using < instead of <= in a condition.

Marking: Award 0.5 mark for each type and 0.5 mark for a valid example.

(2 marks)

QUESTION 2

Topic: fundamentals

a) Draw a flowchart for the grade classification.

Start -> read score -> decision score >= 80 -> A; else score >= 60 -> B; else score >= 50 -> C; else score >= 40 -> D; else F -> display grade -> end.

Marking: Award marks for terminal symbols, input, four/five decisions, each output and correct flow.

(8 marks)

b) Write pseudocode for the algorithm and convert it into a complete C++ program.

IF score >= 80 THEN grade = A ELSE IF score >= 60 THEN grade = B ... ENDIF; use if/else if in C++ and display grade.

Marking: Award marks for correct pseudocode, complete C++ structure, conditions, input and output.

(5 marks)

QUESTION 3

Topic: data types

a) Evaluate the following expressions using the declarations in the code block.

(i) 13, (ii) 20, (iii) 2, (iv) 3, (v) 3.4

Marking: Award 1 mark per correct value.

(5 marks)

b) Write C++ statements to declare two integers a and b, read their values, and display their sum, difference, product and remainder.

int a, b; cin >> a >> b; cout << a+b << a-b << a*b << a%b;

Marking: Award marks for declarations, input, four operations and output.

(6 marks)

QUESTION 4

Topic: input output

a) Trace the program and state the output.

15

Marking: The loop adds 1+2+3+4+5. Award marks for the sequence and final output.

(10 marks)

b) Rewrite the loop using a while loop. Then explain what changes if the condition is i < 5.

int i = 1; while (i <= 5) { total += i; i++; } With i < 5 the result is 10 because 5 is not added.

Marking: Award marks for correct while structure, update and changed result.

(5 marks)

© Hak Cipta Universiti Teknologi MARA

QUESTION 5

Topic: arrays

a) Declare two parallel arrays for the five sports in Table 1 and initialise them with those values.

string sports[5] = {"Swimming","Badminton","Athletics","Cycling","Hockey"}; int medals[5] = {8,12,7,5,9};

Marking: Award marks for both declarations, correct sizes and related indices.

(6 marks)

b) Write a program segment to display each sport with its medals, then calculate the total and average medals.

Loop i=0..4 to display sports[i] and medals[i], accumulate total, average = double(total)/5.

Marking: Award marks for paired display, total, average and output.

(10 marks)

© Hak Cipta Universiti Teknologi MARA

PART C — WORKED ANSWERS

QUESTION 1

A lecturer records the marks of ten students in an array.

Write a complete C++ program that reads ten marks, displays the average, the highest mark and its index, and counts how many marks are above the average.

```
#include <iostream>
using namespace std;
int main() {
    int marks[10], total = 0, highest, highestIndex = 0;
    int aboveAverage = 0;
    for (int i = 0; i < 10; i++) {
        cin >> marks[i];
        total += marks[i];
        if (i == 0 || marks[i] > highest) {
            highest = marks[i];
            highestIndex = i;
        }
    }
    double average = total / 10.0;
    for (int i = 0; i < 10; i++) {
        if (marks[i] > average) aboveAverage++;
    }
    cout << "Average: " << average << endl;
    cout << "Highest: " << highest
         << " at index " << highestIndex << endl;
    cout << "Above average: " << aboveAverage << endl;
    return 0;
}
```

Marking: Award 3 marks for input, 4 for total/average, 3 for highest/index, 3 for above-average count and 2 for output.

(15 marks)

QUESTION 2

A catering company charges the meal prices shown in Table 1.

Write a complete C++ program that reads the customer name and quantity, validates the quantity, calculates the total, displays a receipt, and repeats until the user chooses to stop. At the end, display the total quantity and total sales.

```
#include <iostream>
#include <iomanip>
#include <string>
using namespace std;
int main() {
    string name;
    int quantity, grandQuantity = 0;
    double unitPrice, total, grandTotal = 0;
    char again;
    do {
        cout << "Customer name: ";
        getline(cin >> ws, name);
        cout << "Quantity: ";
        cin >> quantity;
        if (quantity < 0) {
            cout << "Invalid quantity" << endl;
        } else {
            if (quantity >= 200) unitPrice = 9.50;
            else if (quantity >= 100) unitPrice = 10.50;
            else if (quantity >= 50) unitPrice = 11.50;
            else unitPrice = 12.50;
            total = quantity * unitPrice;
            grandTotal += total;
            grandQuantity += quantity;
            cout << fixed << setprecision(2);
            cout << "Receipt for " << name << ": "
```

© Hak Cipta Universiti Teknologi MARA

```
                << quantity << " x RM" << unitPrice
                << " = RM" << total << endl;
        }
        cout << "Another customer? (y/n): ";
        cin >> again;
    } while (again == 'y' || again == 'Y');
    cout << "Total quantity: " << grandQuantity << endl;
    cout << "Total sales: RM" << fixed << setprecision(2)
         << grandTotal << endl;
    return 0;
}
```

Marking: Award 3 marks for input/validation, 6 for price selection and total, 3 for repetition, 2 for final totals and 1 for output clarity.

(15 marks)

END OF MARKING SCHEME

© Hak Cipta Universiti Teknologi MARA