UNIVERSITI TEKNOLOGI MARA
MARKING SCHEME

COURSE	:	PROGRAMMING I
COURSE CODE	:	CSC402
EXAMINATION	:	NOV 2026 (MOCK)
TIME	:	3 HOURS

MARKING SCHEME NOTES

1. This marking scheme accompanies the CSC402 mock paper (November 2026). Generated answers show working; all questions are deterministic and paper-derived; no lecture slides are used.

2. Marking points show the expected answer and the allocation of marks; unresolved slots would remain visible.

3. Part A = 10 x 1 mark; Part B = 5 questions (60 marks); Part C = 2 x 15 marks; total = 100 marks.

4. Questions: 17. Slots: 22. Placeholders: 0. No LLM call. Questions and answers are for local study use only.

5. Structure derived from 21 unique CSC402 past papers; no past-paper text is copied.

FOR MARKERS' USE ONLY

This marking scheme consists of 6 printed pages

© Hak Cipta Universiti Teknologi MARA

PART A — ANSWER KEY

Q	Ans	Question	Solution
A1	D	Which loop is guaranteed to execute its body at least once?	do...while tests the condition after the body.
A2	B	What is displayed by the following code?	Integer division gives 3 and the remainder is 1.
A3	D	Which structure chooses between two alternative paths?	if...else performs two-way selection.
A4	A	Which statement immediately exits a loop?	break terminates the nearest loop or switch.
A5	B	A computer system's hardware includes which of the following?	All five listed components are part of the hardware.
A6	A	Which phase of the program development life cycle defines what the program must do?	Analysis establishes the requirements before design and coding.
A7	C	Given the declaration, what is displayed?	word[3] is 't' because array indexing starts at zero.
A8	C	Which declaration creates an integer array of five elements?	int a[5]; reserves five integer elements.
A9	D	Which of the following are valid identifiers?	total_score and _count are valid identifiers.
A10	A	Which declaration creates a floating-point variable named price?	float is used for real numbers.

© Hak Cipta Universiti Teknologi MARA

PART B — WORKED ANSWERS

QUESTION 1

Topic: fundamentals

a) Define source code and object code.

Source code is the human-readable program text; object code is the machine-oriented output produced by a compiler.

Marking: Award 1 mark for each definition.

(2 marks)

b) Describe THREE stages of the program development life cycle.

Analysis (requirements), design (algorithm/flowchart), coding (implementation), testing (verification), maintenance (updates). Any three stages.

Marking: Award 1 mark for each correctly described stage.

(3 marks)

QUESTION 2

Topic: control structures

a) Draw a flowchart for the ticket price selection.

Start -> read age -> if age < 0 display invalid; else if age <= 12 price = 15; else if age <= 17 price = 25; else price = 40 -> display price -> end.

Marking: Award marks for validation, all ranges, output and flow.

(8 marks)

b) Write pseudocode and a complete C++ program for the ticket price selection.

Use if/else if with the three ranges and an invalid-age branch.

Marking: Award marks for validation, range conditions, assignment and output.

(5 marks)

QUESTION 3

Topic: data types

a) Evaluate the following expressions using the declarations in the code block.

(i) 13, (ii) 20, (iii) 2, (iv) 3, (v) 3.4

Marking: Award 1 mark per correct value.

(6 marks)

b) Write C++ statements to declare two integers a and b, read their values, and display their sum, difference, product and remainder.

int a, b; cin >> a >> b; cout << a+b << a-b << a*b << a%b;

Marking: Award marks for declarations, input, four operations and output.

(5 marks)

QUESTION 4

Topic: input output

a) Trace the program and show the exact output.

1\n12\n123

Marking: Award marks for each line and the exact row lengths.

(10 marks)

b) Identify TWO logic errors in a version that prints four rows but reuses j without resetting it. Rewrite the corrected code.

The inner loop must initialise j = 1 for every row and the outer loop must run to 4. Correct code: for (int i=1;i<=4;i++){for(int j=1;j<=i;j++) cout<<j; cout<<endl;}

Marking: Award marks for each error and the corrected loop.

(5 marks)

© Hak Cipta Universiti Teknologi MARA

QUESTION 5

Topic: arrays

a) Declare an array named prices using the values in Table 1. Display all values.

double prices[5] = {20.5, 55.0, 15.9, 75.0, 10.0}; for (int i=0;i<5;i++) cout << prices[i] << endl;

Marking: Award marks for correct type, initialiser, loop and output.

(6 marks)

b) Write a program segment that applies a 10% discount to prices above RM50 and stores the results in a second array. Display both arrays.

double sale[5]; for(int i=0;i<5;i++){ sale[i] = prices[i] > 50 ? prices[i]*0.9 : prices[i]; } then display both arrays.

Marking: Award marks for second array, condition, discount, preservation and output.

(10 marks)

© Hak Cipta Universiti Teknologi MARA

PART C — WORKED ANSWERS

QUESTION 1

A lecturer records the marks of ten students in an array.

Write a complete C++ program that reads ten marks, displays the average, the highest mark and its index, and counts how many marks are above the average.

```
#include <iostream>
using namespace std;
int main() {
    int marks[10], total = 0, highest, highestIndex = 0;
    int aboveAverage = 0;
    for (int i = 0; i < 10; i++) {
        cin >> marks[i];
        total += marks[i];
        if (i == 0 || marks[i] > highest) {
            highest = marks[i];
            highestIndex = i;
        }
    }
    double average = total / 10.0;
    for (int i = 0; i < 10; i++) {
        if (marks[i] > average) aboveAverage++;
    }
    cout << "Average: " << average << endl;
    cout << "Highest: " << highest
         << " at index " << highestIndex << endl;
    cout << "Above average: " << aboveAverage << endl;
    return 0;
}
```

Marking: Award 3 marks for input, 4 for total/average, 3 for highest/index, 3 for above-average count and 2 for output.

(15 marks)

QUESTION 2

A bookstore records up to five books. Table 1 shows an example of the fields.

Define a struct Book. Write a complete C++ program that reads the records, calculates the total inventory value, and displays the title of the most expensive book.

```
#include <iostream>
#include <string>
using namespace std;
struct Book {
    string title;
    double price;
    int quantity;
};
int main() {
    Book books[5];
    double totalValue = 0;
    int mostExpensive = 0;
    for (int i = 0; i < 5; i++) {
        cin.ignore();
        cout << "Title: ";
        getline(cin, books[i].title);
        cout << "Price and quantity: ";
        cin >> books[i].price >> books[i].quantity;
        totalValue += books[i].price * books[i].quantity;
        if (books[i].price > books[mostExpensive].price) {
            mostExpensive = i;
        }
    }
    cout << "Total inventory value: RM" << totalValue << endl;
    cout << "Most expensive: " << books[mostExpensive].title
         << " (RM" << books[mostExpensive].price << ")" << endl;
    return 0;
```

© Hak Cipta Universiti Teknologi MARA

```
}
```

Marking: Award 3 marks for struct definition, 4 for input, 4 for inventory value, 3 for most expensive and 1 for output.

(15 marks)

END OF MARKING SCHEME

© Hak Cipta Universiti Teknologi MARA