UNIVERSITI TEKNOLOGI MARA
MARKING SCHEME

COURSE	:	PROGRAMMING I
COURSE CODE	:	CSC402
EXAMINATION	:	NOV 2026 (MOCK)
TIME	:	3 HOURS

MARKING SCHEME NOTES

1. This marking scheme accompanies the CSC402 mock paper (November 2026). Generated answers show working; all questions are deterministic and paper-derived; no lecture slides are used.

2. Marking points show the expected answer and the allocation of marks; unresolved slots would remain visible.

3. Part A = 10 x 1 mark; Part B = 5 questions (60 marks); Part C = 2 x 15 marks; total = 100 marks.

4. Questions: 17. Slots: 22. Placeholders: 0. No LLM call. Questions and answers are for local study use only.

5. Structure derived from 21 unique CSC402 past papers; no past-paper text is copied.

FOR MARKERS' USE ONLY

This marking scheme consists of 6 printed pages

© Hak Cipta Universiti Teknologi MARA

PART A — ANSWER KEY

Q	Ans	Question	Solution
A1	B	Which declaration creates an integer array of five elements?	int a[5]; reserves five integer elements.
A2	D	Which data type stores a whole number?	int stores whole numbers; float stores real values.
A3	B	Which operator reads data from cin?	The extraction operator >> reads from an input stream.
A4	A	Which part of a for loop is executed after each iteration?	The update expression runs after each iteration.
A5	B	Which declaration creates a floating-point variable named price?	float is used for real numbers.
A6	C	What does a compiler do?	A compiler translates the complete source file into object code.
A7	B	Which values can a bool variable hold?	A bool holds true or false.
A8	D	Which phase of the program development life cycle defines what the program must do?	Analysis establishes the requirements before design and coding.
A9	C	Which structure chooses between two alternative paths?	if...else performs two-way selection.
A10	B	How many times does a while loop execute when its condition is false initially?	while is a pretest loop; a false condition skips the body.

© Hak Cipta Universiti Teknologi MARA

PART B — WORKED ANSWERS

QUESTION 1

Topic: fundamentals

a) Define syntax error and logic error.

A syntax error violates the language grammar and is detected by the compiler. A logic error produces incorrect output although the program runs.

Marking: Award 1 mark for each definition.

(3 marks)

b) Explain TWO advantages of high-level languages over machine language.

They are easier to read and write, portable across machines, and supported by compilers and debugging tools.

Marking: Award 1.5 marks for each valid advantage.

(2 marks)

QUESTION 2

Topic: fundamentals

a) Draw a flowchart for the sum and average calculation.

Start -> read N -> total = 0, count = 1 -> while count <= N add count -> average = total / N -> display total and average -> end.

Marking: Award marks for input, initialisation, loop condition, accumulator, average and output.

(6 marks)

b) Write pseudocode and a complete C++ program for the algorithm.

Use a for loop from 1 to N, accumulate total, compute average as double(total)/N, then display both values.

Marking: Award marks for loop, accumulator, correct average type and output.

(7 marks)

QUESTION 3

Topic: data types

a) Explain the difference between implicit and explicit type conversion, and give one C++ example of each.

Implicit conversion is automatic (int to double); explicit conversion uses a cast such as double(total) or static_cast<double>(total).

Marking: Award marks for both definitions and valid examples.

(6 marks)

b) Write a C++ program segment that calculates the average of three integer marks as a double and displays it to two decimal places.

double average = (m1 + m2 + m3) / 3.0; cout << fixed << setprecision(2) << average;

Marking: Award marks for floating-point division, fixed/setprecision and output.

(5 marks)

QUESTION 4

Topic: input output

a) Trace the program and state the output.

15

Marking: The loop adds 1+2+3+4+5. Award marks for the sequence and final output.

(7 marks)

b) Rewrite the loop using a while loop. Then explain what changes if the condition is i < 5.

int i = 1; while (i <= 5) { total += i; i++; } With i < 5 the result is 10 because 5 is not added.

Marking: Award marks for correct while structure, update and changed result.

(8 marks)

© Hak Cipta Universiti Teknologi MARA

QUESTION 5

Topic: arrays

a) Declare two parallel arrays for five sports and initialise them with suitable values.

string sports[5] = {"Swimming","Badminton","Athletics","Cycling","Hockey"}; int medals[5] = {8,12,7,5,9};

Marking: Award marks for both declarations, correct sizes and related indices.

(8 marks)

b) Write a program segment to display each sport with its medals, then calculate the total and average medals.

Loop i=0..4 to display sports[i] and medals[i], accumulate total, average = double(total)/5.

Marking: Award marks for paired display, total, average and output.

(8 marks)

© Hak Cipta Universiti Teknologi MARA

PART C — WORKED ANSWERS

QUESTION 1

A bookstore records up to five books. Each book has a title, price and quantity in stock.

Define a struct Book. Write a complete C++ program that reads the records, calculates the total inventory value, and displays the title of the most expensive book.

```
#include <iostream>
#include <string>
using namespace std;
struct Book {
    string title;
    double price;
    int quantity;
};
int main() {
    Book books[5];
    double totalValue = 0;
    int mostExpensive = 0;
    for (int i = 0; i < 5; i++) {
        cin.ignore();
        cout << "Title: ";
        getline(cin, books[i].title);
        cout << "Price and quantity: ";
        cin >> books[i].price >> books[i].quantity;
        totalValue += books[i].price * books[i].quantity;
        if (books[i].price > books[mostExpensive].price) {
            mostExpensive = i;
        }
    }
    cout << "Total inventory value: RM" << totalValue << endl;
    cout << "Most expensive: " << books[mostExpensive].title
         << " (RM" << books[mostExpensive].price << ")" << endl;
    return 0;
}
```

Marking: Award 3 marks for struct definition, 4 for input, 4 for inventory value, 3 for most expensive and 1 for output.

(15 marks)

QUESTION 2

A bookstore records up to five books. Each book has a title, price and quantity in stock.

Define a struct Book. Write a complete C++ program that reads the records, calculates the total inventory value, and displays the title of the most expensive book.

```
#include <iostream>
#include <string>
using namespace std;
struct Book {
    string title;
    double price;
    int quantity;
};
int main() {
    Book books[5];
    double totalValue = 0;
    int mostExpensive = 0;
    for (int i = 0; i < 5; i++) {
        cin.ignore();
        cout << "Title: ";
        getline(cin, books[i].title);
        cout << "Price and quantity: ";
        cin >> books[i].price >> books[i].quantity;
        totalValue += books[i].price * books[i].quantity;
        if (books[i].price > books[mostExpensive].price) {
            mostExpensive = i;
        }
    }
```

© Hak Cipta Universiti Teknologi MARA

```
    cout << "Total inventory value: RM" << totalValue << endl;
    cout << "Most expensive: " << books[mostExpensive].title
         << " (RM" << books[mostExpensive].price << ")" << endl;
    return 0;
}
```

Marking: Award 3 marks for struct definition, 4 for input, 4 for inventory value, 3 for most expensive and 1 for output.

(15 marks)

END OF MARKING SCHEME

© Hak Cipta Universiti Teknologi MARA