UNIVERSITI TEKNOLOGI MARA
MARKING SCHEME

COURSE	:	PROGRAMMING I
COURSE CODE	:	CSC402
EXAMINATION	:	NOV 2026 (MOCK)
TIME	:	3 HOURS

MARKING SCHEME NOTES

1. This marking scheme accompanies the CSC402 mock paper (November 2026). Generated answers show working; all questions are deterministic and paper-derived; no lecture slides are used.

2. Marking points show the expected answer and the allocation of marks; unresolved slots would remain visible.

3. Part A = 10 x 1 mark; Part B = 5 questions (60 marks); Part C = 2 x 15 marks; total = 100 marks.

4. Questions: 17. Slots: 22. Placeholders: 0. No LLM call. Questions and answers are for local study use only.

5. Structure derived from 21 unique CSC402 past papers; no past-paper text is copied.

FOR MARKERS' USE ONLY

This marking scheme consists of 6 printed pages

© Hak Cipta Universiti Teknologi MARA

PART A — ANSWER KEY

Q	Ans	Question	Solution
A1	D	Which statement is most suitable for selecting among several constant cases?	switch selects a case based on a constant expression.
A2	C	Which operator reads data from cin?	The extraction operator >> reads from an input stream.
A3	A	Which values can a bool variable hold?	A bool holds true or false.
A4	D	How many times does a while loop execute when its condition is false initially?	while is a pretest loop; a false condition skips the body.
A5	A	What is pseudocode?	Pseudocode expresses algorithm logic without strict language syntax.
A6	C	Which phase of the program development life cycle defines what the program must do?	Analysis establishes the requirements before design and coding.
A7	C	Which keyword prevents a variable's value from being changed after initialisation?	const defines a read-only variable.
A8	C	Which initialisation is valid for an integer array?	Array initialisers use braces.
A9	C	Which declaration creates a floating-point variable named price?	float is used for real numbers.
A10	A	Which statement immediately exits a loop?	break terminates the nearest loop or switch.

© Hak Cipta Universiti Teknologi MARA

PART B — WORKED ANSWERS

QUESTION 1

Topic: debugging testing

a) Define syntax error and logic error.

A syntax error violates the language grammar and is detected by the compiler. A logic error produces incorrect output although the program runs.

Marking: Award 1 mark for each definition.

(2 marks)

b) Explain TWO advantages of high-level languages over machine language.

They are easier to read and write, portable across machines, and supported by compilers and debugging tools.

Marking: Award 1.5 marks for each valid advantage.

(3 marks)

QUESTION 2

Topic: fundamentals

a) Draw a flowchart for the ticket price selection.

Start -> read age -> if age < 0 display invalid; else if age <= 12 price = 15; else if age <= 17 price = 25; else price = 40 -> display price -> end.

Marking: Award marks for validation, all ranges, output and flow.

(6 marks)

b) Write pseudocode and a complete C++ program for the ticket price selection.

Use if/else if with the three ranges and an invalid-age branch.

Marking: Award marks for validation, range conditions, assignment and output.

(7 marks)

QUESTION 3

Topic: data types

a) Write C++ declarations for: an integer age, a double price, a constant discount rate of 0.10 and a character grade.

int age; double price; const double DISCOUNT = 0.10; char grade;

Marking: Award marks for correct types, names and const initialisation.

(6 marks)

b) Write C++ statements to read age and price, calculate price after discount, and display the result.

cin >> age >> price; price = price - price * DISCOUNT; cout << price;

Marking: Award marks for input, discount expression and output.

(5 marks)

QUESTION 4

Topic: input output

a) Trace the program and show the exact output.

1\n12\n123

Marking: Award marks for each line and the exact row lengths.

(7 marks)

b) Identify TWO logic errors in a version that prints four rows but reuses j without resetting it. Rewrite the corrected code.

The inner loop must initialise j = 1 for every row and the outer loop must run to 4. Correct code: for (int i=1;i<=4;i++){for(int j=1;j<=i;j++) cout<<j; cout<<endl;}

Marking: Award marks for each error and the corrected loop.

(8 marks)

© Hak Cipta Universiti Teknologi MARA

QUESTION 5

Topic: arrays

a) Declare an array named prices with the values 20.5, 55.0, 15.9, 75.0 and 10.0. Display all values.

double prices[5] = {20.5, 55.0, 15.9, 75.0, 10.0}; for (int i=0;i<5;i++) cout << prices[i] << endl;

Marking: Award marks for correct type, initialiser, loop and output.

(8 marks)

b) Write a program segment that applies a 10% discount to prices above RM50 and stores the results in a second array. Display both arrays.

double sale[5]; for(int i=0;i<5;i++){ sale[i] = prices[i] > 50 ? prices[i]*0.9 : prices[i]; } then display both arrays.

Marking: Award marks for second array, condition, discount, preservation and output.

(8 marks)

© Hak Cipta Universiti Teknologi MARA

PART C — WORKED ANSWERS

QUESTION 1

A bookstore records up to five books. Each book has a title, price and quantity in stock.

Define a struct Book. Write a complete C++ program that reads the records, calculates the total inventory value, and displays the title of the most expensive book.

```
#include <iostream>
#include <string>
using namespace std;
struct Book {
    string title;
    double price;
    int quantity;
};
int main() {
    Book books[5];
    double totalValue = 0;
    int mostExpensive = 0;
    for (int i = 0; i < 5; i++) {
        cin.ignore();
        cout << "Title: ";
        getline(cin, books[i].title);
        cout << "Price and quantity: ";
        cin >> books[i].price >> books[i].quantity;
        totalValue += books[i].price * books[i].quantity;
        if (books[i].price > books[mostExpensive].price) {
            mostExpensive = i;
        }
    }
    cout << "Total inventory value: RM" << totalValue << endl;
    cout << "Most expensive: " << books[mostExpensive].title
         << " (RM" << books[mostExpensive].price << ")" << endl;
    return 0;
}
```

Marking: Award 3 marks for struct definition, 4 for input, 4 for inventory value, 3 for most expensive and 1 for output.

(15 marks)

QUESTION 2

A bookstore records up to five books. Each book has a title, price and quantity in stock.

Define a struct Book. Write a complete C++ program that reads the records, calculates the total inventory value, and displays the title of the most expensive book.

```
#include <iostream>
#include <string>
using namespace std;
struct Book {
    string title;
    double price;
    int quantity;
};
int main() {
    Book books[5];
    double totalValue = 0;
    int mostExpensive = 0;
    for (int i = 0; i < 5; i++) {
        cin.ignore();
        cout << "Title: ";
        getline(cin, books[i].title);
        cout << "Price and quantity: ";
        cin >> books[i].price >> books[i].quantity;
        totalValue += books[i].price * books[i].quantity;
        if (books[i].price > books[mostExpensive].price) {
            mostExpensive = i;
        }
    }
```

© Hak Cipta Universiti Teknologi MARA

```
    cout << "Total inventory value: RM" << totalValue << endl;
    cout << "Most expensive: " << books[mostExpensive].title
         << " (RM" << books[mostExpensive].price << ")" << endl;
    return 0;
}
```

Marking: Award 3 marks for struct definition, 4 for input, 4 for inventory value, 3 for most expensive and 1 for output.

(15 marks)

END OF MARKING SCHEME

© Hak Cipta Universiti Teknologi MARA