UNIVERSITI TEKNOLOGI MARA
MARKING SCHEME

COURSE	:	PROGRAMMING I
COURSE CODE	:	CSC402
EXAMINATION	:	NOV 2026 (MOCK)
TIME	:	3 HOURS

MARKING SCHEME NOTES

1. This marking scheme accompanies the CSC402 mock paper (November 2026). Generated answers show working; all questions are deterministic and paper-derived; no lecture slides are used.

2. Marking points show the expected answer and the allocation of marks; unresolved slots would remain visible.

3. Part A = 10 x 1 mark; Part B = 5 questions (60 marks); Part C = 2 x 15 marks; total = 100 marks.

4. Questions: 17. Slots: 22. Placeholders: 0. No LLM call. Questions and answers are for local study use only.

5. Structure derived from 21 unique CSC402 past papers; no past-paper text is copied.

FOR MARKERS' USE ONLY

This marking scheme consists of 6 printed pages

© Hak Cipta Universiti Teknologi MARA

PART A — ANSWER KEY

Q	Ans	Question	Solution
A1	B	What does the % operator return?	% is the modulus operator and returns the remainder.
A2	B	Which tool represents an algorithm using standard graphical symbols?	A flowchart uses standard symbols such as terminals, processes and decisions.
A3	B	Which identifier is valid in C++?	An identifier may contain letters, digits and underscores, but cannot start with a digit or be a keyword.
A4	D	Which data type stores a whole number?	int stores whole numbers; float stores real values.
A5	B	Which part of a for loop is executed after each iteration?	The update expression runs after each iteration.
A6	D	Which structure chooses between two alternative paths?	if...else performs two-way selection.
A7	B	Which statement is most suitable for selecting among several constant cases?	switch selects a case based on a constant expression.
A8	B	What does endl do?	endl inserts a newline and flushes the output buffer.
A9	A	Which loop is commonly used to process every array element?	A for loop with an index visits each element.
A10	B	Which item is NOT a programming paradigm?	Debugging is an activity, not a programming paradigm.

© Hak Cipta Universiti Teknologi MARA

PART B — WORKED ANSWERS

QUESTION 1

Topic: fundamentals

a) Define syntax error and logic error.

A syntax error violates the language grammar and is detected by the compiler. A logic error produces incorrect output although the program runs.

Marking: Award 1 mark for each definition.

(2 marks)

b) Explain TWO advantages of high-level languages over machine language.

They are easier to read and write, portable across machines, and supported by compilers and debugging tools.

Marking: Award 1.5 marks for each valid advantage.

(3 marks)

QUESTION 2

Topic: control structures

a) Draw a flowchart to find the largest of three values.

Start -> read a, b, c -> largest = a -> if b > largest then largest = b -> if c > largest then largest = c -> display largest -> end.

Marking: Award marks for input, initial assumption, two comparisons, output and flow.

(6 marks)

b) Write pseudocode and a complete C++ program for the flowchart.

Use if statements to update largest, then cout the result.

Marking: Award marks for correct comparisons, variable updates and output.

(7 marks)

QUESTION 3

Topic: data types

a) Evaluate the following expressions: (i) 7 + 3 * 2, (ii) (7 + 3) * 2, (iii) 17 % 5, (iv) 17 / 5, (v) 17.0 / 5.

(i) 13, (ii) 20, (iii) 2, (iv) 3, (v) 3.4

Marking: Award 1 mark per correct value.

(5 marks)

b) Write C++ statements to declare two integers a and b, read their values, and display their sum, difference, product and remainder.

int a, b; cin >> a >> b; cout << a+b << a-b << a*b << a%b;

Marking: Award marks for declarations, input, four operations and output.

(6 marks)

QUESTION 4

Topic: control structures

a) Trace the program and state the output.

30

Marking: The sum of 2+4+6+8+10 is 30.

(10 marks)

b) Rewrite the segment using a do...while loop that sums only values greater than 5.

int i=0,s=0; do { if(a[i]>5) s+=a[i]; i++; } while(i<5); cout<<s;

Marking: Award marks for do...while, condition, filter and output.

(5 marks)

QUESTION 5

Topic: arrays

© Hak Cipta Universiti Teknologi MARA

a) Declare an array named prices with the values 20.5, 55.0, 15.9, 75.0 and 10.0. Display all values.

double prices[5] = {20.5, 55.0, 15.9, 75.0, 10.0}; for (int i=0;i<5;i++) cout << prices[i] << endl;

Marking: Award marks for correct type, initialiser, loop and output.

(8 marks)

b) Write a program segment that applies a 10% discount to prices above RM50 and stores the results in a second array. Display both arrays.

double sale[5]; for(int i=0;i<5;i++){ sale[i] = prices[i] > 50 ? prices[i]*0.9 : prices[i]; } then display both arrays.

Marking: Award marks for second array, condition, discount, preservation and output.

(8 marks)

© Hak Cipta Universiti Teknologi MARA

PART C — WORKED ANSWERS

QUESTION 1

A bookstore records up to five books. Each book has a title, price and quantity in stock.

Define a struct Book. Write a complete C++ program that reads the records, calculates the total inventory value, and displays the title of the most expensive book.

```
#include <iostream>
#include <string>
using namespace std;
struct Book {
    string title;
    double price;
    int quantity;
};
int main() {
    Book books[5];
    double totalValue = 0;
    int mostExpensive = 0;
    for (int i = 0; i < 5; i++) {
        cin.ignore();
        cout << "Title: ";
        getline(cin, books[i].title);
        cout << "Price and quantity: ";
        cin >> books[i].price >> books[i].quantity;
        totalValue += books[i].price * books[i].quantity;
        if (books[i].price > books[mostExpensive].price) {
            mostExpensive = i;
        }
    }
    cout << "Total inventory value: RM" << totalValue << endl;
    cout << "Most expensive: " << books[mostExpensive].title
         << " (RM" << books[mostExpensive].price << ")" << endl;
    return 0;
}
```

Marking: Award 3 marks for struct definition, 4 for input, 4 for inventory value, 3 for most expensive and 1 for output.

(15 marks)

QUESTION 2

A catering company charges RM12.50 per meal. Orders of 50-99 meals cost RM11.50 each, 100-199 cost RM10.50 each, and 200 or more cost RM9.50 each.

Write a complete C++ program that reads the customer name and quantity, validates the quantity, calculates the total, displays a receipt, and repeats until the user chooses to stop. At the end, display the total quantity and total sales.

```
#include <iostream>
#include <iomanip>
#include <string>
using namespace std;
int main() {
    string name;
    int quantity, grandQuantity = 0;
    double unitPrice, total, grandTotal = 0;
    char again;
    do {
        cout << "Customer name: ";
        getline(cin >> ws, name);
        cout << "Quantity: ";
        cin >> quantity;
        if (quantity < 0) {
            cout << "Invalid quantity" << endl;
        } else {
            if (quantity >= 200) unitPrice = 9.50;
            else if (quantity >= 100) unitPrice = 10.50;
            else if (quantity >= 50) unitPrice = 11.50;
            else unitPrice = 12.50;
```

© Hak Cipta Universiti Teknologi MARA

```
            total = quantity * unitPrice;
            grandTotal += total;
            grandQuantity += quantity;
            cout << fixed << setprecision(2);
            cout << "Receipt for " << name << ": "
                 << quantity << " x RM" << unitPrice
                 << " = RM" << total << endl;
        }
        cout << "Another customer? (y/n): ";
        cin >> again;
    } while (again == 'y' || again == 'Y');
    cout << "Total quantity: " << grandQuantity << endl;
    cout << "Total sales: RM" << fixed << setprecision(2)
         << grandTotal << endl;
    return 0;
}
```

Marking: Award 3 marks for input/validation, 6 for price selection and total, 3 for repetition, 2 for final totals and 1 for output clarity.

(15 marks)

END OF MARKING SCHEME

© Hak Cipta Universiti Teknologi MARA