UNIVERSITI TEKNOLOGI MARA
MARKING SCHEME

COURSE	:	COMPUTER SECURITY
COURSE CODE	:	CSC662
EXAMINATION	:	OCTOBER 2026 (MOCK)
TIME	:	3 HOURS

MARKING SCHEME NOTES

1. This marking scheme accompanies the CSC662 mock paper (October 2026). Computed answers show working; theory answers are supported by lecture slides (not lecturer-marked) with a verbatim quote and slide citation.

2. Supported theory marking points quote the lecture decks; any unresolved slot would remain a visible placeholder.

3. Part A = 10 x (2 + 6); Part B = 2 x (5 + 5); total = 100 marks.

4. Computed: 3 slot(s). Supported theory: 21 slots. Placeholders: 0. Questions and answers are for local study use only.

5. Near-copy rejection used all 35 past papers; style widening is recorded per slot.

FOR MARKERS' USE ONLY

This marking scheme consists of 15 printed pages

© Hak Cipta Universiti Teknologi MARA

CSC662 - MARKING SCHEME (MOCK OCTOBER 2026)

Labels: computed / supported by lecture slides (not lecturer-marked) / placeholder. No official marking scheme exists for the real CSC662 papers; this is generated for the mock.

Entailment labels: supported = the quote directly supports the marking point (or the point passed the stem-overlap gate without an LLM check); partly supported = the quote supports part of the point or is ambiguous; not supported = the quote does not support the point. Only 'not supported' points triggered regeneration.

Part A: 10 x (2 + 6) = 80 marks. Part B: 2 x (5 + 5) = 20 marks. Total: 100 marks. Slots: 3 computed, 21 supported by lecture slides, 0 placeholder.

Methods: computed answers use verified solvers. Theory answers are supported by lecture slides (not lecturer-marked). Each marking point carries a verbatim quote, a deck/slide/chunk citation and a term-overlap score; low overlap is flagged for human review. Sources are restricted to the slot topic's allowed decks, and a slide is not reused across questions where an alternative exists.

PART A - QUESTION 1

A1a - 2 marks - computed - matches lecture slides 5-9 (Caesar shift 3 examples)

Question:

Using Caesar Cipher technique, decrypt the following ciphertext with a shift of 7 (replace each letter with the one 7 positions to the left).
KLCPJLYLABYULKHUKDPWLKVUL

Answer: DEVICERETURNEDANDWIPEDONE

Working:

```
K (10) -7 mod 26 -> D
L (11) -7 mod 26 -> E
C ( 2) -7 mod 26 -> V
P (15) -7 mod 26 -> I
J ( 9) -7 mod 26 -> C
L (11) -7 mod 26 -> E
Y (24) -7 mod 26 -> R
L (11) -7 mod 26 -> E
A ( 0) -7 mod 26 -> T
B ( 1) -7 mod 26 -> U
Y (24) -7 mod 26 -> R
U (20) -7 mod 26 -> N
L (11) -7 mod 26 -> E
K (10) -7 mod 26 -> D
H ( 7) -7 mod 26 -> A
U (20) -7 mod 26 -> N
K (10) -7 mod 26 -> D
D ( 3) -7 mod 26 -> W
P (15) -7 mod 26 -> I
W (22) -7 mod 26 -> P
L (11) -7 mod 26 -> E
K (10) -7 mod 26 -> D
V (21) -7 mod 26 -> O
U (20) -7 mod 26 -> N
L (11) -7 mod 26 -> E
```

Suggested marks: 1 mark for identifying the cipher/shift direction; 1 mark for the complete plaintext.
Confidence: computed - matches lecture slides 5-9 (Caesar shift 3 examples).

A1b - 6 marks - supported by lecture slides (not lecturer-marked)

Question:

Explain substitution ciphers as a classical cipher family. In your answer, describe how substitution works, what serves as the key, its relation to Shannon's principle of confusion, and its relevance to modern ciphers.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	State that substitution replaces plaintext letters with other letters.	"In substitution ciphers, we replace the plain-text letters with other letters"	031 - Classical Cryptography, slide 4 031 - Classical Cryptography:: s04::1	supported (stem gate)	0.80
2	Note that the text produced by the substitution is the ciphertext.	"The resulting text is the cipher-text"	031 - Classical Cryptography, slide 4 031 - Classical Cryptography:: s04::1	supported	0.20 LOW
3	Identify the substitution rule as the key of the cipher.	"The substitution rule is the key"	031 - Classical Cryptography, slide 4 031 - Classical Cryptography:: s04::1	supported (stem gate)	0.67
4	Relate substitution to Shannon's principle of confusion.	"Corresponds to Shannon's principle of confusion"	031 - Classical Cryptography, slide 4 031 - Classical Cryptography:: s04::1	supported (stem gate)	0.60
5	Explain that the substitution idea is used in modern ciphers.	"This idea is used in modern ciphers"	031 - Classical Cryptography, slide 4 031 - Classical Cryptography:: s04::1	supported (stem gate)	0.75
6	Contrast with transposition, where plaintext is placed into rows of a matrix and ciphertext is read out of columns.	"To encrypt - put plain-text into rows of matrix then read cipher-text out of columns"	031 - Classical Cryptography, slide 20 031 - Classical Cryptography:: s20::1	supported (stem gate)	0.50

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Style confidence: LOW - exact examples n<3; widened via topic+marks (any command).
Citations: 031 - Classical Cryptography, slide 20; 031 - Classical Cryptography, slide 4

PART A - QUESTION 2

A2a - 2 marks - supported by lecture slides (not lecturer-marked)

Question:

Explain how a rail fence transposition cipher works, covering both the encryption and decryption processes.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Encryption writes the plaintext in a zigzag pattern across rows and reads letters row by row to form the ciphertext.	"The plain-text is written in a zigzag pattern in rows and form the cipher-text by reading off the letters from the rows."	031 - Classical Cryptography, slide 25 031 - Classical Cryptography:: s25::1	supported (stem gate)	0.55
2	Decryption rebuilds the empty rail fence table using the known key, fills rows with ciphertext, then reads in zigzag to recover plaintext.	"To decrypt a rail fence cipher, we have to recreate the 'empty' rail fence table (as in (A)) using the known key."	031 - Classical Cryptography, slide 26 031 - Classical Cryptography:: s26::1	partly supported	0.40 LOW

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 031 - Classical Cryptography, slide 25; 031 - Classical Cryptography, slide 26

© Hak Cipta Universiti Teknologi MARA

A2b - 6 marks - computed - matches lecture slide 15 (standard tableau)

Question:

Decrypt the following ciphertext using the Vigenere cipher with the key CIPHER. Use the standard 26 x 26 Vigenere tableau, writing the key over the message and repeating it as necessary.
UMRBVVNWVPREQE

Answer: SECURELOGINNOW

The 26 x 26 Vigenere tableau is printed in the question paper.

Working:

```
Standard 26 x 26 tableau, A=0; key repeated over the ciphertext.
Ciphertext: UMRBVVNWVPREQE
Key:        CIPHERCIPHERCI
Letter-by-letter: C - K mod 26 = P
  U (20) - C ( 2) = 18 -> S
  M (12) - I ( 8) =  4 -> E
  R (17) - P (15) =  2 -> C
  B ( 1) - H ( 7) = 20 -> U
  V (21) - E ( 4) = 17 -> R
  V (21) - R (17) =  4 -> E
  N (13) - C ( 2) = 11 -> L
  W (22) - I ( 8) = 14 -> O
  V (21) - P (15) =  6 -> G
  P (15) - H ( 7) =  8 -> I
  R (17) - E ( 4) = 13 -> N
  E ( 4) - R (17) = 13 -> N
  Q (16) - C ( 2) = 14 -> O
  E ( 4) - I ( 8) = 22 -> W
Plaintext:  SECURELOGINNOW
```

Suggested marks: 1 mark for the key/table setup; 4 marks for the letter-by-letter working; 1 mark for the complete answer.

Confidence: computed - matches lecture slide 15 (standard tableau).

PART A - QUESTION 3

A3a - 2 marks - supported by lecture slides (not lecturer-marked)

Question:

Explain the two stages of the biometric authentication process and state what happens during each stage.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	The identification stage involves acquiring the biometric sample, creating the master characteristics and storing them.	"Identification Stage Acquisition Creation of Master characteristics Storage of Master characteristics"	072 - Biometrics and Authentication, slide 5 072 - Biometrics and Authentication:: s05::1	supported	0.30 LOW
2	The authentication stage involves acquiring a sample, comparing it and making a decision.	"Authentication Stage Acquisition(s) Comparison Decision"	072 - Biometrics and Authentication, slide 5 072 - Biometrics and Authentication:: s05::1	supported	0.43 LOW

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 072 - Biometrics and Authentication, slide 5

A3b - 6 marks - supported by lecture slides (not lecturer-marked)

Question:

Describe six points about biometric mechanisms and technologies, covering what a biometric is, how biometric applications are categorised, and the characteristics and drawbacks of specific biometric technologies.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	A biometric is defined as a physiological or behavioural characteristic of a human being that can distinguish one person from another and can theoretically be used for identification or verification of identity.	"A biometric is a physiological or behavioural characteristic of a human being that can distinguish one person from another and that theoretically can be used for identification or verification of identity."	072 - Biometrics and Authentication, slide 2 072 - Biometrics and Authentication:: s02::1	supported (stem gate)	0.92
2	Biometric applications available today are divided into two sectors.	"Biometric applications available today are categorized into 2 sectors"	072 - Biometrics and Authentication, slide 4 072 - Biometrics and Authentication:: s04::1	supported (stem gate)	0.86
3	The physiological sector of biometrics includes iris, fingerprints, hand, retinal and face recognition.	"Psychological: Iris, Fingerprints, Hand, Retinal and Face recognition"	072 - Biometrics and Authentication, slide 4 072 - Biometrics and Authentication:: s04::1	supported (stem gate)	0.60
4	The behavioural sector of biometrics includes voice, typing pattern and signature.	"Behavioural: Voice, Typing pattern, Signature"	072 - Biometrics and Authentication, slide 4 072 - Biometrics and Authentication:: s04::1	supported (stem gate)	0.57
5	Iris scanning reads the unique pattern of the iris, which is coloured and visible from far, and it requires no touch, thereby overcoming retinal scanner issues.	"Scans unique pattern of iris"	072 - Biometrics and Authentication, slide 10 072 - Biometrics and Authentication:: s10::1	partly supported	0.27 LOW
6	Fingerprint biometrics suffer disadvantages such as racial issues, dirt, grime and wounds, finger placement problems, an overly large database to process, and spoofing, making liveness important.	"Racial issues"	072 - Biometrics and Authentication, slide 7 072 - Biometrics and Authentication:: s07::1	partly supported	0.10 LOW

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 072 - Biometrics and Authentication, slide 10; 072 - Biometrics and Authentication, slide 2; 072 - Biometrics and Authentication, slide 4; 072 - Biometrics and Authentication, slide 7

PART A - QUESTION 4

A4a - 2 marks - supported by lecture slides (not lecturer-marked)

Question:

List two formal security models named in the lecture and, for each, state the specific security concern it is designed to address.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	The Chinese Wall model (Brewer and Nash) is designed to address conflicts of interest for a consultant or contractor.	"Brewer and Nash's Chinese Wall Policy is designed to address a very specific concern: conflicts of interest by a consultant or contractor."	024 - Formal Security Model, slide 27 024 - Formal Security Model:: s27::1	supported (stem gate)	0.91

© Hak Cipta Universiti Teknologi MARA

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
2	The Biba model adds integrity verification on top of access control.	"Biba model: additional integrity verification"	024 - Formal Security Model, slide 5 024 - Formal Security Model:: s05::1	supported (stem gate)	0.50

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Style confidence: LOW - exact examples n<3; widened via topic+marks (any command).
Citations: 024 - Formal Security Model, slide 27; 024 - Formal Security Model, slide 5

Status: computed placeholder - no question generated for this type.

PART A - QUESTION 5

A5a - 2 marks - supported by lecture slides (not lecturer-marked)

Question:

State TWO (2) facts about how a chain of trust is established using the Trusted Platform Module (TPM) in a trusted computing platform.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Each stage of the chain measures and validates the following stage.	"Each stage measures and validates the next one"	073 - Trusted Computing, slide 8 073 - Trusted Computing::s08::1	supported (stem gate)	0.60
2	The measurements produced during this process are stored in Platform Configuration Registers (PCRs) on the TPM.	"Measurements go into Platform Configuration Registers (PCRs) on the TPM"	073 - Trusted Computing, slide 8 073 - Trusted Computing::s08::1	supported (stem gate)	0.60

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 073 - Trusted Computing, slide 8

A5b - 6 marks - supported by lecture slides (not lecturer-marked)

Question:

Explain the roles of the Nexus and the Nexus Computing Agent (NCA) as the two primary system components of the Next Generation Secure Computing Base (NGSCB), and state how the Nexus relates to the TPM and to the operating system.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	The Nexus is a special kernel that forms the core of the trusted operating environment.	"Special kernel (core of the trusted operating)"	073 - Trusted Computing, slide 13 073 - Trusted Computing::s13::1	supported (stem gate)	0.62
2	The Nexus isolates the normal mode process from the trusted mode process by handling them differently in memory.	"Isolate the process of normal mode and trusted mode differently in memory"	073 - Trusted Computing, slide 13 073 - Trusted Computing::s13::1	supported (stem gate)	0.67
3	The Nexus acts as the application interface to the TPM.	"Application interface to TPM"	073 - Trusted Computing, slide 14 073 - Trusted Computing::s14::1	supported (stem gate)	0.60
4	The Nexus is a security kernel that is authenticated on boot and does not trust the operating system.	"Security kernel, authenticated on boot"	073 - Trusted Computing, slide 14 073 - Trusted Computing::s14::1	partly supported	0.40 LOW

© Hak Cipta Universiti Teknologi MARA

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
5	The NCA is a trusted software component that runs in trusted mode and communicates with the Nexus.	"Runs in trusted mode that communicates with Nexus"	073 - Trusted Computing, slide 15 073 - Trusted Computing::s15::1	supported (stem gate)	0.71
6	The NCA specifications are open-source, allowing developers to create their own agents to run on the trusted platform.	"Developers can make their own agents to run on the trusted platform"	073 - Trusted Computing, slide 15 073 - Trusted Computing::s15::1	supported (stem gate)	0.55

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 073 - Trusted Computing, slide 13; 073 - Trusted Computing, slide 14; 073 - Trusted Computing, slide 15

PART A - QUESTION 6

A6a - 2 marks - supported by lecture slides (not lecturer-marked)

Question:

List two types of malware and, for each, state one characteristic behaviour that distinguishes it, as described in the software security lecture.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Trojans masquerade as helpful or harmless programs while stealing private data, deleting files, logging keystrokes or opening the way for further malware.	"They usually masquerade as helpful or harmless programs and begin to steal private data, delete files, log keystrokes or provide an opening for further malware to get installed."	051 - Software Security, slide 12 051 - Software Security::s12::1	supported (stem gate)	0.82
2	Worms exploit a vulnerability in the computer system to cause harm, such as corrupting or deleting critical files and consuming excess bandwidth.	"Worms are another type of malicious software that exploit a vulnerability in the computer system to cause harm."	051 - Software Security, slide 12 051 - Software Security::s12::1	partly supported	0.47 LOW

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Style confidence: LOW - exact examples n<3; widened via topic+marks (any command).
Citations: 051 - Software Security, slide 12

A6b - 6 marks - supported by lecture slides (not lecturer-marked)

Question:

Discuss six techniques by which malware attacks and propagates through a system, drawing on the software security lecture's account of malware behaviour and infection mechanisms.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Rootkits conceal malicious processes so that the attacker retains privileged remote access after a vulnerability has been exploited.	"Rootkits are a type of malware that mask malicious processes and software in the infected systems to ensure privileged remote access."	051 - Software Security, slide 13 051 - Software Security::s13::1	supported	0.46 LOW
2	Spyware performs surveillance of the user, capturing credentials and recording activity such as keystrokes and visited sites.	"spyware are programs that spy on the users. They steal user logins and passwords, document sites visited, log keystrokes and even redirect browsers to unwanted sites."	051 - Software Security, slide 13 051 - Software Security::s13::1	supported	0.42 LOW
3	A virus can propagate by appending its body to a host executable program.	"Append a virus body to a program"	051 - Software Security, slide 10 051 - Software Security::s10::1	supported (stem gate)	0.50

© Hak Cipta Universiti Teknologi MARA

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
4	A virus can hijack execution by overwriting the program header so that the entry point switches to the virus code.	"Over write a program header to switch the entry point to a virus"	051 - Software Security, slide 10 051 - Software Security::s10::1	supported (stem gate)	0.55
5	Early malware spread through boot sector infection of disks, as illustrated by Elk Cloner and the Brain Virus.	"A program spread via boot sector infection"	051 - Software Security, slide 7 051 - Software Security::s07::1	partly supported	0.31 LOW
6	The Morris worm propagated by exploiting a debugging feature of sendmail to achieve remote execution across the network.	"Used a debugging feature of sendmail (remote execution)"	051 - Software Security, slide 7 051 - Software Security::s07::1	supported	0.36 LOW

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Style confidence: LOW - exact examples n<3; widened via topic+marks (any command).
Citations: 051 - Software Security, slide 10; 051 - Software Security, slide 13; 051 - Software Security, slide 7

PART A - QUESTION 7

A7a - 2 marks - supported by lecture slides (not lecturer-marked)

Question:

Explain how the classes of threats described in the introduction to computer security affect confidentiality, integrity and availability.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Disclosure is a threat class involving unauthorized access to information, and it is countered by confidentiality services.	"Disclosure - unauthorized access to information"	011 - Introduction to Computer Security, slide 10 011 - Introduction to Computer Security::s10::1	partly supported	0.40 LOW
2	Deception and disruption are threat classes that involve modification, and they are countered by integrity services.	"Deception - acceptance of false data"	011 - Introduction to Computer Security, slide 10 011 - Introduction to Computer Security::s10::1	partly supported	0.10 LOW

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 011 - Introduction to Computer Security, slide 10

A7b - 6 marks - supported by lecture slides (not lecturer-marked)

Question:

State six facts about the Samy worm and the cross-site scripting (XSS) attack it exploited, covering how the malicious script was injected, how it spread between users, why the browser permitted it, and the outcome of the incident.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	The worm injected JavaScript into a user profile by writing to document.body.innerHTML.	"Inject Javascript into a user profile using document.body.innerHTML"	052 - Web Security, slide 15 052 - Web Security::s15::1	supported (stem gate)	0.70
2	It obtained the list of a user's heroes by issuing a GET request on a user profile.	"Get the list of user's heros by using a GET on a user profile"	052 - Web Security, slide 15 052 - Web Security::s15::1	supported	0.43 LOW
3	It added Samy as a friend by performing XML-HTTP on the addFriends page.	"Add Samy as a field by performing XML-HTTP on the addFriends page"	052 - Web Security, slide 15 052 - Web Security::s15::1	supported (stem gate)	0.88

© Hak Cipta Universiti Teknologi MARA

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
4	Any visitor to an infected profile had their own profile and friends list infected, and roughly 1,000,000 MySpace profiles were eventually infected.	"Eventually about 1,000,000 MySpace profiles were infected."	052 - Web Security, slide 15 052 - Web Security::s15::1	partly supported	0.36 LOW
5	The root cause is that any web application returning user input without filtering is a potential XSS vulnerability, allowing arbitrary JavaScript to run in the user's browser.	"Any web application that returns user input without filtering is a potential XSS vulnerability!"	052 - Web Security, slide 13 052 - Web Security::s13::1	supported (stem gate)	0.56
6	In XSS the JavaScript does not originate from the web server but is dynamically injected via a user request and reflected from a third party, which is the cross-site element.	"In a XSS attack, Javascript does not originate from a web server but is dynamically injected into it via a user request a following reflection from a third-party, a "cross-site"."	052 - Web Security, slide 14 052 - Web Security::s14::1	supported (stem gate)	0.90

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 052 - Web Security, slide 13; 052 - Web Security, slide 14; 052 - Web Security, slide 15

PART A - QUESTION 8

A8a - 2 marks - supported by lecture slides (not lecturer-marked)

Question:

Explain how a buffer overflow arises in a program such as one using strcpy() and how an attacker can exploit it to hijack execution.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	The overflow occurs because strcpy() copies the input without checking its length against the buffer size.	"strcpy() do not check the string length"	051 - Software Security, slide 23 051 - Software Security::s23::1	supported	0.25 LOW
2	Without bound checking the overspill reaches the adjacent upper stack area, letting the attacker overwrite the return address and hijack the execution flow.	"By controlling buffer content, an attacker can overwrite the return address with an arbitrary value and hijack the execution flow."	051 - Software Security, slide 21 051 - Software Security::s21::1	partly supported	0.35 LOW

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 051 - Software Security, slide 21; 051 - Software Security, slide 23

A8b - 6 marks - supported by lecture slides (not lecturer-marked)

Question:

Describe six Windows security mechanisms and related design considerations that a system administrator must understand when securing a Windows host, covering how subjects are represented, how access to objects is controlled, how resources are organised, and why the complexity of these mechanisms can itself be a risk.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Windows provides complex built-in mechanisms for managing user accounts, objects and access control.	"Windows systems contain complex security mechanisms for user account and object management as well as access control."	041 - Windows Security, slide 21 041 - Windows Security::s21::1	supported (stem gate)	0.82
2	Discretionary access control lists allow fine-grained control over diverse entities both in Windows itself and in applications.	"DACS enable fine-grained access control of heterogeneous entities in Windows itself as well as applications."	041 - Windows Security, slide 21 041 - Windows Security::s21::1	supported (stem gate)	0.54

© Hak Cipta Universiti Teknologi MARA

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
3	The very complexity of Windows security mechanisms can backfire, since misconfiguration and implementation bugs can cause serious security incidents.	"The complexity of Windows security mechanisms is also its enemy: misconfiguration as well as implementation bugs may lead to severe security incidents."	041 - Windows Security, slide 21 041 - Windows Security::s21::1	supported (stem gate)	0.50
4	In Windows, the active subjects are processes and threads.	"Windows subjects are processes and threads."	041 - Windows Security, slide 11 041 - Windows Security::s11::1	supported (stem gate)	0.80
5	A subject's security credentials are held in a token, which maps a principal to a subject and can carry extra security attributes.	"Security credentials for a subject are stored in a token."	041 - Windows Security, slide 11 041 - Windows Security::s11::1	partly supported	0.36 LOW
6	Access rights define what a subject may do to an object and are encoded as a 32-bit mask.	"Encoded as a 32-bit mask"	041 - Windows Security, slide 16 041 - Windows Security::s16::1	partly supported	0.33 LOW

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Style confidence: LOW - exact examples n<3; widened via topic+marks (any command).
Citations: 041 - Windows Security, slide 11; 041 - Windows Security, slide 16; 041 - Windows Security, slide 21

PART A - QUESTION 9

A9a - 2 marks - supported by lecture slides (not lecturer-marked)

Question:

State TWO (2) differences between morals and laws as described in the lecture on ethics and computer security.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Morals are described as traditions of belief concerning right and wrong conduct.	"Morals are traditions of belief about right and wrong conduct"	071 - Ethics and Computer Security, slide 5 071 - Ethics and Computer Security::s05::1	supported (stem gate)	0.86
2	Laws are formal rules of conduct imposed by a sovereign authority such as a government on its subjects or citizens.	"Laws are formal rules of conduct that a sovereign authority, such as a government, imposes on its subjects or citizens"	071 - Ethics and Computer Security, slide 5 071 - Ethics and Computer Security::s05::1	supported (stem gate)	1.00

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 071 - Ethics and Computer Security, slide 5

A9b - 6 marks - supported by lecture slides (not lecturer-marked)

Question:

Refer to your answer in (a). Explain how a professional code of ethics and conduct guides a computing professional, using the ACM code to illustrate six (6) distinct professional obligations.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	A code of ethics is a documented set of acceptable behaviours for a professional group, defined by that group.	"Documented set of acceptable behaviors for professional or social groups."	071 - Ethics and Computer Security, slide 6 071 - Ethics and Computer Security::s06::1	supported (stem gate)	0.56

© Hak Cipta Universiti Teknologi MARA

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
2	The professional body's code identifies which specific actions are appropriate or inappropriate.	"Identifies specific actions as appropriate or inappropriate."	071 - Ethics and Computer Security, slide 6 071 - Ethics and Computer Security::s06::1	supported (stem gate)	0.50
3	The ACM, founded in 1947, is an example of a professional body that has a code of ethics and professional conduct.	"Association of Computing Machinery ACM (founded 1947) has a code of ethics and professional conduct."	071 - Ethics and Computer Security, slide 7 071 - Ethics and Computer Security::s07::1	supported (stem gate)	0.80
4	The professional should contribute to society and human well-being, recognising all people as stakeholders in computing.	"Contribute to society and to human well-being, acknowledging that all people are stakeholders in computing."	071 - Ethics and Computer Security, slide 11 071 - Ethics and Computer Security::s11::1	supported (stem gate)	0.73
5	The professional should respect privacy and honour confidentiality.	"Respect privacy."	071 - Ethics and Computer Security, slide 11 071 - Ethics and Computer Security::s11::1	partly supported	0.33 LOW
6	The professional should maintain high standards of professional competence, conduct and ethical practice.	"Maintain high standards of professional competence, conduct, and ethical practice."	071 - Ethics and Computer Security, slide 12 071 - Ethics and Computer Security::s12::1	supported (stem gate)	0.89

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 071 - Ethics and Computer Security, slide 11; 071 - Ethics and Computer Security, slide 12; 071 - Ethics and Computer Security, slide 6; 071 - Ethics and Computer Security, slide 7

PART A - QUESTION 10

A10a - 2 marks - supported by lecture slides (not lecturer-marked)

Question:

State TWO (2) typical locations where IDS sensors are placed in a network-based IDS architecture.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	A sensor can be positioned just inside the firewall.	"Just inside the firewall"	062 - Intrusion Detection System, slide 7 062 - Intrusion Detection System::s07::1	supported (stem gate)	0.50
2	A sensor can be positioned on the DMZ.	"On the DMZ"	062 - Intrusion Detection System, slide 7 062 - Intrusion Detection System::s07::1	supported	0.25 LOW

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Style confidence: LOW - exact examples n<3; widened via topic+marks (any command).
Citations: 062 - Intrusion Detection System, slide 7

A10b - 6 marks - supported by lecture slides (not lecturer-marked)

Question:

Explain six (6) preventive network security mechanisms that an organization can deploy, describing what each mechanism does to protect the network.

© Hak Cipta Universiti Teknologi MARA

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	A firewall controls incoming and outgoing network traffic according to predetermined security policies.	"Control incoming and outgoing traffic on network with predetermined security policies."	061 - Network Security, slide 3 061 - Network Security::s03::1	supported (stem gate)	0.80
2	A proxy server improves data security and network performance by acting as a firewall and web filter, sharing network connections, and caching data.	"Proxy servers act as a firewall and web filter, provide shared network connections, and cache data to speed up common requests."	061 - Network Security, slide 3 061 - Network Security::s03::1	supported (stem gate)	0.79
3	Network segmentation creates boundaries between network segments whose computing assets share a common function, risk or role.	"Boundaries between network segments where computing assets within the segment have a common function, risk or role within an organization."	061 - Network Security, slide 3 061 - Network Security::s03::1	supported (stem gate)	0.77
4	A remote access VPN gives individual hosts or clients remote and secure access to the organization's network.	"Provides remote and secure access to an organization network to individual hosts or clients"	061 - Network Security, slide 4 061 - Network Security::s04::1	supported (stem gate)	0.89
5	Zero Trust Network Access (ZTNA) restricts each user to only the access and permission required to fulfil the role.	"A user should only has access and permission that required to fulfill the role"	061 - Network Security, slide 4 061 - Network Security::s04::1	supported (stem gate)	0.58
6	Intrusion detection/prevention systems detect or prevent network attacks such as brute force attacks, Denial-of-Service attacks and exploits of network vulnerabilities.	"To detect or prevent the network security attacks such as brute force attacks, Denial-of-Service attacks and exploits of network vulnerabilities."	061 - Network Security, slide 4 061 - Network Security::s04::1	supported (stem gate)	0.85

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 061 - Network Security, slide 3; 061 - Network Security, slide 4

PART B - QUESTION 1

B1a - 5 marks - supported by lecture slides (not lecturer-marked)

Question:

Explain five password security controls that an organisation can apply to protect user accounts and password files, and state one password policy practice for the root password.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Apply access control to the password files so that they are protected from unauthorised reading.	"Access control applied to password files"	022 - Identification and Authentication, slide 12 022 - Identification and Authentication:: s12::1	partly supported	0.44 LOW
2	De-activate user accounts automatically after several failed login attempts.	"De-activation of accounts after multiple failed logins"	022 - Identification and Authentication, slide 12 022 - Identification and Authentication:: s12::1	supported (stem gate)	0.56
3	Show the time of the user's last login so that unusual access can be noticed.	"Displaying the time of a last login"	022 - Identification and Authentication, slide 12 022 - Identification and Authentication:: s12::1	partly supported	0.33 LOW

© Hak Cipta Universiti Teknologi MARA

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
4	Store the password in an encrypted form produced by a one-way hash function.	"Password is stored in an encrypted form using a one-way hash function:"	022 - Identification and Authentication, slide 8 022 - Identification and Authentication:: s08::1	supported (stem gate)	0.88
5	For the root password, adopt a policy that it is only entered locally on the machine it controls.	"only entered locally on a machine it controls"	022 - Identification and Authentication, slide 12 022 - Identification and Authentication:: s12::1	supported (stem gate)	0.56

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Style confidence: LOW - exact examples n<3; widened via topic+marks (any command).
Citations: 022 - Identification and Authentication, slide 12; 022 - Identification and Authentication, slide 8

B1b - 5 marks - supported by lecture slides (not lecturer-marked)

Question:

A large organisation wants to reduce the number of passwords its staff must remember and manage. Explain five points about single sign-on and Kerberos that the organisation should consider, covering the motivation for single sign-on, the authentication categories involved, Kerberos design criteria, the initial Kerberos exchange, and the limitations of Kerberos.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Single sign-on reduces the burden on users by cutting down the need to memorise passwords and the time spent typing them.	"Reduce the need to memorize passwords"	022 - Identification and Authentication, slide 16 022 - Identification and Authentication:: s16::1	partly supported	0.23 LOW
2	Smart cards are classified as a 'something you have' authentication mechanism, alongside security tokens.	"Something you have: smart cards, security tokens"	022 - Identification and Authentication, slide 9 022 - Identification and Authentication:: s09::1	supported (stem gate)	0.60
3	Kerberos is designed to be transparent, so the user is unaware of any authentication beyond the initial login.	"Transparency: user is not aware of any authentication beyond an initial login."	022 - Identification and Authentication, slide 18 022 - Identification and Authentication:: s18::1	supported (stem gate)	0.70
4	In the initial exchange the client sends its user ID and the requested service to the authentication server.	"The client sends his user ID and the requested service to authentication server AS: C → AS : (U, S)"	022 - Identification and Authentication, slide 20 022 - Identification and Authentication:: s20::1	supported (stem gate)	0.78
5	Kerberos suffers from being relatively complex to install and from having a single point of failure.	"Relatively complex in installation."	022 - Identification and Authentication, slide 23 022 - Identification and Authentication:: s23::1	partly supported	0.33 LOW

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.

© Hak Cipta Universiti Teknologi MARA

Style confidence: LOW - exact examples n<3; widened via topic+marks (any command).
Citations: 022 - Identification and Authentication, slide 16; 022 - Identification and Authentication, slide 18; 022 - Identification and Authentication, slide 20; 022 - Identification and Authentication, slide 23; 022 - Identification and Authentication, slide 9

PART B - QUESTION 2

B2a - 5 marks - supported by lecture slides (not lecturer-marked)

Scenario:

A security architect is comparing how operating systems and formal models represent access rights. She examines an object-centred list attached to a file, a matrix of subjects against objects, and a capability list held by each subject, and asks how these structures differ in what they make easy to see and easy to revoke.

Question:

State five points about access control structures, covering the three named structures, the requirements they must satisfy, and the advantages and disadvantages of an access control list.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Name the access control matrix as one of the structures used to implement access policies	"Access control structures are mechanisms for implementing access policies:"	023 - Access Control and Authorization, slide 7 023 - Access Control and Authorization::s07::1	supported (stem gate)	0.83
2	Name capabilities, given as C-List, as a second structure	"Capabilities (C-List)"	023 - Access Control and Authorization, slide 7 023 - Access Control and Authorization::s07::1	supported	0.25 LOW
3	State that an ACL is an object-centred description of access rights	"ACL is an object-centered description of access rights:"	023 - Access Control and Authorization, slide 10 023 - Access Control and Authorization::s10::1	supported (stem gate)	0.83
4	Give one advantage of ACLs, namely that object access rights are easy to reach	"easy access to object access rights"	023 - Access Control and Authorization, slide 10 023 - Access Control and Authorization::s10::1	supported (stem gate)	0.57
5	Give one disadvantage of ACLs, namely that revocation is difficult	"difficulty of revocation"	023 - Access Control and Authorization, slide 10 023 - Access Control and Authorization::s10::1	supported	0.25 LOW

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 023 - Access Control and Authorization, slide 10; 023 - Access Control and Authorization, slide 7

B2b - 5 marks - supported by lecture slides (not lecturer-marked)

Question:

Referring to the scenario, discuss the authorization goals that an access control system must serve and explain how a reference monitor supports these goals, including the role of the Chinese Wall model in

© Hak Cipta Universiti Teknologi MARA

controlling access.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	The four authorization goals of access control are granting, limiting, preventing and revoking access.	"Goals of access control: Granting access Limiting access Preventing access Revoking access"	023 - Access Control and Authorization, slide 4 023 - Access Control and Authorization::s04::1	supported (stem gate)	0.88
2	A reference monitor is the component that makes authorization decisions.	"Reference monitor makes authorization decisions."	023 - Access Control and Authorization, slide 4 023 - Access Control and Authorization::s04::1	supported (stem gate)	1.00
3	Reference monitors are instruments for realizing access control policies and can be deployed at all levels of the system hierarchy.	"Reference monitors are instruments for realization of access control policies. They can be deployed at all levels of system hierarchy."	023 - Access Control and Authorization, slide 18 023 - Access Control and Authorization::s18::1	supported (stem gate)	1.00
4	The Chinese Wall model is an access control confidentiality policy that addresses conflicts of interest.	"Brewer and Nash (1989) proposed a policy called the Chinese Wall Policy that addresses such conflicts of interest. Strictly speaking, this is not an integrity policy, but an access control confidentiality policy."	024 - Formal Security Model, slide 21 024 - Formal Security Model::s21::1	supported (stem gate)	0.90
5	Under the Chinese Wall simple security rule, a subject may access an object only if it is within the same company dataset already accessed or belongs to an entirely different conflict of interest class.	"(Chinese Wall) Simple Security Rule: A subject s can be granted access to an object o only if the object: is in the same company datasets as the objects already accessed by s, that is, "within the Wall," or belongs to an entirely different conflict of interest class."	024 - Formal Security Model, slide 25 024 - Formal Security Model::s25::1	supported (stem gate)	0.91

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Style confidence: LOW - exact examples n<3; widened via topic+marks (any command).
Citations: 023 - Access Control and Authorization, slide 18; 023 - Access Control and Authorization, slide 4; 024 - Formal Security Model, slide 21; 024 - Formal Security Model, slide 25

End of marking scheme.

© Hak Cipta Universiti Teknologi MARA