UNIVERSITI TEKNOLOGI MARA
MARKING SCHEME

COURSE	:	COMPUTER SECURITY
COURSE CODE	:	CSC662
EXAMINATION	:	OCTOBER 2026 (MOCK)
TIME	:	3 HOURS

MARKING SCHEME NOTES

1. This marking scheme accompanies the CSC662 mock paper (October 2026). Computed answers show working; theory answers are supported by lecture slides (not lecturer-marked) with a verbatim quote and slide citation.

2. Supported theory marking points quote the lecture decks; any unresolved slot would remain a visible placeholder.

3. Part A = 10 x (2 + 6); Part B = 2 x (5 + 5); total = 100 marks.

4. Computed: 0 slot(s). Supported theory: 22 slots. Placeholders: 2. Questions and answers are for local study use only.

5. Near-copy rejection used all 35 past papers; style widening is recorded per slot.

FOR MARKERS' USE ONLY

This marking scheme consists of 15 printed pages

© Hak Cipta Universiti Teknologi MARA

CSC662 - MARKING SCHEME (MOCK OCTOBER 2026)

Labels: computed / supported by lecture slides (not lecturer-marked) / placeholder. No official marking scheme exists for the real CSC662 papers; this is generated for the mock.

Entailment labels: supported = the quote directly supports the marking point (or the point passed the stem-overlap gate without an LLM check); partly supported = the quote supports part of the point or is ambiguous; not supported = the quote does not support the point. Only 'not supported' points triggered regeneration.

Part A: 10 x (2 + 6) = 80 marks. Part B: 2 x (5 + 5) = 20 marks. Total: 100 marks. Slots: 0 computed, 22 supported by lecture slides, 2 placeholder.

Methods: computed answers use verified solvers. Theory answers are supported by lecture slides (not lecturer-marked). Each marking point carries a verbatim quote, a deck/slide/chunk citation and a term-overlap score; low overlap is flagged for human review. Sources are restricted to the slot topic's allowed decks, and a slide is not reused across questions where an alternative exists.

PART A - QUESTION 1

A1a - 2 marks - supported by lecture slides (not lecturer-marked)

Question:

Explain where network-based IDS sensors should be placed in a network and why their placement matters.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Sensors should be positioned at strategic points so that the most valuable assets are protected.	"Place IDS sensors strategically to defend most valuable assets"	062 - Intrusion Detection System, slide 7 062 - Intrusion Detection System::s07::1	supported (stem gate)	0.56
2	Typical sensor locations include just inside the firewall, on the DMZ, on the server farm segment, and on segments connecting mainframe or midrange hosts.	"Just inside the firewall"	062 - Intrusion Detection System, slide 7 062 - Intrusion Detection System::s07::1	partly supported	0.20 LOW

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 062 - Intrusion Detection System, slide 7

A1b - 6 marks - supported by lecture slides (not lecturer-marked)

Question:

Describe six preventive network security mechanisms and, for each, state the specific protective role it plays in an organization's network.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	A firewall controls incoming and outgoing network traffic according to predetermined security policies.	"Control incoming and outgoing traffic on network with predetermined security policies."	061 - Network Security, slide 3 061 - Network Security::s03::1	supported (stem gate)	0.80
2	A proxy server improves data security and network performance by acting as a firewall and web filter, sharing connections and caching data.	"Proxy servers act as a firewall and web filter, provide shared network connections, and cache data to speed up common requests."	061 - Network Security, slide 3 061 - Network Security::s03::1	supported (stem gate)	0.79
3	Network segmentation creates boundaries between segments whose computing assets share a common function, risk or role.	"Boundaries between network segments where computing assets within the segment have a common function, risk or role within an organization."	061 - Network Security, slide 3 061 - Network Security::s03::1	supported (stem gate)	0.77

© Hak Cipta Universiti Teknologi MARA

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
4	A remote access VPN gives individual hosts or clients secure access to an organization's network.	"Provides remote and secure access to an organization network to individual hosts or clients"	061 - Network Security, slide 4 061 - Network Security::s04::1	supported (stem gate)	0.89
5	Zero Trust Network Access restricts a user to only the access and permissions needed to fulfil their role.	"A user should only has access and permission that required to fulfill the role"	061 - Network Security, slide 4 061 - Network Security::s04::1	supported (stem gate)	0.55
6	IDS/IPS detect or prevent network attacks such as brute force, Denial-of-Service and exploitation of network vulnerabilities.	"To detect or prevent the network security attacks such as brute force attacks, Denial-of-Service attacks and exploits of network vulnerabilities."	061 - Network Security, slide 4 061 - Network Security::s04::1	supported (stem gate)	0.85

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 061 - Network Security, slide 3; 061 - Network Security, slide 4

PART A - QUESTION 2

A2a - 2 marks - supported by lecture slides (not lecturer-marked)

Question:

List TWO (2) reasons why software is insecure, as discussed in the Software Security lecture.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Attackers can cause insecurity by altering system resources that are essential for program execution, such as the instruction pointer or function call addresses.	"Software insecurity stems from attacker's ability to modify system resources criticial for program execution, e.g. instruction pointer, function call addresses, interrupt addresses, etc."	051 - Software Security, slide 30 051 - Software Security::s30::1	supported (stem gate)	0.69
2	A major cause of software insecurity is the failure to properly validate input supplied by users.	"One of the key sources for software insecurity is failed validation of user input."	051 - Software Security, slide 30 051 - Software Security::s30::1	supported (stem gate)	0.50

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 051 - Software Security, slide 30

A2b - 6 marks - supported by lecture slides (not lecturer-marked)

Question:

State six (6) Windows security mechanisms or components, as discussed in the Windows Security lecture, and briefly indicate the role of each.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	The Security Reference Monitor operating in kernel mode performs ACL verification.	"Security Reference Monitor: ACL verification"	041 - Windows Security, slide 3 041 - Windows Security::s03::1	partly supported	0.44 LOW
2	The winlogon process in user mode handles user logon.	"Log-on process (winlogon): user logon"	041 - Windows Security, slide 3 041 - Windows Security::s03::1	supported (stem gate)	0.67
3	The Local Security Authority is responsible for password verification and change, access tokens and audit logs.	"Local Security Authority (LSA): password verification and change, access tokens, audit logs"	041 - Windows Security, slide 3 041 - Windows Security::s03::1	supported (stem gate)	0.82
4	The Security Accounts Manager maintains the accounts database and performs password encryption.	"Security Accounts Manager (SAM): accounts database, password encryption"	041 - Windows Security, slide 3 041 - Windows Security::s03::1	supported (stem gate)	0.75

© Hak Cipta Universiti Teknologi MARA

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
5	User Account Control, introduced in Vista, enforces limited user privileges.	"User Account Control (UAC, Vista): enforcement of limited user privileges"	041 - Windows Security, slide 3 041 - Windows Security::s03::1	supported (stem gate)	0.88
6	Active Directory, introduced in Windows 2000, is an LDAP-like directory service used to organize system resources.	"Active directory introduced in Windows 2000 is an LDAP-like directory service for organization of system resources:"	041 - Windows Security, slide 6 041 - Windows Security::s06::1	supported (stem gate)	1.00

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Style confidence: LOW - exact examples n<3; widened via topic+marks (any command).
Citations: 041 - Windows Security, slide 3; 041 - Windows Security, slide 6

PART A - QUESTION 3

A3a - 2 marks - supported by lecture slides (not lecturer-marked)

Question:

State TWO (2) characteristics of a Trojan horse as a type of malware.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Trojans typically disguise themselves as useful or benign programs.	"They usually masquerade as helpful or harmless programs"	051 - Software Security, slide 12 051 - Software Security::s12::1	supported	0.17 LOW
2	Trojans steal private information or damage the host system.	"malicious programs that replicate themselves and steal information or harm the host computer system"	051 - Software Security, slide 12 051 - Software Security::s12::1	supported (stem gate)	0.57

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 051 - Software Security, slide 12

A3b - 6 marks - supported by lecture slides (not lecturer-marked)

Question:

Discuss six (6) ways in which malware attacks and propagates, referring to historical malware examples, executable infection techniques, and the behaviour of rootkits and spyware.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Early malware such as Elk Cloner spread by infecting the boot sector of disks.	"A program spread via boot sector infection"	051 - Software Security, slide 7 051 - Software Security::s07::1	partly supported	0.40 LOW
2	The Morris worm propagated across the Arpanet by exploiting a debugging feature of sendmail for remote execution.	"Used a debugging feature of sendmail (remote execution)"	051 - Software Security, slide 7 051 - Software Security::s07::1	partly supported	0.40 LOW
3	An executable virus can propagate by appending its virus body to a host program.	"Append a virus body to a program"	051 - Software Security, slide 10 051 - Software Security::s10::1	supported (stem gate)	0.50
4	An executable virus can hijack execution by overwriting a program header to redirect the entry point to the virus.	"Over write a program header to switch the entry point to a virus"	051 - Software Security, slide 10 051 - Software Security::s10::1	supported (stem gate)	0.50
5	Rootkits hide malicious processes and software so that the attacker retains privileged remote access to the infected system.	"Rootkits are a type of malware that mask malicious processes and software in the infected systems to ensure privileged remote access."	051 - Software Security, slide 13 051 - Software Security::s13::1	supported (stem gate)	0.75

© Hak Cipta Universiti Teknologi MARA

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
6	Spyware attacks users by stealing their logins and passwords and by logging keystrokes.	"They steal user logins and passwords, document sites visited, log keystrokes and even redirect browsers to unwanted sites."	051 - Software Security, slide 13 051 - Software Security::s13::1	supported (stem gate)	0.75

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Style confidence: LOW - exact examples n<3; widened via topic+marks (any command).
Citations: 051 - Software Security, slide 10; 051 - Software Security, slide 13; 051 - Software Security, slide 7

PART A - QUESTION 4

A4a - 2 marks - supported by lecture slides (not lecturer-marked)

Question:

Explain the Chinese Wall model as a formal security model, stating the concern it is designed to address and how its access decisions differ from static policies.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	It is designed to address a very specific concern, namely conflicts of interest affecting a consultant or contractor.	"Brewer and Nash's Chinese Wall Policy is designed to address a very specific concern: conflicts of interest by a consultant or contractor."	024 - Formal Security Model, slide 27 024 - Formal Security Model::s27::1	supported (stem gate)	0.89
2	Access decisions are sensitive to the history of past accesses, so permissions change dynamically rather than being fixed in advance.	"The Chinese Wall is an access control policy in which accesses are sensitive to the history of past accesses."	024 - Formal Security Model, slide 27 024 - Formal Security Model::s27::1	supported	0.33 LOW

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 024 - Formal Security Model, slide 27

A4b - 6 marks - supported by lecture slides (not lecturer-marked)

Question:

Explain the three main access control structures used to implement access policies, namely the access control matrix, access control lists and capabilities, and state the requirements that any such structure must satisfy.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Access control structures are the mechanisms through which access policies are implemented, and the access control matrix, capabilities and access control lists are named as such structures.	"Access control structures are mechanisms for implementing access policies:"	023 - Access Control and Authorization, slide 7 023 - Access Control and Authorization::s07::1	supported (stem gate)	0.60
2	The access control matrix is described as the basic control structure, valued for clarity of definition and ease of verification.	"ACM is a basic control structure."	023 - Access Control and Authorization, slide 8 023 - Access Control and Authorization::s08::1	partly supported	0.30 LOW

© Hak Cipta Universiti Teknologi MARA

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
3	The access control matrix suffers from poor scalability and poor handling of changes.	"poor scalability"	023 - Access Control and Authorization, slide 8 023 - Access Control and Authorization::s08::1	partly supported	0.25 LOW
4	An access control list is an object-centred description of access rights, giving easy access to the rights on an object and relative ease of management through abstractions.	"ACL is an object-centered description of access rights:"	023 - Access Control and Authorization, slide 10 023 - Access Control and Authorization::s10::1	partly supported	0.33 LOW
5	Access control lists have the drawbacks of a poor overview of rights per subject and difficulty of revocation and sharing.	"difficulty of revocation"	023 - Access Control and Authorization, slide 10 023 - Access Control and Authorization::s10::1	partly supported	0.08 LOW
6	Any access control structure must be able to express control policies and must offer verifiability of correctness together with scalability and manageability.	"an ability to express control policies"	023 - Access Control and Authorization, slide 7 023 - Access Control and Authorization::s07::1	partly supported	0.21 LOW

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 023 - Access Control and Authorization, slide 10; 023 - Access Control and Authorization, slide 7; 023 - Access Control and Authorization, slide 8

PART A - QUESTION 5

A5a - 2 marks - supported by lecture slides (not lecturer-marked)

Question:

List two goals of access control and state the instrument used to make authorization decisions.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	The reference monitor is the instrument that makes authorization decisions.	"Reference monitor makes authorization decisions."	023 - Access Control and Authorization, slide 4 023 - Access Control and Authorization::s04::1	supported (stem gate)	0.83
2	The reference monitor is the mechanism that makes authorization decisions.	"Reference monitor makes authorization decisions."	023 - Access Control and Authorization, slide 4 023 - Access Control and Authorization::s04::1	supported (stem gate)	0.83

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Style confidence: LOW - exact examples n<3; widened via topic+marks (any command).
Citations: 023 - Access Control and Authorization, slide 4

© Hak Cipta Universiti Teknologi MARA

A5b - 6 marks - supported by lecture slides (not lecturer-marked)

Question:

Refer to your answer in (a). Discuss six distinct features of formal security models, covering the Bell-La Padula, Biba and Chinese Wall models, including what each model controls and how the Chinese Wall model's rules constrain read and write access.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	The Bell-La Padula model is described as providing access control only, without the additional integrity verification found in Biba.	"Bell-La Padula (BLP) model: access control only"	024 - Formal Security Model, slide 5 024 - Formal Security Model:: s05::1	partly supported	0.46 LOW
2	The Biba model is characterised as adding integrity verification on top of access control.	"Biba model: additional integrity verification"	024 - Formal Security Model, slide 5 024 - Formal Security Model:: s05::1	supported	0.44 LOW
3	The Chinese Wall model is presented as a confidentiality access control policy rather than an integrity policy.	"Strictly speaking, this is not an integrity policy, but an access control confidentiality policy."	024 - Formal Security Model, slide 21 024 - Formal Security Model:: s21::1	supported (stem gate)	0.50
4	Under the Chinese Wall simple security rule, a subject may access an object only if it lies within the wall of already accessed company datasets or belongs to an entirely different conflict of interest class.	"is in the same company datasets as the objects already accessed by s, that is, "within the Wall," or"	024 - Formal Security Model, slide 25 024 - Formal Security Model:: s25::1	partly supported	0.33 LOW
5	The Chinese Wall *-property restricts writes: a write is allowed only if the simple security rule permits it and no object readable by the subject belongs to a different company dataset and holds unsanitized information.	"(Chinese Wall) *-property: Write access is only permitted if: access is permitted by the simple security rule, and no object can be read which is: in a different company dataset than the one for which write access is requested, and contains unsanitized information."	024 - Formal Security Model, slide 26 024 - Formal Security Model:: s26::1	supported (stem gate)	0.70
6	Access permissions in the Chinese Wall model change dynamically, since the rights a subject enjoys depend on the history of its past accesses.	"Notice that permissions change dynamically. The access rights that any subject enjoys depends on the history of past accesses"	024 - Formal Security Model, slide 24 024 - Formal Security Model:: s24::1	supported (stem gate)	0.71

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Style confidence: LOW - exact examples n<3; widened via topic+marks (any command).
Citations: 024 - Formal Security Model, slide 21; 024 - Formal Security Model, slide 24; 024 - Formal Security Model, slide 25; 024 - Formal Security Model, slide 26; 024 - Formal Security Model, slide 5

PART A - QUESTION 6

A6a - 2 marks - supported by lecture slides (not lecturer-marked)

Question:

Explain how a disclosure threat and a usurpation threat each cause harm to a system, stating which security objective is affected in each case.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap

© Hak Cipta Universiti Teknologi MARA

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Disclosure is the unauthorized access to information (e.g. via snooping, sniffing or wiretapping), and this harm to confidentiality is countered by confidentiality services.	"Disclosure - unauthorized access to information"	011 - Introduction to Computer Security, slide 10 011 - Introduction to Computer Security::s10::1	partly supported	0.33 LOW
2	Usurpation is the unauthorized control of some part of a system, and the resulting harm to availability is countered by availability services.	"Usurpation - unauthorized control of some part of a system"	011 - Introduction to Computer Security, slide 10 011 - Introduction to Computer Security::s10::1	supported (stem gate)	0.55

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 011 - Introduction to Computer Security, slide 10

A6b - 6 marks - supported by lecture slides (not lecturer-marked)

Question:

The Samy worm spread rapidly across MySpace by exploiting a cross-site scripting flaw. Explain six (6) aspects of this incident, covering the underlying XSS vulnerability, how the worm injected and propagated itself, and the scale of the resulting infection.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	The root cause is that any web application returning user input without filtering is potentially vulnerable to XSS.	"Any web application that returns user input without filtering is a potential XSS vulnerability!"	052 - Web Security, slide 13 052 - Web Security::s13::1	supported (stem gate)	0.77
2	XSS permits arbitrary JavaScript to be executed inside the victim user's browser.	"Allows execution of arbitrary Javascript in user's browser."	052 - Web Security, slide 13 052 - Web Security::s13::1	supported (stem gate)	0.56
3	The worm injected JavaScript into a user profile by manipulating document.body.innerHTML.	"Inject Javascript into a user profile using document.body.innerHTML"	052 - Web Security, slide 15 052 - Web Security::s15::1	supported (stem gate)	0.70
4	It retrieved the victim's list of heroes by issuing a GET request on a user profile.	"Get the list of user's heros by using a GET on a user profile"	052 - Web Security, slide 15 052 - Web Security::s15::1	supported	0.38 LOW
5	It added Samy as a friend by performing XML-HTTP requests against the addFriends page.	"Add Samy as a field by performing XML-HTTP on the addFriends page"	052 - Web Security, slide 15 052 - Web Security::s15::1	supported (stem gate)	0.70
6	Any visitor to an infected profile had their own profile and friends list infected, and roughly 1,000,000 MySpace profiles were eventually infected.	"Eventually about 1,000,000 MySpace profiles were infected."	052 - Web Security, slide 15 052 - Web Security::s15::1	partly supported	0.36 LOW

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 052 - Web Security, slide 13; 052 - Web Security, slide 15

PART A - QUESTION 7

A7a - 2 marks - supported by lecture slides (not lecturer-marked)

Question:

Explain how the chain of trust works in Trusted Computing, referring to the role of the TPM and the stages that are measured and validated.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap

© Hak Cipta Universiti Teknologi MARA

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Each stage of the chain measures and validates the following stage, with the resulting measurements stored in the TPM's Platform Configuration Registers (PCRs).	"Each stage measures and validates the next one"	073 - Trusted Computing, slide 8 073 - Trusted Computing::s08::1	partly supported	0.25 LOW
2	The chain begins at the hardware TPM and then proceeds through software stages such as the RTM, TPM Software Stack, BIOS and kernel, so that the whole platform ends up verified as trusted.	"The chain starts with the hardware TPM, then software:"	073 - Trusted Computing, slide 8 073 - Trusted Computing::s08::1	partly supported	0.26 LOW

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 073 - Trusted Computing, slide 8

A7b - 6 marks - supported by lecture slides (not lecturer-marked)

Question:

Describe six (6) components and characteristics of the NGSCB/Nexus architecture, covering both the Nexus kernel and the Nexus Computing Agent, as presented in the Trusted Computing lecture.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Nexus is described as a security kernel that is authenticated on boot.	"Security kernel, authenticated on boot"	073 - Trusted Computing, slide 14 073 - Trusted Computing::s14::1	supported (stem gate)	0.80
2	Nexus authenticates trusted programs.	"Authenticates trusted programs"	073 - Trusted Computing, slide 14 073 - Trusted Computing::s14::1	supported (stem gate)	0.75
3	Nexus provides the application interface to the TPM.	"Application interface to TPM"	073 - Trusted Computing, slide 14 073 - Trusted Computing::s14::1	supported (stem gate)	0.60
4	Nexus does not trust the operating system.	"Does not trust OS"	073 - Trusted Computing, slide 14 073 - Trusted Computing::s14::1	supported (stem gate)	0.50
5	The Nexus Computing Agent is a trusted software component.	"Trusted software component"	073 - Trusted Computing, slide 15 073 - Trusted Computing::s15::1	supported	0.40 LOW
6	The NCA runs in a trusted mode that communicates with Nexus.	"Runs in trusted mode that communicates with Nexus"	073 - Trusted Computing, slide 15 073 - Trusted Computing::s15::1	supported (stem gate)	0.83

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 073 - Trusted Computing, slide 14; 073 - Trusted Computing, slide 15

PART A - QUESTION 8

A8a - 2 marks - supported by lecture slides (not lecturer-marked)

Question:

State TWO (2) differences between morals and laws as forms of conduct guidance for computing professionals.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Morals are described as traditions of belief concerning right and wrong conduct within a society.	"Morals are traditions of belief about right and wrong conduct"	071 - Ethics and Computer Security, slide 5 071 - Ethics and Computer Security::s05::1	supported (stem gate)	0.67
2	Laws are formal rules of conduct imposed by a sovereign authority such as a government on its subjects or citizens.	"Laws are formal rules of conduct that a sovereign authority, such as a government, imposes on its subjects or citizens"	071 - Ethics and Computer Security, slide 5 071 - Ethics and Computer Security::s05::1	supported (stem gate)	1.00

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 071 - Ethics and Computer Security, slide 5

A8b - 6 marks - supported by lecture slides (not lecturer-marked)

Question:

Discuss how a professional code of ethics and conduct, such as the ACM code, guides a computing professional in carrying out security-related work. Your discussion should cover six (6) distinct obligations or expectations that such a code places on the professional.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	The professional is expected to design and build systems that are secure in a robust and usable manner.	"Design and implement systems that are robustly and usably secure."	071 - Ethics and Computer Security, slide 12 071 - Ethics and Computer Security::s12::1	supported (stem gate)	0.56
2	The professional should only use computing and communication resources when they are authorised to do so or when the public good requires it.	"Access computing and communication resources only when authorized or when compelled by the public good."	071 - Ethics and Computer Security, slide 12 071 - Ethics and Computer Security::s12::1	supported (stem gate)	0.58
3	The professional must give thorough assessments of computer systems and their impacts, including an analysis of possible risks.	"Give comprehensive and thorough evaluations of computer systems and their impacts, including analysis of possible risks."	071 - Ethics and Computer Security, slide 12 071 - Ethics and Computer Security::s12::1	supported (stem gate)	0.73
4	The professional is required to respect the privacy of others.	"Respect privacy."	071 - Ethics and Computer Security, slide 11 071 - Ethics and Computer Security::s11::1	supported	0.40 LOW
5	The professional is required to honour confidentiality.	"Honor confidentiality."	071 - Ethics and Computer Security, slide 11 071 - Ethics and Computer Security::s11::1	supported	0.25 LOW
6	The code is a documented set of acceptable behaviours defined by a professional group, which identifies particular actions as appropriate or inappropriate.	"Documented set of acceptable behaviors for professional or social groups."	071 - Ethics and Computer Security, slide 6 071 - Ethics and Computer Security::s06::1	supported	0.42 LOW

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 071 - Ethics and Computer Security, slide 11; 071 - Ethics and Computer Security, slide 12; 071 - Ethics and Computer Security, slide 6

© Hak Cipta Universiti Teknologi MARA

PART A - QUESTION 9

A9a - 2 marks - supported by lecture slides (not lecturer-marked)

Question:

Explain the stages involved in the biometric authentication process, distinguishing clearly between the identification stage and the authentication stage.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	The identification stage begins with acquisition of the biometric sample.	"Identification Stage Acquisition Creation of Master characteristics Storage of Master characteristics"	072 - Biometrics and Authentication, slide 5 072 - Biometrics and Authentication:: s05::1	supported (stem gate)	0.50
2	During identification, master characteristics are created and stored for later use.	"Creation of Master characteristics Storage of Master characteristics"	072 - Biometrics and Authentication, slide 5 072 - Biometrics and Authentication:: s05::1	supported	0.17 LOW

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 072 - Biometrics and Authentication, slide 5

A9b - 6 marks - supported by lecture slides (not lecturer-marked)

Question:

Biometric technologies are grouped into different categories and each technology has its own operational strengths and weaknesses. Explain the categories of biometric applications and the characteristics of specific biometric technologies, giving six distinct points.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Biometric applications are divided into two sectors, namely physiological and behavioural.	"Biometric applications available today are categorized into 2 sectors"	072 - Biometrics and Authentication, slide 4 072 - Biometrics and Authentication:: s04::1	supported (stem gate)	0.57
2	Physiological biometrics include iris, fingerprints, hand, retinal and face recognition.	"Psychological: Iris, Fingerprints, Hand, Retinal and Face recognition"	072 - Biometrics and Authentication, slide 4 072 - Biometrics and Authentication:: s04::1	supported (stem gate)	0.67
3	Behavioural biometrics include voice, typing pattern and signature.	"Behavioural: Voice, Typing pattern, Signature"	072 - Biometrics and Authentication, slide 4 072 - Biometrics and Authentication:: s04::1	supported (stem gate)	0.67
4	A biometric is defined as a physiological or behavioural characteristic that can distinguish one person from another and can theoretically be used for identification or verification.	"A biometric is a physiological or behavioural characteristic of a human being that can distinguish one person from another and that theoretically can be used for identification or verification of identity."	072 - Biometrics and Authentication, slide 2 072 - Biometrics and Authentication:: s02::1	supported (stem gate)	0.91

© Hak Cipta Universiti Teknologi MARA

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
5	Iris scanning reads the unique pattern of the iris, requires no touch, and overcomes the issues of retinal scanners.	"Scans unique pattern of iris"	072 - Biometrics and Authentication, slide 10 072 - Biometrics and Authentication:: s10::1	partly supported	0.36 LOW
6	Fingerprint biometrics suffer disadvantages such as racial issues, dirt, grime and wounds, finger placement problems, and spoofing, so liveness detection is important.	"Can be spoofed - liveness important!"	072 - Biometrics and Authentication, slide 7 072 - Biometrics and Authentication:: s07::1	partly supported	0.18 LOW

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 072 - Biometrics and Authentication, slide 10; 072 - Biometrics and Authentication, slide 2; 072 - Biometrics and Authentication, slide 4; 072 - Biometrics and Authentication, slide 7

PART A - QUESTION 10

A10a - 2 marks - supported by lecture slides (not lecturer-marked)

Question:

State TWO (2) limitations of misuse detection systems when used to detect attacks.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Misuse detection systems are ineffective against previously unknown attack methods.	"They can detect many or all known attack patterns, but they are of little use for unknown attack methods."	062 - Intrusion Detection System, slide 17 062 - Intrusion Detection System:: s17::1	supported	0.44 LOW
2	State transition analysis misuse detection cannot identify denial of service attacks.	"They can't detect denail of service attacks."	062 - Intrusion Detection System, slide 21 062 - Intrusion Detection System:: s21::1	supported	0.38 LOW

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 062 - Intrusion Detection System, slide 17; 062 - Intrusion Detection System, slide 21

A10b - 6 marks - supported by lecture slides (not lecturer-marked)

Question:

State the distinction between a vulnerability, a threat and an attack as presented in the security fundamentals lecture, and state one countermeasure principle for protecting assets against such dangers.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	A vulnerability is described as a weakness of a system that can be exploited to damage assets.	"Vulnerabilities: Weakness of a system that can be exploited to damage assets"	011 - Introduction to Computer Security, slide 9 011 - Introduction to Computer Security::s09::1	supported (stem gate)	1.00
2	A threat is characterised as a potential violation of security rather than an actual one.	"Threats: A threat is a "potential" violation of security"	011 - Introduction to Computer Security, slide 9 011 - Introduction to Computer Security::s09::1	supported (stem gate)	0.50

© Hak Cipta Universiti Teknologi MARA

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
3	An attack is defined as the actual violation of security.	"Attacks: The actual violation of security"	011 - Introduction to Computer Security, slide 9 011 - Introduction to Computer Security::s09::1	supported (stem gate)	0.80
4	A threat is any object, person or other entity that represents a constant danger to an asset.	"Threat: object, person, or other entity representing a constant danger to an asset"	011 - Introduction to Computer Security, slide 28 011 - Introduction to Computer Security::s28::1	supported (stem gate)	0.90
5	An attack is a deliberate act that exploits a vulnerability.	"Attack: a deliberate act that exploits vulnerability"	011 - Introduction to Computer Security, slide 28 011 - Introduction to Computer Security::s28::1	supported (stem gate)	1.00
6	Protection of assets should combine prevention, detection and response techniques.	"Protection of assets encompasses prevention, detection and response techniques"	011 - Introduction to Computer Security, slide 28 011 - Introduction to Computer Security::s28::1	supported (stem gate)	0.75

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Citations: 011 - Introduction to Computer Security, slide 28; 011 - Introduction to Computer Security, slide 9

PART B - QUESTION 1

B1a - 5 marks - supported by lecture slides (not lecturer-marked)

Question:

State FIVE (5) password security controls that can be applied to protect a system's password files and user accounts.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Apply access control to the password files so that only authorised parties can read them.	"Access control applied to password files"	022 - Identification and Authentication, slide 12 022 - Identification and Authentication:: s12::1	supported	0.36 LOW
2	De-activate an account after several failed login attempts.	"De-activation of accounts after multiple failed logins"	022 - Identification and Authentication, slide 12 022 - Identification and Authentication:: s12::1	supported (stem gate)	0.71
3	Show the time of the user's last login so anomalies can be noticed.	"Displaying the time of a last login"	022 - Identification and Authentication, slide 12 022 - Identification and Authentication:: s12::1	partly supported	0.38 LOW
4	Enforce password policies, for example for the root password.	"Password policies, e.g. for root password"	022 - Identification and Authentication, slide 12 022 - Identification and Authentication:: s12::1	supported (stem gate)	0.60

© Hak Cipta Universiti Teknologi MARA

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
5	Store the password in encrypted form using a one-way hash function.	"Password is stored in an encrypted form using a one-way hash function:"	022 - Identification and Authentication, slide 8 022 - Identification and Authentication:: s08::1	supported (stem gate)	1.00

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Style confidence: LOW - exact examples n<3; widened via topic+marks (any command).
Citations: 022 - Identification and Authentication, slide 12; 022 - Identification and Authentication, slide 8

B1b - 5 marks - supported by lecture slides (not lecturer-marked)

Question:

Explain the design criteria that Kerberos satisfies and the benefits that motivate organisations to adopt single sign-on solutions such as Kerberos, smart cards and two-factor authentication.

Marking points:

No.	Point (1 mark)	Evidence quote	Source	Verdict	Overlap
1	Kerberos prevents eavesdropping because no password is ever transmitted in clear text.	"Security against eavesdropping: no password transmission in clear text."	022 - Identification and Authentication, slide 18 022 - Identification and Authentication:: s18::1	supported	0.44 LOW
2	Kerberos is transparent to the user, who is unaware of any authentication beyond the initial login.	"Transparency: user is not aware of any authentication beyond an initial login."	022 - Identification and Authentication, slide 18 022 - Identification and Authentication:: s18::1	supported (stem gate)	0.70
3	Single sign-on reduces the burden of remembering and typing passwords and lowers password maintenance effort.	"Reduce the need to memorize passwords"	022 - Identification and Authentication, slide 16 022 - Identification and Authentication:: s16::1	partly supported	0.22 LOW
4	Single sign-on can be realised through client-server architectures such as Kerberos and Active Directory.	"Client-server architectures (Kerberos, Active Directory)"	022 - Identification and Authentication, slide 16 022 - Identification and Authentication:: s16::1	supported (stem gate)	0.50
5	Smart cards, biometrics and two-factor authentication are alternatives to passwords and shared secrets.	"Alternative user authentication mechanisms are smart cards, biometric methods and two-factor authentication."	022 - Identification and Authentication, slide 24 022 - Identification and Authentication:: s24::1	supported (stem gate)	0.67

Confidence: supported by lecture slides (not lecturer-marked) - each point carries a verbatim quote from the cited lecture slide.
Style confidence: LOW - exact examples n<3; widened via topic+marks (any command).
Citations: 022 - Identification and Authentication, slide 16; 022 - Identification and Authentication, slide 18; 022 - Identification and Authentication, slide 24

PART B - QUESTION 2

B2a - 5 marks - PLACEHOLDER

Topic: risk/management (ethics); command: Explain

© Hak Cipta Universiti Teknologi MARA

Status: placeholder - no supported question passed verification.
Reason: B2a: near-duplicate (seq 0.69, content 0.65) of accepted A8b: 'Discuss how a professional code of ethics and conduct, such as the ACM code, guides a computing professional in carrying out security-relate'; choose a different question angle

B2b - 5 marks - PLACEHOLDER

Topic: risk/management (ethics); command: Discuss
Status: placeholder - no supported question passed verification.
Reason: B2b: Part B (a) is unresolved

End of marking scheme.

© Hak Cipta Universiti Teknologi MARA