Component C. Personalized Project Reference.

Procedure:

i.

```
function findPNG(states, png, request) {
  for (var i = 0; i < states.length; i++)
  {
    if (states[i] == request)
    {
      return png[i];
    }
  }
  return null;
}
```

ii.

```
function cycleCostumes() {
  currentCostume++;
  if (currentCostume >= costumeTypes.length)
  {
    currentCostume = 0;
  }
  setImageURL("petScreenCostume", findPNG(costumeTypes, costumeImages, costumeTypes[currentCostume]));
}
```

List:

i.

```
var emotionsList = ["Happy", "Playful", "Bored", "Sleepy", "Sad", "Angry", "Hungry"];
var emotionsFaces = ["HappyEmotion.png", "PlayfulEmotion.png", "BoredEmotion.png", "SleepyEmotion.png", "SadEmotion.png", "AngryEmotion.png", "HungryEmotion.png"];
```

ii.

```
function updateStatsAndEmotions() {

  setText("petScreenHungerStat", "Hunger: " + currentHunger + "%");
  setText("petScreenEnergyStat", "Energy: " + currentEnergy + "%");
  setText("petScreenHappinessStat", "Happiness: " + currentHappiness + "%");


  currentEmotion = "Happy";

  if (currentEnergy < 10)
  {
    currentEmotion = "Sleepy";
  }
  else if (currentEnergy < 40)
  {
    currentEmotion = "Bored";
  }
  else if (currentHunger < 20)
  {
    currentEmotion = "Hungry";
  }
  else if (currentHappiness > 75)
  {
    currentEmotion = "Playful";
  }
  else if (currentHappiness > 50)
  {
    currentEmotion = "Happy";
  }
  else if (currentHappiness > 25)
  {
    currentEmotion = "Sad";
  }
  else
  {
    currentEmotion = "Angry";
  }

  setImageURL("petScreenEmotion", findPNG(emotionsList, emotionsFaces, currentEmotion));
  setText("petScreenName", "Hi! My name is "+ name + "! I am " + currentEmotion + ".");
}
```