
nucleardatapy

Release 0.1

Jérôme Margueron, IRL NPA, USA

Jun 27, 2024

CONTENTS

| | | |
|----------|----------------------------|-----------|
| 1 | Contents | 3 |
| 1.1 | Usage | 3 |
| 1.2 | API | 4 |
| 1.3 | Miscellaneous | 4 |
| 2 | Complement | 7 |
| 2.1 | SetupMicro | 7 |
| 2.2 | SetupPheno | 8 |
| 2.3 | SetupEsymLsym | 11 |
| 2.4 | SetupMasses | 16 |
| 2.5 | SetupRadCh | 19 |
| 2.6 | SetupISGMR | 20 |
| 3 | Indices and tables | 23 |
| | Python Module Index | 25 |
| | Index | 27 |

nucleardatapy (/in short nuda/) is a Python library for nuclear physicists facilitating the access to theoretical or experimental nuclear data. It is specifically designed for equation of state practitioners interested in the modeling of neutron stars, and it offers *simple* and *intuitive* APIs.

All data are provided with their reference, so when using these data in a scientific paper, reference to data should be provided explicitly. The reference to this toolkit could be given, but it should not mask the reference to data.

This python toolkit is designed to provide: 1) microscopic calculations in nuclear matter, 2) phenomenological predictions in nuclear matter, 3) experimental data for finite nuclei.

Check out the [Usage](#) section for further information, including how to [install](#) the project.

Note: This project is under active development.

CONTENTS

1.1 Usage

1.1.1 Installation

To use nucleardatapy, first download the .zip file from the git repository, or clone it in your local computer:

```
$ git clone https://github.com/jeromemargueron/nucleardatapy
```

If you have downloaded the .zip file, you can unzip it anywhere in your local computer:

```
$ unzip nucleardatapy.zip
```

Then, in all cases, you shall enter into the new folder */nucleardatapy*:

```
$ cd nucleardatapy
```

and launch the install script:

```
$ bash install.sh
```

This will copy the Python toolkit into `$HOME/mylib/` as well as a few samples. It will also give you the content of the global variable `NUCLEARDATAPY_TK`. If you edit `install.sh`, you can change the version (by default it is set to the latest one) as well as the destination folder (by default it is `$HOME/mylib`).

Finally, you will have to create the global variable `NUCLEARDATAPY_TK` with its right content. If you do not want to create it each time you open a new terminal, then you can define it in your `.profile` or `.zprofil` or `.bash` file as:

```
export NUCLEARDATAPY_TK=$HOME/mylib/nucleardatapy
```

Note: The exact path to write above is given at the end of the installation.

1.1.2 Use nucleardatapy

Go to the folder *mylib/nucleardatapy/samples/nucleardatapy_samples/* and try that:

```
$ python3 sample_SetupMicro.py
```

1.1.3 Test nucleardatapy

A set of tests can be easily performed. They are stored in *tests/* folder.

```
$ bash run_tests.sh
```

1.1.4 Get started

How to obtain microscopic results for APR equation of state:

```
import os
nucleardatapy_tk = os.getenv('NUCLEARDATAPY_TK')
sys.path.insert(0, nucleardatapy_tk)

import nucleardatapy as nuda

mic = nuda.SetupMicro( model = '1998-AM-APR' )

mic.print_outputs( )
```

1.2 API

nucleardatapy

This module provides microscopic, phenomenological and experimental data constraints.

1.2.1 nucleardatapy

This module provides microscopic, phenomenological and experimental data constraints.

1.3 Miscellaneous

1.3.1 Contributing

For the moment, contributions are based on co-optation among the team.

To make contribution easy, we all work in the *main* branch and we shall therefore remember to pull before working and pulling after, with a running version. For long developments, you can work in a local folder (in *mylib* for instance) and copy your contribution to the GitHub folder once you are sure it is functioning. So the final step should last less than 5 minutes, and can be safely done between a pull and before a push. Since we are not numerous, we hope that no one

will work in the same part of the code at the same time (i.e. between a pull and a push). It is probably the simpler way to proceed.

Once the toolkit is released, the rules to contribute will be changing. A team of developpers should be defined and a generic email to contact them should be created. Here is a suggestion to contribute after the release.

This file describes how new contributors to the project can start contributing.

Two ways:

You can provide your data and interacting with one of our developer.

You can also join the developing team and extend the functionality of this toolkit.

Provide your data:

Please contact the developer team directly by shooting an email to TBC.

Then you can interact directly with one of our developer and provide your data. You will not be able to push your data to the repository, but an updated version of the toolkit will contain your new data.

Join the team:

Please contact the developer team directly by shooting an email to TBC. Explain the reason why you wish to join the team and if you have ideas about extending the functionality of the toolkit.

Once in the team, a branch will be dedicated to your contribution. You could show it during our virtual meetings, and your contribution will be merged to the new version of the toolkit.

1.3.2 License

TBC.

1.3.3 Report issues

For the current version, we report issues chatting among us. Once this toolkit is released, we should setup a way that users could contact us and report issues or difficulties in installing or using the toolkit.

1.3.4 Thanks

A special thanks to all contributors who accepted to share their results in this toolkit.

COMPLEMENT

2.1 SetupMicro

class nucleardatapy.setup_micro.**SetupMicro**(*model*='1998-VAR-AM-APR')

Instantiate the object with microscopic results chosen by the toolkit practitioner.

This choice is defined in *model*, which can be chosen among the following choices: '1998-VAR-AM-APR', '2008-AFDMC-NM', '2008-QMC-NM-swave', '2008-QMC-NM-AV4', '2009-dQMC-NM', '2010-NM-Hebeler', '2013-QMC-NM', '2014-AFQMC-NM', '2016-QMC-NM', '2016-MBPT-AM', '2018-QMC-NM', '2020-MBPT-AM-DHSL59', '2020-MBPT-AM-DHSL69', '2023-MBPT-AM'.

Parameters

model (*str*, *optional*.) – Fix the name of model. Default value: '1998-VAR-AM-APR'.

Attributes:

label

Attribute providing the label the data is references for figures.

model

Attribute model.

nm_den

Attribute neutron matter density.

nm_e2a

Attribute neutron matter energy per particle.

nm_e2a_err

Attribute uncertainty in the neutron matter energy per particle.

nm_gap

Attribute neutron matter pairing gap.

nm_kfn

Attribute neutron matter Fermi momentum.

nm_pre

Attribute neutron matter pressure.

nm_pre_err

Attribute uncertainty in the neutron matter pressure.

note

Attribute providing additional notes about the data.

print_outputs()

Method which print outputs on terminal's screen.

ref

Attribute providing the full reference to the paper to be cited.

sm_den

Attribute symmetric matter density.

sm_e2a

Attribute symmetric matter energy per particle.

sm_e2a_err

Attribute uncertainty in the symmetric matter energy per particle.

sm_gap

Attribute symmetric matter pairing gap.

sm_kfn

Attribute symmetric matter Fermi momentum.

sm_pre

Attribute symmetric matter pressure.

sm_pre_err

Attribute uncertainty in the symmetric matter pressure.

nucleardatapy.setup_micro.models_micro()

Return a list with the name of the models available in this toolkit and print them all on the prompt. These models are the following ones: '1998-VAR-AM-APR', '2008-AFDMC-NM', '2008-QMC-NM-swave', '2008-QMC-NM-AV4', '2009-dQMC-NM', '2010-NM-Hebeler', '2013-QMC-NM', '2014-AFQMC-NM', '2016-QMC-NM', '2016-MBPT-AM', '2018-QMC-NM', '2020-MBPT-AM-DHSL59', '2020-MBPT-AM-DHSL69', '2023-MBPT-AM'.

Returns

The list of models.

Return type

list[str].

Here are a set of figures which are produced with the Python sample: `/sample/nucleardatapy_plots/plot_setupMicro.py`

2.2 SetupPheno

class nucleardatapy.setup_pheno.SetupPheno(model='Skyrme', param='SLY5')

Instantiate the object with results based on phenomenological interactions and chosen by the toolkit practitioner. This choice is defined in the variables *model* and *param*.

If *models* == 'skyrme', *param* can be: 'BSK14', 'BSK16', 'BSK17', 'BSK27', 'F-', 'F+', 'F0', 'FPL', 'LNS', 'LNS1', 'LNS5', 'NRAPR', 'RATP', 'SAMI', 'SGII', 'SIII', 'SKGSIGMA', 'SKI2', 'SKI4', 'SKMP', 'SKMS', 'SKO', 'SKOP', 'SKP', 'SKRSIGMA', 'SKX', 'Skz2', 'SLY4', 'SLY5', 'SLY230A', 'SLY230B', 'SV', 'T6', 'T44', 'UNEDF0', 'UNEDF1'.

If *models* == 'NLRH', *param* can be: 'NL-SH', 'NL3', 'NL3II', 'PK1', 'PK1R', 'TM1'.




Fig. 1: This figure shows the energy in neutron matter (NM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the complete list of model available in the nucleardatapy toolkit.




Fig. 2: This figure shows the pairing gap in neutron matter (NM) over the Fermi energy (top) and the pairing gap (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the models available in the nucleardatapy toolkit.

If *models* == 'DDRH', *param* can be: 'DDME1', 'DDME2', 'DDMed', 'PKDD', 'TW99'.

If *models* == 'DDRHF', *param* can be: 'PKA1', 'PKO1', 'PKO2', 'PKO3'.

Parameters

- **model** (*str*, *optional*.) – Fix the name of model: 'Skyrme', 'NLRH', 'DDRH', 'DDRHF'. Default value: 'Skyrme'.
- **param** (*str*, *optional*.) – Fix the parameterization associated to model. Default value: 'SLY5'.

Attributes:

label

Attribute providing the label the data is references for figures.

model

Attribute model.

nm_cs2

Attribute neutron matter sound speed $(c_s/c)^2$.

nm_den

Attribute neutron matter density.

nm_e2a

Attribute neutron matter energy per particle.

nm_gap

Attribute neutron matter pairing gap.

nm_kfn

Attribute neutron matter Fermi momentum.

nm_pre

Attribute neutron matter pressure.

note

Attribute providing additional notes about the data.

param

Attribute param.

print_outputs()

Method which print outputs on terminal's screen.

ref

Attribute providing the full reference to the paper to be cited.

sm_cs2

Attribute symmetric matter sound speed $(c_s/c)^2$.

sm_den

Attribute symmetric matter density.

sm_e2a

Attribute symmetric matter energy per particle.

sm_gap

Attribute symmetric matter pairing gap.

sm_kfn

Attribute symmetric matter Fermi momentum.

sm_pre

Attribute symmetric matter pressure.

nucleardatapy.setup_pheno.models_pheno()

Return a list of models available in this toolkit and print them all on the prompt.

Returns

The list of models with can be 'Skyrme', 'NLRH', 'DDRH', 'DDRHF'.

Return type

list[str].

nucleardatapy.setup_pheno.params_pheno(model)

Return a list with the parameterizations available in this toolkit for a given model and print them all on the prompt.

Parameters

model (*str.*) – The type of model for which there are parametrizations. They should be chosen among the following options: 'Skyrme', 'NLRH', 'DDRH', 'DDRHF'.

Returns

The list of parametrizations. If *models* == 'skyrme': 'BSK14', 'BSK16', 'BSK17', 'BSK27', 'F-', 'F+', 'F0', 'FPL', 'LNS', 'LNS1', 'LNS5', 'NRAPR', 'RATP', 'SAMI', 'SGII', 'SIII', 'SKGSIGMA', 'SKI2', 'SKI4', 'SKMP', 'SKMS', 'SKO', 'SKOP', 'SKP', 'SKRSIGMA', 'SKX', 'Skz2', 'SLY4', 'SLY5', 'SLY230A', 'SLY230B', 'SV', 'T6', 'T44', 'UNEDF0', 'UNEDF1'. If *models* == 'NLRH': 'NL-SH', 'NL3', 'NL3II', 'PK1', 'PK1R', 'TM1'. If *models* == 'DDRH': 'DDME1', 'DDME2', 'DDMed', 'PKDD', 'TW99'. If *models* == 'DDRHF': 'PKA1', 'PKO1', 'PKO2', 'PKO3'.

Return type

list[str].

Here are a set of figures which are produced with the Python sample: `/sample/nucleardatapy_plots/plot_setupPheno.py`

2.3 SetupEsymLsym

class nucleardatapy.setup_EsymLsym.SetupEsymLsym(constraint='2014-IAS')

Instantiate the values of Esym and Lsym from the constraint.

The name of the constraint to be chosen in the following list: '2009-HIC', '2010-RNP', '2012-FRDM', '2013-NS', '2014-IAS', '2014-IAS+RNP', '2015-POL-208PB', '2015-POL-120SN', '2015-POL-68NI', '2017-UG', '2021-PREXII-Reed', '2021-PREXII-Reinhard', '2021-PREXII-Zhang'.

Parameters

constraint (*str, optional.*) – Fix the name of *constraint*. Default value: '2014-IAS'.

Attributes:**Esym**

Attribute Esym.




Fig. 3: This figure shows the energy in neutron matter (NM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the complete list of phenomenological models based on non-linear meson(s) relativistic Hartree (NLRH) approach available in the nucleardatapy toolkit.




Fig. 4: This figure shows the energy in symmetric matter (SM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the complete list of phenomenological models based on non-linear meson(s) relativistic Hartree (NLRH) approach available in the nucleardatapy toolkit.




Fig. 5: This figure shows the energy in neutron matter (NM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the complete list of phenomenological models based on density-dependent relativistic Hartree (DDRH) approach available in the nuclear-datapy toolkit.




Fig. 6: This figure shows the energy in symmetric matter (SM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the complete list of phenomenological models based on density-dependent relativistic Hartree (DDRH) approach available in the nuclear-datapy toolkit.




Fig. 7: This figure shows the energy in neutron matter (NM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the complete list of phenomenological models based on density-dependent relativistic Hartree-Fock (DDRHF) approach available in the nucleardatapy toolkit.




Fig. 8: This figure shows the energy in symmetric matter (SM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the complete list of phenomenological models based on density-dependent relativistic Hartree-Fock (DDRHF) approach available in the nucleardatapy toolkit.




Fig. 9: This figure shows the energy in neutron matter (NM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the complete list of phenomenological models based on the standard Skyrme interaction available in the nucleardatapy toolkit.




Fig. 10: This figure shows the energy in symmetric matter (SM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the complete list of phenomenological models based on the standard Skyrme interaction available in the nucleardatapy toolkit.

Esym_err

Attribute with uncertainty in Esym.

Lsym

Attribute Lsym.

Lsym_err

Attribute with uncertainty in Lsym.

constraint

Attribute constraint.

label

Attribute providing the label the data is references for figures.

note

Attribute providing additional notes about the constraint.

print_outputs()

Method which print outputs on terminal's screen.

ref

Attribute providing the full reference to the paper to be citted.

nucleardatapy.setup_EsymLsym.constraints_EsymLsym()

Return a list of constraints available in this toolkit in the following list: '2009-HIC', '2010-RNP', '2012-FRDM', '2013-NS', '2014-IAS', '2014-IAS+RNP', '2015-POL-208PB', '2015-POL-120SN', '2015-POL-68NI', '2017-UG', '2021-PREXII-Reed', '2021-PREXII-Reinhard', '2021-PREXII-Zhang'; and print them all on the prompt.

Returns

The list of constraints.

Return type

list[str].

Here are a set of figures which are produced with the Python sample: `/sample/nucleardatapy_plots/plot_setupEsymLsym.py`

2.4 SetupMasses

class nucleardatapy.setup_masses.SetupMasses(table='AME', version='2020')

Instantiate the experimental nuclear masses from AME mass table.

This choice is defined in the variables *table* and *version*.

table can chosen among the following ones: 'AME'.

version can be chosen among the following choices: '2020', '2016', '2012'.

Parameters

- **table** (*str*, *optional*.) – Fix the name of *table*. Default value: 'AME'.
- **version** (*str*, *optional*.) – Fix the name of *version*. Default value: 2020'.

Attributes:**A**

Attribute A (mass of the nucleus).




Fig. 11: This figure shows the $E_{\text{sym},2}$ versus $L_{\text{sym},2}$ correlation for the different constraints available in the nucleardatapy toolkit.

BE

Attribute BE (Binding Energy) of the nucleus.

BE_err

Attribute uncertainty in the BE (Binding Energy) of the nucleus.

HT

Attribute HT (half-Time) of the nucleus.

I

Attribute I.

Interp

Attribute Interp (interpolation). Interp='y' is the nucleus has not been measured but is in the table based on interpolation expressions. otherwise Interp = 'n' for nuclei produced in laboratory and measured.

N

Attribute N (number of neutrons of the nucleus).

Z

Attribute Z (charge of the nucleus).

Zmax

maximum charge of nuclei present in the table.

Type

Attribute Zmax

drip(Zmax=95)

Method which find the drip-line nuclei (on the two sides).

Parameters

Zmax (*int, optional. Default: 95.*) – Fix the maximum charge for the search of the drip line.

label

Attribute providing the label the data is references for figures.

nbLine

Attribute with the number of line in the file.

nbNuc

Attribute with the number of nuclei read in the file.

note

Attribute providing additional notes about the data.

print_outputs()

Method which print outputs on terminal's screen.

ref

Attribute providing the full reference to the paper to be cited.

select (*Amin=0, Zmin=0, interp='n', state='gs', nucleus='unstable', every=1*)

Method which select some nuclei from the table according to some criteria.

Parameters

- **interp** (*str, optional. Default = 'n'.*) – If `interp='n'`, exclude the interpolated nuclei from the selected ones. If `interp='y'` consider them in the table, in addition to the others.
- **state** (*str, optional. Default 'gs'.*) – select the kind of state. If `state='gs'`, select nuclei measured in their ground state.
- **nucleus** (*str, optional. Default 'unstable'.*) – 'unstable'.
- **every** (*int, optional. Default every = 1.*) – consider only 1 out of *every* nuclei in the table.

stbl

Attribute stbl. `stbl='y'` if the nucleus is stable (according to the table). Otherwise `stbl = 'n'`.

symb

Attribute symb (symbol) of the element, e.g., Fe.

year

Attribute year of the discovery of the nucleus.

nucleardatapy.setup_masses.tables_masses()

Return a list of the tables available in this toolkit for the experimental masses and print them all on the prompt. These tables are the following ones: 'AME'.

Returns

The list of tables.

Return type

list[str].

`nucleardatapy.setup_masses.versions_masses(table)`

Return a list of versions of tables available in this toolkit for a given model and print them all on the prompt.

Parameters

table (*str.*) – The table for which there are different versions.

Returns

The list of versions. If `table == 'AME'`: '2020', '2016', '2012'.

Return type

`list[str]`.

Here are a set of figures which are produced with the Python sample: `/sample/nucleardatapy_plots/plot_setupMasses.py`




Fig. 12: This figure shows the nuclear chart based on AME 2020 table.

2.5 SetupRadCh

`class nucleardatapy.setup_rad_ch.SetupRadCh(table='2013-Angeli')`

Instantiate the object with charge radii choosen from a table.

This choice is defined in the variable *table*.

The tables can chosen among the following ones: '2013-Angeli'.

Parameters

table (*str, optional.*) – Fix the name of *table*. Default value: '2013-Angeli'.

Attributes:

A

Attribute A (mass of the nucleus).

N

Attribute N (number of neutrons of the nucleus).

R_ch

Attribute R_ch (charge radius) in fm.

R_ch_err

Attribute uncertainty in R_ch (charge radius) in fm.

R_unit

Attribute radius unit.

Z

Attribute Z (charge of the nucleus).

label

Attribute providing the label the data is references for figures.

note

Attribute providing additional notes about the data.

print_outputs()

Method which print outputs on terminal's screen.

ref

Attribute providing the full reference to the paper to be cited.

symb

Attribute symb (symbol) of the element, e.g., Fe.

nucleardatapy.setup_rad_ch.tables_rad_ch()

Return a list of the tables available in this toolkit for the charge radius and print them all on the prompt. These tables are the following ones: '2013-Angeli'.

Returns

The list of tables.

Return type

list[str].

2.6 SetupISGMR

class nucleardatapy.setup_ISGMR.SetupISGMR(table='2018-ISGMR-GARG')

Instantiate the object with microscopic results chosen by the toolkit practitioner. This choice is defined in the variable *table*.

The *table* can be chosen among the following ones: '2010-ISGMR-LI', '2018-ISGMR-GARG'.

Parameters

table (*str*, *optional*.) – Fix the name of *table*. Default value: '2018-ISGMR-GARG'.

Attributes:**A**

Attribute A (mass of the nucleus).

E_cen

Attribute energy centroid.

E_erra

Attribute list with + and - uncertainty

E_errm

Attribute (-) uncertainty in the energy centroid.

E_errp

Attribute (+) uncertainty in the energy centroid.

E_errs

Attribute symmetrised uncertainty (average between + and - uncertainty).

E_unit

Attribute energy unit.

Z

Attribute Z (charge of the nucleus).

label

Attribute providing the label the data is references for figures.

note

Attribute providing additional notes about the data.

print_outputs()

Method which print outputs on terminal's screen.

ref

Attribute providing the full reference to the paper to be citted.

table

Attribute table.

nucleardatapy.setup_ISGMR.tables_isgmr()

Return a list of tables available in this toolkit for the ISGMR energy and print them all on the prompt. These tables are the following ones: '2010-ISGMR-LI', '2018-ISGMR-GARG'.

Returns

The list of tables.

Return type

list[str].

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

n

- nucleardatapy, 4
- nucleardatapy.setup_EsymLsym, 11
- nucleardatapy.setup_ISGMR, 20
- nucleardatapy.setup_masses, 16
- nucleardatapy.setup_micro, 7
- nucleardatapy.setup_pheno, 8
- nucleardatapy.setup_rad_ch, 19

A

A (*nuclear_datapy.setup_ISGMR.SetupISGMR* attribute), 20
A (*nuclear_datapy.setup_masses.SetupMasses* attribute), 16
A(*nuclear_datapy.setup_rad_ch.SetupRadCh* attribute), 19

B

BE (*nuclear_datapy.setup_masses.SetupMasses* attribute), 16
BE_err (*nuclear_datapy.setup_masses.SetupMasses* attribute), 17

C

constraint (*nuclear_datapy.setup_EsymLsym.SetupEsymLsym* attribute), 16
constraints_EsymLsym() (in module *nuclear_datapy.setup_EsymLsym*), 16

D

drip() (*nuclear_datapy.setup_masses.SetupMasses* method), 17

E

E_cen (*nuclear_datapy.setup_ISGMR.SetupISGMR* attribute), 20
E_erra (*nuclear_datapy.setup_ISGMR.SetupISGMR* attribute), 21
E_errm (*nuclear_datapy.setup_ISGMR.SetupISGMR* attribute), 21
E_errp (*nuclear_datapy.setup_ISGMR.SetupISGMR* attribute), 21
E_errs (*nuclear_datapy.setup_ISGMR.SetupISGMR* attribute), 21
E_unit (*nuclear_datapy.setup_ISGMR.SetupISGMR* attribute), 21
Esym (*nuclear_datapy.setup_EsymLsym.SetupEsymLsym* attribute), 11
Esym_err (*nuclear_datapy.setup_EsymLsym.SetupEsymLsym* attribute), 11

H

HT (*nuclear_datapy.setup_masses.SetupMasses* attribute), 17

I

I (*nuclear_datapy.setup_masses.SetupMasses* attribute), 17
Interp (*nuclear_datapy.setup_masses.SetupMasses* attribute), 17

L

label (*nuclear_datapy.setup_EsymLsym.SetupEsymLsym* attribute), 16
label (*nuclear_datapy.setup_ISGMR.SetupISGMR* attribute), 21
label (*nuclear_datapy.setup_masses.SetupMasses* attribute), 18
label (*nuclear_datapy.setup_micro.SetupMicro* attribute), 7
label (*nuclear_datapy.setup_pheno.SetupPheno* attribute), 10
label (*nuclear_datapy.setup_rad_ch.SetupRadCh* attribute), 20
Lsym (*nuclear_datapy.setup_EsymLsym.SetupEsymLsym* attribute), 16
Lsym_err (*nuclear_datapy.setup_EsymLsym.SetupEsymLsym* attribute), 16

M

model (*nuclear_datapy.setup_micro.SetupMicro* attribute), 7
model (*nuclear_datapy.setup_pheno.SetupPheno* attribute), 10
models_micro() (in module *nuclear_datapy.setup_micro*), 8
models_pheno() (in module *nuclear_datapy.setup_pheno*), 11
module
 nuclear_datapy, 4
 nuclear_datapy.setup_EsymLsym, 11
 nuclear_datapy.setup_ISGMR, 20

nucleardatapy.setup_masses, 16
 nucleardatapy.setup_micro, 7
 nucleardatapy.setup_pheno, 8
 nucleardatapy.setup_rad_ch, 19

N

N (*nucleardatapy.setup_masses.SetupMasses* attribute), 17
 N (*nucleardatapy.setup_rad_ch.SetupRadCh* attribute), 19
 nbLine (*nucleardatapy.setup_masses.SetupMasses* attribute), 18
 nbNuc (*nucleardatapy.setup_masses.SetupMasses* attribute), 18
 nm_cs2 (*nucleardatapy.setup_pheno.SetupPheno* attribute), 10
 nm_den (*nucleardatapy.setup_micro.SetupMicro* attribute), 7
 nm_den (*nucleardatapy.setup_pheno.SetupPheno* attribute), 10
 nm_e2a (*nucleardatapy.setup_micro.SetupMicro* attribute), 7
 nm_e2a (*nucleardatapy.setup_pheno.SetupPheno* attribute), 10
 nm_e2a_err (*nucleardatapy.setup_micro.SetupMicro* attribute), 7
 nm_gap (*nucleardatapy.setup_micro.SetupMicro* attribute), 7
 nm_gap (*nucleardatapy.setup_pheno.SetupPheno* attribute), 10
 nm_kfn (*nucleardatapy.setup_micro.SetupMicro* attribute), 7
 nm_kfn (*nucleardatapy.setup_pheno.SetupPheno* attribute), 10
 nm_pre (*nucleardatapy.setup_micro.SetupMicro* attribute), 7
 nm_pre (*nucleardatapy.setup_pheno.SetupPheno* attribute), 10
 nm_pre_err (*nucleardatapy.setup_micro.SetupMicro* attribute), 7
 note (*nucleardatapy.setup_EsymLsym.SetupEsymLsym* attribute), 16
 note (*nucleardatapy.setup_ISGMR.SetupISGMR* attribute), 21
 note (*nucleardatapy.setup_masses.SetupMasses* attribute), 18
 note (*nucleardatapy.setup_micro.SetupMicro* attribute), 7
 note (*nucleardatapy.setup_pheno.SetupPheno* attribute), 10
 note (*nucleardatapy.setup_rad_ch.SetupRadCh* attribute), 20
 nucleardatapy
 module, 4
 nucleardatapy.setup_EsymLsym

 module, 11
 nucleardatapy.setup_ISGMR
 module, 20
 nucleardatapy.setup_masses
 module, 16
 nucleardatapy.setup_micro
 module, 7
 nucleardatapy.setup_pheno
 module, 8
 nucleardatapy.setup_rad_ch
 module, 19

P

param (*nucleardatapy.setup_pheno.SetupPheno* attribute), 10
 params_pheno() (in module *nucleardatapy.setup_pheno*), 11
 print_outputs() (*nucleardatapy.setup_EsymLsym.SetupEsymLsym* method), 16
 print_outputs() (*nucleardatapy.setup_ISGMR.SetupISGMR* method), 21
 print_outputs() (*nucleardatapy.setup_masses.SetupMasses* method), 18
 print_outputs() (*nucleardatapy.setup_micro.SetupMicro* method), 8
 print_outputs() (*nucleardatapy.setup_pheno.SetupPheno* method), 10
 print_outputs() (*nucleardatapy.setup_rad_ch.SetupRadCh* method), 20

R

R_ch (*nucleardatapy.setup_rad_ch.SetupRadCh* attribute), 20
 R_ch_err (*nucleardatapy.setup_rad_ch.SetupRadCh* attribute), 20
 R_unit (*nucleardatapy.setup_rad_ch.SetupRadCh* attribute), 20
 ref (*nucleardatapy.setup_EsymLsym.SetupEsymLsym* attribute), 16
 ref (*nucleardatapy.setup_ISGMR.SetupISGMR* attribute), 21
 ref (*nucleardatapy.setup_masses.SetupMasses* attribute), 18
 ref (*nucleardatapy.setup_micro.SetupMicro* attribute), 8
 ref (*nucleardatapy.setup_pheno.SetupPheno* attribute), 10
 ref (*nucleardatapy.setup_rad_ch.SetupRadCh* attribute), 20

S

`select()` (*nucleardatapy.setup_masses.SetupMasses* method), 18

`SetupEsymLsym` (class in *nucleardatapy.setup_EsymLsym*), 11

`SetupISGMR` (class in *nucleardatapy.setup_ISGMR*), 20

`SetupMasses` (class in *nucleardatapy.setup_masses*), 16

`SetupMicro` (class in *nucleardatapy.setup_micro*), 7

`SetupPheno` (class in *nucleardatapy.setup_pheno*), 8

`SetupRadCh` (class in *nucleardatapy.setup_rad_ch*), 19

`sm_cs2` (*nucleardatapy.setup_pheno.SetupPheno* attribute), 10

`sm_den` (*nucleardatapy.setup_micro.SetupMicro* attribute), 8

`sm_den` (*nucleardatapy.setup_pheno.SetupPheno* attribute), 10

`sm_e2a` (*nucleardatapy.setup_micro.SetupMicro* attribute), 8

`sm_e2a` (*nucleardatapy.setup_pheno.SetupPheno* attribute), 10

`sm_e2a_err` (*nucleardatapy.setup_micro.SetupMicro* attribute), 8

`sm_gap` (*nucleardatapy.setup_micro.SetupMicro* attribute), 8

`sm_gap` (*nucleardatapy.setup_pheno.SetupPheno* attribute), 10

`sm_kfn` (*nucleardatapy.setup_micro.SetupMicro* attribute), 8

`sm_kfn` (*nucleardatapy.setup_pheno.SetupPheno* attribute), 11

`sm_pre` (*nucleardatapy.setup_micro.SetupMicro* attribute), 8

`sm_pre` (*nucleardatapy.setup_pheno.SetupPheno* attribute), 11

`sm_pre_err` (*nucleardatapy.setup_micro.SetupMicro* attribute), 8

`stbl` (*nucleardatapy.setup_masses.SetupMasses* attribute), 18

`symb` (*nucleardatapy.setup_masses.SetupMasses* attribute), 18

`symb` (*nucleardatapy.setup_rad_ch.SetupRadCh* attribute), 20

T

`table` (*nucleardatapy.setup_ISGMR.SetupISGMR* attribute), 21

`tables_isgmr()` (in module *nucleardatapy.setup_ISGMR*), 21

`tables_masses()` (in module *nucleardatapy.setup_masses*), 18

`tables_rad_ch()` (in module *nucleardatapy.setup_rad_ch*), 20

V

`versions_masses()` (in module *nucleardatapy.setup_masses*), 18

Y

`year` (*nucleardatapy.setup_masses.SetupMasses* attribute), 18

Z

`Z` (*nucleardatapy.setup_ISGMR.SetupISGMR* attribute), 21

`Z` (*nucleardatapy.setup_masses.SetupMasses* attribute), 17

`Z` (*nucleardatapy.setup_rad_ch.SetupRadCh* attribute), 20

`Zmax` (*nucleardatapy.setup_masses.SetupMasses* attribute), 17