
nucleardatapy

Release 0.1

Jérôme Margueron, IRL NPA, USA

Jul 18, 2024

CONTENTS

| | | |
|----------|--------------------------------|-----------|
| 1 | Contents | 3 |
| 1.1 | Usage | 3 |
| 1.2 | API | 4 |
| 1.3 | Miscellaneous | 4 |
| 2 | Complement | 7 |
| 2.1 | SetupMicroMatter | 7 |
| 2.2 | SetupMicroMatterBand | 8 |
| 2.3 | SetupMicroLP | 13 |
| 2.4 | SetupPhenoMatter | 14 |
| 2.5 | SetupHICMatter | 17 |
| 2.6 | SetupCrust | 22 |
| 2.7 | SetupMassesExp | 24 |
| 2.8 | SetupMassesTheory | 28 |
| 2.9 | SetupRadCh | 29 |
| 2.10 | SetupISGMR | 31 |
| 2.11 | SetupEsymLsym | 33 |
| 3 | Indices and tables | 35 |
| | Python Module Index | 37 |
| | Index | 39 |

nucleardatapy (/in short nuda/) is a Python library for nuclear physicists facilitating the access to theoretical or experimental nuclear data. It is specifically designed for equation of state practitioners interested in the modeling of neutron stars, and it offers *simple* and *intuitive* APIs.

All data are provided with their reference, so when using these data in a scientific paper, reference to data should be provided explicitly. The reference to this toolkit could be given, but it should not mask the reference to data.

This python toolkit is designed to provide: 1) microscopic calculations in nuclear matter, 2) phenomenological predictions in nuclear matter, 3) experimental data for finite nuclei.

Check out the [Usage](#) section for further information, including how to *install* the project.

Note: This project is under active development.

CONTENTS

1.1 Usage

1.1.1 Installation

To use nucleardatapy, first download the .zip file from the git repository, or clone it in your local computer:

```
$ git clone https://github.com/jeromemargueron/nucleardatapy
```

If you have downloaded the .zip file, you can unzip it anywhere in your local computer:

```
$ unzip nucleardatapy.zip
```

Then, in all cases, you shall enter into the new folder */nucleardatapy*:

```
$ cd nucleardatapy
```

and launch the install script:

```
$ bash install.sh
```

This will copy the Python toolkit into `$HOME/mylib/` as well as a few samples. It will also give you the content of the global variable `NUCLEARDATAPY_TK`. If you edit `install.sh`, you can change the version (by default it is set to the latest one) as well as the destination folder (by default it is `$HOME/mylib`).

Finally, you will have to create the global variable `NUCLEARDATAPY_TK` with its right content. If you do not want to create it each time you open a new terminal, then you can define it in your `.profile` or `.zprofil` or `.bash` file as:

```
export NUCLEARDATAPY_TK=$HOME/mylib/nucleardatapy
```

Note: The exact path to write above is given at the end of the installation.

1.1.2 Use nucleardatapy

Go to the folder *mylib/nucleardatapy/samples/nucleardatapy_samples/* and try that:

```
$ python3 sample_SetupMicroMatter.py
```

1.1.3 Test nucleardatapy

A set of tests can be easily performed. They are stored in *tests/* folder.

```
$ bash run_tests.sh
```

1.1.4 Get started

How to obtain microscopic results for APR equation of state:

```
import os
nucleardatapy_tk = os.getenv('NUCLEARDATAPY_TK')
sys.path.insert(0, nucleardatapy_tk)

import nucleardatapy as nuda

mic = nuda.SetupMicroMatter( model = '1998-VAR-AM-APR' )

mic.print_outputs( )
```

1.2 API

nucleardatapy

This module provides microscopic, phenomenological and experimental data constraints.

1.2.1 nucleardatapy

This module provides microscopic, phenomenological and experimental data constraints.

1.3 Miscellaneous

1.3.1 Contributing

For the moment, contributions are based on co-optation among the team.

To make contribution easy, we all work in the *main* branch and we shall therefore remember to pull before working and pulling after, with a running version. For long developments, you can work in a local folder (in *mylib* for instance) and copy your contribution to the GitHub folder once you are sure it is functioning. So the final step should last less than 5 minutes, and can be safely done between a pull and before a push. Since we are not numerous, we hope that no one

will work in the same part of the code at the same time (i.e. between a pull and a push). It is probably the simpler way to proceed.

Once the toolkit is released, the rules to contribute will be changing. A team of developers should be defined and a generic email to contact them should be created. Here is a suggestion to contribute after the release.

This file describes how new contributors to the project can start contributing.

Two ways:

You can provide your data and interacting with one of our developer.

You can also join the developing team and extend the functionality of this toolkit.

Provide your data:

Please contact the developer team directly by shooting an email to TBC.

Then you can interact directly with one of our developer and provide your data. You will not be able to push your data to the repository, but an updated version of the toolkit will contain your new data.

Join the team:

Please contact the developer team directly by shooting an email to TBC. Explain the reason why you wish to join the team and if you have ideas about extending the functionality of the toolkit.

Once in the team, a branch will be dedicated to your contribution. You could show it during our virtual meetings, and your contribution will be merged to the new version of the toolkit.

1.3.2 License

TBC.

1.3.3 Report issues

For the current version, we report issues chatting among us. Once this toolkit is released, we should setup a way that users could contact us and report issues or difficulties in installing or using the toolkit.

1.3.4 Thanks

A special thanks to all contributors who accepted to share their results in this toolkit.

COMPLEMENT

2.1 SetupMicroMatter

class nucleardatapy.setup_micro_matter.SetupMicroMatter(*model*='1998-VAR-AM-APR')

Instantiate the object with microscopic results choosen by the toolkit practitioner.

This choice is defined in *model*, which can chosen among the following choices: '1981-VAR-AM-FP', '1998-VAR-AM-APR', '2006-BHF-AM*', '2008-BCS-NM', '2008-AFDMC-NM', '2008-QMC-NM-swave', '2010-QMC-NM-AV4', '2009-DLQMC-NM', '2010-MBPT-NM', '2012-AFDMC-NM-1', '2012-AFDMC-NM-2', '2012-AFDMC-NM-3', '2012-AFDMC-NM-4', '2012-AFDMC-NM-5', '2012-AFDMC-NM-6', '2012-AFDMC-NM-7', '2013-QMC-NM', '2014-AFQMC-NM', '2016-QMC-NM', '2016-MBPT-AM', '2018-QMC-NM', '2019-MBPT-AM-L59', '2019-MBPT-AM-L69', '2020-MBPT-AM', '2022-AFDMC-NM', '2024-NLEFT-AM', '2024-BHF-AM-2BF-Av8p', '2024-BHF-AM-2BF-Av18', '2024-BHF-AM-2BF-BONN', '2024-BHF-AM-2BF-CDBONN', '2024-BHF-AM-2BF-NSC97a', '2024-BHF-AM-2BF-NSC97b', '2024-BHF-AM-2BF-NSC97c', '2024-BHF-AM-2BF-NSC97d', '2024-BHF-AM-2BF-NSC97e', '2024-BHF-AM-2BF-NSC97f', '2024-BHF-AM-2BF-SSCV14', '2024-BHF-AM-23BF-Av8p', '2024-BHF-AM-23BF-Av18', '2024-BHF-AM-23BF-BONN', '2024-BHF-AM-23BF-CDBONN', '2024-BHF-AM-23BF-NSC97a', '2024-BHF-AM-23BF-NSC97b', '2024-BHF-AM-23BF-NSC97c', '2024-BHF-AM-23BF-NSC97d', '2024-BHF-AM-23BF-NSC97e', '2024-BHF-AM-23BF-NSC97f', '2024-BHF-AM-23BF-SSCV14'

Parameters

model (*str*, *optional*.) – Fix the name of model. Default value: '1998-VAR-AM-APR'.

Attributes:

init_self()

Initialize variables in self.

model

Attribute model.

print_outputs()

Method which print outputs on terminal's screen.

nucleardatapy.setup_micro_matter.models_micro_matter()

Return a list with the name of the models available in this toolkit and print them all on the prompt. These models are the following ones: '1981-VAR-AM-FP', '1998-VAR-AM-APR', '2006-BHF-AM*', '2008-BCS-NM', '2008-AFDMC-NM', '2012-AFDMC-NM-1', '2012-AFDMC-NM-2', '2012-AFDMC-NM-3', '2012-AFDMC-NM-4', '2012-AFDMC-NM-5', '2012-AFDMC-NM-6', '2012-AFDMC-NM-7', '2008-QMC-NM-swave', '2010-QMC-NM-AV4', '2009-DLQMC-NM', '2010-MBPT-NM', '2013-QMC-NM', '2014-AFQMC-NM', '2016-QMC-NM', '2016-MBPT-AM', '2018-QMC-NM', '2019-MBPT-AM-L59', '2019-MBPT-AM-L69', '2020-MBPT-AM', '2022-AFDMC-NM', '2024-NLEFT-AM', '2024-BHF-AM-2BF-Av8p',

'2024-BHF-AM-2BF-Av18', '2024-BHF-AM-2BF-BONN', '2024-BHF-AM-2BF-CDBONN', '2024-BHF-AM-2BF-NSC97a', '2024-BHF-AM-2BF-NSC97b', '2024-BHF-AM-2BF-NSC97c', '2024-BHF-AM-2BF-NSC97d', '2024-BHF-AM-2BF-NSC97e', '2024-BHF-AM-2BF-NSC97f', '2024-BHF-AM-2BF-SSCV14', '2024-BHF-AM-23BF-Av8p', '2024-BHF-AM-23BF-Av18', '2024-BHF-AM-23BF-BONN', '2024-BHF-AM-23BF-CDBONN', '2024-BHF-AM-23BF-NSC97a', '2024-BHF-AM-23BF-NSC97b', '2024-BHF-AM-23BF-NSC97c', '2024-BHF-AM-23BF-NSC97d', '2024-BHF-AM-23BF-NSC97e', '2024-BHF-AM-23BF-NSC97f', '2024-BHF-AM-23BF-SSCV14', '2024-BHF-AM-23BFmicro-Av18', '2024-BHF-AM-23BFmicro-BONNB', '2024-BHF-AM-23BFmicro-NSC93':return: The list of models. :rtype: list[str].

Here are a set of figures which are produced with the Python sample: /sample/nucleardatapy_plots/plot_setupMicro.py




Fig. 1: This figure shows the energy in neutron matter (NM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the variational models available in the nucleardatapy toolkit.

2.2 SetupMicroMatterBand

```
class nucleardatapy.setup_micro_matter_band.SetupMicroMatterBand(models=['2016-MBPT-AM'],
                                                                    nden=10, ne=200, den=None,
                                                                    matter='NM', e2a_min=-20.0,
                                                                    e2a_max=50.0)
```

Instantiate the object with statistical distributions averaging over the models given as inputs and in NM.

Parameters

- **models** (*list.*) – The models given as inputs.
- **nden** (*int, optional.*) – number of density points.
- **ne** (*int, optional.*) – number of points along the energy axis.
- **den** (*None or numpy array, optional.*) – if not None (default), impose the densities.
- **matter** (*str, optional.*) – can be 'NM' (default), 'SM' or 'ESYM'.




Fig. 2: This figure shows the energy in neutron matter (NM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the AFDMC models available in the nucleardatapy toolkit.




Fig. 3: This figure shows the energy in neutron matter (NM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the BHF models available in the nucleardatapy toolkit.




Fig. 4: This figure shows the energy in neutron matter (NM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the QMC models available in the nucleardatapy toolkit.




Fig. 5: This figure shows the energy in neutron matter (NM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the MBPT models available in the nucleardatapy toolkit.




Fig. 6: This figure shows the pairing gap in neutron matter (NM) over the Fermi energy (top) and the pairing gap (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the models available in the nucleardatapy toolkit.

Attributes:

den

Attribute a set of density points.

init_self()

Initialize variables in self.

matter

Attribute matter str.

models

Attribute model.

nden

Attribute number of points in density.

print_outputs()

Method which print outputs on terminal's screen.




Fig. 7: Uncertainty band in NM obtained from the analysis of different predictions: MBPT-2016, QMC-2016 and MBPT-2020.




Fig. 8: Uncertainty band in SM obtained from the analysis of different predictions: MBPT-2016 and MBPT-2020.




Fig. 9: Uncertainty band for the symmetry energy obtained from the analysis of different predictions: MBPT-2016 and MBPT-2020.

2.3 SetupMicroLP

class nucleardatapy.setup_micro_LP.**SetupMicroLP**(*model*='1994-BHF-SM-LP-AV14-GAP')

Instantiate the object with Landau parameters from microscopic calculations chosen by the toolkit practitioner.

This choice is defined in *model*, which can be chosen among the following choices: '1994-BHF-SM-LP-AV14-GAP', '1994-BHF-SM-LP-AV14-CONT', '1994-BHF-SM-LP-REID-GAP', '1994-BHF-SM-LP-REID-CONT', '1994-BHF-SM-LP-AV14-CONT-0.7'.

Parameters

model (*str*, *optional*.) – Fix the name of model. Default value: '1994-BHF-LP'.

Attributes:

init_self()

Initialize variables in self.

model

Attribute model.

print_outputs()

Method which print outputs on terminal's screen.

nucleardatapy.setup_micro_LP.**models_micro_LP()**

Return a list with the name of the models available in this toolkit and print them all on the prompt. These models are the following ones: '1994-BHF-SM-LP-AV14-GAP', '1994-BHF-SM-LP-AV14-CONT', '1994-BHF-SM-LP-REID-GAP', '1994-BHF-SM-LP-REID-CONT', '1994-BHF-SM-LP-AV14-CONT-0.7'.

Returns

The list of models.

Return type

list[str].

Here are a set of figures which are produced with the Python sample: /sample/nucleardatapy_plots/plot_setupLP.py




Fig. 10: This figure shows the $L=0$ Landau parameters in SM for different NN interactions obtained from BHF calculations.

2.4 SetupPhenoMatter

class nucleardatapy.setup_pheno_matter.**SetupPhenoMatter**(*model*='Skyrme', *param*='SLY5')

Instantiate the object with results based on phenomenological interactions and chosen by the toolkit practitioner. This choice is defined in the variables *model* and *param*.

If *models* == 'skyrme', *param* can be: 'BSK14', 'BSK16', 'BSK17', 'BSK27', 'F-', 'F+', 'F0', 'FPL', 'LNS', 'LNS1', 'LNS5', 'NRAPR', 'RATP', 'SAMI', 'SGII', 'SIII', 'SKGSIGMA', 'SKI2', 'SKI4', 'SKMP', 'SKMS', 'SKO', 'SKOP', 'SKP', 'SKRSIGMA', 'SKX', 'Skz2', 'SLY4', 'SLY5', 'SLY230A', 'SLY230B', 'SV', 'T6', 'T44', 'UNEDF0', 'UNEDF1'.

If *models* == 'NLRH', *param* can be: 'NL-SH', 'NL3', 'NL3II', 'PK1', 'PK1R', 'TM1'.

If *models* == 'DDRH', *param* can be: 'DDME1', 'DDME2', 'DDMEd', 'PKDD', 'TW99'.

If *models* == 'DDRHF', *param* can be: 'PKA1', 'PKO1', 'PKO2', 'PKO3'.

Parameters

- **model** (*str*, *optional*.) – Fix the name of model: 'Skyrme', 'NLRH', 'DDRH', 'DDRHF'. Default value: 'Skyrme'.
- **param** (*str*, *optional*.) – Fix the parameterization associated to model. Default value: 'SLY5'.

Attributes:




Fig. 11: This figure shows the L=1 Landau parameters in SM for different NN interactions obtained from BHF calculations.

Esat

Attribute the NEP.

esym_den

Attribute the density for the symmetry energy.

esym_e2a

Attribute the symmetry energy.

esym_kf

Attribute the Fermi momentum for the symmetry energy.

label

Attribute providing the label the data is references for figures.

model

Attribute model.

nm_cs2

Attribute the neutron matter sound speed $(c_s/c)^2$.

nm_den

Attribute the neutron matter density.

nm_e2a

Attribute the neutron matter energy per particle.

nm_gap

Attribute the neutron matter pairing gap.

nm_kfn

Attribute the neutron matter neutron Fermi momentum.

nm_pre

Attribute the neutron matter pressure.

note

Attribute providing additional notes about the data.

param

Attribute param.

print_outputs()

Method which print outputs on terminal's screen.

ref

Attribute providing the full reference to the paper to be cited.

sm_cs2

Attribute the symmetric matter sound speed $(c_s/c)^2$.

sm_den

Attribute the symmetric matter density.

sm_e2a

Attribute the symmetric matter energy per particle.

sm_gap

Attribute the symmetric matter pairing gap.

sm_kf

Attribute the symmetric matter Fermi momentum.

sm_kfn

Attribute the symmetric matter neutron Fermi momentum.

sm_pre

Attribute the symmetric matter pressure.

nucleardatapy.setup_pheno_matter.models_pheno_matter()

Return a list of models available in this toolkit and print them all on the prompt.

Returns

The list of models with can be 'Skyrme', 'NLRH', 'DDRH', 'DDRHF'.

Return type

list[str].

nucleardatapy.setup_pheno_matter.params_pheno_matter(model)

Return a list with the parameterizations available in this toolkit for a given model and print them all on the prompt.

Parameters

model (*str.*) – The type of model for which there are parametrizations. They should be chosen among the following options: 'Skyrme', 'NLRH', 'DDRH', 'DDRHF'.

Returns

The list of parametrizations. If *models* == 'skyrme': 'BSK14', 'BSK16', 'BSK17', 'BSK27', 'F-', 'F+', 'F0', 'FPL', 'LNS', 'LNS1', 'LNS5', 'NRAPR', 'RATP', 'SAMI', 'SGII', 'SIII', 'SKGSIGMA', 'SKI2', 'SKI4', 'SKMP', 'SKMS', 'SKO', 'SKOP', 'SKP', 'SKRSIGMA', 'SKX', 'Skz2', 'SLY4', 'SLY5', 'SLY230A', 'SLY230B', 'SV', 'T6', 'T44', 'UNEDF0', 'UNEDF1'. If *models* == 'NLRH': 'NL-SH', 'NL3', 'NL3II', 'PK1', 'PK1R', 'TM1'. If *models* == 'DDRH': 'DDME1', 'DDME2', 'DDMed', 'PKDD', 'TW99'. If *models* == 'DDRHF': 'PKA1', 'PKO1', 'PKO2', 'PKO3'.

Return type

list[str].

Here are a set of figures which are produced with the Python sample: `/sample/nucleardatapy_plots/plot_setupPhenoMatter.py`




Fig. 12: This figure shows the energy in neutron matter (NM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the complete list of phenomenological models based on non-linear meson(s) relativistic Hartree (NLRH) approach available in the nucleardatapy toolkit.

2.5 SetupHICMatter

class nucleardatapy.setup_hic_matter.**SetupHICMatter**(*constraint*='DLL-2002')

Instantiate the constraints on the EOS from HIC.

This choice is defined in the variable *constraint*.

constraint can chosen among the following ones: ['DLL-2002', 'FOPI-2016'].

Parameters

constraint (*str*, *optional*.) – Fix the name of *constraint*. Default value: 'DLL-2002'.

Attributes:

init_self()

Initialize variables in self.

print_outputs()

Method which print outputs on terminal's screen.

nucleardatapy.setup_hic_matter.**constraints_HIC_matter()**

Return a list of the HIC constraints available in this toolkit for the equation of state in SM and NM and print them all on the prompt. These constraints are the following ones: ['DLL-2002', 'FOPI-2016'].




Fig. 13: This figure shows the energy in symmetric matter (SM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the complete list of phenomenological models based on non-linear meson(s) relativistic Hartree (NLRH) approach available in the nucleardatapy toolkit.




Fig. 14: This figure shows the energy in neutron matter (NM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the complete list of phenomenological models based on density-dependent relativistic Hartree (DDRH) approach available in the nucleardatapy toolkit.




Fig. 15: This figure shows the energy in symmetric matter (SM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the complete list of phenomenological models based on density-dependent relativistic Hartree (DDRH) approach available in the nucleardatapy toolkit.




Fig. 16: This figure shows the energy in neutron matter (NM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the complete list of phenomenological models based on density-dependent relativistic Hartree-Fock (DDRHF) approach available in the nucleardatapy toolkit.




Fig. 17: This figure shows the energy in symmetric matter (SM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the complete list of phenomenological models based on density-dependent relativistic Hartree-Fock (DDRHF) approach available in the nucleardatapy toolkit.




Fig. 18: This figure shows the energy in neutron matter (NM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the complete list of phenomenological models based on the standard Skyrme interaction available in the nucleardatapy toolkit.




Fig. 19: This figure shows the energy in symmetric matter (SM) over the free Fermi gas energy (top) and the energy per particle (bottom) as function of the density (left) and the neutron Fermi momentum (right) for the complete list of phenomenological models based on the standard Skyrme interaction available in the nucleardatapy toolkit.




Fig. 20: Distribution of NEP for phenomenological models available in the nucleardatapy toolkit.

Returns

The list of constraints.

Return type

list[str].




Fig. 21: HIC Experimental constraints for the energy per particle (left) and pressure (right) in SM as a function of the particle density for different analyses available in the *nuda* toolkit.

2.6 SetupCrust

class nucleardatapy.setup_crust.SetupCrust(modcrust='1973-Negele-Vautherin')

Instantiate the properties of the crust for the existing models.

This choice is defined in the variable *crust*.

crust can chosen among the following ones: 'Negele-Vautherin-1973'.

Parameters

crust (str, optional.) – Fix the name of *crust*. Default value: 'Negele-Vautherin-1973'.

Attributes:**A**

Attribute A (mass of the nucleus).

N

Attribute N (total number of neutrons of the WS cell).

N_bound

Attribute N_bound (number of bound neutrons).

N_g

Attribute N_g (number of neutrons in the gas).

RWS

Attribute the radius of the WS cell (in fm).

Z

Attribute Z (charge of the nucleus).

den

Attribute the density of the system (in fm⁻³).

den_cgs

Attribute the density of the system (in cm⁻³).

den_g

Attribute the approximate density of neutron in the gas (in fm⁻³).

e2a_int

Attribute the internal energy (in MeV).

e2a_int2

Attribute the energy minus the neutron mass (in MeV).

e2a_int_g

Attribute the internal energy of the gas component (in MeV).

e2a_rm

Attribute the rest mass energy (in MeV).

mu_n

Attribute the neutron chemical potential (in MeV).

mu_p

Attribute the proton chemical potential (in MeV).

print_outputs()

Method which print outputs on terminal's screen.

xn

Attribute the fraction of neutrons.

xn_bound

Attribute the fraction of bound neutrons.

xp

Attribute the fraction of protons.

xpn_bound

Attribute the approximate ratio of proton to neutron in the nucleus.

nucleardatapy.setup_crust.models_crust()

Return a list of the tables available in this toolkit for the experimental masses and print them all on the prompt. These tables are the following ones: 'Negele-Vautheron-1973'.

Returns

The list of tables.

Return type

list[str].




Fig. 22: Properties of the crust as given by the models available in the nuda toolkit.

2.7 SetupMassesExp

class nucleardatapy.setup_masses_exp.**SetupMassesExp**(*table*='AME', *version*='2020')

Instantiate the experimental nuclear masses from AME mass table.

This choice is defined in the variables *table* and *version*.

table can chosen among the following ones: 'AME'.

version can be chosen among the following choices: '2020', '2016', '2012'.

Parameters

- **table** (*str*, *optional*.) – Fix the name of *table*. Default value: 'AME'.
- **version** (*str*, *optional*.) – Fix the name of *version*. Default value: '2020'.

Attributes:

Zmax

maximum charge of nuclei present in the table.

Type

Attribute Zmax

dist_nbNuc

attribute number of nuclei discovered per year

dist_year

attribute distribution of years

drip(Zmax=95)

Method which find the drip-line nuclei (on the two sides).

Parameters

Zmax (*int, optional. Default: 95.*) – Fix the maximum charge for the search of the drip line.

Attributes:**flagI**

Attribute I.

flagInterp

Attribute Interp (interpolation). Interp='y' is the nucleus has not been measured but is in the table based on interpolation expressions. otherwise Interp = 'n' for nuclei produced in laboratory and measured.

label

Attribute providing the label the data is references for figures.

nbLine

Attribute with the number of line in the file.

nbNuc

Attribute with the number of nuclei read in the file.

note

Attribute providing additional notes about the data.

nucA

Attribute A (mass of the nucleus).

nucBE

Attribute BE (Binding Energy) of the nucleus.

nucBE_err

Attribute uncertainty in the BE (Binding Energy) of the nucleus.

nucHT

Attribute HT (half-Time) of the nucleus.

nucN

Attribute N (number of neutrons of the nucleus).

nucStbl

Attribute stbl. stbl='y' if the nucleus is stable (according to the table). Otherwise stbl = 'n'.

nucSymb

Attribute symb (symbol) of the element, e.g., Fe.

nucYear

Attribute year of the discovery of the nucleus.

nucZ

Attribute Z (charge of the nucleus).

print_outputs()

Method which print outputs on terminal's screen.

ref

Attribute providing the full reference to the paper to be cited.

```
select(Amin=0, Zmin=0, interp='n', state='gs', nucleus='unstable', every=1)
```

Method which select some nuclei from the table according to some criteria.

Parameters

- **interp** (*str*, optional. Default = 'n'.) – If interp='n', exclude the interpolated nuclei from the selected ones. If interp='y' consider them in the table, in addition to the others.
- **state** (*str*, optional. Default 'gs'.) – select the kind of state. If state='gs', select nuclei measured in their ground state.
- **nucleus** (*str*, optional. Default 'unstable'.) – 'unstable'.

It can be set to 'stable', 'longlive' (with $LT > 10$ min), 'shortlive' (with $10\text{min} > LT > 1$ ns), 'veryshortlive' (with $LT < 1$ ns) :param every: consider only 1 out of *every* nuclei in the table. :type every: int, optional. Default every = 1.

Attributes:

```
select_year(year_min=1940, year_max=1960, state='gs')
```

Method which select some nuclei from the table according to the discovery year.

Parameters

- **year_min** –
- **year_max** –
- **state** (*str*, optional. Default 'gs'.) – select the kind of state. If state='gs', select nuclei measured in their ground state.

Attributes:

```
nucleardatapy.setup_masses_exp.tables_masses_exp()
```

Return a list of the tables available in this toolkit for the experimental masses and print them all on the prompt. These tables are the following ones: 'AME'.

Returns

The list of tables.

Return type

list[str].

```
nucleardatapy.setup_masses_exp.versions_masses_exp(table)
```

Return a list of versions of tables available in this toolkit for a given model and print them all on the prompt.

Parameters

table (*str*.) – The table for which there are different versions.

Returns

The list of versions. If table == 'AME': '2020', '2016', '2012'.

Return type

list[str].

Here are a set of figures which are produced with the Python sample: `/sample/nucleardatapy_plots/plot_setupMassesExp.py`




Fig. 23: The nuclear chart based on AME 2020 table. The different colors correspond to the different measured half-times of nuclei.




Fig. 24: Histogram showing the distribution of nuclei per discovery year, since the first one discovered in 1851.

2.8 SetupMassesTheory

class nucleardatapy.setup_masses_theory.SetupMassesTheory(*table*='1995-DZ')

Instantiate the theory nuclear masses.

This choice is defined in the variable *table*.

table can chosen among the following ones: ['1988-MJ', '1995-DZ', '1995-ETFSI', '1995-FRDM', '2005-KTUY', '2007-HFB14', '2010-WS3', '2010-HFB21', '2011-WS3', '2013-HFB26']

Parameters

table (*str*, *optional.*) – Fix the name of *table*. Default value: '1995-DZ'.

Attributes:

diff(*table*, *Zref*=50)

Method calculates the difference between a given mass model and *table_ref*.

Parameters

- **table** (*str.*) – Fix the table to analyze.
- **Zref** (*int*, *optional.* *Default:* 50.) – Fix the isotopic chain to study.

Attributes:

diff_exp(*table_exp*, *version_exp*, *Zref*=50)

Method calculates the difference between a given experimental mass (identified by *table_exp* and *version_exp*) and *table_ref*.

Parameters

- **table** (*str.*) – Fix the table to analyze.
- **Zref** (*int*, *optional.* *Default:* 50.) – Fix the isotopic chain to study.

Attributes:

drip(*Zmax*=95)

Method which find the drip-line nuclei (on the two sides).

Parameters

Zmax (*int*, *optional.* *Default:* 95.) – Fix the maximum charge for the search of the drip line.

Attributes:

init_self()

Initialize variables in self.

print_outputs()

Method which print outputs on terminal's screen.

nucleardatapy.setup_masses_theory.tables_masses_theory()

Return a list of the tables available in this toolkit for the masses predicted by theoretical approaches and print them all on the prompt. These tables are the following ones: ['1988-MJ', '1995-DZ', '1995-ETFSI', '1995-FRDM', '2005-KTUY', '2007-HFB14', '2010-WS3', '2010-HFB21', '2011-WS3', '2013-HFB26']

Returns

The list of tables.

Return type

list[str].

Here are a set of figures which are produced with the Python sample: `/sample/nucleardatapy_plots/plot_setupMassesTheory.py`




Fig. 25: Differences between binding energies predicted by different models with respect to the one predicted by Duflo-Zuker for $Z = 20$.

2.9 SetupRadCh

class `nucleardatapy.setup_rad_ch.SetupRadCh`(*table*='2013-Angeli')

Instantiate the object with charge radii choosen from a table.

This choice is defined in the variable *table*.

The tables can chosen among the following ones: '2013-Angeli'.

Parameters

table (*str*, *optional.*) – Fix the name of *table*. Default value: '2013-Angeli'.

Attributes:

R_unit

Attribute radius unit.

RadCh_isotopes(*Zref*=50)

This method provide a list if radii for an isotopic chain defined by *Zref*.

label

Attribute providing the label the data is references for figures.

note

Attribute providing additional notes about the data.




Fig. 26: Differences between binding energies predicted by different models with respect to the one predicted by Duflo-Zuker for $Z = 50$.

nucA

Attribute A (mass of the nucleus).

nucN

Attribute N (number of neutrons of the nucleus).

nucRch

Attribute R_ch (charge radius) in fm.

nucRch_err

Attribute uncertainty in R_ch (charge radius) in fm.

nucSymb

Attribute symb (symbol) of the element, e.g., Fe.

nucZ

Attribute Z (charge of the nucleus).

print_outputs()

Method which print outputs on terminal's screen.

ref

Attribute providing the full reference to the paper to be cited.

nucleardatapy.setup_rad_ch.tables_rad_ch()

Return a list of the tables available in this toolkit for the charge radius and print them all on the prompt. These tables are the following ones: '2013-Angeli'.

Returns

The list of tables.

Return type

list[str].




Fig. 27: Charge radii for Zn, Sn, and Pb isotopes and for the models available in the nuda toolkit.

2.10 SetupISGMR

class `nucleardatapy.setup_ISGMR.SetupISGMR`(*table*='2018-ISGMR-GARG')

Instantiate the object with microscopic results choosen by the toolkit practitioner. This choice is defined in the variable *table*.

The *table* can choosen among the following ones: '2010-ISGMR-LI', '2018-ISGMR-GARG'.

Parameters

table (*str*, *optional*.) – Fix the name of *table*. Default value: '2018-ISGMR-GARG', '2018-ISGMR-GARG-LATEX'.

Attributes:

E_unit

Attribute energy unit.

label

Attribute providing the label the data is references for figures.

note

Attribute providing additional notes about the data.

nucA

Attribute A (mass of the nucleus).

nucM12Mm1_cent

Attribute energy centroid.

nucM12Mm1_errm

Attribute (-) uncertainty in the energy centroid.

nucM12Mm1_errp

Attribute (+) uncertainty in the energy centroid.

nucSymbol

Attribute the symbol of the element.

nucZ

Attribute Z (charge of the nucleus).

print_outputs()

Method which print outputs on terminal's screen.

ref

Attribute providing the full reference to the paper to be citted.

table

Attribute table.

nucleardatapy.setup_ISGMR.tables_isgmr()

Return a list of tables available in this toolkit for the ISGMR energy and print them all on the prompt. These tables are the following ones: '2010-ISGMR-LI', '2018-ISGMR-GARG', '2018-ISGMR-GARG-LATEX'.

Returns

The list of tables.

Return type

list[str].




Fig. 28: ISGMR energies available in the nucleardatapy toolkit.

2.11 SetupEsymLsym

class nucleardatapy.setup_EsymLsym.**SetupEsymLsym**(*constraint*='2014-IAS')

Instantiate the values of Esym and Lsym from the constraint.

The name of the constraint to be chosen in the following list: '2009-HIC', '2010-RNP', '2012-FRDM', '2013-NS', '2014-IAS', '2014-IAS+RNP', '2015-POL-208PB', '2015-POL-120SN', '2015-POL-68NI', '2017-UG', '2021-PREXII-Reed', '2021-PREXII-Reinhard', '2021-PREXII+CREX-Zhang'.

Parameters

constraint (*str*, *optional*.) – Fix the name of *constraint*. Default value: '2014-IAS'.

Attributes:

Esym

Attribute Esym.

Esym_err

Attribute with uncertainty in Esym.

Esym_max

Attribute max of Esym.

Esym_min

Attribute min of Esym.

Lsym

Attribute Lsym.

Lsym_err

Attribute with uncertainty in Lsym.

Lsym_max

Attribute max of Lsym.

Lsym_min

Attribute min of Lsym.

alpha

Attribute the plot alpha

constraint

Attribute constraint.

label

Attribute providing the label the data is references for figures.

note

Attribute providing additional notes about the constraint.

print_outputs()

Method which print outputs on terminal's screen.

ref

Attribute providing the full reference to the paper to be cited.

`nucleardatapy.setup_EsymLsym.constraints_EsymLsym()`

Return a list of constraints available in this toolkit in the following list: '2009-HIC', '2010-RNP', '2012-FRDM', '2013-NS', '2014-IAS', '2014-IAS+RNP', '2015-POL-208PB', '2015-POL-120SN', '2015-POL-68NI', '2017-UG', '2021-PREXII-Reed', '2021-PREXII-Reinhard', '2023-PREXII+CREX-Zhang'; and print them all on the prompt.

Returns

The list of constraints.

Return type

list[str].

Here are a set of figures which are produced with the Python sample: `/sample/nucleardatapy_plots/plot_setupEsymLsym.py`




Fig. 29: This figure shows the $E_{\text{sym},2}$ versus $L_{\text{sym},2}$ correlation for the different constraints available in the nucleardatapy toolkit.

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

n

- nucleardatapy, 4
- nucleardatapy.setup_crust, 22
- nucleardatapy.setup_EsymLsym, 33
- nucleardatapy.setup_hic_matter, 17
- nucleardatapy.setup_ISGMR, 31
- nucleardatapy.setup_masses_exp, 24
- nucleardatapy.setup_masses_theory, 28
- nucleardatapy.setup_micro_LP, 13
- nucleardatapy.setup_micro_matter, 7
- nucleardatapy.setup_micro_matter_band, 8
- nucleardatapy.setup_pheno_matter, 14
- nucleardatapy.setup_rad_ch, 29

A

`A` (*nucleardatapy.setup_crust.SetupCrust* attribute), 22
`alpha` (*nucleardatapy.setup_EsymLsym.SetupEsymLsym* attribute), 33

C

`constraint` (*nucleardatapy.setup_EsymLsym.SetupEsymLsym* attribute), 33
`constraints_EsymLsym()` (in module *nucleardatapy.setup_EsymLsym*), 33
`constraints_HIC_matter()` (in module *nucleardatapy.setup_hic_matter*), 17

D

`den` (*nucleardatapy.setup_crust.SetupCrust* attribute), 23
`den` (*nucleardatapy.setup_micro_matter_band.SetupMicroMatterBand* attribute), 11
`den_cgs` (*nucleardatapy.setup_crust.SetupCrust* attribute), 23
`den_g` (*nucleardatapy.setup_crust.SetupCrust* attribute), 23
`diff()` (*nucleardatapy.setup_masses_theory.SetupMassesTheory* method), 28
`diff_exp()` (*nucleardatapy.setup_masses_theory.SetupMassesTheory* method), 28
`dist_nbNuc` (*nucleardatapy.setup_masses_exp.SetupMassesExp* attribute), 24
`dist_year` (*nucleardatapy.setup_masses_exp.SetupMassesExp* attribute), 24
`drip()` (*nucleardatapy.setup_masses_exp.SetupMassesExp* method), 24
`drip()` (*nucleardatapy.setup_masses_theory.SetupMassesTheory* method), 28

E

`e2a_int` (*nucleardatapy.setup_crust.SetupCrust* attribute), 23

`e2a_int2` (*nucleardatapy.setup_crust.SetupCrust* attribute), 23
`e2a_int_g` (*nucleardatapy.setup_crust.SetupCrust* attribute), 23
`e2a_rm` (*nucleardatapy.setup_crust.SetupCrust* attribute), 23
`E_unit` (*nucleardatapy.setup_ISGMR.SetupISGMR* attribute), 31
`Esat` (*nucleardatapy.setup_pheno_matter.SetupPhenoMatter* attribute), 14
`Esym` (*nucleardatapy.setup_EsymLsym.SetupEsymLsym* attribute), 33
`esym_den` (*nucleardatapy.setup_pheno_matter.SetupPhenoMatter* attribute), 15
`esym_e2a` (*nucleardatapy.setup_pheno_matter.SetupPhenoMatter* attribute), 15
`Esym_err` (*nucleardatapy.setup_EsymLsym.SetupEsymLsym* attribute), 33
`esym_kf` (*nucleardatapy.setup_pheno_matter.SetupPhenoMatter* attribute), 15
`Esym_max` (*nucleardatapy.setup_EsymLsym.SetupEsymLsym* attribute), 33
`Esym_min` (*nucleardatapy.setup_EsymLsym.SetupEsymLsym* attribute), 33

F

`flagI` (*nucleardatapy.setup_masses_exp.SetupMassesExp* attribute), 25
`flagInterp` (*nucleardatapy.setup_masses_exp.SetupMassesExp* attribute), 25

I

`init_self()` (*nucleardatapy.setup_hic_matter.SetupHICMatter* method), 17

`init_self()` (*nucleardatapy.setup_masses_theory.SetupMassesTheory* method), 28
`init_self()` (*nucleardatapy.setup_micro_LP.SetupMicroLP* method), 13
`init_self()` (*nucleardatapy.setup_micro_matter.SetupMicroMatter* method), 7
`init_self()` (*nucleardatapy.setup_micro_matter_band.SetupMicroMatterBand* method), 11

L

`label` (*nucleardatapy.setup_EsymLsym.SetupEsymLsym* attribute), 33
`label` (*nucleardatapy.setup_ISGMR.SetupISGMR* attribute), 31
`label` (*nucleardatapy.setup_masses_exp.SetupMassesExp* attribute), 25
`label` (*nucleardatapy.setup_pheno_matter.SetupPhenoMatter* attribute), 15
`label` (*nucleardatapy.setup_rad_ch.SetupRadCh* attribute), 29
`Lsym` (*nucleardatapy.setup_EsymLsym.SetupEsymLsym* attribute), 33
`Lsym_err` (*nucleardatapy.setup_EsymLsym.SetupEsymLsym* attribute), 33
`Lsym_max` (*nucleardatapy.setup_EsymLsym.SetupEsymLsym* attribute), 33
`Lsym_min` (*nucleardatapy.setup_EsymLsym.SetupEsymLsym* attribute), 33

M

`matter` (*nucleardatapy.setup_micro_matter_band.SetupMicroMatterBand* attribute), 11
`model` (*nucleardatapy.setup_micro_LP.SetupMicroLP* attribute), 13
`model` (*nucleardatapy.setup_micro_matter.SetupMicroMatter* attribute), 7
`model` (*nucleardatapy.setup_pheno_matter.SetupPhenoMatter* attribute), 15
`models` (*nucleardatapy.setup_micro_matter_band.SetupMicroMatterBand* attribute), 11
`models_crust()` (in module *nucleardatapy.setup_crust*), 23
`models_micro_LP()` (in module *nucleardatapy.setup_micro_LP*), 13
`models_micro_matter()` (in module *nucleardatapy.setup_micro_matter*), 7
`models_pheno_matter()` (in module *nucleardatapy.setup_pheno_matter*), 16
`module`
`nucleardatapy`, 4
`nucleardatapy.setup_crust`, 22
`nucleardatapy.setup_EsymLsym`, 33
`nucleardatapy.setup_hic_matter`, 17
`nucleardatapy.setup_ISGMR`, 31
`nucleardatapy.setup_masses_exp`, 24
`nucleardatapy.setup_masses_theory`, 28
`nucleardatapy.setup_micro_LP`, 13
`nucleardatapy.setup_micro_matter`, 7
`nucleardatapy.setup_micro_matter_band`, 8
`nucleardatapy.setup_pheno_matter`, 14
`nucleardatapy.setup_rad_ch`, 29
`mu_n` (*nucleardatapy.setup_crust.SetupCrust* attribute), 23
`mu_p` (*nucleardatapy.setup_crust.SetupCrust* attribute), 23

N

`N` (*nucleardatapy.setup_crust.SetupCrust* attribute), 22
`N_bound` (*nucleardatapy.setup_crust.SetupCrust* attribute), 22
`N_g` (*nucleardatapy.setup_crust.SetupCrust* attribute), 22
`nbLine` (*nucleardatapy.setup_masses_exp.SetupMassesExp* attribute), 25
`nbNuc` (*nucleardatapy.setup_masses_exp.SetupMassesExp* attribute), 25
`nden` (*nucleardatapy.setup_micro_matter_band.SetupMicroMatterBand* attribute), 11
`nm_cs2` (*nucleardatapy.setup_pheno_matter.SetupPhenoMatter* attribute), 15
`nm_den` (*nucleardatapy.setup_pheno_matter.SetupPhenoMatter* attribute), 15
`nm_e2a` (*nucleardatapy.setup_pheno_matter.SetupPhenoMatter* attribute), 15
`nm_gap` (*nucleardatapy.setup_pheno_matter.SetupPhenoMatter* attribute), 15
`nm_kfn` (*nucleardatapy.setup_pheno_matter.SetupPhenoMatter* attribute), 15
`nm_pre` (*nucleardatapy.setup_pheno_matter.SetupPhenoMatter* attribute), 15
`note` (*nucleardatapy.setup_EsymLsym.SetupEsymLsym* attribute), 33
`note` (*nucleardatapy.setup_ISGMR.SetupISGMR* attribute), 31
`note` (*nucleardatapy.setup_masses_exp.SetupMassesExp* attribute), 25
`note` (*nucleardatapy.setup_pheno_matter.SetupPhenoMatter* attribute), 16
`note` (*nucleardatapy.setup_rad_ch.SetupRadCh* attribute), 29

nucA (*nucleardatapy.setup_ISGMR.SetupISGMR attribute*), 31
 nucA (*nucleardatapy.setup_masses_exp.SetupMassesExp attribute*), 25
 nucA (*nucleardatapy.setup_rad_ch.SetupRadCh attribute*), 29
 nucBE (*nucleardatapy.setup_masses_exp.SetupMassesExp attribute*), 25
 nucBE_err (*nucleardatapy.setup_masses_exp.SetupMassesExp attribute*), 25
 nucHT (*nucleardatapy.setup_masses_exp.SetupMassesExp attribute*), 25
 nucleardatapy module, 4
 nucleardatapy.setup_crust module, 22
 nucleardatapy.setup_EsymLsym module, 33
 nucleardatapy.setup_hic_matter module, 17
 nucleardatapy.setup_ISGMR module, 31
 nucleardatapy.setup_masses_exp module, 24
 nucleardatapy.setup_masses_theory module, 28
 nucleardatapy.setup_micro_LP module, 13
 nucleardatapy.setup_micro_matter module, 7
 nucleardatapy.setup_micro_matter_band module, 8
 nucleardatapy.setup_pheno_matter module, 14
 nucleardatapy.setup_rad_ch module, 29
 nucM12Mm1_cent (*nucleardatapy.setup_ISGMR.SetupISGMR attribute*), 31
 nucM12Mm1_errm (*nucleardatapy.setup_ISGMR.SetupISGMR attribute*), 31
 nucM12Mm1_errp (*nucleardatapy.setup_ISGMR.SetupISGMR attribute*), 31
 nucN (*nucleardatapy.setup_masses_exp.SetupMassesExp attribute*), 25
 nucN (*nucleardatapy.setup_rad_ch.SetupRadCh attribute*), 30
 nucRch (*nucleardatapy.setup_rad_ch.SetupRadCh attribute*), 30
 nucRch_err (*nucleardatapy.setup_rad_ch.SetupRadCh attribute*), 30
 nucStbl (*nucleardatapy.setup_masses_exp.SetupMassesExp attribute*), 25
 nucSymb (*nucleardatapy.setup_masses_exp.SetupMassesExp attribute*), 25
 nucSymb (*nucleardatapy.setup_rad_ch.SetupRadCh attribute*), 30
 nucSymbol (*nucleardatapy.setup_ISGMR.SetupISGMR attribute*), 32
 nucYear (*nucleardatapy.setup_masses_exp.SetupMassesExp attribute*), 25
 nucZ (*nucleardatapy.setup_ISGMR.SetupISGMR attribute*), 32
 nucZ (*nucleardatapy.setup_masses_exp.SetupMassesExp attribute*), 25
 nucZ (*nucleardatapy.setup_rad_ch.SetupRadCh attribute*), 30

P

param (*nucleardatapy.setup_pheno_matter.SetupPhenoMatter attribute*), 16
 params_pheno_matter() (in module *nucleardatapy.setup_pheno_matter*), 16
 print_outputs() (*nucleardatapy.setup_crust.SetupCrust method*), 23
 print_outputs() (*nucleardatapy.setup_EsymLsym.SetupEsymLsym method*), 33
 print_outputs() (*nucleardatapy.setup_hic_matter.SetupHICMatter method*), 17
 print_outputs() (*nucleardatapy.setup_ISGMR.SetupISGMR method*), 32
 print_outputs() (*nucleardatapy.setup_masses_exp.SetupMassesExp method*), 25
 print_outputs() (*nucleardatapy.setup_masses_theory.SetupMassesTheory method*), 28
 print_outputs() (*nucleardatapy.setup_micro_LP.SetupMicroLP method*), 13
 print_outputs() (*nucleardatapy.setup_micro_matter.SetupMicroMatter method*), 7
 print_outputs() (*nucleardatapy.setup_micro_matter_band.SetupMicroMatterBand method*), 11
 print_outputs() (*nucleardatapy.setup_pheno_matter.SetupPhenoMatter method*), 16
 print_outputs() (*nucleardatapy.setup_rad_ch.SetupRadCh method*), 30

R

`R_unit` (`nucleardatapy.setup_rad_ch.SetupRadCh` attribute), 29
`RadCh_isotopes()` (`nucleardatapy.setup_rad_ch.SetupRadCh` method), 29
`ref` (`nucleardatapy.setup_EsymLsym.SetupEsymLsym` attribute), 33
`ref` (`nucleardatapy.setup_ISGMR.SetupISGMR` attribute), 32
`ref` (`nucleardatapy.setup_masses_exp.SetupMassesExp` attribute), 25
`ref` (`nucleardatapy.setup_pheno_matter.SetupPhenoMatter` attribute), 16
`ref` (`nucleardatapy.setup_rad_ch.SetupRadCh` attribute), 30
`RWS` (`nucleardatapy.setup_crust.SetupCrust` attribute), 22

S

`select()` (`nucleardatapy.setup_masses_exp.SetupMassesExp` method), 25
`select_year()` (`nucleardatapy.setup_masses_exp.SetupMassesExp` method), 26
`SetupCrust` (class in `nucleardatapy.setup_crust`), 22
`SetupEsymLsym` (class in `nucleardatapy.setup_EsymLsym`), 33
`SetupHICMatter` (class in `nucleardatapy.setup_hic_matter`), 17
`SetupISGMR` (class in `nucleardatapy.setup_ISGMR`), 31
`SetupMassesExp` (class in `nucleardatapy.setup_masses_exp`), 24
`SetupMassesTheory` (class in `nucleardatapy.setup_masses_theory`), 28
`SetupMicroLP` (class in `nucleardatapy.setup_micro_LP`), 13
`SetupMicroMatter` (class in `nucleardatapy.setup_micro_matter`), 7
`SetupMicroMatterBand` (class in `nucleardatapy.setup_micro_matter_band`), 8
`SetupPhenoMatter` (class in `nucleardatapy.setup_pheno_matter`), 14
`SetupRadCh` (class in `nucleardatapy.setup_rad_ch`), 29
`sm_cs2` (`nucleardatapy.setup_pheno_matter.SetupPhenoMatter` attribute), 16
`sm_den` (`nucleardatapy.setup_pheno_matter.SetupPhenoMatter` attribute), 16
`sm_e2a` (`nucleardatapy.setup_pheno_matter.SetupPhenoMatter` attribute), 16
`sm_gap` (`nucleardatapy.setup_pheno_matter.SetupPhenoMatter` attribute), 16
`sm_kf` (`nucleardatapy.setup_pheno_matter.SetupPhenoMatter` attribute), 16

`sm_kfn` (`nucleardatapy.setup_pheno_matter.SetupPhenoMatter` attribute), 16
`sm_pre` (`nucleardatapy.setup_pheno_matter.SetupPhenoMatter` attribute), 16

T

`table` (`nucleardatapy.setup_ISGMR.SetupISGMR` attribute), 32
`tables_isgmr()` (in module `nucleardatapy.setup_ISGMR`), 32
`tables_masses_exp()` (in module `nucleardatapy.setup_masses_exp`), 26
`tables_masses_theory()` (in module `nucleardatapy.setup_masses_theory`), 28
`tables_rad_ch()` (in module `nucleardatapy.setup_rad_ch`), 30

V

`versions_masses_exp()` (in module `nucleardatapy.setup_masses_exp`), 26

X

`xn` (`nucleardatapy.setup_crust.SetupCrust` attribute), 23
`xn_bound` (`nucleardatapy.setup_crust.SetupCrust` attribute), 23
`xp` (`nucleardatapy.setup_crust.SetupCrust` attribute), 23
`xpn_bound` (`nucleardatapy.setup_crust.SetupCrust` attribute), 23

Z

`Z` (`nucleardatapy.setup_crust.SetupCrust` attribute), 23
`Zmax` (`nucleardatapy.setup_masses_exp.SetupMassesExp` attribute), 24