

# Painters Buddy

# ACRYLIC GAP SEALANT

# PRODUCT DESCRIPTION

PIONEER PRO Painters Buddy Acrylic Gap Sealant is an acrylic sealant designed as a cost effective gap filler. It has been formulated for use as a multipurpose, interior/exterior sealant that when cured, forms a flexible, durable, weather resistant seal that bonds to most common building materials. PIONEER PRO Painters Buddy Acrylic Gap Sealant is fully paintable and sandable when cured. Uncured sealant cleans up easily with water. It will not bleed, stain or discolor. Sealant guns and tools easily.

### TECHNICAL & PERFORMANCE DATA

Color:	White
% Non-Volatile,	
by weight:	84%
Tack-Free Time,	
ASTM D 2377-84:	20-30 min
Specific Gravity:	1.65
Tooling Time, min.:	10-15
Hardness - Shore A:	30
Staining:	None
Slump:	Nil
pH:	7.0-8.7
Elongation:	200-300%

#### **FEATURES**

- Paintable
- Sandable
- Mildew Resistant
- · Weatherproofs / Waterproofs
- Non-Yellowing
- · Permanently Flexible
- Interior/Exterior Use
- · Water Clean up

#### **APPLICATION**

All surfaces should be clean and free of dirt, dust, debris, any oils and grease prior to application.

- Cut nozzle of cartridge to desired bead size and insert in standard cartridge gun.
- 2. Apply Acrylic Gap sealant into the joint.
- 3. Tool off excess sealant.

#### SHELF LIFE

When stored in the original unopened at or below 32°C Painters Buddy Acrylic Gap Sealant has a shelf life of 12 months from date of shipment. Containers should always be kept sealed when not in use.

#### CAUTION

Product may cause eye and skin irritation on prolonged exposure. In case of eye contact, flush thoroughly with running water. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.

# **PACKAGING**

Painters Buddy Acrylic Gap Sealant is packed in 480 g cartridge for use with standard cartridge gun.



