




A Scalable Multi-User Uplink for Wi-Fi

Adriana B. Flores

Sadia Quadri, and Edward W. Knightly


NSDI, March 2016

Start of Wi-Fi




- Standardized in 1997
- SISO
- Single user at a time
- Omni-directional transmission

MIMO in 802.11




- Multiple concurrent transmissions
- $M \times N$ MIMO increases throughput by $\min(\text{Tx antennas}, \text{Rx antennas})$

MIMO in 802.11




- Multiple concurrent transmissions
- $M \times N$ MIMO increases throughput by $\min(\text{Tx antennas}, \text{Rx antennas})$

MIMO in 802.11



- Multiple concurrent transmissions
- $M \times N$ MIMO increases throughput by $\min(\text{Tx antennas}, \text{Rx antennas})$

Antenna Asymmetry



- MxN MIMO increases throughput by $\min(\text{Tx antennas}, \text{Rx antennas})$
- Client devices often have $N=1$ antenna due to **cost** and **space**

Antenna Asymmetry



- MxN MIMO increases throughput by $\min(\text{Tx antennas}, \text{Rx antennas})$
- Client devices often have $N=1$ antenna due to **cost** and **space**



Antenna Asymmetry

8
Antennas




1
Antenna




- MxN MIMO increases throughput by $\min(\text{Tx antennas}, \text{Rx antennas})$
- Client devices often have $N=1$ antenna due to **cost** and **space**

Antenna Asymmetry




- $M \times N$ MIMO increases throughput by $\min(\text{Tx antennas}, \text{Rx antennas})$
- Client devices often have $N=1$ antenna due to **cost** and **space**

Antenna Asymmetry




- $M \times N$ MIMO increases throughput by $\min(\text{Tx antennas}, \text{Rx antennas})$
- Client devices often have $N=1$ antenna due to **cost** and **space**

Downlink Multi-User MIMO




- $M \times N$ MIMO increases throughput by $\min(\text{Tx antennas}, \text{Rx antennas})$
- Downlink Multi-User MIMO allows for APs to leverage antennas
- Transmitter sends multiple streams concurrently to different users
- Remove Interference by “Zero-Forcing Beamforming” (ZFBF)

Downlink Multi-User MIMO




- $M \times N$ MIMO increases throughput by $\min(\text{Tx antennas}, \text{Rx antennas})$
- Downlink Multi-User MIMO allows for APs to leverage antennas
- Transmitter sends multiple streams concurrently to different users
- Remove Interference by “Zero-Forcing Beamforming” (ZFBF)

Downlink Multi-User MIMO




- $M \times N$ MIMO increases throughput by $\min(\text{Tx antennas}, \text{Rx antennas})$
- Downlink Multi-User MIMO allows for APs to leverage antennas
- Transmitter sends multiple streams concurrently to different users
- Remove Interference by “Zero-Forcing Beamforming” (ZFBF)

Uplink Multi-User MIMO?




- $M \times N$ MIMO increases throughput by $\min(\text{Tx antennas}, \text{Rx antennas})$
- Back to 1997 – SISO transmission

Uplink Multi-User MIMO?




- $M \times N$ MIMO increases throughput by $\min(\text{Tx antennas}, \text{Rx antennas})$
- Back to 1997 – SISO transmission

Why Not Mimic Downlink MU-MIMO?




- Paradigm Shift
- Many \rightarrow One
- No connection between devices
- How do we remove interference?

MUSE : Multi-User ScalableE Uplink




- Match the number of transmitters to the number of antennas at AP
- No control signaling

MUSE : Multi-User ScalableE Uplink



- Match the number of transmitters to the number of antennas at AP
- No control signaling

MUSE : Multi-User ScalableE Uplink





- Match the number of transmitters to the number of antennas at AP
- No control signaling

- Multiple transmitters act as a **single device** with multiple antennas
 - No control channel
 - Remove interference



Transmit Simultaneously

- **Association ID** for user selection and grouping
- **Arbitrary index** for each user
- AP informs the network the Max ID





Transmit Simultaneously

- **Association ID** for user selection and grouping
- **Arbitrary index** for each user
- AP informs the network the Max ID





Transmit Simultaneously

- **Association ID** for user selection and grouping
- **Arbitrary index** for each user
- AP informs the network the Max ID





Transmit Simultaneously

- **Association ID** for user selection and grouping
- **Arbitrary index** for each user
- AP informs the network the Max ID





Transmit Simultaneously

- **Association ID** for user selection and grouping
- **Arbitrary index** for each user
- AP informs the network the Max ID




Transmit Simultaneously

- **Association ID** for user selection and grouping
- **Arbitrary index** for each user
- AP informs the network the Max ID




Remove Interference

- Environmental Multipath
- Independent paths (channels)
- Receiver (AP) estimate channels





Remove Interference

- Environmental Multipath
- Independent paths (channels)
- Receiver (AP) estimate channels





Receiver Channel Estimation

- Known set of training signals
- Enable distributed usage
- Fixed size (# Streams = # Rx antennas)
- User has assigned set of training signals
- Assignment through Association ID
- No control signaling (coordination) required





Receiver Channel Estimation

- Known set of training signals
- Enable distributed usage
- Fixed size (# Streams = # Rx antennas)
- User has assigned set of training signals
- Assignment through Association ID
- No control signaling (coordination) required



Group Adaptation



- **Association ID** Reassignment
- AP learning process: which users are most likely to transmit



Time

Group Adaptation


- **Association ID** Reassignment
- AP learning process: which users are most likely to transmit



Time

Group Adaptation


- **Association ID** Reassignment
- AP learning process: which users are most likely to transmit



Time

MUSE Implementation


- OTA experiments WARPLab
- 1 to 4 concurrent spatial streams
- Evaluation Setup:
 - Clients: single WARP board with independent RF clocks
 - Time synchronized through triggering cables
 - Conference room 645sq ft or 60 sq m
 - Evaluate over 20 locations



MUSE Scalability

- Scalability can be limited by inter-stream interference and channel correlation between users
- MUSE PHY ability to achieve full-rank capacity and permit scaling


- Setup:
 - 1x1, 2x2, 3x3, 4x4
 - 2000 packets
 - 24 Mbps



MUSE Scalability

- Scalability can be limited by inter-stream interference and channel correlation between users
- MUSE PHY ability to achieve full-rank capacity and permit scaling

- Setup:
 - 1x1, 2x2, 3x3, 4x4
 - 2000 packets
 - 24 Mbps




Tx Beamforming is **NOT** needed for distributed uplink multi-user transmission

MUSE Scalability

- Empirical capacity with estimated channels

$$C(\text{bps/Hz}) = \log_2[\det(I_N + (SNR/M)(HH^*))]_{[1]}$$





193 Mbps to 669 Mbps

Conclusion MUSE

- **Scalable** Multi-User MIMO uplink WLAN
- Match the number of transmitters to the number of antennas at AP
- No control signaling

Emulate Single Multi-Antenna device

- Transmit Simultaneously
- ID-Based Grouping and Synchronization
- Enable distributed and dynamic Rx channel estimation
- Leverage environmental multipath
- Standard compatible



Conclusion MUSE

- **Scalable** Multi-User MIMO uplink WLAN
- Match the number of transmitters to the number of antennas at AP
- No control signaling

Emulate Single Multi-Antenna device

- Transmit Simultaneously
- ID-Based Grouping and Synchronization
- Enable distributed and dynamic Rx channel estimation
- Leverage environmental multipath
- Standard compatible

