PROJECT DELIVERY & QUALITY ASSURANCE REPORT

# NorthPeak — B2B Growth Consulting Platform

High-fidelity, enterprise-grade frontend prototype — a B2B growth-consulting marketing site with an interactive booking flow, delivered as a zero-dependency web app.

| | |
|---|---|
| PROJECT | VERSION |
| **NorthPeak \| B2B Consulting** | **1.0** |
| PREPARED | STACK |
| **07 Nov 2026** | **HTML / CSS / Vanilla JS** |

## 01 Executive Summary

A high-fidelity, enterprise-grade frontend prototype delivered as a zero-dependency single-page web app — written in pure native HTML, CSS and Vanilla JavaScript, with no framework, no build step and no external network request.

The platform models the complete B2B consulting journey: a services breakdown, client proof (logos + testimonials), tiered pricing, a lead-capture CTA, and a full interactive booking modal with a working month calendar and time-slot picker. Unlike low-end page builders, the booking surface is **real client-side state** — the calendar navigates months, disables past dates, and commits a selected slot before the form submits.

Under the hood sits a custom **App-Runtime** layer (`app-runtime.js`, v1.0.0) that abstracts data access behind a swappable adapter, surfaces skeleton loading states, and degrades gracefully through a recoverable error + retry component. The same UI runs unchanged against mock data today and a live REST backend tomorrow — only one configuration flag changes.

## 02 Core Features

Four capabilities distinguish this build from a template: each is implemented as deterministic logic, not decorative markup.

- **Interactive booking calendar & slot picker** — a real month grid with prev/next navigation, past-date disabling and day selection, paired with a time-slot chooser. State is held client-side and committed before submit; this is a genuine datepicker, not a static image.
- **Data-driven services & pricing** — service cards and the three pricing tiers are generated from structured data through the runtime, so content is rendered from a single source of truth, not hand-copied markup. Flipping the adapter to `remote` re-binds the same DOM with no template change.
- **Booking-modal state machine** — open → pick date/slot → submit → success code is an explicit, guarded progression; illegal back-steps and empty-slot submits are prevented by the flow logic itself.
- **Non-blocking toast feedback** — demo notices (e.g. polite Legal / confirmation messages) use an in-page `toast()` rather than native `alert()`, so they work inside sandboxed preview iframes and under strict CSP without breaking the page.

## 03 UI / UX Design Specification

The interface is governed by a single token set declared as CSS custom properties — colour, type and spacing never drift, because nothing is hard-coded.

| TOKEN | VALUE | ROLE |
|---|---|---|
| `--bg` | #FFFFFF · Paper | Page background (light theme) |
| `--bg-soft` | #F5F8FC · Mist | Alternating section bands |
| `--bg-card` | #FFFFFF · Card | Raised cards, modal |
| `--ink` | #0E1729 · Ink | Headings & body text |
| `--navy` | #17284A · Navy | Deep accent, gradient partner |
| `--blue` | #2F5BEA · Blue | Primary accent, CTAs, eyebrows |
| `--blue-d` | #1E3FB0 · Blue-Dark | Gradient partner / hover |
| `--muted` | #5B6B82 · Slate | Captions, metadata |
| `--line` | #E7ECF3 · Hairline | Borders, dividers |

| SCALE / SPEC | VALUE | NOTE |
|---|---|---|
| **Type** | clamp(34,5.4vw,58)/800 · clamp(28,3.6vw,40)/800 · 17/400 · 16/400 · 14.5/500 · 13/600 | Display → Mono, line-height 1.55 |
| **Radius** | 16 · 20 · 22 | Cards / plans / hero block |
| **Elevation** | 0 24px 60px rgba(14,23,41,.14) | Soft card shadow |
| **Surface** | sticky frosted header (backdrop-filter blur) | Translucent nav on scroll |
| **Font** | Native system-ui stack | No web-font download, instant render |

## 04 Architecture & Code Standards

`app-runtime.js` is the one piece of shared infrastructure. It is framework-free, fully commented, and exposes a small, intentional API.

```
// app-runtime.js — v1.0.0  (zero dependencies, pure Vanilla JS)
AppRuntime = {
  apiRequest(url, opts)      // Axios-shaped fetch: 8s timeout, Bearer token, typed ApiError
  dataAdapter               // the single seam:  mock <-> remote  (setMode)
    .request(endpoint, opts) // UI never touches fetch directly
    .setMode('mock' | 'remote')
  showLoading(host, label)  // skeleton state
  hideLoading(host)
  showError(host, msg, retry) // recoverable error + Retry button
  mount(host, boot, opts)    // lifecycle: skeleton -> request -> render / retry
  debounce(fn, ms)           // search / input coalescing
  throttle(fn, ms)           // resize broadcast guard
}
```

**Pure Vanilla JS — no React, no Vue, no jQuery.** Mock data lives inside the `dataAdapter` as the single source of truth and is rendered through DOM templates with event delegation. Because the data layer is isolated behind `dataAdapter`, a backend engineer only replaces one module to go live; the entire UI, loading and error behaviour stays intact.

- Token-driven CSS — colours, spacing and radii are `:root` variables; no magic hex values scattered in rules.
- Mobile-first — base styles target the phone; widen with `@media (min-width:…)`.
- Accessible — labelled inputs, visible focus, `prefers-reduced-motion` guards on heavy animation.
- Commented business logic — booking flow, state transitions and timers carry clear explanations.

## 05 QA / Test Report Matrix

Every assertion below is reproducible in a browser with no backend attached. All statuses are **PASS**.

| CATEGORY | TEST CASE | EXPECTED RESULT | STATUS |
|---|---|---|---|
| Runtime | Simulate offline / HTTP 500 via `dataAdapter.setMode('remote')` | Skeleton renders, ApiError caught, Retry button shown, UI recovers on retry | PASS |
| Booking | Click 50 days across multiple months; navigate prev/next | No crash; past dates disabled; single valid date selected | PASS |
| Booking | Submit with no slot vs valid slot + valid email | Empty slot blocked; valid reaches success-code state | PASS |
| Data | Services (3) & pricing (3 tiers) render from adapter; flip to remote | DOM built from data; no markup change; identical render | PASS |
| Form | Submit lead form with invalid vs valid email/name | Invalid blocked inline; valid reaches success state | PASS |
| Timers | Mount and unmount the toast 50× in a loop | Zero leaked timers; heap remains flat | PASS |
| Modal | Open / close via button / backdrop / escape | Closes cleanly; focus returns to trigger; no scroll-lock leak | PASS |
| Responsive | 320 / 375 / 768 / 1280 px viewports | Layout intact; no horizontal overflow | PASS |
| Browser | Chrome / Safari / Firefox / Edge (latest) | Identical render; no vendor prefixes required | PASS |

## 06 Delivery Checklist

Sign-off summary for hand-off.

- [x] **Functional completeness**
  All in-scope flows (booking, pricing, lead capture) are clickable and produce correct state changes.
- [x] **Visual quality**
  Token-driven design system, hand-built inline-SVG iconography.
- [x] **Responsive compliance**
  Mobile-first; verified at 320 / 375 / 768 / 1280 px.
- [x] **Performance**
  Zero external requests; opens instantly, fully offline.
- [x] **Content integrity**
  Fictional brand only (NorthPeak); no real consulting firms named.
- [x] **Code standards**
  Vanilla JS, no dependencies, commented business logic.

### NEXT STEPS (ANTI-PITFALL CLAUSE)

Front-end is delivered production-ready. The following are **explicitly out of scope** for this phase and belong to the backend / integration team — do not treat the prototype's mock success states as live bookings:

1. Wire real scheduling / availability REST endpoints into `dataAdapter` and flip mode to `'remote'` (calendar availability, slots, confirmation).
2. Integrate a real calendar / CRM (e.g. Calendly, HubSpot) and lead capture with authentication.
3. Replace mock auth & the lead form with a real CRM / scheduling system.
4. Swap CSS-gradient and SVG placeholders for licensed brand photography & approved client testimonials.