

# Naive Bayesian Learning in Social Networks


**Jerry Anunrojwong (Harvard)**

joint with Nat Sothanaphan (MIT)

EC'18

# Social Learning

---




state of the world  
unknown to the agents

Rule: can only talk to your  
neighbors

Prior works:  
Bayesian Learning  
Naive Learning

# Bayesian Learning (Rational)


---



**Beliefs are distributions.  
Perfectly rational and  
Bayesian.**

# Bayesian Learning (Rational)

---




**Beliefs are distributions.  
Perfectly rational and  
Bayesian.**

**Weigh  
confidence in beliefs**



# Bayesian Learning (Rational)

I need to subtract other people's beliefs from yours. But how? I need superhuman reasoning & knowledge.



Beliefs are distributions.  
Perfectly rational and  
Bayesian.

Weigh  
confidence in beliefs



Do very sophisticated  
Bayesian reasoning




Network structure is  
common knowledge




# Naive Learning (DeGroot)

---



**Beliefs are scalars.  
Update beliefs by taking  
(weighted) average of  
neighbors' beliefs.**

# Naive Learning (DeGroot)



**Beliefs are scalars.  
Update beliefs by taking  
(weighted) average of  
neighbors' beliefs.**


**Simple and intuitive  
belief update rule**



**Only need to know  
neighbors**



# Naive Learning (DeGroot)



**Beliefs are scalars.  
Update beliefs by taking  
(weighted) average of  
neighbors' beliefs.**

**No notion of  
confidence in beliefs**



**Simple and intuitive  
belief update rule**



**Only need to know  
neighbors**





# Question: How can we combine the pros of naive and Bayesian learning?

## Naive Bayesian Learning

Weigh  
confidence in beliefs



**Bayesian**

Beliefs are distributions.  
Agents use Bayes' rule.

Simple and intuitive  
belief update rule



**Naive**

Agents treat neighbors as independent.


Only need to know  
neighbors



**Naive**

Belief update rule only depends on neighbors.


# Naive Bayesian Learning (Our paper)



**My mental model**

**Beliefs are distributions.  
Update beliefs by Bayes  
rule, assuming naively  
that neighbors are  
independent information  
sources.**

# Naive Bayesian Learning (Our paper)



**My mental model**


Each time step:

I have access to  
my and my neighbors' **beliefs**

**My update rule**

**Beliefs are distributions.**  
Update beliefs by Bayes  
rule, *assuming naively*  
*that neighbors are*  
*independent information*  
*sources.*

# Naive Bayesian Learning (Our paper)



**My mental model**

Each time step:


I have access to  
my and my neighbors' **beliefs**

I infer my and my neighbors'  
signals **assuming their beliefs**  
**arise from my mental model**

**My update rule**

**Beliefs are distributions.**  
**Update beliefs by Bayes**  
**rule, assuming naively**  
**that neighbors are**  
**independent information**  
**sources.**

# Naive Bayesian Learning (Our paper)



Each time step:

I have access to  
my and my neighbors' **beliefs**

I infer my and my neighbors'  
signals **assuming their beliefs**  
**arise from my mental model**


I update my beliefs from common  
prior by **conditioning on my and**  
**my neighbors' inferred signals**

My update rule

**Beliefs are distributions.**  
**Update beliefs by Bayes**  
**rule, assuming naively**  
**that neighbors are**  
**independent information**  
**sources.**

# Naive Bayesian Update Rule: Example

---



belief  $t=0$

$$p(\theta|X_1)$$

$$p(\theta|X_2)$$

$$p(\theta|X_3)$$

inferred signals

$$\{X_1\}$$

$$\{X_2\}$$

$$\{X_3\}$$

belief  $t=1$


$$p(\theta|X_1, X_2)$$

$$p(\theta|X_1, X_2, X_3)$$

$$p(\theta|X_2, X_3)$$

# Naive Bayesian Update Rule: Example

---



belief t=1

$$p(\theta|X_1, X_2)$$

$$p(\theta|X_1, X_2, X_3)$$

$$p(\theta|X_2, X_3)$$

inferred signals

$$\{X_1, X_2\}$$

$$\{X_1, X_2, X_3\}$$

$$\{X_2, X_3\}$$

belief t=2

$$p(\theta|X_1, X_2, X_1, X_2, X_3)$$

$$p(\theta|X_1, X_2, X_1, X_2, X_3, X_2, X_3)$$

$$p(\theta|X_1, X_2, X_3, X_2, X_3)$$

# Naive Bayesian Update Rule: Example

Copies of signals “flow”

Mental model assumes beliefs are “fresh”

1

2

3

belief t=1

$$p(\theta | X_1, X_2)$$

$$p(\theta | X_1, X_2, X_3)$$

$$p(\theta | X_2, X_3)$$

inferred signals

$\{X_1, X_2\}$

$\{X_1, X_2, X_3\}$

$\{X_2, X_3\}$

belief t=2

$$p(\theta | X_1, X_2, X_1, X_2, X_3)$$

$$p(\theta | X_1, X_2, X_1, X_2, X_3, X_2, X_3)$$

$$p(\theta | X_1, X_2, X_3, X_2, X_3)$$




# Main Result (Informal)

we **analytically characterize the consensus** and the formula for the consensus says ...



# Main Result (Informal)

we **analytically characterize the consensus** and the formula for the consensus says ...




eigenvector of  
adjacency matrix

$$A\mathbf{v} = r\mathbf{v}$$

# Main Result (Informal)

we **analytically characterize the consensus** and the formula for the consensus says ...




eigenvector of  
adjacency matrix

an agent is central  
if it connects to other central agents

$$A\mathbf{v} = r\mathbf{v} \Rightarrow rv_i = \sum_{j \in N(i)} v_j$$

# Main Result (Informal)

we **analytically characterize the consensus** and the formula for the consensus says ...



eigenvector of  
adjacency matrix

an agent is central  
if it connects to other central agents

also appear in DeGroot learning  
but from different dynamics


$$A\mathbf{v} = r\mathbf{v} \Rightarrow rv_i = \sum_{j \in N(i)} v_j$$

# Main Result (Formal)

**DEFINITION**  
weighted log-likelihood function

$$\ell(\theta) = \sum_{i=1}^n v_i \log \left( \frac{f_i(\theta)}{f_*(\theta)} \right)$$

for each state  $\theta$



**Theorem** Every agent's belief converges to the point distribution at maximizer of  $\ell(\theta)$ .


# Main Result (Formal)

$f_i$  agent  $i$ 's initial belief  
 $f_*$  common prior

**DEFINITION**  
weighted log-likelihood function

$$\ell(\theta) = \sum_{i=1}^n v_i \underbrace{\log \left( \frac{f_i(\theta)}{f_*(\theta)} \right)}_{\text{"confidence of beliefs at } \theta"}$$

for each state  $\theta$



**"confidence of beliefs at  $\theta$ "**  
how much agent  $i$  believes in  $\theta$   
compared to the prior baseline

**Theorem Every agent's belief converges to the point distribution at maximizer of  $\ell(\theta)$ .**


# Main Result (Formal)

$f_i$  agent  $i$ 's initial belief  
 $f_*$  common prior

**DEFINITION**  
weighted log-likelihood function

$$\ell(\theta) = \sum_{i=1}^n v_i \log \left( \frac{f_i(\theta)}{f_*(\theta)} \right)$$

for each state  $\theta$



centrality-weighted  
average of

**“confidence of beliefs at  $\theta$ ”**  
how much agent  $i$  believes in  $\theta$   
compared to the prior baseline

**Theorem Every agent’s belief converges to the point distribution at maximizer of  $\ell(\theta)$ .**

# Understanding Main Result Intuitively

— — —

- **agents take a lot of signals as independent**  
→ **beliefs converge to a point**



# Understanding Main Result Intuitively

— — —

- **agents take a lot of signals as independent**  
→ **beliefs converge to a point**
- **initial beliefs come from independent signals**  
→ **“confident beliefs” = “informative signals”**

# Example: Gaussian Beliefs

— — —

agent  $i$ 's initial belief

$$\mathcal{N}(\mu_i, 1/\tau_i)$$

interpretation: scalar belief  $\mu_i$  with confidence  $\tau_i$

# Example: Gaussian Beliefs

— — —

agent i's initial belief

$$\mathcal{N}(\mu_i, 1/\tau_i)$$

interpretation: scalar belief  $\mu_i$  with confidence  $\tau_i$

a scenario: at the beginning, agent i receives signal  $\mu_i = \theta^* + \varepsilon_i$  with  $\varepsilon_i \sim \mathcal{N}(0, 1/\tau_i)$  independent

# Example: Gaussian Beliefs

— — —

agent i's initial belief

$$\mathcal{N}(\mu_i, 1/\tau_i)$$

interpretation: scalar belief  $\mu_i$  with confidence  $\tau_i$

a scenario: at the beginning, agent i receives signal  $\mu_i = \theta^* + \varepsilon_i$  with  $\varepsilon_i \sim \mathcal{N}(0, 1/\tau_i)$  independent

**consensus**

$$\theta_{\max} = \sum_{i=1}^n c_i \mu_i$$

# Example: Gaussian Beliefs

---

agent i's initial belief

$$\mathcal{N}(\mu_i, 1/\tau_i)$$

interpretation: scalar belief  $\mu_i$  with confidence  $\tau_i$

a scenario: at the beginning, agent i receives signal  $\mu_i = \theta^* + \varepsilon_i$  with  $\varepsilon_i \sim \mathcal{N}(0, 1/\tau_i)$  independent

consensus

$$\theta_{\max} = \sum_{i=1}^n c_i \mu_i$$

agent i's influence

$$c_i = \frac{v_i \tau_i}{\sum_{j=1}^n v_j \tau_j} \propto v_i \tau_i$$

influence on  
consensus

=

centrally  
located

+

informative  
signals


# Policy Implication I: how to seed opinion leaders

Learning quality = precision of consensus, as a random variable!

$$\frac{\partial(\text{learning quality})}{\partial(\text{signal precision})} > 0 \quad \text{unless agent is central but poorly informed}$$


If social planners want to seed opinion leaders,  
they must make those leaders well informed.

ELSE you get this →




# Policy Implication II: how to solve clustered seeding

**Key point: their model has no notion of “confidence in beliefs”**



Information loss from *clustered seeding* occurs in their model but not ours.



# Conclusion

— — —

- **We propose a model that combines the pros of naive and Bayesian learning.**
- **consensus = maximizer of the weighted log-likelihood function**
- **centrally located + confident beliefs = influence on consensus**
- **Two policy implications:**  
**how to seed opinion leaders + clustered seeding**



# Gaussian Beliefs: Quality of Learning

$$\theta_{\max} \sim \mathcal{N}(\theta^*, 1/Q) \quad Q = \frac{(\sum_i v_i \tau_i)^2}{\sum_i v_i^2 \tau_i}$$

consensus is a random variable  
precision  $Q$  captures learning quality

Comparative statics

$$\frac{\partial Q}{\partial \tau_k} > 0 \quad \text{unless } v_k \text{ is large and } \tau_k \text{ is small}$$

## POLICY IMPLICATION

If social planners want to seed opinion leaders,  
they must make those leaders well informed.

ELSE you get this →

