a. The cube code (11 min)

0–1.5 min / 1 Qubits indexed by the points of $\mathbb{F}_2^3$ Binary vectors are functions on the points. Steps: u1, u2, u3, then the constant vector. They span RM(1,3).

1.5–3 min / 2 CSS codes and logical states Logical basis, X and Z checks, d_X and d_Z.

3–4 min / 3 The cube code $[\![8,3,2]\!]$ K has rows u1, u2, u3, which is why qubits are points.

4–5 min / 4 Distances of the cube code Z000 Z100 commutes with the check and flips x1: d_Z = 2. The smallest interesting colour code.

5–5.5 min / 5 Transversal gates Single-qubit transversal. Define T and CCZ.

5.5–6.5 min / 6 Codeword weight, physical phase, and logical phase T sites minus T-dagger sites. The gate condition mod 8.

6.5–8 min / 7 Choosing the signs on the cube Affine functions have 4 ones. p is the codeword of label 111. Define d_H.

8–9 min / 8 Weights of sums expand into overlaps Per-position parity identity, summed over positions.

9–10.5 min / 9 Reading the cube phase from overlaps Face, edge, vertex: W = 0, 0, -1, so the phase is CCZ.

10.5–11 min / 10 The gate condition becomes conditions on generator rows Mod 8, mod 4, mod 2. Define the bracket.

b. History and the CH conditions (4.5 min)

11–12.5 min / 11 Historical context Cite the CSS-T work of Camps-Moreno, López, Matthews et al.

12.5–14 min / 12 Triorthogonal matrix and triorthogonal space Nezami-Haah puncture parent spaces. We fix S first and find K.

14–15.5 min / 13 Conditions for quasi-transversal CCZ Mod 2 reduction gives the nine parities. A physical layer needs the signed congruences.

c. Results and finite geometry (8 min)

15.5–17 min / 14 Result: a 48-qubit code with a transversal T/T† CCZ 39 to 46 excluded by Wills, Jain and Singh.

17–18 min / 15 Fix S using finite/projective geometry code Four steps. Only the logical rows are searched.

18–19 min / 16 Projectivity rules out weight-one and weight-two Z logicals Independent of the choice of logical rows.

19–20.5 min / 17 Complement of a projective subspace 63 points, remove the 15 with w = 00, three blocks of 16.

20.5–22 min / 18 Hyperplane sections and codeword weights u1 gives 24, w1 gives 32. Both divisible by 8.

22–23.5 min / 19 More geometric constructions The table of codes found. Counts are lower bounds except 48.

d. Column picture and search (9 min)

23.5–25 min / 20 Column indicators from the generator matrix Show G for the cube. chi_G = y because every x occurs with y = 1.

25–27 min / 21 The CH conditions are inner products with monomials Overlap parity is an inner product. Coset of RM(r-4, r).

27–29 min / 22 Logical rows in the column picture Logical label, T_K, T_S, the bracket. Step 2 shows K1.

29–31 min / 23 Finding the logical rows Algorithm 1: V_P, pairs, then Gaussian elimination for kappa 3. Witness gives d_Z = 3.

31–32.5 min / 24 Solving for the T/T† pattern Binary unknowns, linear over Z4. 26 T plus 22 T-dagger.

e. Bounds and implications (7.5 min)

32.5–34.5 min / 25 Stabilizer supports are Reed–Muller codewords Monomials of positive degree vanish at the origin.

34.5–36.5 min / 26 Our exclusion argument covers every length through 38 Analytic reductions plus a complete finite enumeration.

36.5–38.5 min / 27 Existence of a valid code at different block lengths Jacinto support is the affine version, not Q48 punctured.

38.5–40 min / 28 Takeaways and open questions Leave the QR codes up during questions.

40 minutes: finish and invite questions.