

Overview of Semantic Analysis

Lecture 9

Prof. Aiken CS 143 Lecture 9

1

Announcements

- WA2 due today
 - Electronic hand-in
 - Or after class
 - Or under my office door by 5pm
- PA2 due tonight
 - Electronic hand-in
- Regrades
 - One deduction for each error
 - But you have to prove it to us . . .

Prof. Aiken CS 143 Lecture 9

2

Midterm Thursday

- In class
 - SCPD students come to campus for the exam
- Material through lecture 8
- Four sheets hand- or type-written notes

Prof. Aiken CS 143 Lecture 9

3

Outline

- The role of semantic analysis in a compiler
 - A laundry list of tasks
- Scope
 - Implementation: symbol tables
- Types

Prof. Aiken CS 143 Lecture 9

4

The Compiler So Far

- Lexical analysis
 - Detects inputs with illegal tokens
- Parsing
 - Detects inputs with ill-formed parse trees
- Semantic analysis
 - Last "front end" phase
 - Catches all remaining errors

Prof. Aiken CS 143 Lecture 9

5

Why a Separate Semantic Analysis?

- Parsing cannot catch some errors
- Some language constructs not context-free

Prof. Aiken CS 143 Lecture 9

6

What Does Semantic Analysis Do?

- Checks of many kinds . . . coolc checks:

1. All identifiers are declared
 2. Types
 3. Inheritance relationships
 4. Classes defined only once
 5. Methods in a class defined only once
 6. Reserved identifiers are not misused
- And others . . .

- The requirements depend on the language

Prof. Aiken CS 143 Lecture 9

7

Scope

- Matching identifier declarations with uses
 - Important static analysis step in most languages
 - Including COOL!

Prof. Aiken CS 143 Lecture 9

8

What's Wrong?

- Example 1

```
Let y: String ← "abc" in y + 3
```

- Example 2

```
Let y: Int in x + 3
```

Note: An example property that is not context free.

Prof. Aiken CS 143 Lecture 9

9

Scope (Cont.)

- The *scope* of an identifier is the portion of a program in which that identifier is accessible
- The same identifier may refer to different things in different parts of the program
 - Different scopes for same name don't overlap
- An identifier may have restricted scope

Prof. Aiken CS 143 Lecture 9

10

Static vs. Dynamic Scope

- Most languages have *static* scope
 - Scope depends only on the program text, not run-time behavior
 - Cool has static scope
- A few languages are *dynamically* scoped
 - Lisp, SNOBOL
 - Lisp has changed to mostly static scoping
 - Scope depends on execution of the program

Prof. Aiken CS 143 Lecture 9

11

Static Scoping Example

```
let x: Int ← 0 in
{
  x;
  let x: Int ← 1 in
    x;
  x;
}
```

Prof. Aiken CS 143 Lecture 9

12

Static Scoping Example (Cont.)

```
let x: Int ← 0 in
{
  let x: Int ← 1 in
  {
    x;
  }
}
```

Uses of `x` refer to closest enclosing definition

Prof. Aiken CS 143 Lecture 9

13

Dynamic Scope

- A dynamically-scoped variable refers to the closest enclosing binding in the execution of the program

- Example

```
g(y) = let a ← 4 in f(3);
f(x) = a;
```

- More about dynamic scope later in the course

Prof. Aiken CS 143 Lecture 9

14

Scope in Cool

- Cool identifier bindings are introduced by
 - Class declarations (introduce class names)
 - Method definitions (introduce method names)
 - Let expressions (introduce object id's)
 - Formal parameters (introduce object id's)
 - Attribute definitions (introduce object id's)
 - Case expressions (introduce object id's)

Prof. Aiken CS 143 Lecture 9

15

Scope in Cool (Cont.)

- Not all kinds of identifiers follow the most-closely nested rule
- For example, class definitions in Cool
 - Cannot be nested
 - Are *globally visible* throughout the program
- In other words, a class name can be used before it is defined

Prof. Aiken CS 143 Lecture 9

16

Example: Use Before Definition

```
Class Foo {
  ... let y: Bar in ...
};

Class Bar {
  ...
};
```

Prof. Aiken CS 143 Lecture 9

17

More Scope in Cool

Attribute names are global within the class in which they are defined

```
Class Foo {
  f(): Int { a };
  a: Int ← 0;
}
```

Prof. Aiken CS 143 Lecture 9

18

More Scope (Cont.)

- Method/attribute names have complex rules
- A method need not be defined in the class in which it is used, but in some parent class
- Methods may also be redefined (overridden)

Prof. Aiken CS 143 Lecture 9

19

Implementing the Most-Closely Nested Rule

- Much of semantic analysis can be expressed as a recursive descent of an AST

- *Before*: Process an AST node n
- *Recurse*: Process the children of n
- *After*: Finish processing the AST node n

- When performing semantic analysis on a portion of the the AST, we need to know which identifiers are defined

Prof. Aiken CS 143 Lecture 9

20

Implementing . . . (Cont.)

- Example: the scope of `let` bindings is one subtree of the AST:

`let x: Int ← 0 in e`

- `x` is defined in subtree `e`

Prof. Aiken CS 143 Lecture 9

21

Symbol Tables

- Consider again: `let x: Int ← 0 in e`
- Idea:
 - *Before* processing `e`, add definition of `x` to current definitions, overriding any other definition of `x`
 - *Recurse*
 - *After* processing `e`, remove definition of `x` and restore old definition of `x`
- A *symbol table* is a data structure that tracks the current bindings of identifiers

Prof. Aiken CS 143 Lecture 9

22

A Simple Symbol Table Implementation

- Structure is a stack
- Operations
 - `add_symbol(x)` push `x` and associated info, such as `x`'s type, on the stack
 - `find_symbol(x)` search stack, starting from top, for `x`. Return first `x` found or NULL if none found
 - `remove_symbol()` pop the stack
- Why does this work?

Prof. Aiken CS 143 Lecture 9

23

Limitations

- The simple symbol table works for `let`
 - Symbols added one at a time
 - Declarations are perfectly nested
- What doesn't it work for?

Prof. Aiken CS 143 Lecture 9

24

A Fancier Symbol Table

- `enter_scope()` start a new nested scope
- `find_symbol(x)` finds current `x` (or null)
- `add_symbol(x)` add a symbol `x` to the table
- `check_scope(x)` true if `x` defined in current scope
- `exit_scope()` exit current scope

We will supply a symbol table manager for your project

Prof. Aiken CS 143 Lecture 9

25

Class Definitions

- Class names can be used before being defined
- We can't check class names
 - using a symbol table
 - or even in one pass
- Solution
 - Pass 1: Gather all class names
 - Pass 2: Do the checking
- Semantic analysis requires multiple passes
 - Probably more than two

Prof. Aiken CS 143 Lecture 9

26

Types

- What is a type?
 - The notion varies from language to language
- Consensus
 - A set of values
 - A set of operations on those values
- Classes are one instantiation of the modern notion of type

Prof. Aiken CS 143 Lecture 9

27

Why Do We Need Type Systems?

Consider the assembly language fragment

```
add $r1, $r2, $r3
```

What are the types of `$r1`, `$r2`, `$r3`?

Prof. Aiken CS 143 Lecture 9

28

Types and Operations

- Certain operations are legal for values of each type
 - It doesn't make sense to add a function pointer and an integer in C
 - It does make sense to add two integers
 - But both have the same assembly language implementation!

Prof. Aiken CS 143 Lecture 9

29

Type Systems

- A language's type system specifies which operations are valid for which types
- The goal of type checking is to ensure that operations are used with the correct types
 - Enforces intended interpretation of values, because nothing else will!

Prof. Aiken CS 143 Lecture 9

30

Type Checking Overview

- Three kinds of languages:
 - *Statically typed*: All or almost all checking of types is done as part of compilation (C, Java, Cool)
 - *Dynamically typed*: Almost all checking of types is done as part of program execution (Scheme, Python)
 - *Untyped*: No type checking (machine code)

Prof. Aiken CS 143 Lecture 9

31

The Type Wars

- Competing views on static vs. dynamic typing
- Static typing proponents say:
 - Static checking catches many programming errors at compile time
 - Avoids overhead of runtime type checks
- Dynamic typing proponents say:
 - Static type systems are restrictive
 - Rapid prototyping difficult within a static type system

Prof. Aiken CS 143 Lecture 9

32

The Type Wars (Cont.)

- In practice, much code is written in statically typed languages with an “escape” mechanism
 - Unsafe casts in C, Java
- It's debatable whether this compromise represents the best or worst of both worlds

Prof. Aiken CS 143 Lecture 9

33

Types Outline

- Type concepts in COOL
- Notation for type rules
 - Logical rules of inference
- COOL type rules
- General properties of type systems

Prof. Aiken CS 143 Lecture 9

34

Cool Types

- The types are:
 - Class Names
 - `SELF_TYPE`
- The user declares types for identifiers
- The compiler infers types for expressions
 - Infers a type for *every* expression

Prof. Aiken CS 143 Lecture 9

35

Type Checking and Type Inference

- *Type Checking* is the process of verifying fully typed programs
- *Type Inference* is the process of filling in missing type information
- The two are different, but the terms are often used interchangeably

Prof. Aiken CS 143 Lecture 9

36

Rules of Inference

- We have seen two examples of formal notation specifying parts of a compiler
 - Regular expressions
 - Context-free grammars
- The appropriate formalism for type checking is logical rules of inference

Prof. Aiken CS 143 Lecture 9

37

Why Rules of Inference?

- Inference rules have the form
If Hypothesis is true, then Conclusion is true
- Type checking computes via reasoning
If E_1 and E_2 have certain types, then E_3 has a certain type
- Rules of inference are a compact notation for "If-Then" statements

Prof. Aiken CS 143 Lecture 9

38

From English to an Inference Rule

- The notation is easy to read with practice
- Start with a simplified system and gradually add features
- Building blocks
 - Symbol \wedge is "and"
 - Symbol \Rightarrow is "if-then"
 - $x:T$ is " x has type T "

Prof. Aiken CS 143 Lecture 9

39

From English to an Inference Rule (2)

If e_1 has type Int and e_2 has type Int ,
then $e_1 + e_2$ has type Int

$(e_1 \text{ has type } \text{Int} \wedge e_2 \text{ has type } \text{Int}) \Rightarrow$
 $e_1 + e_2 \text{ has type } \text{Int}$

$(e_1: \text{Int} \wedge e_2: \text{Int}) \Rightarrow e_1 + e_2: \text{Int}$

Prof. Aiken CS 143 Lecture 9

40

From English to an Inference Rule (3)

The statement

$(e_1: \text{Int} \wedge e_2: \text{Int}) \Rightarrow e_1 + e_2: \text{Int}$

is a special case of

$\text{Hypothesis}_1 \wedge \dots \wedge \text{Hypothesis}_n \Rightarrow \text{Conclusion}$

This is an inference rule

Prof. Aiken CS 143 Lecture 9

41

Notation for Inference Rules

- By tradition inference rules are written

$$\frac{\text{Hypothesis}_1 \dots \text{Hypothesis}_n}{\text{Conclusion}}$$

- Cool type rules have hypotheses and conclusions

$\vdash e:T$

- \vdash means "it is provable that ..."

Prof. Aiken CS 143 Lecture 9

42

Two Rules

$$\frac{i \text{ is an integer}}{\vdash i : \text{Int}} \quad [\text{Int}]$$
$$\frac{\vdash e_1 : \text{Int} \quad \vdash e_2 : \text{Int}}{\vdash e_1 + e_2 : \text{Int}} \quad [\text{Add}]$$

Prof. Aiken CS 143 Lecture 9

43

Two Rules (Cont.)

- These rules give templates describing how to type integers and + expressions
- By filling in the templates, we can produce complete typings for expressions

Prof. Aiken CS 143 Lecture 9

44

Example: 1 + 2

$$\frac{\frac{1 \text{ is an integer}}{\vdash 1 : \text{Int}} \quad \frac{2 \text{ is an integer}}{\vdash 2 : \text{Int}}}{\vdash 1+2 : \text{Int}}$$

Prof. Aiken CS 143 Lecture 9

45

Soundness

- A type system is *sound* if
 - Whenever $\vdash e : T$
 - Then e evaluates to a value of type T
- We only want sound rules
 - But some sound rules are better than others:

$$\frac{i \text{ is an integer}}{\vdash i : \text{Object}}$$

Prof. Aiken CS 143 Lecture 9

46

Type Checking Proofs

- Type checking proves facts $\vdash e : T$
 - Proof is on the structure of the AST
 - Proof has the shape of the AST
 - One type rule is used for each AST node
- In the type rule used for a node e :
 - Hypotheses are the proofs of types of e 's subexpressions
 - Conclusion is the type of e
- Types are computed in a bottom-up pass over the AST

Prof. Aiken CS 143 Lecture 9

47

Rules for Constants

$$\frac{}{\vdash \text{false} : \text{Bool}} \quad [\text{Bool}]$$
$$\frac{s \text{ is a string constant}}{\vdash s : \text{String}} \quad [\text{String}]$$

Prof. Aiken CS 143 Lecture 9

48

Rule for New

`new T` produces an object of type `T`
 - Ignore `SELF_TYPE` for now ...

$$\frac{}{\vdash \text{new } T : T} \quad [\text{New}]$$

Prof. Aiken CS 143 Lecture 9

49

Two More Rules

$$\frac{\vdash e : \text{Bool}}{\vdash \neg e : \text{Bool}} \quad [\text{Not}]$$

$$\frac{\vdash e_1 : \text{Bool} \quad \vdash e_2 : T}{\vdash \text{while } e_1 \text{ loop } e_2 \text{ pool} : \text{Object}} \quad [\text{Loop}]$$

Prof. Aiken CS 143 Lecture 9

50

A Problem

- What is the type of a variable reference?

$$\frac{\text{x is an identifier}}{\vdash x : ?} \quad [\text{Var}]$$

- The local, structural rule does not carry enough information to give `x` a type.

Prof. Aiken CS 143 Lecture 9

51

A Solution

- Put more information in the rules!
- A *type environment* gives types for *free* variables
 - A type environment is a function from `Object Identifiers` to `Types`
 - A variable is free in an expression if it is not defined within the expression

Prof. Aiken CS 143 Lecture 9

52

Type Environments

Let \mathcal{O} be a function from `Object Identifiers` to `Types`

The sentence

$$\mathcal{O} \vdash e : T$$

is read: Under the assumption that variables have the types given by \mathcal{O} , it is provable that the expression `e` has the type `T`

Prof. Aiken CS 143 Lecture 9

53

Modified Rules

The type environment is added to the earlier rules:

$$\frac{i \text{ is an integer}}{\mathcal{O} \vdash i : \text{Int}} \quad [\text{Int}]$$

$$\frac{\mathcal{O} \vdash e_1 : \text{Int} \quad \mathcal{O} \vdash e_2 : \text{Int}}{\mathcal{O} \vdash e_1 + e_2 : \text{Int}} \quad [\text{Add}]$$

Prof. Aiken CS 143 Lecture 9

54

New Rules

And we can write new rules:

$$\frac{O(x) = T}{O \vdash x : T} \quad [\text{Var}]$$

Prof. Aiken CS 143 Lecture 9

55

Let

$$\frac{O[T_0/x] \vdash e_1 : T_1}{O \vdash \text{let } x:T_0 \text{ in } e_1 : T_1} \quad [\text{Let-No-Init}]$$

$O[T/y]$ means O modified to return T on argument y

Note that the **let**-rule enforces variable scope

Prof. Aiken CS 143 Lecture 9

56

Notes

- The type environment gives types to the free identifiers in the current scope
- The type environment is passed down the AST from the root towards the leaves
- Types are computed up the AST from the leaves towards the root

Prof. Aiken CS 143 Lecture 9

57

Let with Initialization

Now consider **let** with initialization:

$$\frac{O \vdash e_0 : T_0 \quad O[T_0/x] \vdash e_1 : T_1}{O \vdash \text{let } x:T_0 \leftarrow e_0 \text{ in } e_1 : T_1} \quad [\text{Let-Init}]$$

This rule is weak. Why?

Prof. Aiken CS 143 Lecture 9

58

Subtyping

- Define a relation \leq on classes
 - $X \leq X$
 - $X \leq Y$ if X inherits from Y
 - $X \leq Z$ if $X \leq Y$ and $Y \leq Z$
- An improvement

$$\frac{O \vdash e_0 : T \quad T \leq T_0 \quad O[T_0/x] \vdash e_1 : T_1}{O \vdash \text{let } x:T_0 \leftarrow e_0 \text{ in } e_1 : T_1} \quad [\text{Let-Init}]$$

Prof. Aiken CS 143 Lecture 9

59

Assignment

- Both **let** rules are sound, but more programs typecheck with the second one
- More uses of subtyping:

$$\frac{O(l d) = T_0 \quad O \vdash e_1 : T_1 \quad T_1 \leq T_0}{O \vdash l d \leftarrow e_1 : T_1} \quad [\text{Assign}]$$

Prof. Aiken CS 143 Lecture 9

60

Initialized Attributes

- Let $O_C(x) = T$ for all attributes $x:T$ in class C
- Attribute initialization is similar to `let`, except for the scope of names

$$\frac{O_C(l d) = T_0 \quad O_C \setminus e_1 : T_1 \quad T_1 \leq T_0}{O_C \setminus l d : T_0 \leftarrow e_1;} \quad [\text{Attr-Init}]$$

Prof. Aiken CS 143 Lecture 9

61

If-Then-Else

- Consider:
`if e_0 then e_1 else e_2 fi`
- The result can be either e_1 or e_2
- The type is either e_1 's type or e_2 's type
- The best we can do is the smallest supertype larger than the type of e_1 or e_2

Prof. Aiken CS 143 Lecture 9

62

Least Upper Bounds

- $\text{lub}(X, Y)$, the least upper bound of X and Y , is Z if
 - $X \leq Z \wedge Y \leq Z$
 Z is an upper bound
 - $X \leq Z' \wedge Y \leq Z' \Rightarrow Z \leq Z'$
 Z is least among upper bounds
- In COOL, the least upper bound of two types is their least common ancestor in the inheritance tree

Prof. Aiken CS 143 Lecture 9

63

If-Then-Else Revisited

$$\frac{O \setminus e_0 : \text{Bool} \quad O \setminus e_1 : T_1 \quad O \setminus e_2 : T_2}{O \setminus \text{if } e_0 \text{ then } e_1 \text{ else } e_2 \text{ fi} : \text{lub}(T_1, T_2)} \quad [\text{If-Then-Else}]$$

Prof. Aiken CS 143 Lecture 9

64

Case

- The rule for `case` expressions takes a lub over all branches

$$\frac{O \setminus e_0 : T_0 \quad O[T_1 / x_1] \setminus e_1 : T_1' \quad \dots \quad O[T_n / x_n] \setminus e_n : T_n'}{O \setminus \text{case } e_0 \text{ of } x_1 : T_1 \mid e_1; \dots; x_n : T_n \mid e_n; \text{esac} : \text{lub}(T_1', \dots, T_n')} \quad [\text{Case}]$$

Prof. Aiken CS 143 Lecture 9

65

Method Dispatch

- There is a problem with type checking method calls:

$$\frac{O \setminus e_0 : T_0 \quad O \setminus e_1 : T_1 \quad \vdots \quad O \setminus e_n : T_n}{O \setminus e_0.f(e_1, \dots, e_n) : ?} \quad [\text{Dispatch}]$$

- We need information about the formal parameters and return type of f

Prof. Aiken CS 143 Lecture 9

66

Notes on Dispatch

- In Cool, method and object identifiers live in different name spaces
 - A method `foo` and an object `foo` can coexist in the same scope
- In the type rules, this is reflected by a separate mapping M for method signatures

$M(C, f) = (T_1, \dots, T_n, T_{n+1})$
 means in class C there is a method f
 $f(x_1:T_1, \dots, x_n:T_n): T_{n+1}$

Prof. Aiken CS 143 Lecture 9

67

The Dispatch Rule Revisited

$$\begin{array}{c}
 O, M \vdash e_0 : T_0 \\
 O, M \vdash e_1 : T_1 \\
 \vdots \\
 O, M \vdash e_n : T_n \\
 M(T_0, f) = (T'_1, \dots, T'_n, T'_{n+1}) \quad [\text{Dispatch}] \\
 \hline
 T_i \leq T'_i \text{ for } 1 \leq i \leq n \\
 O, M \vdash e_0.f(e_1, \dots, e_n) : T'_{n+1}
 \end{array}$$

Prof. Aiken CS 143 Lecture 9

68

Static Dispatch

- Static dispatch is a variation on normal dispatch
- The method is found in the class explicitly named by the programmer
- The inferred type of the dispatch expression must conform to the specified type

Prof. Aiken CS 143 Lecture 9

69

Static Dispatch (Cont.)

$$\begin{array}{c}
 O, M \vdash e_0 : T_0 \\
 O, M \vdash e_1 : T_1 \\
 \vdots \\
 O, M \vdash e_n : T_n \\
 T_0 \leq T \quad [\text{StaticDispatch}] \\
 M(T, f) = (T'_1, \dots, T'_n, T'_{n+1}) \\
 \hline
 T_i \leq T'_i \text{ for } 1 \leq i \leq n \\
 O, M \vdash e_0.T.f(e_1, \dots, e_n) : T'_{n+1}
 \end{array}$$

Prof. Aiken CS 143 Lecture 9

70

The Method Environment

- The method environment must be added to all rules
- In most cases, M is passed down but not actually used
 - Only the dispatch rules use M

$$\begin{array}{c}
 O, M \vdash e_1 : \text{Int} \\
 \hline
 O, M \vdash e_2 : \text{Int} \quad [\text{Add}] \\
 \hline
 O, M \vdash e_1 + e_2 : \text{Int}
 \end{array}$$

Prof. Aiken CS 143 Lecture 9

71

More Environments

- For some cases involving `SELF_TYPE`, we need to know the class in which an expression appears
- The full type environment for COOL:
 - A mapping O giving types to object id's
 - A mapping M giving types to methods
 - The current class C

Prof. Aiken CS 143 Lecture 9

72

Sentences

The form of a *sentence* in the logic is

$$O, M, C \vdash e : T$$

Example:

$$\frac{O, M, C \vdash e_1 : \text{int} \quad O, M, C \vdash e_2 : \text{int}}{O, M, C \vdash e_1 + e_2 : \text{int}} \quad [\text{Add}]$$

Prof. Aiken CS 143 Lecture 9

73

Type Systems

- The rules in this lecture are COOL-specific
 - More info on rules for [self](#) next time
 - Other languages have very different rules
- General themes
 - Type rules are defined on the structure of expressions
 - Types of variables are modeled by an environment
- Warning: Type rules are very compact!

Prof. Aiken CS 143 Lecture 9

74

One-Pass Type Checking

- COOL type checking can be implemented in a single traversal over the AST
- Type environment is passed down the tree
 - From parent to child
- Types are passed up the tree
 - From child to parent

Prof. Aiken CS 143 Lecture 9

75

Implementing Type Systems

$$\frac{O, M, C \vdash e_1 : \text{Int} \quad O, M, C \vdash e_2 : \text{Int}}{O, M, C \vdash e_1 + e_2 : \text{Int}} \quad [\text{Add}]$$

```
TypeCheck(Environment, e1 + e2) = {  
  T1 = TypeCheck(Environment, e1);  
  T2 = TypeCheck(Environment, e2);  
  Check T1 == T2 == Int;  
  return Int; }
```

Prof. Aiken CS 143 Lecture 9

76