

From: jerry okeefe jerry@ologicinc.com
Subject: Module:Arduino_Nano pin out
Date: May 21, 2026 at 11:59 AM
To: jerry Okeefe jerryok826@att.net

JO

Left Side (Pins 1–15, Antenna heading UP to USB-C)

Pin 1: D0 / TX1 (Right next to the RF Antenna)

Pin 2: D1 / RX1

Pin 3: ~RST (Reset Input)

Pin 4: GND (Ground)

Pin 5: D2

Pin 6: D3

Pin 7: D4

Pin 8: D5

Pin 9: D6

Pin 10: D7

Pin 11: D8

Pin 12: D9

Pin 13: D10

Pin 14: D11

Pin 15: D12 (Top-left corner pin right next to the USB-C port)

Right Side (Pins 16–30, USB-C heading DOWN to Antenna)

Pin 16: D13 (Top-right corner pin right next to the USB-C port)

Pin 17: +3.3V (Regulated Power Output)

Pin 18: AREF (Analog Reference Reference)

Pin 19: A0 (First Analog Input)

Pin 20: A1

Pin 21: A2

Pin 22: A3

Pin 23: A4 / SDA

Pin 24: A5 / SCL

Pin 25: A6

Pin 26: A7

Pin 27: +5V (Regulated 5V Output or USB Bus Power Input)

Pin 28: NC

Pin 29: GND (Ground 2)

Pin 30: VIN (Unregulated Power Input, bottom-right across from Pin 1)