

# Provecta™ Aromatic

## FS4078

FS4078 is an ester-based highly elastic film. It is designed to deliver great recovery and rubber-like elasticity.

### Features:

- Excellent elasticity
- Excellent recovery
- Low hardness

### Applications:

- Stretch fabric lamination; such as activewear

Hardness	Specific Gravity	Tensile Strength	Tear Strength	300% Modulus	Elongation	Melting Point
(Shore A/D) D2240	D792	(kg/cm <sup>2</sup> ) D412	(kg/cm) D624 (Die C)	(kg/cm <sup>2</sup> ) D412	(%) D412	(°C)
75A	1.19	warp: 355 weft: 375	warp: 75 weft: 80	warp: 70 weft: 60	warp: 480 weft: 505	105

The data and information provided are for reference only and are not guaranteed.

### About DingZing

DingZing is a leader in the development and production of high-performance polymers. We specialize in thermoplastic polyurethane and polyurethane products and solutions, with a focus on advanced technical films.

### DingZing Chemical Corporation

No.8-1, Pei-Lin Road, Hsiao-Kang District,  
Kaohsiung 812, Taiwan  
T +886-7-807-0166  
F +886-7-807-1616  
www.dingzing.com

**DingZing**

Science. Innovation. Collaboration.