

# Provecta™ Aromatic

## FS80HT

FS80HT is a clear technical film with a smooth glassy surface. It is easy to weld with and can be used for prints and embossment on footwear.

### Features:

- Smooth glassy surface
- Great UV resistance
- Easy to weld with

### Applications:

- Prints and embossment on footwear
- Easy to weld into different shapes
- Bag logos and decorations
- Hand bags

Hardness	Specific Gravity	Tensile Strength	Tear Strength	300% Modulus	Elongation	Melting Point
(Shore A/D) D2240	D792	(kg/cm <sup>2</sup> ) D412	(kg/cm) D624 (Die C)	(kg/cm <sup>2</sup> ) D412	(%) D412	(°C)
82A	1.20	warp: 284 weft: 249	warp: 84 weft: 87	warp: 62 weft: 56	warp: 790 weft: 872	130

The data and information provided are for reference only and are not guaranteed.

### About DingZing

DingZing is a leader in the development and production of high-performance polymers. We specialize in thermoplastic polyurethane and polyurethane products and solutions, with a focus on advanced technical films.

### DingZing Chemical Corporation

No.8-1, Pei-Lin Road, Hsiao-Kang District,  
Kaohsiung 812, Taiwan  
T +886-7-807-0166  
F +886-7-807-1616  
www.dingzing.com

**DingZing**

Science. Innovation. Collaboration.