

Provecta™ Aromatic

FS5098

FS5098 is an ester-based technical film with great hydrolysis resistance. It is designed to deliver excellent durability across a range of applications. FS5098 is ideal for outdoor and water sports goods.

Features:

- Great physical properties
- Great hydrolysis resistance
- High temperature resistance
- Good tear strength

Applications:

- Elastic tape
- Stretch fabric lamination; such as activewear

Hardness	Specific Gravity	Tensile Strength	Tear Strength	300% Modulus	Elongation	Melting Point
(Shore A/D) D2240	D792	(kg/cm ²) D412	(kg/cm) D624 (Die C)	(kg/cm ²) D412	(%) D412	(°C)
77A	1.13	warp: 454 weft: 386	warp: 111 weft: 110	warp: 104 weft: 67	warp: 612 weft: 707	152

The data and information provided are for reference only and are not guaranteed.

About DingZing

DingZing is a leader in the development and production of high-performance polymers. We specialize in thermoplastic polyurethane and polyurethane products and solutions, with a focus on advanced technical films.

DingZing Chemical Corporation

No.8-1, Pei-Lin Road, Hsiao-Kang District,
Kaohsiung 812, Taiwan
T +886-7-807-0166
F +886-7-807-1616
www.dingzing.com

DingZing

Science. Innovation. Collaboration.