

# Provecta™ Aromatic

## FS1035

FS1035 is an aromatic technical film with low hardness. It has excellent low temperature resistance and can be applied on outdoor and water sporting goods.

### Features:

- Ester-based technical film
- Low hardness
- Low temperature resistance
- Great tear strength

### Applications:

- Medical devices / products
- Outdoor / water sporting goods

Hardness	Specific Gravity	Tensile Strength	Tear Strength	300% Modulus	Elongation	Melting Point
(Shore A/D) D2240	D792	(kg/cm <sup>2</sup> ) D412	(kg/cm) D624 (Die C)	(kg/cm <sup>2</sup> ) D412	(%) D412	(°C)
74A	1.17	warp: 404 weft: 389	warp: 87 weft: 83	warp: 43 weft: 43	warp: 736 weft: 740	140

The data and information provided are for reference only and are not guaranteed.

### About DingZing

DingZing is a leader in the development and production of high-performance polymers. We specialize in thermoplastic polyurethane and polyurethane products and solutions, with a focus on advanced technical films.

### DingZing Chemical Corporation

No.8-1, Pei-Lin Road, Hsiao-Kang District,  
Kaohsiung 812, Taiwan  
T +886-7-807-0166  
F +886-7-807-1616  
www.dingzing.com

# DingZing

Science. Innovation. Collaboration.