

Provecta™ Foam

FF9S88E

Provecta™ closed-cell TPU foam is thermoplastic and easy for high-frequency welding process. It is low density and light weight-an excellent material for backpacks and protective gear.

Features:

- White TPU foam
- Good for heat-press / high-frequency welding

Applications:

- Good for light-weight watersport goods
- 3-D logos and graphics

Hardness	Specific Gravity	Tensile Strength	Tear Strength	300% Modulus	Elongation	Melting Point
(ASKER C) JIS S 6050 SRIS 0101	D792	(kg/cm ²) D412	(kg/cm) D624 (Die C)	(kg/cm ²) D412	(%) D412	(°C)
32C	0.36	warp: 32 weft: 20	warp: 12 weft: 13	warp: -- weft: 13	warp: 252 weft: 435	140

The data and information provided are for reference only and are not guaranteed.

About DingZing

DingZing is a leader in the development and production of high-performance polymers. We specialize in thermoplastic polyurethane and polyurethane products and solutions, with a focus on advanced technical films.

DingZing Corporation

No.8-1, Pei-Lin Road, Hsiao-Kang District,
Kaohsiung 812, Taiwan
T +886-7-807-0166
F +886-7-807-1616
www.dingzing.com

DingZing

Science. Innovation. Collaboration.