

Provecta™ Aromatic

FT1038

FT1038 is a low-hardness film that has great hydrolysis resistance, tear strength, and durability. It can be used on various applications for outdoor and water sporting goods.

Features:

- Ether base
- Hardness: 80A
- Good tear strength
- Great hydrolysis resistance
- Great flexibility at low temperature

Applications:

- Water sporting goods such as life jacket
- Outdoor sporting goods
- Medical devices

Hardness	Specific Gravity	Tensile Strength	Tear Strength	300% Modulus	Elongation	Melting Point
(Shore A/D) D2240	D792	(kg/cm ²) D412	(kg/cm) D624 (Die C)	(kg/cm ²) D412	(%) D412	(°C)
80A	1.13	warp: 300 weft: 325	warp: 110 weft: 115	warp: 65 weft: 65	warp: 645 weft: 665	130

The data and information provided are for reference only and are not guaranteed.

About DingZing

DingZing is a leader in the development and production of high-performance polymers. We specialize in thermoplastic polyurethane and polyurethane products and solutions, with a focus on advanced technical films.

DingZing Chemical Corporation

No.8-1, Pei-Lin Road, Hsiao-Kang District,
Kaohsiung 812, Taiwan
T +886-7-807-0166
F +886-7-807-1616
www.dingzing.com

DingZing

Science. Innovation. Collaboration.