

# Provecta™ Aromatic

## FS1008

FS1008 is an aromatic hot melt adhesive that can be applied on PU foam and fabric laminations.

### Features:

- Great physical properties
- Strong abrasion resistance
- Great tear strength
- PU foam lamination

### Applications:

- Automotive soundproofing
- Car seats
- Headrest

Hardness	Specific Gravity	Tensile Strength	Tear Strength	300% Modulus	Elongation	Melting Point
(Shore A/D) D2240	D792	(kg/cm <sup>2</sup> ) D412	(kg/cm) D624 (Die C)	(kg/cm <sup>2</sup> ) D412	(%) D412	(°C)
92A	1.21	warp: 360 weft: 350	warp: 130 weft: 130	warp: 130 weft: 140	warp: 465 weft: 440	145

The data and information provided are for reference only and are not guaranteed.

### About DingZing

DingZing is a leader in the development and production of high-performance polymers. We specialize in thermoplastic polyurethane and polyurethane products and solutions, with a focus on advanced technical films.

### DingZing Chemical Corporation

No.8-1, Pei-Lin Road, Hsiao-Kang District,  
Kaohsiung 812, Taiwan  
T +886-7-807-0166  
F +886-7-807-1616  
www.dingzing.com

# DingZing

Science. Innovation. Collaboration.