

# Provecta™ Aromatic

## FT1014

FT1014 is a high-hardness film that has great hydrolysis resistance, tear strength, and durability. It can be used on various applications for outdoor and water sporting goods.

### Features:

- Hardness: 70D
- Ether base
- Great hydrolysis resistance
- High temperature resistance
- Great tear strength
- Oil resistance

### Applications:

- Water sporting goods
- Outdoor sporting goods
- Medical devices

Hardness	Specific Gravity	Tensile Strength	Tear Strength	300% Modulus	Elongation	Melting Point
(Shore A/D) D2240	D792	(kg/cm <sup>2</sup> ) D412	(kg/cm) D624 (Die C)	(kg/cm <sup>2</sup> ) D412	(%) D412	(°C)
70D	1.19	warp: 518 weft: 458	warp: 236 weft: 232	warp: 304 weft: 347	warp: 319 weft: 401	175

The data and information provided are for reference only and are not guaranteed.

### About DingZing

DingZing is a leader in the development and production of high-performance polymers. We specialize in thermoplastic polyurethane and polyurethane products and solutions, with a focus on advanced technical films.

### DingZing Chemical Corporation

No.8-1, Pei-Lin Road, Hsiao-Kang District,  
Kaohsiung 812, Taiwan  
T +886-7-807-0166  
F +886-7-807-1616  
www.dingzing.com

**DingZing**

Science. Innovation. Collaboration.