






PLAN FILL PATTERN	FLOOR USAGE	SUPERIMPOSED a. DEAD LOAD b. GRAV/SEISMIC	LIVE LOAD	VIBRATION CRITERIA
	OFFICE SPACE	a. 34 PSF b. 24 PSF	100 PSF RED.	SENSITIVE EQUIP V <16,000 microin/sec @ 75 steps/min
	LAB SPACE	a. 44 PSF b. 34 PSF	100 PSF RED.	SENSITIVE EQUIP V <2,000 microin/sec @ 75 steps/min
	BALCONY	a. 75 PSF b. 75 PSF	100 PSF RED.	N/A

CLADDING LOADS LEGEND


PLAN LINEWORK STYLE	CLADDING DESCRIPTION	SUPERIMPOSED DEAD LOAD
	FACADE	570 PLF (15 PSF x 38'-0" HEIGHT)
	FACADE	225 PLF (15 PSF x 15'-0" HEIGHT)

55 Second Street, Suite 600
San Francisco, CA 94105
(415) 568-4400

Research Facilities Design
LABORATORY PLANNING
3965 Fifth Avenue, Suite 300
San Diego, CA 92103
(619) 297-0150

Colin Gordon Associates
ACOUSTICS
150 North Hill Drive, Suite 15
Brisbane, CA 94005
(650) 570-0350

Reviewed by: Gini Krippner
Date: Gini Krippner 7/25/11
Project #: 900020

[illegible]

1/16" = 1'-0"

\$0.05

DRAWING NUMBER

