








PLAN FILL PATTERN	FLOOR USAGE	SUPERIMPOSED a. DEAD LOAD b. GRAV/SEISMIC	LIVE LOAD	VIBRATION CRITERIA
	OFFICE SPACE	a. 38 PSF b. 28 PSF	100 PSF RED.	SENSITIVE EQUIP V <16,000 microin/sec @ 75 steps/min/Hz
	LAB SPACE	a. 48 PSF b. 48 PSF	100 PSF RED.	SENSITIVE EQUIP V <4,000 microin/sec @ 75 steps/min
	BREEZE WAY	a. 90 PSF b. 90 PSF	150 PSF UNRED.	N/A


PLAN LINEWORK STYLE	CLADDING DESCRIPTION	SUPERIMPOSED DEAD LOAD
	FACADE	225 PLF (15 PSF x 15'-0" HEIGHT)
	PRE-CAST PANEL	933 PLF (62.5 PSF x 15'-0" HEIGHT)

PLAN LINEWORK STYLE	CLADDING DESCRIPTION	SUPERIMPOSED DEAD LOAD
	FACADE	225 PLF (15 PSF x 15'-0" HEIGHT)
	PRE-CAST PANEL	933 PLF (62.5 PSF x 15'-0" HEIGHT)


Research Facilities Design
LABORATORY PLANNING
3965 Fifth Avenue, Suite 300
San Diego, CA 92103
(619) 297-0159

150 North Hill Drive, Suite 15
Brisbane, CA 94005
(650) 570-0350

Reviewed by: Gini Krippner
Date: Gini Krippner 1/25/11
Project #: 900020

SEALS AND SIGNATURES

KEYPLAN


$$1/16'' = 1'-0''$$

\$0.04

DRAWING NUMBER

