




AIPC 11-20-10-20 EXTERIOR PLACARDS AND MARKINGS SIDE,RH

Sheet 1




Effectivity: ALL






Sheet 2











Effectivity: ALL





Sheet 4





Effectivity: ALL





FIG ITEM	PART NUMBER	NOMENCLATURE	EFFECT. USAGE CODE	UNI. PER ASSY
		1234567 INDEX		
20 -001A		EXTERIOR PLACARDS AND MARKINGS SIDE,RH		1
010A	FGFB090100020	.MARK. TOILET SERVICE PANEL OPT TO F1061-08	From: 001 To: 400	1
015A	FGFB090100020	.MARK. TOILET SERVICE PANEL OPT TO F1061-08 (WITHOUT M-OPT 0707 AND M- OPT 0038)	From: 001 To: 400	1
020A	FGFB090100021	.MARK. PRESSURE FUELING PANEL	From: 001 To: 400	1
020B	F7XC112010043	.MARK. REFUELING PANEL	From: 002 To: 002 From: 004 To: 022 From: 026 To: 026	1
020C	F7XC112010043A1	.MARK. REFUELING PANEL	From: 001 To: 400	1
030A	FGFB090100048	.MARK. TOILET DRAIN	From: 001 To: 400	1
035A	FGFB090100048	.MARK. TOILET DRAIN (WITHOUT M-OPT 0707 AND M- OPT 0038)	From: 001 To: 400	1
040A	FGFB090100058	.PLAC. VENT / DRAIN	From: 001 To: 400	1
-050A	F7XC112010019	.MARK. DRAIN	From: 001 To: 400	1
060A	F7XC112010020	.MARK. DRAIN	From: 001 To: 400	1
090A	F7XC112010024	.MARK. DRAIN	From: 001 To: 400	1
100A	F7XC112010030	.PLAC. DO NOT OVER FILL	From: 001 To: 400	2
105A	F7XC112010038	.PLAC. GROUND SERVICING MANUAL	From: 001 To: 001 From: 002 To: 002 AFTER SBF7X0043 From: 003 To: 003 From: 004 To: 022 AFTER SBF7X0043 From: 023 To: 025 From: 026 To: 026 AFTER SBF7X0043 From: 027 To: 400	1
110A	F7XC112010032	.PLAC. TOILET FILLING UP	From: 001 To: 400	2
120A	F7XC112010035	.PLAC. FULL LEAK POTABLE WATER	From: 001 To: 400	1
130A	F7XC112010036	.MARK. POTABLE WATER	From: 001 To: 400	1
140A	F7XC112010037	.PLAC. POTABLE WATER	From: 001 To: 400	1

Effectivity: ALL





FIG ITEM	PART NUMBER	NOMENCLATURE	EFFECT. USAGE CODE	UNI. PER ASSY
		1234567 INDEX		
150A	F7XC112010040	.MARK. PUSH TO OPEN	From: 001 To: 400	1
160A	F7XC112010044A1	.PLAC. FUEL TYPES	From: 001 To: 091	1
160B	F7XC112010044A2	.PLAC. FUEL TYPES	From: 001 To: 112	1
160C	F7XC112010044A3	.PLAC. FUEL TYPES	From: 001 To: 266 From: 283 To: 400	1
160D	F7XC112010044A4	.PLAC. FUEL TYPES	From: 001 To: 400	1
170A	F7XC112010045A1	.PLAC. FUELING	From: 001 To: 200 From: 202 To: 219 From: 221 To: 228	1
170B	F7XC112010045A2	.PLAC. FUELING	From: 001 To: 228 AFTER SBF7X0328 From: 229 To: 400	1
175A	F7XC112010054	.PLAC. GROUNDING	From: 001 To: 001 From: 002 To: 002 AFTER SBF7X0043 From: 003 To: 003 From: 004 To: 022 AFTER SBF7X0043 From: 023 To: 025 From: 026 To: 026 AFTER SBF7X0043 From: 027 To: 400	1
180A	F7XC112010047	.MARK. GROUND PNEUMATIC POWER	From: 001 To: 400	1
190A	F7XC112010048	.PLAC. PNEUMATIC VALVE	From: 001 To: 171	1
190B	F7XC112010048A1	.PLACARD PNEUMATIC VALVE	From: 172 To: 400	1
200A	F7XC112010049	.PLAC. PNEUMATIC GPU	From: 001 To: 400	1
210A	F7XC112010050	.MARK. ELECTRICAL POWER	From: 001 To: 400	1
220A	F7XC112010051	.PLAC. OVERVOLTAGE	From: 001 To: 200 From: 202 To: 219 From: 221 To: 228	1
220B	F7XC112010051A1	.PLAC. GPU	From: 001 To: 228 AFTER SBF7X0334 From: 229 To: 400	1
223A	F7XC112010116	.PLAC. ON	From: 001 To: 228 AFTER SBF7X0334 From: 229 To: 400	1

Effectivity: ALL

Rev. Date: FEB 01/2018





FIG ITEM	PART NUMBER	NOMENCLATURE	EFFECT. USAGE	UNI. PER ASSY
		1234567 INDEX	CODE	ASSY
225A	F7XC112010117	.PLAC. OFF	From: 001 To: 228 AFTER SBF7X0334 From: 229 To: 400	1
230A	F7XC112010052	.PLAC. ELECTRICAL GPU	From: 001 To: 200 From: 202 To: 219 From: 221 To: 228	1
230B	F7XC112010052A1	.PLAC. ELECTRICAL GPU	From: 001 To: 228 AFTER SBF7X0334 From: 229 To: 400	1
235A	F7XC112010115	.PLAC.CAUTION GPU	From: 001 To: 228 AFTER SBF7X0334 From: 229 To: 400	1
240A	F7XC112010053	.PLAC. BONDING INTERFACE	From: 001 To: 400	1
250A	F7XC112010073	.PLAC. NOSE CONE R/H	From: 001 To: 400	1
260A	F7XC112010079	.MARK. CVR-DFDR OPT TO F1061N-197	From: 001 To: 400	1
270A	F7XC112010090	(NP) .ANTI PEELING TAPE MADE FROM SJ8591	From: 001 To: 400	1
280A	F7XC112010017	.MARK. HYDROPHOBIC COATING	From: 001 To: 400	1
290A	F7XC112010018	.MARK. NOZZLE ORIENTATION	From: 001 To: 400	1

Effectivity: ALL Rev. Date: FEB 01/2018

11-20-10-20