

# OGC API - Common - Part 2

## *Geospatial Data*

# Open Geospatial Consortium

Submission Date: <yyyy-mm-dd>

Approval Date: <yyyy-mm-dd>

Publication Date: 2021-08-06

External identifier of this OGC® document: <http://www.opengis.net/doc/IS/ogcapi-common-2/1.0>

Internal reference number of this OGC® document: 20-024

Version: 0.0.9

Category: OGC® Implementation Standard

Editor: Charles Heazel

## OGC API - Common - Part 2: Geospatial Data

### Copyright notice

Copyright © 2021 Open Geospatial Consortium

To obtain additional rights of use, visit <http://www.opengeospatial.org/legal/>

### Warning

This document is not an OGC Standard. This document is distributed for review and comment. This document is subject to change without notice and may not be referred to as an OGC Standard.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Document type: OGC® Implementation Standard

Document stage: Draft

Document language: English

## License Agreement

Permission is hereby granted by the Open Geospatial Consortium, ("Licensor"), free of charge and subject to the terms set forth below, to any person obtaining a copy of this Intellectual Property and any associated documentation, to deal in the Intellectual Property without restriction (except as set forth below), including without limitation the rights to implement, use, copy, modify, merge, publish, distribute, and/or sublicense copies of the Intellectual Property, and to permit persons to whom the Intellectual Property is furnished to do so, provided that all copyright notices on the intellectual property are retained intact and that each person to whom the Intellectual Property is furnished agrees to the terms of this Agreement.

If you modify the Intellectual Property, all copies of the modified Intellectual Property must include, in addition to the above copyright notice, a notice that the Intellectual Property includes modifications that have not been approved or adopted by LICENSOR.

THIS LICENSE IS A COPYRIGHT LICENSE ONLY, AND DOES NOT CONVEY ANY RIGHTS UNDER ANY PATENTS THAT MAY BE IN FORCE ANYWHERE IN THE WORLD.

THE INTELLECTUAL PROPERTY IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE DO NOT WARRANT THAT THE FUNCTIONS CONTAINED IN THE INTELLECTUAL PROPERTY WILL MEET YOUR REQUIREMENTS OR THAT THE OPERATION OF THE INTELLECTUAL PROPERTY WILL BE UNINTERRUPTED OR ERROR FREE. ANY USE OF THE INTELLECTUAL PROPERTY SHALL BE MADE ENTIRELY AT THE USER'S OWN RISK. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR ANY CONTRIBUTOR OF INTELLECTUAL PROPERTY RIGHTS TO THE INTELLECTUAL PROPERTY BE LIABLE FOR ANY CLAIM, OR ANY DIRECT, SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM ANY ALLEGED INFRINGEMENT OR ANY LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR UNDER ANY OTHER LEGAL THEORY, ARISING OUT OF OR IN CONNECTION WITH THE IMPLEMENTATION, USE, COMMERCIALIZATION OR PERFORMANCE OF THIS INTELLECTUAL PROPERTY.

This license is effective until terminated. You may terminate it at any time by destroying the Intellectual Property together with all copies in any form. The license will also terminate if you fail to comply with any term or condition of this Agreement. Except as provided in the following sentence, no such termination of this license shall require the termination of any third party end-user sublicense to the Intellectual Property which is in force as of the date of notice of such termination. In addition, should the Intellectual Property, or the operation of the Intellectual Property, infringe, or in LICENSOR's sole opinion be likely to infringe, any patent, copyright, trademark or other right of a third party, you agree that LICENSOR, in its sole discretion, may terminate this license without any compensation or liability to you, your licensees or any other party. You agree upon termination of any kind to destroy or cause to be destroyed the Intellectual Property together with all copies in any form, whether held by you or by any third party.

Except as contained in this notice, the name of LICENSOR or of any other holder of a copyright in all or part of the Intellectual Property shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Intellectual Property without prior written authorization of LICENSOR or such copyright holder. LICENSOR is and shall at all times be the sole entity that may authorize you or any third party to use certification marks, trademarks or other special designations to indicate compliance with any LICENSOR standards or specifications. This Agreement is governed by the laws of the Commonwealth of Massachusetts. The application to this Agreement of the United Nations Convention on Contracts for the International Sale of Goods is hereby expressly excluded. In the event any provision of this Agreement shall be deemed unenforceable, void or invalid, such provision shall be modified so as to make it valid and enforceable, and as so modified the entire Agreement shall remain in full force and effect. No decision, action or inaction by LICENSOR shall be construed to be a waiver of any rights or remedies available to it.

# Table of Contents

1. Introduction	5
2. Scope	7
3. Conformance	8
4. References	9
5. Terms, Definitions and Abbreviated Terms	11
5.1. Terms and Definitions	11
5.2. Abbreviated terms	13
6. Conventions	14
6.1. Identifiers	14
6.2. Link relations	14
6.3. Geometry	15
6.3.1. Spatial Geometry	15
6.3.2. Temporal Geometry	15
6.4. Coordinate Reference Systems	16
6.5. Timezones	16
6.6. API definition	16
6.6.1. General remarks	16
6.6.2. Role of OpenAPI	17
6.6.3. References to OpenAPI components in normative statements	17
6.6.4. Reusable OpenAPI components	17
7. Overview	18
7.1. Collections	18
7.2. Views	18
8. Requirements Class "Collections"	20
8.1. Collections	20
8.1.1. Operation	20
8.1.2. Response	21
8.1.3. Error situations	24
8.2. Resource Collection	24
8.2.1. Operation	24
8.2.2. Response	25
8.2.3. Error Situations	25
8.2.4. Collection Resource Definition	25
9. Requirements Class "Simple Query"	31
9.1. Parameter Requirements	31
9.1.1. Parameter bbox	31
9.1.2. Parameter datetime	34
9.1.3. Parameter limit	36

9.2. Target Resource Requirements . . . . .	38
9.2.1. Spatial and Temporal Filtering . . . . .	38
9.2.2. Volumetric Filtering . . . . .	39
9.2.3. Paged Response . . . . .	40
10. Encoding Requirements Classes . . . . .	41
10.1. Overview . . . . .	41
10.2. Requirement Class "HTML" . . . . .	41
10.3. Requirement Class "JSON" . . . . .	42
11. Media Types . . . . .	44
12. Security Considerations . . . . .	45
Annex A: Abstract Test Suite (Normative) . . . . .	46
A.1. Introduction . . . . .	46
A.2. Conformance Class Collections . . . . .	46
A.2.1. Collections {root}/collections Tests . . . . .	46
A.2.2. Collection {root}/collections/{collectionId} Tests . . . . .	49
A.2.3. Simple Query Tests . . . . .	51
A.3. Conformance Class Simple query . . . . .	51
A.3.1. Bounding Box Tests . . . . .	52
A.3.2. Date-Time Tests . . . . .	54
A.3.3. Limit Tests . . . . .	55
A.4. Conformance Class JSON . . . . .	57
A.4.1. GeoJSON Definition . . . . .	57
A.4.2. GeoJSON Content . . . . .	58
A.5. Conformance Class HTML . . . . .	58
A.5.1. HTML Definition . . . . .	58
A.5.2. HTML Content . . . . .	59
Annex B: Examples (Informative) . . . . .	60
B.1. Collections Response Example . . . . .	60
B.2. Collection Object Examples . . . . .	60
B.2.1. Building Collection . . . . .	60
Annex C: Revision History . . . . .	62
Annex D: Glossary . . . . .	63
Annex E: Bibliography . . . . .	65
Annex F: HTTP Status Codes . . . . .	66
Annex G: OGC Web API Guidelines . . . . .	67

# Chapter 1. Introduction

## i. Abstract

The OGC has extended their suite of standards to include Resource Oriented Architectures and Web APIs. In the course of developing these standards, some practices proved to be common across multiple OGC Web API standards. These common practices are documented in the OGC API - Common Multi-Part Standard. OGC API - Common standards serve as reusable building-blocks. Standards developers will use these building-blocks in the construction of OGC Web API Standards. The result is a modular suite of coherent API standards which can be adapted by a system designer for the unique requirements of their system.

Spatial data is rarely considered as a single entity. [Feature Collections](#), [Coverages](#), [Data Sets](#), they are all aggregations of [Spatial](#) or [Temporal](#) Things. It stands to reason that an OGC Web API would also expose its' holdings as aggregates of spatial resources.

The purpose of the OGC API - Common - Part 2: Geospatial Data Standard (API-GeoData) is to provide a common connection between the API landing page and resource-specific details. That connection includes metadata which describes the hosted geospatial resources, common parameters for selecting subsets of those resources, and URI templates for identifying the above.

This common connection is sufficient to start the client down the path to resource discovery. Developers of OGC Web API standards extend these first steps with details specific to the resources they intend to expose.

## ii. Keywords

The following are keywords to be used by search engines and document catalogues.

ogcdoc, OGC document, geographic information, spatial data, spatial things, dataset, distribution, API, json, html, OpenAPI, REST, Common

## iii. Preface

### OGC Declaration

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. The Open Geospatial Consortium Inc. shall not be held responsible for identifying any or all such patent rights.

Recipients of this document are requested to submit, with their comments, notification of any relevant patent claims or other intellectual property rights of which they may be aware that might be infringed by any implementation of the standard set forth in this document, and to provide supporting documentation.

## iv. Submitting organizations

The following organizations submitted this Document to the Open Geospatial Consortium (OGC):

- Heazeltech LLC
- CubeWerx Inc.

## v. Submitters

All questions regarding this submission should be directed to the editors or the submitters:

Name	Affiliation
Chuck Heazel ( <i>editor</i> )	Heazeltech
Panagiotis (Peter) A. Vretanos	CubeWerx Inc.
others	TBD

# Chapter 2. Scope

The OGC API - Common Standard is a multi-part standard which defines a standard set of modules which can be used to build resource and mission-specific Web API standards. The OGC API - Common - Part 2: Geospatial Data Standard (API-GeoData) is one of those modules.

Geospatial resources are typically packaged into sets or collections of related resources. A single API may host a large number of collections. This API-Geodata standard provides a means of organizing these collections and defines operations for discovering and selecting individual collections.

API-GeoData does not specify the nature of the geospatial data that make up a collection. Rather, it provides a basic capability which should be applicable to any geospatial resource type. Additional OGC Web API standards extend this foundation to define resource-specific capabilities.



# Chapter 3. Conformance

Conformance with this standard shall be checked using the tests specified in Annex A (normative) of this document. The framework, concepts, and methodology for testing, and the criteria to claim conformance are specified in the [OGC Compliance Testing Policies and Procedures](#) and the [OGC Compliance Testing](#) web site.

The one Standardization Target for this standard is Web APIs.

API-GeoData defines an API module intended for re-use by other OGC Web API standards. It is anticipated that this standard will only be implemented through inclusion in other standards. Therefore, all the relevant abstract tests in Annex A shall be included or referenced in the Abstract Test Suite for each separate standard that normatively references this standard.

This standard identifies five [conformance classes](#). The conformance classes implemented by an OGC API are advertised through the [/conformance](#) path on the landing page. Each conformance class is defined by one [requirements class](#). The tests in Annex A are organized by Requirements Class. So an implementation of the *Collections* conformance class must pass all tests specified in Annex A for the *Collections* requirements class.

The requirements classes for API-GeoData are:

- [Collections](#)
- [Simple Query](#)
- [Subsetting](#)
- [Encodings](#)
  - [HTML](#)
  - [JSON](#)

The [Collections Requirements Class](#) defines a common means to describe and access [collections](#) of [spatial resources](#).

The [Simple Query Requirements Class](#) defines basic query parameters for the selection of individual [collections](#) of [spatial resources](#).

The [Subsetting Requirements Class](#) extends the [Simple Query Requirements Class](#) to support selection of individual [collections](#) of [spatial resources](#) in an arbitrary n-dimensional space.

The [Collections Requirements Class](#) does not mandate a specific encoding or format for representing resources. The [HTML](#) and [JSON](#) requirements classes specify representations for these resources in commonly used encodings for spatial data on the web.

The structure and organization of a collection of spatial resources is very much dependent on the nature of that resource and the expected access patterns. This is information which cannot be specified in a common manner. This Standard specifies the requirements necessary to discover and understand a generic collection and its' contents. Requirements governing a specific type of resource are specified in resource-specific OGC API standards.

# Chapter 4. References

The following normative documents contain provisions that, through reference in this text, constitute provisions of this document. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. For undated references, the latest edition of the normative document referred to applies.

- Rescorla, E.: **IETF RFC 2818, HTTP Over TLS**, <http://tools.ietf.org/rfc/rfc2818.txt>
- Klyne, G., Newman, C.: **IETF RFC 3339, Date and Time on the Internet: Timestamps**, <http://tools.ietf.org/rfc/rfc3339.txt>
- Berners-Lee, T., Fielding, R., Masinter, L.: **IETF RFC 3986, Uniform Resource Identifier (URI): Generic Syntax**, <http://tools.ietf.org/rfc/rfc3986.txt>
- Greforio, J., Fielding, R., Hadley, M., Nottingham, M., Orchard, D.: **IETF RFC 6570, URI Template**, <https://tools.ietf.org/html/rfc6570>
- Fielding, R., Reschke, J.: **IETF RFC 7230, Hypertext Transfer Protocol (HTTP/1.1): Message Syntax and Routing**, <https://tools.ietf.org/rfc/rfc7230.txt>
- Fielding, R., Reschke, J., Schaub, J.: **IETF RFC 7231, Hypertext Transfer Protocol (HTTP/1.1): Semantics and Content**, <https://tools.ietf.org/rfc/rfc7231.txt>
- Fielding, R., Reschke, J.: **IETF RFC 7232, Hypertext Transfer Protocol (HTTP/1.1): Conditional Requests**, <https://tools.ietf.org/rfc/rfc7232.txt>
- Fielding, R., Reschke, J.: **IETF RFC 7235, Hypertext Transfer Protocol (HTTP/1.1): Authentication**, <https://tools.ietf.org/rfc/rfc7235.txt>
- Reschke, J.: **IETF RFC 7538, The Hypertext Transfer Protocol Status Code 308 (Permanent Redirect)**, <https://tools.ietf.org/rfc/rfc7538.txt>
- Bray, T.: **IETF RFC 8259, The JavaScript Object Notation (JSON) Data Interchange Format**, <http://tools.ietf.org/rfc/rfc8259.txt>\* Nottingham, M.: **IETF RFC 8288, Web Linking**, <http://tools.ietf.org/rfc/rfc8288.txt>
- Nottingham, M.: **IETF RFC 8288, Web Linking**, <http://tools.ietf.org/rfc/rfc8288.txt>
- ISO 8601-1:2019, **Date and time - Representations for information interchange - Part 1: Basic rules**
- ISO 19111:2019, **Geographic information — Spatial referencing by coordinates**
- ISO 15836-2:2019, **Information and documentation — The Dublin Core metadata element set — Part 2: DCMI Properties and classes**
- ISO 19108:2002/Cor 1:2006, **Geographic information — Temporal schema**
- json-schema-org: **JSON Schema**, September 2019, <https://json-schema.org/specification.html>
- Open API Initiative: **OpenAPI Specification 3.0.3**, <https://github.com/OAI/OpenAPI-Specification/blob/master/versions/3.0.3.md>
- Whiteside, A., Greenwood, J.: **OGC Web Services Common Standard**, version 2.0, [OGC 06-121r9](https://www.ogc.org/standards/ows)
- Herring, J.: **OGC 06-104r4, OpenGIS® Implementation Standard for Geographic information - Simple feature access - Part 2: SQL option**

[http://portal.opengeospatial.org/files/?artifact\\_id=25354](http://portal.opengeospatial.org/files/?artifact_id=25354)

- van den Brink, L., Portele, C., Vretanos, P.: OGC 10-100r3, **Geography Markup Language (GML) Simple Features Profile**, [http://portal.opengeospatial.org/files/?artifact\\_id=42729](http://portal.opengeospatial.org/files/?artifact_id=42729)
- Heazel, C.: OGC 19-072, **OGC API - Common - Part 1: Core**, <http://docs.opengeospatial.org/DRAFTS/19-072.html>
- W3C: **HTML5, W3C Recommendation**, <http://www.w3.org/TR/html5/>
- **Schema.org**: <http://schema.org/docs/schemas.html>
- W3C Recommendation: **XML Schema Part 2: Datatypes Second Edition**, 28 October 2004, <https://www.w3.org/TR/xmlschema-2/>

# Chapter 5. Terms, Definitions and Abbreviated Terms

## 5.1. Terms and Definitions

This document uses the terms defined in Sub-clause 5 of [OGC API - Common - Part 1: Core](#) (OGC 19-072), which is based on the ISO/IEC Directives, Part 2, Rules for the structure and drafting of International Standards. In particular, the word "shall" (not "must") is the verb form used to indicate a requirement to be strictly followed to conform to this standard.

For the purposes of this document, the following additional terms and definitions apply.

- **Collection**

A body of resources that belong or are used together. An aggregate, set, or group of related resources. (OGC 20-024)

- **Coverage**

feature that acts as a function to return values from its range for any direct position within its spatiotemporal domain, as defined in OGC Abstract Topic 6 ([OGC 09-146r6](#))

- **Dataset**

A collection of data, published or curated by a single agent, and available for access or download in one or more representations. ([DCAT](#))

- **Distribution**

A specific representation of a [dataset](#). A [dataset](#) might be available in multiple serializations that may differ in various ways, including natural language, media-type or format, schematic organization, temporal and spatial resolution, level of detail or profiles (which might specify any or all of the above). ([DCAT](#))

EXAMPLE: a downloadable file, an RSS feed or an API.

- **Extent**

The area covered by something. Within this document, we always imply spatial extent; e.g. size or shape that may be expressed using coordinates. ([W3C/OGC Spatial Data on the Web Best Practice](#))

- **Feature**

abstraction of real world phenomena ([ISO 19101-1:2014](#))

<b>NOTE:</b>	More details about the term <b>feature</b> may be found in the <a href="#">W3C/OGC Spatial Data on the Web Best Practice</a> in the section <a href="#">Spatial Things, Features and Geometry</a> .
--------------	---

- **Feature Collection**

a set of **Features** from a **dataset**

- **Geometry**

An ordered set of  $n$ -dimensional points in a given coordinate reference system. ([W3C/OGC Spatial Data on the Web Best Practice](#))

- **Resource**

entity that might be identified ([Dublin Core Metadata Initiative - DCMI Metadata Terms](#))

<b>NOTE:</b>	The term "resource", when used in the context of an OGC Web API standard, should be understood to mean a <a href="#">Web Resource</a> unless otherwise indicated.
--------------	---

- **Resource Type**

the definition of a type of [resource](#). Resource types are re-usable components which are independent of where the resource resides in the API.

<b>NOTE:</b>	Resource types are re-usable components that are independent of where the resource resides in the API."
--------------	---

- **Spatial Resource**

the [resources](#) which we usually think of as Geospatial Data. A [Spatial Thing](#). ([OGC 19-072](#))

- **Spatial Thing**

anything with spatial extent, (i.e. size, shape, or position) and is a combination of the real-world phenomenon and its abstraction. ([W3C/OGC Spatial Data on the Web Best Practice](#))

- **Temporal Coordinate System**

temporal reference system based on an interval scale on which distance is measured as a multiple of a single unit of time. ([ISO 19108](#))

- **Temporal Position**

location relative to a temporal reference system ([ISO 19108](#))

- **Temporal Reference System**

reference system against which time is measured ([ISO 19108](#))

- **Temporal Resource**

the [resources](#) which we usually think of as time and date focused data. A [Temporal Thing](#). ([OGC 19-072](#))

- **Temporal Thing**

Anything with temporal extent, i.e. duration. e.g. the taking of a photograph, a scheduled meeting, a GPS time-stamped track-point. ([W3C Basic Geo](#))

- **Web API**

API using an architectural style that is founded on the technologies of the Web. ([W3C Data on the Web Best Practices](#))

- **Web Resource**

a [resource](#) that is identified by an URI.

## 5.2. Abbreviated terms

### **API**

Application Programming Interface

### **CORS**

Cross-Origin Resource Sharing

### **CRS**

Coordinate Reference System

### **HTTP**

Hypertext Transfer Protocol

### **HTTPS**

Hypertext Transfer Protocol Secure

### **IANA**

Internet Assigned Numbers Authority

### **OGC**

Open Geospatial Consortium

### **TRS**

Temporal Coordinate Reference System

### **URI**

Uniform Resource Identifier

### **YAML**

YAML Ain't Markup Language

# Chapter 6. Conventions

All conventions described in the [OGC API - Common Part 1: Core Standard](#) are also applicable to this API-Common Part 2: Geospatial Data Standard except where modified in the following section.

## 6.1. Identifiers

The normative provisions in this standard are denoted by the URI <http://www.opengis.net/spec/ogcapi-common-2/1.0>.

All [Requirements](#), [Requirements Modules](#) and [Conformance Modules](#) that appear in this document are denoted by partial URIs that are relative to this base.

Additional information about the use of Identifiers in API-Common is provided in the [OGC API - Common Users Guide](#).

## 6.2. Link relations

[RFC 8288 \(Web Linking\)](#) is used by this standard to express relationships between resources. Link relation types from the [IANA Link Relations Registry](#) are used wherever possible. Additional link relation types are registered with the [OGC Naming Authority](#).

The link relationships used in API-Common GeoData are described in [Table 1](#). Additional relation types may be used if the implementation warrants it.

Table 1. Link Relations

Link Relation	Purpose
<a href="#">alternate</a>	Refers to a substitute for this context [IANA]. Refers to a representation of the current resource which is encoded using another media type (the media type is specified in the <a href="#">type</a> link attribute).
<a href="http://www.opengis.net/def/rel/ogc/1.0/data-meta">http://www.opengis.net/def/rel/ogc/1.0/data-meta</a>	Identifies general metadata for the context (dataset or collection) that is primarily intended for consumption by machines.
<a href="#">collection</a>	The target IRI points to a resource which represents the collection resource for the context IRI. [IANA]
<a href="http://www.opengis.net/def/rel/ogc/1.0/conformance">http://www.opengis.net/def/rel/ogc/1.0/conformance</a>	Refers to a resource that identifies the specifications that the link's context conforms to. [OGC]
<a href="http://www.opengis.net/def/rel/ogc/1.0/data">http://www.opengis.net/def/rel/ogc/1.0/data</a>	Indicates that the link's context is a distribution of a dataset that is an API and refers to the root resource of the dataset in an API. [OGC]
<a href="#">describedby</a>	Refers to a resource providing information about the link's context.[IANA] Links to external resources which further describe the subject resource

Link Relation	Purpose
<a href="#">item</a>	The target IRI points to a resource that is a member of the collection represented by the context IRI. [IANA]
<a href="http://www.opengis.net/def/rel/ogc/1.0/items">http://www.opengis.net/def/rel/ogc/1.0/items</a>	Refers to a resource that is comprised of members of the collection represented by the link's context. [OGC]
<a href="#">license</a>	Refers to a license associated with this context. [IANA]
<a href="#">self</a>	Conveys an identifier for the link's context. [IANA] A link to another representation of this resource.
<a href="#">service-desc</a>	Identifies service description for the context that is primarily intended for consumption by machines. [IANA] API definitions are considered service descriptions.
<a href="#">service-doc</a>	Identifies service documentation for the context that is primarily intended for human consumption. [IANA]
<a href="#">service-meta</a>	Identifies general metadata for the context that is primarily intended for consumption by machines. [IANA]

Additional information on the use of link relationships is provided in the [OGC API - Common Users Guide](#).

## 6.3. Geometry

### 6.3.1. Spatial Geometry

Standardized concepts for spatial characteristics are needed in order to share geographic information between applications. Concepts for shape (geometry) are key. These concepts are standardized in [ISO 19107](#).

The spatial geometry used in the OGC API - Common Standards is documented in the [GML Simple Features Profile](#) Standard. This Profile defines a subset of the ISO 19107 geometry which is aligned with the OGC [Simple Features for SQL](#) Standard. That geometry includes: Point, Curve (LineString), Surface (Polygon), MultiPoint, MultiCurve, and MultiSurface.

### 6.3.2. Temporal Geometry

Standardized concepts are also needed for temporal characteristics. The temporal geometry used in the API-Common Standards is defined in [ISO 19108](#). Only a subset of this geometry is used. Specifically:

- TM\_Instant - a point representing position in time
- TM\_Period - a one dimensional geometric primitive representing an extent in time and bounded by two different temporal positions (TM\_Instant)



## 6.4. Coordinate Reference Systems

As discussed in Chapter 9 of the [W3C/OGC Spatial Data on the Web Best Practices document](#), the ability to express and share location in a consistent way is one of the most fundamental aspects of publishing geographic data. To do so, it is important to be clear about the coordinate reference system (CRS) within which the coordinates are expressed.

This OGC API - Common Geospatial Data standard does not mandate the use of a specific coordinate reference system. However, if no CRS is specified, the following default coordinate reference systems apply for spatial geometries.

- CRS84 - WGS 84 longitude and latitude without height
- CRS84h - WGS 84 longitude and latitude with ellipsoidal height

Temporal geometry is measured relative to an underlying temporal coordinate reference system (TRS). This OGC API - Common - Part 2: Geospatial Data Standard does not mandate a specific temporal coordinate reference system. However, all dates or timestamps discussed in this document are in the Gregorian calendar and conform to [RFC 3339](#). In data, other temporal coordinate reference systems may be used where appropriate.

[ISO 19111](#) provides the conceptual model for Coordinate Reference Systems.

## 6.5. Timezones

A default time zone of UTC as defined by ISO 8601:2004 and ISO 8601:2000 (or Greenwich Mean Time, also referred to as "Z" for Zulu Time), should be used for all temporal data passed or returned to/from OGC Web APIs. ISO 8601 accounts for local time by specifying an offset to UTC. When time zone offsets are used in a temporal element of a client request, the server processing the request should interpret temporal information with respect to the client's requested time zone. When there is no time zone offset expressed in a temporal element, the server should assume a UTC zone. The local time zone of client or server should not be assumed; it shall either be explicitly stated as an offset or assumed to be UTC.

## 6.6. API definition

### 6.6.1. General remarks

This OGC standard specifies requirements and recommendations for the development of APIs that share spatial resources using a standard way of doing so. In general, APIs will go beyond the requirements and recommendations stated in this standard. They will support additional operations, parameters, and so on that are specific to the API or the software tool used to implement the API.

So that developers can more easily learn how to use the API, good documentation is essential. In the best case, documentation would be available both in HTML for human consumption and in a machine readable format that can be processed by software for run-time binding. OpenAPI is one way to provide that machine readable documentation.

## 6.6.2. Role of OpenAPI

This OGC API Standard uses OpenAPI 3.0 fragments in examples and to formally state requirements. Using OpenAPI 3.0 is not required for implementing an OGC API. Other API definition languages may be used along with, or instead of, OpenAPI. However, any API definition language used should have an associated conformance class advertised through the `/conformance` path.

This standard includes a `conformance class` for API definitions that follow the [OpenAPI specification 3.0](#). Alternative API definition languages are also allowed. Conformance classes for additional API definition languages will be added as the OGC API landscape continues to evolve.

## 6.6.3. References to OpenAPI components in normative statements

Some normative statements (requirements, recommendations and permissions) use a phrase that a component in the API definition of the server must be "based upon" a schema or parameter component in the OGC schema repository.

In this case, the following changes to the pre-defined OpenAPI component are permitted:

- If the server supports an XML encoding, `xml` properties may be added to the relevant OpenAPI schema components.
- The range of values of a parameter or property may be extended (additional values) or constrained (only a subset of all possible values is allowed). An example for a constrained range of values is to explicitly specify the supported values of a string parameter or property using an *enum*.
- Additional properties may be added to the schema definition of a Response Object.
- Informative text, such as comments or description properties, may be changed or added.

For OGC API definitions that do not conform to the [OpenAPI Specification 3.0](#), the normative statement should be interpreted in the context of the API definition language used.

## 6.6.4. Reusable OpenAPI components

Reusable components for OpenAPI definitions for an OGC API are referenced from this document. They are available from the OGC Schemas Registry at <http://schemas.opengis.net/ogcapi/common/part1/1.0> and <http://schemas.opengis.net/ogcapi/common/part2/1.0>

Additional information on the use of OpenAPI as an API definition is provided in the [OGC API - Common Users Guide](#).

# Chapter 7. Overview

This API-Common Geospatial Data Standard provides a common connection between the API landing page and resource-specific specifications or standards.

## 7.1. Collections

Spatial data is rarely considered as a single entity. [Feature Collections](#), [Coverages](#), [Data Sets](#), they are all aggregations of [Spatial](#) or [Temporal](#) Things. It stands to reason that an OGC Web API would also expose its holdings as aggregates of spatial/temporal resources.

The purpose of the OGC API - Common - Part 2: Geospatial Data Standard is to provide a common connection between the API landing page and resource-specific details. That connection includes metadata which describes the hosted resources, common parameters for selecting subsets of the hosted resources, and URI templates for identifying the above.

A contentious issue is the term used to describe an aggregation of resources. The term should be consistent with its colloquial use, should indicate that the members of the aggregation are somehow associated, and it should be independent of any resource type.

Merriam Websters Dictionary provides a few relevant definitions :

- Collection: "An accumulation of objects gathered for study, comparison, or exhibition or as a hobby."
- Aggregate: (a synonym to collection) "A mass or body of units or parts somewhat loosely associated with one another."
- Set: "A number of things of the same kind that belong or are used together."

Based on these definitions, the term **collection** will be used in this standard to indicate an aggregation of resources. **For purposes of this standard**, a collection is defined as follows:

- **Collection**: A body of resources that belong or are used together. An aggregate, set, or group of related resources.

OGC Web API standards should extend this definition to address the specific properties of the resources they describe.

## 7.2. Views

A collection of geospatial data may be represented in more than one way. For example, a point cloud may be represented as a collection of Features, or as a Coverage, or as a color-coded map. Each is a representation of the same data. But the access methods and returned data structures are very different. OGC Web API standards refer to these representations as **views**.

**Views** should not be confused with encodings. HTTP content negotiation allows a client to negotiate the encoding (XML, JSON, etc.) to be used for the returned data. Regardless of the encoding, the underlying data model is the same. A **view**, on the other hand, is both a data model and a set of access mechanisms. It is an addressible resource in its own right and must be treated as such.

The API-Common Geodata Standard does not define any **views**. These are defined in separate OGC Web API standards. What is important to understand is how these view-specific standards extend the API-Common Geodata Standard.

The URI for a view of a collection follows the URI template:

```
/collections/{collectionId}/{viewId}
```

Where:

1. collectionId = an identifier for the collection
2. viewId = an identifier for the type of view.

So the URIs for the point cloud described above could be:

For Features: **/collections/mycollection/items**

For coverages: **/collections/mycollection/coverage**

For Maps: **/collections/mycollection/maps**

The view identifiers are maintained as a controlled vocabulary by the OGC.

Additional information on Views is provided in the [OGC API - Common Users Guide](#).

# Chapter 8. Requirements Class "Collections"

Requirements Class	
<a href="http://www.opengis.net/spec/ogcapi-common-2/1.0/req/collections">http://www.opengis.net/spec/ogcapi-common-2/1.0/req/collections</a>	
Target type	Web API
Dependency	<a href="http://www.opengis.net/spec/ogcapi-common-1/1.0/req/core">http://www.opengis.net/spec/ogcapi-common-1/1.0/req/core</a>
Dependency	ISO 19107
Dependency	GML Simple Features Profile
Dependency	Simple Features for SQL
Dependency	ISO 19108
Dependency	ISO 19111
Dependency	ISO 19108
Dependency	ISO 8601

This Requirements Class describes the resources and operations used to describe and access resource collections exposed through an OGC Web API. It does not include any requirements about how resources are aggregated into collections nor about the aggregated resources themselves. That detail is reserved for resource-specific OGC Web API standards (see [Views Section](#)).

The two resources defined in this Requirements Class are summarized in [Table 2](#).

Table 2. Collection Resources

Resource	URI	HTTP Method	Description
<a href="#">Collections</a>	/collections	GET	Information which describes the set of available Collections
<a href="#">Collection</a>	/collections/{collectionId}	GET	Information about a specific collection of geospatial data with links to distribution

## 8.1. Collections

OGC APIs typically organize their Spatial Resources into collections. Information about those collections is accessed through the `/collections` path and the <http://www.opengis.net/def/rel/ogc/1.0/data> link relation.

### 8.1.1. Operation

Requirement 1	<code>/req/collections/rc-md-op</code>
---------------	--

A	The API SHALL support the HTTP GET operation at the path <a href="#">/collections</a> .
---	---

### 8.1.2. Response

<b>Requirement 2</b>	<b><a href="#">/req/collections/rc-md-success</a></b>
A	A successful execution of the operation SHALL be reported as a response with a HTTP status code <a href="#">200</a> .
B	The content of that response SHALL comply with the requirements in the <a href="#">Collection Resource Definition</a> section of this Standard.

The collections response returned by this operation is based on the [collections.json](#) JSON schema. Examples of collections responses are provided in [Collections Response Example](#).

```

{
  "$schema": "http://json-schema.org/draft-07/schema#",
  "title": "Collections Schema",
  "description": "This schema defines the resource returned from /collections
path.",
  "type": "object",
  "required": [
    "links",
    "collections"
  ],
  "properties": {
    "links": {
      "type": "array",
      "items": {"$href": "link.json"}
    },
    "timeStamp": {
      "type": "string",
      "format": "date-time"
    },
    "numberMatched": {
      "type": "integer",
      "min": "0"
    },
    "numberReturned": {
      "type": "integer",
      "min": "0"
    },
    "collections": {
      "type": "array",
      "items": {"$href": "collectionDesc.json"}
    }
  }
}

```

This schema is further constrained by the following requirements and recommendations.

To support hypermedia navigation, the **links** property must be populated with sufficient hyperlinks to navigate through the whole dataset.

<b>Requirement 3</b>	<b>/req/collections/rc-md-links</b>
----------------------	-------------------------------------

A	<p>A <b>200</b>-response SHALL include the following links in the <b>links</b> property of the response:</p> <ul style="list-style-type: none"> <li>• A link to this response document (relation: <b>self</b>),</li> <li>• A link to the response document in every other media type supported by the API (relation: <b>alternate</b>).</li> </ul>
B	All links SHALL include the <b>rel</b> and <b>type</b> link parameters.

Additional information may be available to assist in understanding and using this dataset. Links to those resources should be provided as well.

<b>Recommendation 1</b>	<b>/rec/collections/rc-md-descriptions</b>
A	If external schemas or descriptions exist that provide additional information about the structure or semantics for the resource, a <b>200</b> -response SHOULD include links to each of those resources in the <b>links</b> property of the response (relation: <b>describedby</b> ).
B	The <b>type</b> link parameter SHOULD be provided for each link. This applies to resources that describe the whole dataset.

The **timeStamp** property of the Collections response indicates when the response was generated.

<b>Requirement 4</b>	<b>/req/collections/rc-timeStamp</b>
A	If a property <b>timeStamp</b> is included in the response, the value SHALL be set to the time stamp when the response was generated.

The **collections** property of the Collections response provides a description of each individual collection hosted by the API. These descriptions are based on the [Resource Collection Schema](#). This schema is described in detail in the [Resource Collection](#) section of this Standard.

<b>Requirement 5</b>	<b>/req/collections/rc-md-items</b>
A	For each spatial resource collection accessible through this API, metadata describing that collection SHALL be provided in the <b>collections</b> property of the Collections response.
B	This metadata shall be based on the same schema as the Collection resource.

A client may wish to select a subset of the hosted collections using HTTP query parameters. The



[Simple Query](#) Conformance Class defines the **bbox** and the **datetime** parameter for that purpose. It also defines how a server should process those parameters. These parameters are evaluated against the **extent** element of each Collection item in the Collections response.

The requirements governing the processing of these parameters are provided by the [Simple Query](#) Requirements Class.

Requirement 6	/req/collections/rc-bbox-unsupported
A	If the <b>bbox</b> parameter is provided by the client but it is not supported by the server, then the server SHALL process the request as if the parameter had not been provided.

Requirement 7	/req/collections/rc-datetime-unsupported
A	If the <b>datetime</b> parameter is provided by the client but it is not supported by the server, then the server SHALL process the request as if the parameter had not been provided.

The [Simple Query](#) Conformance Class also defines a parameter to limit the number of collections returned in a response. This **limit** parameter indicates the maximum number of collections which should be included in a single response.

Requirement 8	/req/collections/rc-limit-unsupported
A	If the <b>limit</b> parameter is provided by the client but it is not supported by the server, then the server SHALL process the request as if the parameter had not been provided.

<b>NOTE</b>	This requirement does not preclude server imposed limits on the size of a response.
-------------	---

### 8.1.3. Error situations

See [HTTP Status Codes](#) for general guidance.

## 8.2. Resource Collection

Each resource collection is described by a set of metadata. That metadata is accessed directly using the `/collections/{collectionId}` path or as an entry in the **collections** property of the Collections resource.

### 8.2.1. Operation

<b>Requirement 9</b>	<b>/req/collections/src-md-op</b>
A	The API SHALL support the HTTP GET operation at the path <b>/collections/{collectionId}</b> .
B	The parameter <b>collectionId</b> is each <b>id</b> property in the <b>collections</b> response (JSONPath: <b>\$.collections[*].id</b> ).

### 8.2.2. Response

<b>Requirement 10</b>	<b>/req/collections/src-md-success</b>
A	A successful execution of the operation SHALL be reported as a response with a HTTP status code <b>200</b> .
B	The content of that response SHALL comply with the requirements in the <a href="#">Collection Resource Definition</a> section of this Standard.
C	The content of that response SHALL be consistent with the content for this collection in the <b>/collections</b> response. That is, the values for <b>id</b> , <b>title</b> , <b>description</b> and <b>extent</b> SHALL be identical.

### 8.2.3. Error Situations

See [HTTP Status Codes](#) for general guidance.

If the parameter **collectionId** does not exist on the server, the status code of the response will be **404** (see [Table 5](#)).

### 8.2.4. Collection Resource Definition

<b>Requirements Module</b>	
<a href="http://www.opengis.net/spec/ogcapi-common-2/1.0/rm/collection">http://www.opengis.net/spec/ogcapi-common-2/1.0/rm/collection</a>	
Target type	Web API
Description	The Collection resource provides clients with a basic understanding of a single collection. It also serves as a starting point for further navigation through the collection.
Requirements	<a href="#">/req/collections/collection-definition</a> <a href="#">/req/collections/rc-md-items-links</a> <a href="#">/req/collections/rc-md-extent</a>

Recommendations and Permissions	<a href="#">/rec/collections/rc-md-item-type</a> <a href="#">/rec/collections/rc-md-items-descriptions</a> <a href="#">/rec/collections/rc-md-extent</a> <a href="#">/rec/collections/rc-md-extent-single</a> <a href="#">/per/collections/rc-md-extent-extensions</a>
---------------------------------	--

Examples of Collection resources are provided in [Collection Object Examples](#).

<b>Requirement 11</b>	<b>/req/collections/collection-definition</b>
A	The content of a <b>Collection</b> resource SHALL be based upon the JSON schema <a href="#">collectionDesc.json</a> .

### Collection Resource Schema

```
{
  "$schema": "http://json-schema.org/draft-07/schema#",
  "title": "Collection Resource Schema",
  "description": "This schema defines the resource returned from
/collections/{collectionId}.",
  "type": "object",
  "required": [
    "id",
    "links"
  ],
  "properties": {
    "id": {
      "description": "identifier of the collection used, for example, in URIs",
      "type": "string"
    },
    "title": {
      "description": "human readable title of the collection",
      "type": "string"
    },
    "description": {
      "description": "a description of the members of the collection",
      "type": "string"
    },
    "attribution" : {
      "type" : "string",
      "title" : "attribution for the collection",
      "description" : "The `attribution` should be short and intended for
presentation to a user, for example, in a corner of a map. Parts of the text can be
links to other resources if additional information is needed. The string can include
HTML markup."
    },
    "links": {
      "type": "array",
      "items": {"$href": "link.json"}
    }
  }
}
```

```

    },
    "extent": {"$href": "extent.json"},
    "itemType": {
      "description": "An indicator about the type of the items in the
collection.",
      "type": "string"
    },
    "crs": {
      "description": "the list of coordinate reference systems supported by the
API; the first item is the default coordinate reference system",
      "type": "array",
      "items": {
        "type": "string"
      },
      "default": [
        "http://www.opengis.net/def/crs/OGC/1.3/CRS84"
      ],
      "example": [
        "http://www.opengis.net/def/crs/OGC/1.3/CRS84",
        "http://www.opengis.net/def/crs/EPSG/0/4326"
      ]
    }
  }
}

```

Many of the properties of the Collection resource are self-explanatory. However, a few call for additional explanation.

## Attribution

The attribution element is a special type of string property. Specifically, it can contain markup text. Markup allows a text string to import images and format text. The capabilities are only limited by the markup language used. See the example [collection response](#) for an example of the use of markup in the attribution element.

## Item Type

In some Geospatial collections, the members (**items**) that make up that collection can be individually accessed by a client. In this case, the **itemType** property in the Collection resource identifies the type of the **items** accessible from that collection.

Recommendation 2	/rec/collections/rc-md-item-type
A	If the members ( <b>items</b> ) that make up a collection can be individually accessed by a client, then the <b>itemType</b> key SHOULD be included in the Collection resource to indicate the type of the items (e.g. <b>feature</b> or <b>record</b> ).

## Links

To support hypermedia navigation, the **links** property must be populated with sufficient hyperlinks to navigate through the whole dataset.

Requirement 12	/req/collections/rc-md-items-links
A	<p>200-response SHALL include the following links in the <b>links</b> property of the response:</p> <ul style="list-style-type: none"><li>• A link to this response document (relation: <b>self</b>),</li><li>• A link to the response document in every other media type supported by the API (relation: <b>alternate</b>).</li></ul>
B	All links SHALL include the <b>rel</b> and <b>type</b> properties.

Additional information may be available to assist in understanding and using this dataset. Links to those resources should be provided as well.

Recommendation 3	/rec/collections/rc-md-items-descriptions
A	If external schemas or descriptions exist that provide additional information about the structure or semantics of the collection, a 200-response SHOULD include links to each of those resources in the <b>links</b> property of the response (relation: <b>describedby</b> ).
B	The <b>type</b> link parameter SHOULD be provided for each link.

## Extent

The extent property defines a spatial-temporal surface which encompasses the geospatial data in the collection. Since not all collections are nicely clustered around a single place in space and time, the extent property provides flexibility in how that surface can be defined.

- Spatial Bounding Box (Bbox) provides a set of rectangular bounding boxes which use geographic coordinates to envelope portions of the collection. Typically only the first element would be populated. Additional boxes may be useful, for example, when the collection is clustered in multiple, widely-separated locations.
- Temporal Interval provides a set of temporal periods. Typically only the first temporal period would be populated. However, like bbox, additional periods can be added if the collection does not form a single temporal cluster.

Requirement 13	/req/collections/rc-md-extent
----------------	-------------------------------

A	For each spatial collection resource, the <b>extent</b> property, if provided, SHALL define boundaries that encompass the spatial and temporal properties of all of the resources in this collection. The temporal extent may use <b>null</b> values to indicate an open time interval.
B	If a spatial resource has multiple properties with spatial or temporal information, it is the decision of the API implementation whether only a single spatial or temporal geometry property is used to determine the extent or all relevant geometries.

<b>Recommendation 4</b>	<b>/rec/collections/rc-md-extent</b>
A	If an extent contains multiple spatial boundaries (multiple <b>bbox</b> , etc.), then the extent SHOULD include in the first <b>bbox</b> a boundary which represents the union of all of the other boundaries.
B	If an extent contains multiple temporal intervals, then the extent SHOULD include as the first interval an interval which represents the union of all of the other intervals.

<b>Recommendation 5</b>	<b>/rec/collections/rc-md-extent-single</b>
A	While the spatial and temporal extents support multiple bounding boxes ( <b>bbox</b> array) and time intervals ( <b>interval</b> array) for advanced use cases, implementations SHOULD provide only a single bounding box or time interval unless the use of multiple values is important for the use of the dataset and agents using the API are known to be support multiple bounding boxes or time intervals.

<b>Permission 1</b>	<b>/per/collections/rc-md-extent-extensions</b>
A	API-Common only specifies requirements for spatial and temporal extents. However, the <b>extent</b> object MAY be extended with additional members to represent other extents, such as thermal or pressure ranges.

B	<p>API-Common only supports</p> <ul style="list-style-type: none"> <li>• Spatial extents in CRS84 or CRS84h and</li> <li>• Temporal extents in the Gregorian calendar</li> </ul> <p>These are the only <i>enum</i> values in <a href="#">extent.json</a>).</p>
C	<p>Extensions MAY add additional reference systems to the <b>extent</b> object.</p>

# Chapter 9. Requirements Class "Simple Query"

Requirements Class	
<a href="http://www.opengis.net/spec/ogcapi-common-2/1.0/req/simple-query">http://www.opengis.net/spec/ogcapi-common-2/1.0/req/simple-query</a>	
Target type	Web API
Dependency	<a href="#">Collections Requirements Class</a>
Dependency	<a href="#">ISO 19107</a>
Dependency	<a href="#">GML Simple Features Profile</a>
Dependency	<a href="#">Simple Features for SQL</a>
Dependency	<a href="#">ISO 19108</a>
Dependency	<a href="#">ISO 19111</a>
Dependency	<a href="#">ISO 19108</a>
Dependency	<a href="#">ISO 8601</a>

This Requirements Class describes query parameters that can be used to discover and select resource collections exposed through an OGC Web API.

## 9.1. Parameter Requirements

Query parameters are used in URIs to limit the resources which are returned on a GET request. The OGC API - Common - Part 2: Geospatial Data Standard identifies three query parameters for use in OGC API standards:

- [bbox](#): Bounding Box
- [datetime](#): Date and Time
- [limit](#): Response resource count limit

The behavior generated by these parameters is specific to the operation and resource upon which they are applied. Those behaviors are described for each resource type and operation in the [Target Resource Requirements](#) section.

Use of these query parameters with any specific operation is optional. Developers of API-GeoData servers should document their supported parameters in the API definition as describe in [API-Core](#).

### 9.1.1. Parameter bbox

Requirements Module	
<a href="http://www.opengis.net/spec/ogcapi-common-2/1.0/rm/bbox">http://www.opengis.net/spec/ogcapi-common-2/1.0/rm/bbox</a>	
Target type	Web API Query Parameter



The **bbox** parameter is used to select resources based on the geospatial footprint or extent.

The **bbox** parameter is defined as follows:

Requirement 14	/req/collections/rc-bbox-definition
A	<p>The <b>bbox</b> parameter SHALL possess the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre>name: bbox in: query required: false schema:   type: array   minItems: 4   maxItems: 6   items:     type: number style: form explode: false</pre>
B	<p>The bounding box SHALL be provided as four or six numbers, depending on whether the coordinate reference system includes a vertical axis (height or depth):</p> <ul style="list-style-type: none"><li>• Lower left corner, coordinate axis 1</li><li>• Lower left corner, coordinate axis 2</li><li>• Minimum value, coordinate axis 3 (optional)</li><li>• Upper right corner, coordinate axis 1</li><li>• Upper right corner, coordinate axis 2</li><li>• Maximum value, coordinate axis 3 (optional)</li></ul>
C	<p>If the bounding box consists of four numbers, the coordinate reference system of the values SHALL be interpreted as WGS 84 longitude/latitude (<a href="http://www.opengis.net/def/crs/OGC/1.3/CRS84">http://www.opengis.net/def/crs/OGC/1.3/CRS84</a>) unless a different coordinate reference system is specified in a parameter <b>bbox-crs</b>.</p>
D	<p>If the bounding box consists of six numbers, the coordinate reference system of the values SHALL be interpreted as WGS 84 longitude/latitude/ellipsoidal height (<a href="http://www.opengis.net/def/crs/OGC/0/CRS84h">http://www.opengis.net/def/crs/OGC/0/CRS84h</a>) unless a different coordinate reference system is specified in a parameter <b>bbox-crs</b>.</p>

While the processing of the **bbox** parameter is specific to the resource and operation for which it is

applied, there is a general set of requirements which all implementations must address.

Requirement 15	/req/collections/rc-bbox-response
A	If the <b>bbox</b> parameter is provided by the client and supported by the server, then only resources that have a spatial geometry that intersects the bounding box SHALL be part of the result set.
B	If a resource has multiple spatial geometry properties, it is the decision of the server whether only a single spatial geometry property is used to determine the extent or all relevant geometries.
C	The <b>bbox</b> parameter SHALL also match all resources in the collection that are not associated with a spatial geometry.
D	The coordinate values provided with the <b>bbox</b> parameter SHALL be within the extent specified for the coordinate reference system.

"Intersects" means that a coordinate that is part of the spatial geometry of the resource falls within the area specified in the parameter **bbox**. This includes the boundaries of the geometries. For curves the boundary includes the start and end position. For surfaces the boundary includes the outer and inner rings.

In case of a degenerate bounding box, the resulting geometry is used. For example, if the lower left corner is the same as the upper right corner, all resources match where the geometry intersects with this point.

This standard does not specify requirements for the parameter **bbox-crs**. Those requirements will be specified in a later version of this standard.

The bounding box for WGS 84 longitude/latitude is, in most cases, the sequence of minimum longitude, minimum latitude, maximum longitude and maximum latitude. However, in cases where the box spans the anti-meridian (180th meridian) the first value (west-most box edge) is larger than the third value (east-most box edge).

*Example 1. The bounding box of the New Zealand Exclusive Economic Zone*

The bounding box of the New Zealand Exclusive Economic Zone in WGS84 (from 160.6°E to 170°W and from 55.95°S to 25.89°S) would be represented in JSON as [ 160.6, -55.95, -170, -25.89 ] and in a query as **bbox=160.6,-55.95,-170,-25.89**.

Note that the server will return an error if a latitude value of **160.0** is used.

If the vertical axis is included, the third and the sixth number are the bottom and the top of the 3-dimensional bounding box.

A template for the definition of the parameter in YAML according to OpenAPI 3.0 is available at [bbox.yaml](http://bbox.yaml).

### 9.1.2. Parameter datetime

Requirements Module	
<a href="http://www.opengis.net/spec/ogcapi-common-2/1.0/rm/datetime">http://www.opengis.net/spec/ogcapi-common-2/1.0/rm/datetime</a>	
Target type	Web API Query Parameter

The **datetime** parameter selects resources based on their temporal extent. The definition of temporal extent is specific to the resource type being filtered.

The **datetime** parameter is defined as follows:

Requirement 16	/req/collections/rc-datetime-definition
A	<p>The <b>datetime</b> parameter SHALL have the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre>name: datetime in: query required: false schema:   type: string style: form explode: false</pre>
B	<p>Temporal geometries are either a date-time value or a time interval. The parameter value SHALL conform to the following syntax (using <a href="#">ABNF</a>):</p> <pre>interval-closed      = date-time "/" date-time interval-open-start  = "../" date-time interval-open-end    = date-time "/.." interval              = interval-closed / interval-open- start / interval-open-end datetime              = date-time / interval</pre>
C	<p>The syntax of <b>date-time</b> is specified by <a href="#">RFC 3339, 5.6</a>.</p>
D	<p>Open ranges in time intervals at the start or end are supported using a double-dot (..) or an empty string for the start/end..</p>

While the processing of the **datetime** parameter is specific to the resource and operation for which

it is applied, there is a general set of requirements which all implementations must address.

Requirement 17	/req/collections/rc-datetime-response
A	If the <b>datetime</b> parameter is provided by the client and supported by the server, then only resources that have a temporal geometry that intersects the temporal information in the <b>datetime</b> parameter SHALL be part of the result set.
B	If a resource has multiple temporal properties, the decision of the server whether only a single temporal property is used to determine the extent or all relevant temporal properties.
C	The <b>datetime</b> parameter SHALL match all resources in the collection that are not associated with a temporal geometry.

"Intersects" means that the time (instant or period) specified in the parameter **datetime** includes a timestamp that is part of the temporal geometry of the resource (again, a time instant or period). For time periods this includes the start and end time.

Note	ISO 8601-2 distinguishes open start/end timestamps (double-dot) and unknown start/end timestamps (empty string). For queries, an unknown start/end has the same effect as an open start/end.
------	--

#### Example 2. A date-time

February 12, 2018, 23:20:52 GMT:

**time=2018-02-12T23%3A20%3A52Z**

For resources with a temporal property that is a timestamp (like **lastUpdate**), a date-time value would match all resources where the temporal property is identical.

For resources with a temporal property that is a date or a time interval, a date-time value would match all resources where the timestamp is on that day or within the time interval.

### Example 3. Intervals

February 12, 2018, 00:00:00 GMT to March 18, 2018, 12:31:12 GMT:

`datetime=2018-02-12T00%3A00%3A00Z%2F2018-03-18T12%3A31%3A12Z`

February 12, 2018, 00:00:00 UTC or later:

`datetime=2018-02-12T00%3A00%3A00Z%2F..`

March 18, 2018, 12:31:12 UTC or earlier:

`datetime=..%2F2018-03-18T12%3A31%3A12Z`

A template for the definition of the parameter in YAML according to OpenAPI 3.0 is available at [datetime.yaml](#).

### 9.1.3. Parameter limit

#### Requirements Module

<http://www.opengis.net/spec/ogcapi-common-2/1.0/rm/limit>

Target type	Web API Query Parameter
-------------	-------------------------

The **limit** parameter limits the number of resources that can be returned in a single response.

Requirement 18	/req/collections/rc-limit-definition
A	<p>The <b>limit</b> parameter SHALL possess the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre>name: limit in: query required: false schema:   type: integer   minimum: 1   maximum: 10000   default: 10 style: form explode: false</pre>
Note:	The values for <b>minimum</b> , <b>maximum</b> and <b>default</b> are only examples and MAY be changed.

While the processing of the **limit** parameter is specific to the resource and operation for which it is applied, there is a general set of requirements which all implementations must address.

<b>Requirement 19</b>	<b>/req/collections/rc-limit-response</b>
A	If the <b>limit</b> parameter is provided by the client and supported by the server, then the response SHALL not contain more resources than specified by the <b>limit</b> parameter.
B	If the API definition specifies a maximum value for the <b>limit</b> parameter, the response SHALL not contain more resources than this maximum value.
C	Only items are counted that are on the first level of the collection. Any nested objects contained within the explicitly requested items SHALL not be counted.

The number of resources returned depends on the server and the value of the **limit** parameter.

- The client can request a limit to the number of resources returned.
- The server may have a default value for the limit, and a maximum limit.
- If the server has any more results available than it returns (the number it returns is less than or equal to the requested/default/maximum limit) then the server will include a link to the next set of results.

<b>Permission 2</b>	<b>/per/collections/rc-server-limit</b>
A	If a server is configured with a maximum response size, then the server MAY page responses which exceed that threshold.

<b>Recommendation 6</b>	<b>/rec/collections/rc-server-limit</b>
A	Clients SHOULD be prepared to handle a paged response even if they have not specified a <b>limit</b> parameter in their query.

The effect of the limit parameter is to divide the response into a number of pages. Each page (except for the last) contains the specified number of entities. The response contains the first page. Additional pages can be accessed through hyperlink navigation.

<b>Recommendation 7</b>	<b>/rec/collections/rc-next-1</b>
A	A <b>200</b> -response SHOULD include a link to the next "page" (relation: <b>next</b> ), if more resources have been selected than returned in the response.

<b>Recommendation 8</b>	<b>/rec/collections/rc-next-2</b>
A	Dereferencing a <b>next</b> link SHOULD return additional resources from the set of selected resources that have not yet been returned.

<b>Recommendation 9</b>	<b>/rec/collections/rc-next-3</b>
A	The number of resources in a response to a <b>next</b> link SHOULD follow the same rules as for the response to the original query and again include a <b>next</b> link, if there are more resources in the selection that have not yet been returned.

Providing **prev** links supports navigating back and forth between pages, but depending on the implementation approach it may be too complex to implement.

<b>Permission 3</b>	<b>/per/collections/rc-prev</b>
A	A response to a <b>next</b> link MAY include a <b>prev</b> link to the resource that included the <b>next</b> link.

## 9.2. Target Resource Requirements

The target of the parameters defined in this conformance class is the **Collection** resource described in the **Collections** Requirements Class. The purpose of these parameters is to select a subset of **Collection** resources to be included in the response to a **/collections** request.

Three parameters are defined for use with the **Collections** resource. These parameters subset the set of **Collection** entries returned based on spatial, temporal, and volumetric filters. These parameters are documented in the **Parameter Requirements** section.

The **collections** property of the Collections response provides a description of each individual collection hosted by the API. These descriptions are based on the **Resource Collection Schema**. This schema is described in detail in the **Resource Collection** section of this Standard.

### 9.2.1. Spatial and Temporal Filtering

A client may select a subset of the hosted collections using the **bbox** and the **datetime** parameter. These parameters are evaluated against the **extent** element of each Collection item in the Collections response.

The requirements governing the processing of these parameters are:

<b>Requirement 20</b>	<b>/req/collections/rc-bbox-collection-response</b>
-----------------------	---

A	The API server SHALL process the <b>bbox</b> parameter against the <b>Collection</b> resources (/collections/{collectionId}) accessible through that API.
B	The <b>bbox</b> parameter SHALL be evaluated against the geometry defined by the <b>bbox</b> element of the <b>extent</b> property of the <b>Collection</b> resource.

<b>Requirement 21</b>	<b>/req/collections/rc-datetime-collection-response</b>
A	The API server SHALL process the <b>datetime</b> parameter against the <b>Collection</b> resources (/collections/{collectionId}) accessible through that API.
B	The <b>datetime</b> parameter SHALL be evaluated against the temporal geometry defined by the <b>interval</b> element of the <b>extent</b> property of the <b>Collection</b> resource.

### 9.2.2. Volumetric Filtering

The client may limit the number of collections returned in a response by using the **limit** parameter. When applied against the **/collections** resource, the **limit** parameter indicates the maximum number of collections which should be included in a single response.

<b>Requirement 22</b>	<b>/req/collections/rc-limit-collection-response</b>
A	If the <b>limit</b> parameter is provided by the client, then the <b>collections</b> element of the collections response SHALL not contain more items than specified by the <b>limit</b> parameter.
B	If the API definition specifies a maximum value for the <b>limit</b> parameter, the <b>collections</b> element of the collections response SHALL not contain more items than this maximum value.

The server also has the option of limiting the size of the Collections response.

<b>Permission 4</b>	<b>/per/collections/rc-md-items</b>
A	To support servers with many collections, servers MAY limit the number of items included in the <b>collections</b> property.



### 9.2.3. Paged Response

If the collections response does not contain all of the collection resources available from this server, then the client must be informed of that fact.

Requirement 23	/req/collections/rc-paged-response
A	If the number of items in the <b>collections</b> element is less than the number available through the API, then the <b>numberMatched</b> and <b>numberReturned</b> properties SHALL be included in the Collections response.

The **numberMatched** property of the Collections response indicates the number of Collection items included in the Collections response. This may be a subset of the total set of collections hosted by the API. Selection of which collections to include in a subset is controled through the **bbox**, **datetime** and other selection parameters provided by the client.

Requirement 24	/req/collections/rc-numberMatched
A	If a property <b>numberMatched</b> is included in the response, the value SHALL be identical to the number of hosted collections that meet the selection parameters provided by the client.
B	A server MAY omit this information in a response, if the information about the number of matching resources is not known or difficult to compute.

The number of collection items included in a Collections response may be a subset of the number matched. In that case, the **numberReturned** property of the Collections response indicates the number of collection items returned in this "page" of the Collections response.

Requirement 25	/req/collections/rc-numberReturned
A	If a property <b>numberReturned</b> is included in the response, the value SHALL be identical to the number of items in the <b>collections</b> array in the <b>Collections</b> document.
B	A server MAY omit this information in a response, if the information about the number of resources in the response is not known or difficult to compute.

If the Collections response contains a subset of the selected collection items (**numberReturned** is less than **numberMatched**) then the Collections response should contain links for navigating to the rest of the collection items as described in the [limit parameter](#) section.

# Chapter 10. Encoding Requirements Classes

## 10.1. Overview

This clause specifies two requirements classes for encodings to be used with the [Collections](#) and [Collection](#) resources. These encodings are commonly used encodings for spatial data on the web:

- [HTML](#)
- [JSON](#)

None of these encodings are mandatory. An implementation of the [Collections](#) requirements class may implement either, both, or none of them.

## 10.2. Requirement Class "HTML"

Geographic information that is only accessible in formats like GeoJSON or GML has two issues:

- The data is not discoverable using the most common mechanism for discovering information, that is the search engines of the Web,
- The data can not be viewed directly in a browser - additional tools are required to view the data.

Therefore, sharing data on the Web should include publication in HTML. To be consistent with the Web, it should be done in a way that enables users and search engines to access all data.

This is discussed in detail in [W3C Best Practice](#). This standard therefore [recommends](#) supporting HTML as an encoding.

Requirements Class	
<a href="http://www.opengis.net/spec/ogcapi_common-2/1.0/req/html">http://www.opengis.net/spec/ogcapi_common-2/1.0/req/html</a>	
Target type	Web API
Dependency	<a href="#">Collections Requirements Class</a>
Dependency	<a href="#">HTML5</a>
Dependency	<a href="#">Schema.org</a>

<b>Requirement 26</b>	<b>/req/html/definition</b>
A	Every <b>200</b> -response of an operation of the API SHALL support the media type <b>text/html</b> .

<b>Requirement 27</b>	<b>/req/html/content</b>
-----------------------	--------------------------

A	<p>Every <b>200</b>-response of the API with the media type "text/html" SHALL be a <b>HTML 5 document</b> that includes the following information in the HTML body:</p> <ul style="list-style-type: none"> <li>• All information identified in the schemas of the <b>Response Object</b> in the HTML <code>&lt;body/&gt;</code>, and</li> <li>• All links in HTML <code>&lt;a/&gt;</code> elements in the HTML <code>&lt;body/&gt;</code>.</li> </ul>
<b>Recommendation 10</b>	<b>/rec/html/schema-org</b>
A	A <b>200</b> -response with the media type <b>text/html</b> , SHOULD include <b>Schema.org</b> annotations.

## 10.3. Requirement Class "JSON"

JSON is a text syntax that facilitates structured data interchange between programming languages. It commonly used for Web-based software-to-software interchanges. Most Web developers are comfortable with using a JSON-based format, so supporting JSON is recommended for machine-to-machine interactions.

Requirements Class	
<a href="http://www.opengis.net/spec/ogcapi_common-2/1.0/req/json">http://www.opengis.net/spec/ogcapi_common-2/1.0/req/json</a>	
Target type	Web API
Dependency	<a href="#">Collections Requirements Class</a>
Dependency	<a href="#">IETF RFC 8259: The JavaScript Object Notation (JSON) Data Interchange Format</a>
Dependency	<a href="#">JSON Schema</a>

<b>Requirement 28</b>	<b>/req/json/definition</b>
A	<b>200</b> -responses of the server SHALL support the <b>application/json</b> media type.

<b>Requirement 29</b>	<b>/req/json/content</b>
A	Every <b>200</b> -response with the media type <b>application/json</b> SHALL include, or link to, a payload encoded according to the <b>JSON Interchange Format</b> .

B	The schema of all responses with the media type <code>application/json</code> SHALL conform with the JSON Schema specified for that resource.
---	---

JSON Schema for the Collections and Collection responses are available at [collections.yaml](#) and [collectionDesc.yaml](#).

These are generic schemas that do not include any application schema information about specific resource types or their properties.

# Chapter 11. Media Types

JSON media types that would typically be supported by a server that supports JSON are:

- `application/geo+json` for feature collections and features, and
- `application/json` for all other resources.

XML media types that would typically be supported by a server that supports XML are:

- `application/gml+xml;version=3.2` for any GML 3.2 feature collections and features,
- `application/gml+xml;version=3.2;profile=http://www.opengis.net/def/profile/ogc/2.0/gml-sf0` for GML 3.2 feature collections and features conforming to the GML Simple Feature Level 0 profile,
- `application/gml+xml;version=3.2;profile=http://www.opengis.net/def/profile/ogc/2.0/gml-sf2` for GML 3.2 feature collections and features conforming to the GML Simple Feature Level 2 profile, and
- `application/xml` for all other resources.

The typical HTML media type for all "web pages" in a server would be `text/html`.

# Chapter 12. Security Considerations

See [OGC API - Common - Part 1: Core](#), Clause 11.

add additional text as needed

# Annex A: Abstract Test Suite (Normative)

## A.1. Introduction

OGC Web APIs are not a Web Services in the traditional sense. Rather, they define the behavior and content of a set of Resources exposed through a Web Application Programming Interface (Web API). Therefore, an API may expose resources in addition to those defined by the standard. A test engine must be able to traverse the API, identify and validate test points, and ignore resource paths which are not to be tested.

## A.2. Conformance Class Collections

Conformance Class	
<a href="http://www.opengis.net/spec/ogcapi-common-2/1.0/conf/collections">http://www.opengis.net/spec/ogcapi-common-2/1.0/conf/collections</a>	
Target type	Web API
Requirements Class	<a href="http://www.opengis.net/spec/ogcapi_common-2/1.0/req/collections">http://www.opengis.net/spec/ogcapi_common-2/1.0/req/collections</a>
Dependency	<a href="http://www.opengis.net/spec/ogcapi-common-1/1.0/req/core">http://www.opengis.net/spec/ogcapi-common-1/1.0/req/core</a>

Conformance with the [Collections](#) Conformance Class is demonstrated by execution, in order, of the following tests:

1. [/ats/collections/rc-md-op](#)
2. [/ats/collections/src-md-op](#)

IF the [Simple Query](#) Conformance Class has not been implemented, then also execute test [ats/collections/rc-md-simple-query-unsupported](#)

### A.2.1. Collections {root}/collections Tests

Abstract Test 1	<a href="#">/ats/collections/rc-md-op</a>
Test Purpose	Validate that information about the Collections can be retrieved from the expected location.
Requirement	<a href="#">/req/collections/rc-md-op</a> <a href="#">/req/collections/rc-md-success</a>

Test Method	<ol style="list-style-type: none"> <li>1. Issue an HTTP GET request without query parameters to the URL {root}/collections</li> <li>2. Validate that a document was returned with a status code 200</li> <li>3. Validate the contents of the returned document using test <a href="#">/ats/collections/rc-md-success</a>.</li> </ol>
-------------	--

<b>Abstract Test 2</b>	<b><a href="#">/ats/collections_rc-md-success</a></b>
Test Purpose	Validate that the Collections content complies with the required structure and contents.
Requirement	<a href="#">/req/collections/rc-md-success</a> <a href="#">/req/collections/rc-md-links</a> <a href="#">/req/collections/rc-timestamp</a> <a href="#">/req/collections/rc-md-items</a>
Test Method	<ol style="list-style-type: none"> <li>1. Validate that the response document complies with <a href="#">/ats/collections/rc-md-links</a></li> <li>2. Validate that the response document complies with <a href="#">/ats/collections/rc-timestamp</a></li> <li>3. Validate that the response document complies with <a href="#">/ats/collections/rc-md-items</a></li> <li>4. Validate the Collections resource for all supported media types using the resources and tests identified in <a href="#">Table 3</a></li> </ol>

The Collections content may be retrieved in a number of different formats. The following table identifies the applicable schema document for each format and the test to be used to validate against that schema. All supported formats should be exercised.

*Table 3. Schema and Tests for Collections content*

Format	Schema Document	Test ID
HTML	<a href="#">collections.json</a>	<a href="#">/ats/html/content</a>
JSON	<a href="#">collections.json</a>	<a href="#">/ats/json/content</a>

<b>Abstract Test 3</b>	<b><a href="#">/ats/collections/rc-md-links</a></b>
Test Purpose	Validate that the required links are included in the Collections document.
Requirement	<a href="#">/req/collections/rc-md-links</a>



Test Method	<p>Verify that the response document includes:</p> <ol style="list-style-type: none"> <li>1. a link to this response document (relation: <b>self</b>),</li> <li>2. a link to the response document in every other media type supported by the server (relation: <b>alternate</b>).</li> </ol> <p>Verify that all links include the <b>rel</b> and <b>type</b> link parameters.</p>
-------------	--

<b>Abstract Test 4</b>	<b>/ats/collections/rc-timestamp</b>
Test Purpose	If a <b>timeStamp</b> property is included in the Collections document, then validate that the value of that property equates to the time that the response was generated.
Requirement	<a href="#">/req/collections/rc-timestamp</a>
Test Method	<p>IF the Collections document contains a <b>timeStamp</b> property, THEN</p> <ol style="list-style-type: none"> <li>1. Get the current date and time</li> <li>2. Verify that the value of that property is within two minutes of the current date and time.</li> </ol>
Note:	The two minute threshold was chosen to allow for test script processing time and clock synchronization issues.

<b>Abstract Test 5</b>	<b>/ats/collections/rc-md-items</b>
Test Purpose	Validate that each collection accessible through the API is described in the Collections document.
Requirement	<a href="#">/req/collections/rc-md-items</a>
Test Method	<ol style="list-style-type: none"> <li>1. Verify that the Collections document includes a <b>collections</b> property.</li> <li>2. Verify that the <b>collections</b> property is an array.</li> <li>3. Verify that there is an entry in the <b>collections</b> property for each resource collection accessible through the API.</li> <li>4. Verify that each entry in the <b>collections</b> array is valid according to <a href="#">/ats/collections/rc-md-collection-content</a>.</li> </ol>

### A.2.2. Collection {root}/collections/{collectionId} Tests

<b>Abstract Test 6</b>	<b>/ats/collections/src-md-op</b>
Test Purpose	Validate that the Collection content can be retrieved from the expected location.
Requirement	<a href="#">/req/collections/src-md-op</a> <a href="#">/ats/collections/req-md-success</a>
Test Method	<p>For every Collection described in the Collections content, issue an HTTP GET request to the URL <code>/collections/{collectionId}</code> where <code>{collectionId}</code> is the <code>id</code> property for the collection.</p> <ol style="list-style-type: none"><li>1. Validate that a Collection was returned with a status code 200</li><li>2. Validate the contents of the returned document using test <a href="#">/ats/collections/src-md-success</a>.</li></ol>

<b>Abstract Test 7</b>	<b>/ats/collections/src-md-success</b>
Test Purpose	Validate that the Collection content complies with the required structure and contents.
Requirement	<a href="#">/req/collections/src-md-success</a>
Test Method	<ol style="list-style-type: none"><li>1. Validate the structure and content of the response document using <a href="#">/ats/collections/rc-md-items-collection-content</a></li><li>2. Verify that the content of the response is consistent with the content for this Resource Collection in the <code>/collections</code> response. That is, the values for <code>id</code>, <code>title</code>, <code>description</code> and <code>extent</code> are identical.</li></ol>

<b>Abstract Test 8</b>	<b>/ats/collections/rc-md-collection-content</b>
Test Purpose	Validate that a Collection document complies with the required structure and values.
Requirement	<a href="#">/req/collections/collection-definition</a> <a href="#">/req/collections/rc-md-items-links</a> <a href="#">/req/collections/rc-md-extent</a>

Test Method	<p>FOR a each Collection document, validate:</p> <ol style="list-style-type: none"> <li>1. That the Collection document includes an <b>id</b> property.</li> <li>2. That the Collection document complies with <a href="#">/ats/collections/rc-md-items-links</a></li> <li>3. That any extent properties included in the Collection document comply with <a href="#">/collections/rc-md-extent</a></li> <li>4. Validate the content of the Collection document for all supported media types using the resources and tests identified in <a href="#">Table 4</a></li> </ol>
-------------	---

The Collection content may be retrieved in a number of different formats. The following table identifies the applicable schema document for each format and the test to be used to validate against that schema. All supported formats should be exercised.

*Table 4. Schema and Tests for Collection content*

Format	Schema Document	Test ID
HTML	<a href="#">collectionDesc.json</a>	<a href="#">/ats/html/content</a>
JSON	<a href="#">collectionDesc.json</a>	<a href="#">/ats/json/content</a>

<b>Abstract Test 9</b>	<b><a href="#">/ats/collections/rc-md-items-links</a></b>
Test Purpose	Validate that a Collection document includes all required links.
Requirement	<a href="#">/req/collections/rc-md-items-links</a>
Test Method	<ol style="list-style-type: none"> <li>1. Verify that the Collection document includes a <b>links</b> property.</li> <li>2. Verify that the <b>links</b> property includes an item which refers back to the Collection document (relation: <b>self</b>).</li> <li>3. Verify that the <b>links</b> property includes an item for each supported encoding of this Collection document and that each of these items includes an <b>href</b> to an appropriate resource (relation: <b>alternate</b>).</li> <li>4. Verify that all links include the <b>rel</b> and <b>type</b> link parameters.</li> </ol>

<b>Abstract Test 10</b>	<b><a href="#">/ats/collections/rc-md-extent</a></b>
Test Purpose	Validate the <b>extent</b> property if it is present
Requirement	<a href="#">/req/collections/rc-md-extent</a>

Test Method	<p>IF the <b>extent</b> property is present, THEN:</p> <ol style="list-style-type: none"> <li>1. Verify that the <b>extent</b> provides bounding boxes that include all spatial geometries in this collection.</li> <li>2. Verify that the <b>extent</b> provides time intervals that include all temporal geometries in this collection.</li> </ol>
Note:	A temporal extent of <b>null</b> indicates an open time interval.

### A.2.3. Simple Query Tests

Abstract Test 11	<b>/ats/collections/rc-md-simple-query-unsupported</b>
Test Purpose	Validate proper handling of the Simple Query parameters if the <a href="#">Simple Query</a> Conformance Class has not been implemented.
Requirement	<a href="#">/req/collections/rc-bbox-unsupported</a> <a href="#">/req/collections/rc-datetime-unsupported</a> <a href="#">/req/collections/rc-limit-unsupported</a>
Test Method	<p>IF the <a href="#">Simple Query</a> Conformance Class is not supported by this API implementation, THEN:</p> <ol style="list-style-type: none"> <li>1. Issue an HTTP GET request to the URL {root}/collections which includes the <b>bbox</b>, <b>datetime</b>, and <b>limit</b> query parameters.</li> <li>2. Validate that a document was returned with a status code 200</li> <li>3. Validate the contents of the returned document using test <a href="#">/ats/collections/rc-md-success</a>.</li> </ol>

## A.3. Conformance Class Simple query

<b>Conformance Class</b>	
<a href="http://www.opengis.net/spec/ogcapi-common-2/1.0/conf/simple-query">http://www.opengis.net/spec/ogcapi-common-2/1.0/conf/simple-query</a>	
Target type	Web API
Requirements Class	<a href="http://www.opengis.net/spec/ogcapi_common-2/1.0/req/simple-query">http://www.opengis.net/spec/ogcapi_common-2/1.0/req/simple-query</a>
Dependency	<a href="#">Collections Conformance Class</a>

Conformance with the [Simple Query](#) Conformance Class is demonstrated by execution of the following tests:

1. [/ats/collections/rc-op-bbox](#)

2. [/ats/collections/rc-op-datetime](#)

3. [/ats/collections/rc-op-limit](#)

### A.3.1. Bounding Box Tests

<b>Abstract Test 12</b>	<b><a href="#">/ats/collections/rc-op-bbox</a></b>
Test Purpose	Validate that resources can be identified and extracted from an API server using the bbox query parameter.
Requirement	<a href="#">/req/collections/rc-bbox-definition</a> <a href="#">/req/collections/rc-bbox-response</a>
Test Method	<ol style="list-style-type: none"><li>1. Select a valid bbox value which intersects a subset of the resource collections available through the API implementation.</li><li>2. Construct a bbox query parameter using the selected value.</li><li>3. Validate the bbox query parameter using <a href="#">/ats/collections/rc-bbox-definition</a></li><li>4. Issue an HTTP GET request to the URL <code>{root}/collections</code>. Include the validated bbox query parameter.</li><li>5. Validate that a document was returned with a status code 200</li><li>6. Validate the contents of the returned document using:<ol style="list-style-type: none"><li>a. <a href="#">/ats/collections_rc-md-success</a> and</li><li>b. <a href="#">/ats/collections/rc-bbox-response</a> and</li><li>c. <a href="#">/ats/collections/rc-paged-response</a>.</li></ol></li></ol>

<b>Abstract Test 13</b>	<b><a href="#">/ats/collections/rc-bbox-definition</a></b>
Test Purpose	Validate that the bounding box query parameter is constructed correctly.
Requirement	<a href="#">/req/collections/rc-bbox-definition</a>

Test Method	<p>Verify that the <b>bbox</b> query parameter complies with the following definition (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: bbox in: query required: false schema:   type: array   minItems: 4   maxItems: 6   items:     type: number style: form explode: false </pre> <p>Use a bounding box with four numbers in all requests where the collection has spatial geometries in 2D:</p> <ul style="list-style-type: none"> <li>• Lower left corner, WGS 84 longitude</li> <li>• Lower left corner, WGS 84 latitude</li> <li>• Upper right corner, WGS 84 longitude</li> <li>• Upper right corner, WGS 84 latitude</li> </ul> <p>Use a bounding box with six numbers in all requests where the collection has spatial geometries in 3D:</p> <ul style="list-style-type: none"> <li>• Lower left corner, WGS 84 longitude</li> <li>• Lower left corner, WGS 84 latitude</li> <li>• Minimum value, WGS 84 ellipsoidal height</li> <li>• Upper right corner, WGS 84 longitude</li> <li>• Upper right corner, WGS 84 latitude</li> <li>• Maximum value, WGS 84 ellipsoidal height</li> </ul>
<b>Abstract Test 14</b>	<b>/ats/collections/rc-bbox-response</b>
Test Purpose	Validate that the <b>bbox</b> query parameter is processed correctly.
Requirement	<a href="#">/req/collections/rc-bbox-response</a> <a href="#">/req/collections/rc-bbox-collection-response</a>

Test Method	<p>DO FOR each <b>Collection</b> in the <b>collections</b> element of the response:</p> <ol style="list-style-type: none"> <li>1. Extract the spatial geometry from the <b>bbox</b> element of the <b>extent</b> property of the <b>Collection</b> resource.</li> <li>2. IF there is a spatial geometry, verify that the coordinate reference system of the spatial geometry is WGS 84 longitude/latitude (<a href="http://www.opengis.net/def/crs/OGC/1.3/CRS84">http://www.opengis.net/def/crs/OGC/1.3/CRS84</a> or <a href="http://www.opengis.net/def/crs/OGC/0/CRS84h">http://www.opengis.net/def/crs/OGC/0/CRS84h</a>).</li> <li>3. IF there is a spatial geometry, verify that the spatial geometry intersects the bounding box defined by the <b>bbox</b> parameter.</li> </ol>
-------------	---

### A.3.2. Date-Time Tests

<b>Abstract Test 15</b>	<b>/ats/collections/rc-op-datetime</b>
Test Purpose	Validate that resources can be identified and extracted from an API server using the datetime query parameter.
Requirement	<a href="#">/req/collections/rc-datetime-definition</a> <a href="#">/req/collections/rc-datetime-response</a>
Test Method	<ol style="list-style-type: none"> <li>1. Select a valid datetime value which intersects a subset of the resource collections available through the API implementation.</li> <li>2. Construct a datetime query parameter using the selected value.</li> <li>3. Validate the datetime query parameter using <a href="#">/ats/collections/rc-datetime-definition</a></li> <li>4. Issue an HTTP GET request to the URL <b>{root}/collections</b>. Include the validated datetime query parameter.</li> <li>5. Validate that a document was returned with a status code 200</li> <li>6. Validate the contents of the returned document using: <ol style="list-style-type: none"> <li>a. <a href="#">/ats/collections_rc-md-success</a> and</li> <li>b. <a href="#">/ats/collections/rc-datetime-response</a> and</li> <li>c. <a href="#">/ats/collections/rc-paged-response</a>.</li> </ol> </li> </ol>
<b>Abstract Test 16</b>	<b>/ats/collections/rc-datetime-definition</b>

Test Purpose	Validate that the <code>dateTime</code> query parameter is constructed correctly.
Requirement	<a href="#">/req/collections/rc-datetime-definition</a>
Test Method	<p>Verify that the <code>datetime</code> query parameter complies with the following definition (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: datetime in: query required: false schema:   type: string   style: form   explode: false </pre>

<b>Abstract Test 17</b>	<b><a href="#">/ats/collections/rc-datetime-response</a></b>
Test Purpose	Validate that the <code>datetime</code> query parameter is processed correctly.
Requirement	<a href="#">/req/collections/rc-datetime-definition</a> <a href="#">/req/collections/rc-datetime-response</a> <a href="#">/req/collections/rc-datetime-collection-response</a>
Test Method	<p>DO FOR each <code>Collection</code> in the <code>collections</code> element of the response:</p> <ol style="list-style-type: none"> <li>1. Extract the temporal geometry from the <code>interval</code> element of the <code>extent</code> property of the <code>Collection</code> resource.</li> <li>2. IF there is a temporal geometry, verify that the temporal geometry intersects the temporal period defined by the <code>datetime</code> parameter.</li> <li>3. IF there is a temporal geometry, validate that the processing of the <code>datetime</code> parameter complies with the syntax described in <a href="#">/req/collections/rc-datetime-definition</a> (B, C, and D).</li> </ol>

### A.3.3. Limit Tests

<b>Abstract Test 18</b>	<b><a href="#">/ats/collections/rc-op-limit</a></b>
-------------------------	---



Test Purpose	Validate that the client can place a limit on the number of resources returned.
Requirement	<a href="#">/req/collections/rc-limit-definition</a> <a href="#">/req/collections/rc-limit-response</a>
Test Method	<ol style="list-style-type: none"> <li>1. Select a valid limit value which is less than the number of resource collections available through the API implementation and less than any limits advertised for the server.</li> <li>2. Construct a limit query parameter using the selected value.</li> <li>3. Validate the limit query parameter using <a href="#">/ats/collections/rc-limit-definition</a></li> <li>4. Issue an HTTP GET request to the URL <code>{root}/collections</code>. Include the validated limit query parameter.</li> <li>5. Validate that a document was returned with a status code 200</li> <li>6. Validate the contents of the returned document using: <ol style="list-style-type: none"> <li>a. <a href="#">/ats/collections_rc-md-success</a> and</li> <li>b. <a href="#">/ats/collections/rc-limit-response</a> and</li> <li>c. <a href="#">/ats/collections/rc-paged-response</a>.</li> </ol> </li> </ol>

<b>Abstract Test 19</b>	<b><a href="#">/ats/collections/rc-limit-definition</a></b>
Test Purpose	Validate that the limit query parameter is constructed correctly.
Requirement	<a href="#">/req/collections/rc-limit-definition</a>
Test Method	<p>Verify that the <code>limit</code> query parameter complies with the following definition (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: datetime in: query required: false schema:   type: string   style: form   explode: false </pre>

<b>Abstract Test 20</b>	<b><a href="#">/ats/collections/rc-limit-response</a></b>
-------------------------	---

Test Purpose	Validate that the limit query parameters are processed correctly.
Requirement	<a href="#">/req/collections/rc-limit-response</a> <a href="#">/req/collections/rc-limit-collection-response</a>
Test Method	<ol style="list-style-type: none"> <li>1. Count the items in the <b>collections</b> element of the response:</li> <li>2. Verify that this count is not greater than the value specified for the <b>limit</b> parameter.</li> <li>3. If the API definition specifies a maximum value for limit parameter, verify that the count does not exceed this maximum value.</li> </ol>

<b>Abstract Test 21</b>	<b><a href="#">/ats/collections/rc-paged-response</a></b>
Test Purpose	Validate that the <b>numberMatched</b> and <b>numberReturned</b> parameters, if present, are populated correctly..
Requirement	<a href="#">/req/collections/rc-numberMatched</a> <a href="#">/req/collections/rc-numberReturned</a>
Test Method	<ol style="list-style-type: none"> <li>1. IF the <b>numberMatched</b> property is included in the response, THEN verify that the value of the <b>numberMatched</b> parameter is identical to the number of hosted resources that meet the selection parameters provided by the client.</li> <li>2. IF the <b>numberReturned</b> property is included in the response, THEN verify that the value of the <b>numberReturned</b> parameter is identical to the number of resources returned in the response.</li> </ol>

## A.4. Conformance Class JSON

<b>Conformance Class</b>	
<a href="http://www.opengis.net/spec/ogcapi-common-2/1.0/conf/json">http://www.opengis.net/spec/ogcapi-common-2/1.0/conf/json</a>	
Target type	Web API
Requirements Class	<a href="http://www.opengis.net/spec/ogcapi_common-2/1.0/req/json">http://www.opengis.net/spec/ogcapi_common-2/1.0/req/json</a>
Dependency	<a href="#">Conformance Class "OAPI Core"</a>

### A.4.1. GeoJSON Definition

<b>Abstract Test 22</b>	<b><a href="#">/ats/json/definition</a></b>
-------------------------	---

Test Purpose	Verify support for JSON
Requirement	<a href="#">/req/json/definition</a>
Test Method	<ol style="list-style-type: none"> <li>1. A resource is requested with response media type of <b>application/json</b></li> <li>2. All <b>200</b>-responses SHALL support the media type <b>application/json</b>.</li> </ol>

#### A.4.2. GeoJSON Content

<b>Abstract Test 23</b>	<b><a href="#">/ats/json/content</a></b>
Test Purpose	Verify the content of a JSON document given an input document and schema.
Requirement	<a href="#">/req/json/content</a>
Test Method	<ol style="list-style-type: none"> <li>1. Validate that the document is a JSON document.</li> <li>2. Validate the document against the schema using a JSON Schema validator.</li> </ol>

### A.5. Conformance Class HTML

<b>Conformance Class</b>	
<a href="http://www.opengis.net/spec/ogcapi-common-2/1.0/conf/html">http://www.opengis.net/spec/ogcapi-common-2/1.0/conf/html</a>	
Target type	Web API
Requirements Class	<a href="http://www.opengis.net/spec/ogcapi_common-2/1.0/req/html">http://www.opengis.net/spec/ogcapi_common-2/1.0/req/html</a>
Dependency	<a href="#">Conformance Class "OAPI Core"</a>

#### A.5.1. HTML Definition

<b>Abstract Test 24</b>	<b><a href="#">/ats/html/definition</a></b>
Test Purpose	Verify support for HTML
Requirement	<a href="#">/req/html/definition</a>
Test Method	Verify that every <b>200</b> -response of every operation of the API where HTML was requested is of media type <b>text/html</b>

### A.5.2. HTML Content

Abstract Test 25	<a href="#">/ats/html/content</a>
Test Purpose	Verify the content of an HTML document given an input document and schema.
Requirement	<a href="#">/req/html/content</a>
Test Method	<ol style="list-style-type: none"><li>1. Validate that the document is an <a href="#">HTML 5 document</a></li><li>2. Manually inspect the document against the schema.</li></ol>

# Annex B: Examples (Informative)

## B.1. Collections Response Example

This collections example response in JSON is for a dataset with a single "buildings" feature collection.

There is a link to the collections response itself ([link relation type: "self"](#)).

Representations of this resource in other formats are referenced ([link relation type: "alternate"](#)).

An additional link is to a GML application schema for the collection ([link relation type: "describedby"](#)).

```
{
  "links": [
    { "href": "http://data.example.org/collections.json",
      "rel": "self", "type": "application/json", "title": "this document" },
    { "href": "http://data.example.org/collections.html",
      "rel": "alternate", "type": "text/html", "title": "this document as HTML" },
    { "href": "http://schemas.example.org/1.0/foobar.xsd",
      "rel": "describedby", "type": "application/xml", "title": "XML schema for Acme
Corporation data" }
  ],
  "collections": [
    {
      "id": "buildings",
      "title": "Buildings",
      "description": "Buildings in the city of Bonn.",
      "extent": {
        "spatial": [ 7.01, 50.63, 7.22, 50.78 ],
        "temporal": [ "2010-02-15T12:34:56Z", "2018-03-18T12:11:00Z" ]
      },
      "links": [
        { "href": "http://example.org/concepts/building.html",
          "rel": "describedby", "type": "text/html",
          "title": "Feature catalogue for buildings" }
      ]
    }
  ]
}
```

## B.2. Collection Object Examples

### B.2.1. Building Collection

This Collection Description example response in JSON is for a single "buildings" collection.

The basic descriptive information includes:

- "id": an identifier for this collection
- "title": the title of this collection
- "description": self evident
- "attribution": markup providing attribution (owner, producer, logo, etc.) of this collection

The response includes links to:

- There is a link to the response itself (**link relation type**: "self").
- Representations of this response in other formats are referenced using **link relation type** "alternate".
- An additional link is to a GML application schema for the collection - using: <https://www.iana.org/assignments/link-relations/link-relations.xhtml> [**link relation type** "describedby"].

Finally, this response includes both spatial and temporal extents.

Reference system information is not provided as the service provides geometries only in the default system (spatial: WGS 84 longitude/latitude; temporal: Gregorian calendar).

```
{
  "id": "1234567890",
  "title": "Example Collection Description Response",
  "description": "This is an example of a Collection Description in JSON format",
  "attribution": "<a href='www.ign.es' rel=' '>IGN</a> <a href='www.govdata.de/dl-
de/by-2-0'>(c)</a>",
  "links": [
    { "href": "http://data.example.org/collections.json",
      "rel": "self", "type": "application/json", "title": "this document" },
    { "href": "http://data.example.org/collections.html",
      "rel": "alternate", "type": "text/html", "title": "this document as HTML" },
    { "href": "http://schemas.example.org/1.0/foobar.xsd",
      "rel": "describedby", "type": "application/xml", "title": "XML schema for Acme
Corporation data" }
  ],
  "extent": {
    "spatial": [ 7.01, 50.63, 7.22, 50.78 ],
    "temporal": [ "2010-02-15T12:34:56Z", "2018-03-18T12:11:00Z" ]
  }
}
```

# Annex C: Revision History

Date	Release	Editor	Primary clauses modified	Description
2019-11-25	1.0.0-SNAPSHOT	Panagiotis (Peter) Vretanos, Clemens Portele	all	initial version
2020-04-21	1.0.1-SNAPSHOT	Chuck Heazel	all	Initial API-Common version

# Annex D: Glossary

- **Conformance Test Module**

set of related tests, all within a single conformance test class (OGC 08-131r3)

<b>NOTE:</b>	When no ambiguity is possible, the word <b>test</b> may be omitted. i.e. <b>conformance test module</b> is the same as <b>conformance module</b> . Conformance modules may be nested in a hierarchical way. This term and those associated to it are included here for consistency with ISO 19105.
--------------	---

- **Conformance Test Class; Conformance Test Level**

set of **conformance test modules** that must be applied to receive a single **certificate of conformance**. (OGC 08-131r3)

<b>NOTE:</b>	When no ambiguity is possible, the word <b>test</b> may be left out, so <b>conformance test class</b> may be called a <b>conformance class</b> .
--------------	--

- **Executable Test Suite (ETS)**

A set of code (e.g. Java and CTL) that provides runtime tests for the assertions defined by the ATS. Test data required to do the tests are part of the ETS (OGC 08-134)

- **Recommendation**

expression in the content of a document conveying that among several possibilities one is recommended as particularly suitable, without mentioning or excluding others, or that a certain course of action is preferred but not necessarily required, or that (in the negative form) a certain possibility or course of action is deprecated but not prohibited (OGC 08-131r3)

<b>NOTE:</b>	"Although using normative language, a <b>recommendation</b> is not a <b>requirement</b> . The usual form replaces the <b>shall</b> (imperative or command) of a <b>requirement</b> with a <b>should</b> (suggestive or conditional)." (ISO Directives Part 2)
--------------	---

- **Requirement**

expression in the content of a document conveying criteria to be fulfilled if compliance with the document is to be claimed and from which no deviation is permitted (OGC 08-131r3)

- **Requirements Class**

aggregate of all requirement modules that must all be satisfied to satisfy a conformance test class (OGC 08-131r3)

- **Requirements Module**

aggregate of **requirements** and **recommendations** of a specification against a single **standardization target** type (OGC 08-131r3)

- **Standardization Target**

entity to which some requirements of a standard apply (OGC 08-131r3)



<b>NOTE:</b>	The standardization target is the entity which may receive a certificate of conformance for a requirements class.
--------------	---

# Annex E: Bibliography

- Fielding, Roy Thomas. **Architectural Styles and the Design of Network-based Software Architectures**. Doctoral dissertation, University of California, Irvine, 2000.
- **YAML Ain't Markup Language** [online, viewed 2020-03-16]. Edited by O. Ben-Kiki, C. Evans, Ingy döt Net. Available at <https://yaml.org>.
- Internet Assigned Numbers Authority (IANA). **Link Relation Types** [online, viewed 2020-03-16], Available at <https://www.iana.org/assignments/link-relations/link-relations.xml>.
- Open Geospatial Consortium: **The Specification Model—A Standard for Modular specifications**, [OGC 08-131](#)
- Open Geospatial Consortium (OGC) / World Wide Web Consortium (W3C): **Spatial Data on the Web Best Practices** [online]. Edited by J. Tandy, L. van den Brink, P. Barnaghi. 2017 [viewed 2020-03-16]. Available at <https://www.w3.org/TR/sdw-bp/>.
- World Wide Web Consortium (W3C): **Data on the Web Best Practices** [online]. Edited by B.F. Lóscio, C. Burle, N. Calegari. 2017 [viewed 2020-03-16]. Available at <https://www.w3.org/TR/dwbp/>.
- World Wide Web Consortium (W3C): **Data Catalog Vocabulary (DCAT) - Version 3** [online]. Edited by R. Albertoni, D. Browning, S. Cox, A.G. Beltran, A. Perego, P. Winstanley. W3C Editors Draft 15 June 2021. Available at <https://w3c.github.io/dxwg/dcat/>.
- Open Geospatial Consortium (OGC): **Welcome To The OGC APIs** [online, viewed 2020-03-16]. Available at <http://www.ogcapi.org/>.
- Open Geospatial Consortium (OGC): **OGC Link Relations Registry**, [online, viewed 2020-04-17]. Available at <https://github.com/opengeospatial/NamingAuthority/blob/master/incubation/linkRelationTypes/linkrelations.csv>.
- Open Geospatial Consortium (OGC): **Compliance Testing Program Policies & Procedures** [online, viewed 2020-04-18]. Available at [https://portal.ogc.org/files/?artifact\\_id=28982](https://portal.ogc.org/files/?artifact_id=28982).

# Annex F: HTTP Status Codes

Table 5 lists the main HTTP status codes that clients should be prepared to receive. This includes support for specific security schemes or URI redirection. In addition, other error situations may occur in the transport layer outside of the server.

Table 5. Typical HTTP status codes

Status code	Description
200	A successful request.
302	The target resource was found but resides temporarily under a different URI. A 302 response is not evidence that the operation has been successfully completed.
303	The server is redirecting the user agent to a different resource. A 303 response is not evidence that the operation has been successfully completed.
304	An entity tag was provided in the request and the resource has not changed since the previous request.
307	The target resource resides temporarily under a different URI and the user agent MUST NOT change the request method if it performs an automatic redirection to that URI.
308	Indicates that the target resource has been assigned a new permanent URI and any future references to this resource ought to use one of the enclosed URIs.
400	The server cannot or will not process the request due to an apparent client error. For example, a query parameter had an incorrect value.
401	The request requires user authentication. The response includes a <b>WWW-Authenticate</b> header field containing a challenge applicable to the requested resource.
403	The server understood the request, but is refusing to fulfill it. While status code 401 indicates missing or bad authentication, status code 403 indicates that authentication is not the issue, but the client is not authorized to perform the requested operation on the resource.
404	The requested resource does not exist on the server. For example, a path parameter had an incorrect value.
405	The request method is not supported. For example, a POST request was submitted, but the resource only supports GET requests.
406	Content negotiation failed. For example, the <b>Accept</b> header submitted in the request did not support any of the media types supported by the server for the requested resource.
500	An internal error occurred in the server.

The status codes described in Table 5 do not cover all possible conditions. See [IETF RFC 7231](#) for a complete list of HTTP status codes.

# Annex G: OGC Web API Guidelines

The following table discusses how this standard addresses the design principles documented in the [OGC Web API Guidelines](#).

#	Principle	Discussion
1	<b>Don't reinvent</b>	Great care was taken in the development of this standard to only address capabilities that were not already standardized and to define how the needed capabilities integrate into a single API.
2	<b>Keep it simple and intuitive</b>	OGC Web APIs are developed using a building block approach. Conformance Classes are defined that encompass requirements sufficient to create a usable software module and no more. Complex APIs are constructed by assembling the applicable Conformance Classes.
3	<b>Use well-known resource types</b>	Except where unique to a specific Conformance Class, all resource types are IANA or OGC registered types. OGC Web API standards do not mandate an encoding. The encodings supported by an API are specified by the corresponding encoding Conformance Classes. All encodings used to-date are IANA registered media types.
4	<b>Construct consistent URIs</b>	OGC Web APIs are built from standardized modules using standardized patterns. This modular approach assures that the URIs are consistent across OGC Web APIs. OGC Web API Common defines stylistic conventions for query parameters, query values, identifiers, and path elements used to create OGC Web API URIs.
5	<b>Use HTTP methods consistent with RFC 7231</b>	OGC web APIs are restricted to the HTTP methods defined in IETF <a href="#">RFC 7231</a> .
6	<b>Put selection criteria behind the '?'</b>	<a href="#">Section 6.1</a> of this Standard defines the conventions to be used when creating URIs for OGC Web API standards. This includes the use of the "?" to delimitate query parameters from the rest of the URI. Note that this does not preclude the use of resource identifiers (ex. collection identifiers) as part of the path. However those can be considered identifying criteria rather than selection criteria.
7	<b>Error handling and use of HTTP status codes</b>	This standard identifies the applicable HTTP status codes and under what conditions they should be returned. Status codes and supporting information are returned in the HTTP response using a reporting structure based on RFC 7807.
8	<b>Use explicit list of HTTP status codes</b>	<a href="#">HTTP Status Codes</a> provides a list of the HTTP status codes that implementers of this standard should be prepared to generate and accept. This list is not exhaustive (see guideline #1).

9	<b>Use of HTTP header</b>	OGC API Common does not preclude use of HTTP headers where it is appropriate to do so. Only standard HTTP headers are used. Due to the common use of the HATEOAS pattern in OGC Web APIs, HTTP headers are not always accessible. The use of query parameter overrides is allowed.
10	<b>Allow flexible content negotiation</b>	IETF <a href="#">RFC 7231</a> content negotiation is available on all transactions. Since the HTTP headers are not always accessible, content negotiation may be performed through a query parameter (see #9).
11	<b>Pagination</b>	Of the resources defined in API-Common Core only the conformance resource is "listable". We do not anticipate the conformance resource to grow to any size, so support for pagination would add complexity will little to no value (violating #2) If an OpenAPI document is used as the API definition, then pagination could become an issue for this resource. The question of how to handle large OpenAPI documents is still an open issue being worked across the Standards Working Groups.
12	<b>Processing resources</b>	Processing resources are not addressed by this Standard.
13	<b>Support metadata</b>	Support for metadata is provided through metadata resource links. Examples include links with the relation type <a href="#">service-desc</a> , <a href="#">service-doc</a> , <a href="#">service-meta</a> , or <a href="#">data-meta</a> .
14	<b>Consider your security needs</b>	While not mandated, use of HTTPS vs. HTTP is encouraged throughout this standard. Authentication is not precluded by this standard, but in keeping with guideline #1, this standard does not presume to dictate what authentication methods can be used. API-Common - Core only defines GET requests. The security issues associated with CRUD are not applicable to this standard.
15	<b>API description</b>	The API definition is available using the <a href="#">service-desc</a> (machine readable) and <a href="#">service-doc</a> (human readable) associations from the landing page. OpenAPI is the only API definition type currently supported.
16	<b>Use well-known identifiers</b>	IANA identifiers are used where they are available. Where no IANA identifiers are appropriate, OGC registered identifiers are used. OGC identifiers are only used after they have been reviewed and approved by the OGC Naming Authority.
17	<b>Use explicit relations</b>	All relations in this standard are typed using relation types registered in the IANA or the OGC relation type registers.
18	<b>Support W3C cross-origin resource sharing</b>	This guideline is addressed in <a href="#">[cross-origin-section]</a> .

19	<b>Resource encodings</b>	Conformance classes for both HTML and JSON have been defined. Implementation of both the HTML and JSON Conformance Classes is recommended.
20	<b>Good APIs are testable from the beginning</b>	The Abstract Test Suite (ATS) for this standard is provided in Annex A. The ATS is defined to sufficient level of detail to validate that it is implementable and comprehensive
21	<b>Specify whether operations are safe and/or idempotent</b>	According to IETF <a href="#">RFC 7231</a> "the GET, HEAD, OPTIONS, and TRACE methods are defined to be safe." and the "PUT, DELETE, and safe request methods are idempotent". All request methods in this standard (GET) are both safe and idempotent.
22	<b>Make resources discoverable</b>	All resouces defined in this standard can be navigated to through resource links and optional standard paths. All resource links are typed using registered relation types. These links are encoded using a standard link structure that includes the media type, language, and title of the resource.
23	<b>Make default behavior explicit</b>	This Standard defines the proper and allowed responses for any valid or invalid request.