

[illegible]

G & J Steel & Tubing Inc. A 06

Part # A513-10200-011

GOOD LUCK INDUSTRIES (A UNIT OF GOOD LUCK INDIA LTD) A-51 & A59, SIKANDRABAD INDUSTRIAL AREA, SIKANDRABAD, DISTT-BULANDSAHAR UP(INDIA) TEL. NO. +91-120-419600, FAX. NO. +91-120-419666 An IATF-16949, ISO-14001 & ISO-45001 Certified Company		DEPARTMENT- QUALITY ASSURANCE TEST CERTIFICATE		Doc.No.: GLI-FT-QA-20E Rev. No. 06 REV. Date: 22-01-2022		GOODLUCK																																																																																																																																																																																																																																																																																																																																												
Material Description Purchase Order No.: 24049/01PS R/M Supplier: JSW -India Invoice No. & Date:- SIA512425/000738 , 11-07-2024 Container No. : MSMU-5165967 Quantity : 413 PCS (413X1) Bundle No. : 24049/01PS-1-1 Item Code : 1 FT : 9010.66 LBS : 1873																																																																																																																																																																																																																																																																																																																																																		
Carbon Steel Round Tubing																																																																																																																																																																																																																																																																																																																																																		
<table border="1"><thead><tr><th rowspan="2">Heat No.</th><th colspan="6">CHEMICAL PROPERTIES</th><th colspan="4">MECHANICAL PROPERTIES</th></tr><tr><th>C%</th><th>Mn%</th><th>S %</th><th>P %</th><th>Al %</th><th>SI %</th><th>N %</th><th>Cr%</th><th>Cu%</th><th>Ca%</th><th>Mo%</th><th>NI%</th><th>Tensile Strength (PSI) Min</th><th>Yield Strength (PSI) Min</th><th>EL (%) Min</th><th>Hardness (HRB) Min</th></tr></thead><tbody><tr><td>Specified</td><td>0.18 - 0.23</td><td>0.3 - 0.6</td><td>0.035</td><td>0.035</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>65,000</td><td>55,000</td><td>10</td><td>75</td></tr><tr><td>C541910</td><td>0.1935</td><td>0.470</td><td>0.0030</td><td>0.018</td><td>0.030</td><td>0.085</td><td>0.0039</td><td></td><td></td><td></td><td></td><td></td><td>98,972.92</td><td>91,232.65</td><td>17</td><td>93.0 - 94.0</td></tr><tr><td colspan="17">Other Test/ Inspection Requirements</td></tr><tr><td colspan="17">SPECIFIED</td></tr><tr><td colspan="17">OBSERVED</td></tr><tr><td colspan="17">EDDY CURRENT TEST</td></tr><tr><td colspan="17">FLARING (%)</td></tr><tr><td colspan="17">FLATTENING (INCH)</td></tr><tr><td colspan="17">STRAIGHTNESS (INCH)</td></tr><tr><td colspan="17">MATERIAL</td></tr><tr><td colspan="17">SURFACE</td></tr><tr><td colspan="17">Observed Value</td></tr><tr><td colspan="17">100% Tubes tested found ok</td></tr><tr><td colspan="17">Min 15% of ID Passed</td></tr><tr><td colspan="17">Min 1/3 of OD Passed</td></tr><tr><td colspan="17">0.030"/36" Max within limit</td></tr><tr><td colspan="17">Fully Killed Steel</td></tr><tr><td colspan="17">Satisfactory</td></tr></tbody></table>						Heat No.	CHEMICAL PROPERTIES						MECHANICAL PROPERTIES				C%	Mn%	S %	P %	Al %	SI %	N %	Cr%	Cu%	Ca%	Mo%	NI%	Tensile Strength (PSI) Min	Yield Strength (PSI) Min	EL (%) Min	Hardness (HRB) Min	Specified	0.18 - 0.23	0.3 - 0.6	0.035	0.035									65,000	55,000	10	75	C541910	0.1935	0.470	0.0030	0.018	0.030	0.085	0.0039						98,972.92	91,232.65	17	93.0 - 94.0	Other Test/ Inspection Requirements																	SPECIFIED																	OBSERVED																	EDDY CURRENT TEST																	FLARING (%)																	FLATTENING (INCH)																	STRAIGHTNESS (INCH)																	MATERIAL																	SURFACE																	Observed Value																	100% Tubes tested found ok																	Min 15% of ID Passed																	Min 1/3 of OD Passed																	0.030"/36" Max within limit																	Fully Killed Steel																	Satisfactory																
Heat No.	CHEMICAL PROPERTIES						MECHANICAL PROPERTIES																																																																																																																																																																																																																																																																																																																																											
	C%	Mn%	S %	P %	Al %	SI %	N %	Cr%	Cu%	Ca%	Mo%	NI%	Tensile Strength (PSI) Min	Yield Strength (PSI) Min	EL (%) Min	Hardness (HRB) Min																																																																																																																																																																																																																																																																																																																																		
Specified	0.18 - 0.23	0.3 - 0.6	0.035	0.035									65,000	55,000	10	75																																																																																																																																																																																																																																																																																																																																		
C541910	0.1935	0.470	0.0030	0.018	0.030	0.085	0.0039						98,972.92	91,232.65	17	93.0 - 94.0																																																																																																																																																																																																																																																																																																																																		
Other Test/ Inspection Requirements																																																																																																																																																																																																																																																																																																																																																		
SPECIFIED																																																																																																																																																																																																																																																																																																																																																		
OBSERVED																																																																																																																																																																																																																																																																																																																																																		
EDDY CURRENT TEST																																																																																																																																																																																																																																																																																																																																																		
FLARING (%)																																																																																																																																																																																																																																																																																																																																																		
FLATTENING (INCH)																																																																																																																																																																																																																																																																																																																																																		
STRAIGHTNESS (INCH)																																																																																																																																																																																																																																																																																																																																																		
MATERIAL																																																																																																																																																																																																																																																																																																																																																		
SURFACE																																																																																																																																																																																																																																																																																																																																																		
Observed Value																																																																																																																																																																																																																																																																																																																																																		
100% Tubes tested found ok																																																																																																																																																																																																																																																																																																																																																		
Min 15% of ID Passed																																																																																																																																																																																																																																																																																																																																																		
Min 1/3 of OD Passed																																																																																																																																																																																																																																																																																																																																																		
0.030"/36" Max within limit																																																																																																																																																																																																																																																																																																																																																		
Fully Killed Steel																																																																																																																																																																																																																																																																																																																																																		
Satisfactory																																																																																																																																																																																																																																																																																																																																																		
This is to certify that the material supplied confirm to all requirements as specified by the customer. This test certificate confirms to EN 10204-3.1						GLI REMARK:																																																																																																																																																																																																																																																																																																																																												
Prepared By: GOPAL SHARMA (FOR GOODLUCK INDUSTRIES)						Quality Assurance Deptt. Good Luck Industries A51 & A59, Industrial Area, Sikandrabad, U.P. Pin-203205						Approved By: DGM QUALITY MR. VINOD SHARMA (FOR GOODLUCK INDUSTRIES)																																																																																																																																																																																																																																																																																																																																						