

Makes drones in cirle Experiments Report

Zhang Jinrui*

jerryzhang40@gmail.com

Su Zinan

suzinan20050803@aliyun.com

Xu Haoran[†]

haoranxu288@gmail.com

20250720

Abstract

In this article, I tried to do apply a simple policy to each drone to make them fly in cirle

1 recite of the problem & assumptions

There are 10 drones and fly on the sky obeys Newton's second law of motion. which is

$$\begin{aligned}\vec{F} &= m\vec{a} \\ \vec{a} &= \frac{d\vec{v}}{dt} = \frac{d^2\vec{x}}{dt^2}\end{aligned}$$

And I mean the policy by, we need a function of force depending on some communication between drones to decide the \vec{F}

$$\vec{F} = f(\text{thecurrentinformation})$$

And then we want the following dynamic system

$$\begin{bmatrix} \frac{d\vec{d}}{dt} \\ \frac{d\vec{v}}{dt} \end{bmatrix} = \begin{bmatrix} \vec{v} \\ \vec{a} = f/m \end{bmatrix}$$

*alternative email:zhangjr1022@mails.jlu.edu.cn

[†]alternative email:Xuhr1023@mails.jlu.edu.cn

has some Self-organized emergent phenomena, to automatically emergent a circle rounding pattern.

2 Jinrui Zhang's prompt

2.1 a simple prompt

To be more clear of the notations we use, we have $i \in \{1, 2, \dots, 10\} = N$ And the drones are ignored of its flying height, which the position vector can be a 2d vector note it as \vec{d}_i And so the velocity and acceleration we denote as $\vec{v}_i = \frac{d\vec{d}_i}{dt}$ and $\vec{a}_i = \frac{d\vec{v}_i}{dt}$ I want to prompt a f so that it can form a circle.

$$\vec{f}_i = m_i \left(\sum_{\forall k \neq i, \|\vec{d}_i - \vec{d}_k\| \leq R} \left(\frac{\vec{d}_i - \vec{d}_k}{\|\vec{d}_i - \vec{d}_k\|^3} \right) + \left(\frac{d_{t(i)}^{\vec{}} - \vec{d}_i}{\|d_{t(i)}^{\vec{}} - \vec{d}_i\|} - v_i \right) \right)$$

This model is easy to explain, the first term is just a inverse square propell force, the second term is make the velocity quickly approach a set direction the $t(i)$ is just a randomly choosed target drone other than i that is $t(i) \in N, t(i) \neq i$

This formula can be rewrite without physical term as follow.

$$\vec{a}_i = \sum_{\forall k \neq i, \|\vec{d}_i - \vec{d}_k\| \leq R} \left(\frac{\vec{d}_i - \vec{d}_k}{\|\vec{d}_i - \vec{d}_k\|^3} \right) + \left(\frac{d_{t(i)}^{\vec{}} - \vec{d}_i}{\|d_{t(i)}^{\vec{}} - \vec{d}_i\|} - v_i \right)$$

separately view this is combined by two independent force

$$\begin{aligned} (\vec{a}_i)_{target} &= \left(\frac{d_{t(i)}^{\vec{}} - \vec{d}_i}{\|d_{t(i)}^{\vec{}} - \vec{d}_i\|} - v_i \right) \\ (\vec{a}_i)_{propell} &= \sum_{\forall k \neq i, \|\vec{d}_i - \vec{d}_k\| \leq R} \left(\frac{\vec{d}_i - \vec{d}_k}{\|\vec{d}_i - \vec{d}_k\|^3} \right) \end{aligned}$$

2.2 a simple prompt:simulation

2.2.1 Four drone case:derivation

This case just choose $N = \{1, 2, 3, 4\}$ and don't allow $t(t(i)) = i$ which definitely form a three element loop and a dangling drone.

We have a (4,2)-tensor \vec{d}_i and two other (4,2)-tensor \vec{v}_i and \vec{a}_i . The initial points are randomly choosed in Uniformly $[0, 1] \times [0, 1]$

choose a time increment dt and the simulation update formula is simple to write

just as follow

$$\begin{bmatrix} \vec{d}_{n+1_i} \\ \vec{v}_{n+1_i} \end{bmatrix} = \begin{bmatrix} \vec{d}_{n_i} + \vec{v}_{n_i} dt \\ \vec{v}_{n_i} + (\sum_{\forall k \neq i, \|\vec{d}_{n_i} - \vec{d}_{n_k}\| \leq R} (\frac{\vec{d}_{n_i} - \vec{d}_{n_k}}{\|\vec{d}_{n_i} - \vec{d}_{n_k}\|^3}) + (\frac{\vec{d}_{n_t(i)} - \vec{d}_{n_i}}{\|\vec{d}_{n_t(i)} - \vec{d}_{n_i}\|} - \vec{v}_{n_i})) dt \end{bmatrix}$$

simple Euler method.

2.2.2 Four drone case:code & result

the computational code are [1, FourDroneCase] . the results are shown by the following pictures which generated by the code. The video are [2, sample1-video] and [3, sample2-video] and more other in the same folder on github.




图 1: sample1 randomly initial position




图 2: sample1 after a period of time

2.2.3 Ten drone case:derivation

undergoing

2.2.4 Ten drone case:result

undergoing




图 3: sample1 randomly initial position




图 4: sample2 after a period of time

2.3 some analysis why it will have a stability property

2.3.1 the terminate radius R

undergoing

2.3.2 the terminate center O

undergoing

2.3.3 graph theory part

The $t(i)$ forms a graph which have n points and n oriented edges, this forms a tree with a extra edges, and this case It will obviously form a Unicyclic Graph.

Which is a tree if we treat all the point on the loop as the same point.

3 Zinan Su's approach

3.1 notations & equations

safe collide radius is d_s

$$\sigma = 2d_s$$

NUM is the total number of the drones. And then we want the following dynamic system

$$\begin{bmatrix} \frac{d\vec{p}_i}{dt} \\ \frac{d\vec{v}_i}{dt} \end{bmatrix} = \begin{bmatrix} \vec{v}_i \\ \vec{a}_i \end{bmatrix}$$

circle origin is a function

$$c = \frac{1}{NUM} \sum_{k=1}^{NUM} p_k$$

Four constants.

$$k_p =$$

$$k_d =$$

$$k_v =$$

$$k_r =$$

$$R^* = \frac{1}{NUM} \sum_{k=1}^{NUM} p_k(0) - c(0)$$

$$v_d = \frac{1}{NUM} \sum_{k=1}^{NUM} \|v_k(0)\|$$

and

$$r_i = p_i - c$$

$$d_i = \|r_i\|$$

$$\hat{r}_i = \frac{r_i}{d_i}$$

$$\hat{\theta}_i = \mathbb{M}_\theta r_i$$

$$\mathbb{M}_\theta = \begin{bmatrix} 0 & 1 \\ -1 & 0 \end{bmatrix}$$

$$v_{i\parallel} = \hat{r}_i \cdot v_i$$

$$v_{i\perp} = \hat{\theta}_i \cdot v_i$$

$$U(r) = k_r e^{-\frac{r}{2\sigma^2}}$$

$$U_{ij} = U(\|p_i - p_j\|)$$

$$\vec{u}_{i1} = [-k_p(d_i - R^*) - k_d v_{i\parallel}] \hat{r}_i$$

$$\begin{aligned}
\vec{u}_{i2} &= [-k_v(v_{i\perp} - v_d)]\hat{\theta}_i \\
\vec{u}_{i3} &= \sum_{\forall k \neq i} (-\nabla_{\mathbf{p}_i} U_{ij}) \\
\vec{u}_i &= \vec{u}_{i1} + \vec{u}_{i2} + \vec{u}_{i3}
\end{aligned}$$

3.2 analysis

考虑带阻力的动力方程

$$m \frac{d^2 \mathbf{p}_i}{dt^2} + c \left\| \frac{d\mathbf{p}_i}{dt} \right\| \frac{d\mathbf{p}_i}{dt} = \mathbf{u}_i,$$

其中 m 为质量, c 为阻力系数, 即

$$\frac{d\mathbf{X}}{dt} = \mathbf{F}(\mathbf{X}), \quad (1)$$

其中

$$\mathbf{X} = \begin{pmatrix} \mathbf{p} \\ \mathbf{v} \end{pmatrix} \in \mathbb{R}^{40}, \quad \mathbf{p} = \begin{pmatrix} \mathbf{p}_1 \\ \vdots \\ \mathbf{p}_{10} \end{pmatrix}, \quad \mathbf{v} = \begin{pmatrix} \mathbf{v}_1 \\ \vdots \\ \mathbf{v}_{10} \end{pmatrix}, \quad \mathbf{F}(\mathbf{X}) = \begin{pmatrix} \mathbf{v} \\ m^{-1}(\mathbf{u} - c\|\mathbf{v}\|\mathbf{v}) \end{pmatrix}.$$

易知质心 $\mathbf{c}(\mathbf{X})$, $\|\mathbf{r}_i\|$, $\hat{\mathbf{r}}_i$, Φ 均为 Lipschitz 连续函数, 且初值条件满足

$$\min_{i \neq j} \|\mathbf{p}_i(0) - \mathbf{p}_j(0)\| > d_s > 0.$$

由 Picard 定理可知方程 (1) 的解存在且唯一, 解为

$$\mathbf{X}(t) = \mathbf{X}(0) + \int_0^t \mathbf{F}(\mathbf{X}(s)) ds,$$

即

$$\begin{aligned}
\mathbf{v}_i(t) &= \mathbf{v}_i(0) + \int_0^t \left[m^{-1} \mathbf{u}_i(\mathbf{X}(s)) - \frac{c}{m} \|\mathbf{v}_i(s)\| \mathbf{v}_i(s) \right] ds, \\
\mathbf{p}_i(t) &= \mathbf{p}_i(0) + \int_0^t \mathbf{v}_i(s) ds.
\end{aligned}$$

下面证明防撞性. 定义

$$\begin{aligned}
\Psi(d) &= k_r \exp \left\{ -\frac{(d - d_s)^2}{2\sigma^2} \right\}, \\
\Phi(d) &= -\frac{d\Psi}{dd} = \frac{k_r}{\sigma^2} \exp \left\{ -\frac{(d - d_s)^2}{2\sigma^2} \right\} (d - d_s), \\
E_{ij}(t) &= \frac{1}{2} \left(\frac{dd_{ij}}{dt} \right)^2 + \psi(d_{ij}(t)),
\end{aligned}$$

其中 $d_{ij}(t) = \|\mathbf{p}_i(t) - \mathbf{p}_j(t)\|$. 则系统能量为

$$\mathcal{E}(t) = \sum_{1 \leq i < j \leq N} E_{ij}(t).$$

而

$$\begin{aligned} \frac{dE_{ij}}{dt} &= \frac{dd_{ij}}{dt} \cdot \frac{d^2d_{ij}}{dt^2} + \Phi(d_{ij}) \frac{dd_{ij}}{dt}, \\ \frac{d^2d_{ij}}{dt^2} &= \frac{1}{d_{ij}} \left[\|\mathbf{v}_i - \mathbf{v}_j\|^2 + (\mathbf{p}_i - \mathbf{p}_j) \cdot (\mathbf{u}_i - \mathbf{u}_j) - \left(\frac{dd_{ij}}{dt} \right)^2 \right], \end{aligned} \quad (2)$$

其中 $\mathbf{u}_i = \dot{\mathbf{v}}_i$. 对于 \mathbf{u}_i , 有

$$\mathbf{u}_i = \frac{1}{m} [-k_p(d_i - R^*)\hat{\mathbf{r}}_i - k_d v_{r,i} \hat{\mathbf{r}}_i - k_v(v_{\theta,i} - v_d)\hat{\boldsymbol{\theta}}_i] + \frac{1}{m} \sum_{k \neq i} \Phi(d_{ik})(\mathbf{p}_i - \mathbf{p}_k) =: \mathbf{u}_{i_1} + \mathbf{u}_{i_2}.$$

设 $\|\mathbf{u}_{i_1} - \mathbf{u}_{j_1}\| \leq L$. 取

$$k_r > L\sigma^2 e^{\frac{1}{2}} \max \left\{ \frac{1}{d_s}, \frac{1}{\min_{k \neq l} d_{kl}(0)} \right\},$$

则当 $d_{ij} \leq d_s + \sigma$ 时, 有

$$\|\mathbf{u}_{i_2} - \mathbf{u}_{j_2}\| > 2L.$$

于是

$$(\mathbf{p}_i - \mathbf{p}_j) \cdot (\mathbf{u}_i - \mathbf{u}_j) \geq \|\mathbf{u}_{i_2} - \mathbf{u}_{j_2}\| d_{ij} - L d_{ij} > L d_{ij}.$$

代入 (2) 式有

$$\frac{dE_{ij}}{dt} \geq \frac{dd_{ij}}{dt} (L + \Phi(d_{ij})) > 0.$$

由此即知

$$\frac{d\mathcal{E}}{dt} \geq -\kappa \mathcal{E}(t),$$

其中 $\kappa > 0$ 为常数. 而

$$\mathcal{E}(0) \geq \sum_{i < j} \Psi(d_{ij}(0)) > \psi(d_s + \sigma) \cdot \binom{N}{2},$$

$$\mathcal{E}(t) \geq \mathcal{E}(0) e^{-\kappa t} > 0,$$

$$\Psi(d_{ij}(t)) \leq E_{ij}(t) \leq \mathcal{E}(t).$$

由 Ψ 严格单调递减可知

$$d_{ij}(t) \geq \Psi^{-1}(\mathcal{E}(t)) > \Psi^{-1}(\mathcal{E}(0))e^{-\kappa t}.$$

令 $t \rightarrow \infty$, 有

$$\lim_{t \rightarrow \infty} d_{ij}(t) \geq \Psi^{-1}(0) = d_s.$$

故总是不会相撞.

下面讨论收敛性, 即讨论系统收敛至

$$\mathcal{S} = \{\|\mathbf{r}_i\| = R, \mathbf{v}_i \cdot \hat{\mathbf{r}}_i = 0, \|\mathbf{v}_i\| = v_d\}.$$

构造 Lyapunov 函数

$$V = \frac{1}{2} \sum_{i=1}^N [k_p(d_i - R)^2 + \|\mathbf{v}_i - v_d \hat{\boldsymbol{\theta}}_i\|^2] + \sum_{i < j} \Psi(d_{ij}),$$

则

$$\dot{V} = - \sum_i k_d v_{r,i}^2 - \sum_i k_v (v_{\theta,i} - v_d)^2 - \sum_i c \|\mathbf{v}_i\|^3 \leq 0,$$

故方程渐进收敛至 \mathcal{S} .

3.3 some constants calculation

undergoing c is air resistance constant.

$$m \frac{d^2 \vec{p}_i}{dt^2} + c \left\| \frac{d\vec{p}_i}{dt} \right\| \frac{d\vec{p}_i}{dt} = \mathbf{u}_i$$

References

- [1] Zhang Jinrui. Fourdronecase.py. https://github.com/jerzha40/2025_exchange_at_universityofalberta/blob/main/DroneInCircleEXP/FourDroneCase.py. Accessed: 2025-07-20.
- [2] Zhang Jinrui. sample1-video. https://github.com/jerzha40/2025_exchange_at_universityofalberta/blob/main/DroneInCircle/fig/sample1/0001-18255.mp4. Accessed: 2025-07-20.
- [3] Zhang Jinrui. sample2-video. https://github.com/jerzha40/2025_exchange_at_universityofalberta/blob/main/DroneInCircle/fig/sample2/0001-18994.mp4. Accessed: 2025-07-20.