

## Design Document: Dog

Julia Sales  
CruzID: jesales

### 1) Goals

The goal of this program is to perform functionality similar to that of the cat function in terminal. Dog will read the files entered and print out the contents of each file. Dog needs to be able to handle reading and out putting the contents of multiple files to the command line.

Dog needs to be able to handle dashes ( - ), process files one at a time, needs to process binary, and have error messages.

### 2) Design

Part 1: Handling and Reading the arguments

Part 2: Process each argument and print results

#### 2.1 Handling and Reading the arguments

In this part of the program, we initialize our variables. We define our argument count, and we set up an array to hold the arguments.

Reminder: import needed libraries for allowed library functions

**Input:** Argument count: arg\_count

**Input:** Array of arguments: arg

**Output:** contents of the files: std\_out

```
1- int main (int arg_count, char *arg[ ]) *from stack overflow*
2- arg_count <- cmd line
3- char *arg[ ] <- datatype(char) args[arg_count]
4- int i, j, in;
5- char *p = ""
6- char *buffer
5- if arg_count = 1 then
6-     | read (stdin, buffer, size of buffer)
7-     | while (not eof)
8-         | write (stdout, buffer, size of buffer)
9-         | read (stdin, buffer, size of buffer)
7- else
8-     | for(i=1; i<=arg_count; i++)
9-         | if arg_count[1] = " - " <-char
10-            | read (stdin, buffer, size of buffer)
```

```

7-      | while (not eof)
8-      |   write (stdout, buffer, size of buffer)
9-      |   read (stdin, buffer, size of buffer)
11-     | else
12-     | Process each argument

```

## 2.2 Process each argument and print results

In this part of the program, we read each file one by one and take the contents of each file and print them to stdout. This part of the program determines the difference between txt and binary files. The contents of each file will get stored in a linked list.

### **Loop:**

```

1- int <- j
2- for(j=1; j<=arg_count; j++)
3-   | read/open arg_count[ j ] <- file_#
4-   | store contents of file into linked list
5-   | print out contents of linked list from beginning - last
6-   | clear linked list
7-   end

```